

---

# MPI for Python

*Release 3.1.6*

**Lisandro Dalcin**

July 17, 2024

## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	What is MPI? . . . . .	3
1.2	What is Python? . . . . .	3
1.3	Related Projects . . . . .	4
<b>2</b>	<b>Overview</b>	<b>5</b>
2.1	Communicating Python Objects and Array Data . . . . .	5
2.2	Communicators . . . . .	5
2.3	Point-to-Point Communications . . . . .	6
2.4	Collective Communications . . . . .	7
2.5	Support for GPU-aware MPI . . . . .	7
2.6	Dynamic Process Management . . . . .	8
2.7	One-Sided Communications . . . . .	8
2.8	Parallel Input/Output . . . . .	9
2.9	Environmental Management . . . . .	9
<b>3</b>	<b>Tutorial</b>	<b>10</b>
3.1	Running Python scripts with MPI . . . . .	12
3.2	Point-to-Point Communication . . . . .	12
3.3	Collective Communication . . . . .	13
3.4	MPI-IO . . . . .	15
3.5	Dynamic Process Management . . . . .	16
3.6	CUDA-aware MPI + Python GPU arrays . . . . .	17
3.7	One-Sided Communications . . . . .	17
3.8	Wrapping with SWIG . . . . .	18
3.9	Wrapping with F2Py . . . . .	19
<b>4</b>	<b>mpi4py</b>	<b>20</b>
4.1	Runtime configuration options . . . . .	20
4.2	Environment variables . . . . .	22
4.3	Miscellaneous functions . . . . .	25
<b>5</b>	<b>mpi4py.MPI</b>	<b>25</b>
5.1	Classes . . . . .	25
5.2	Functions . . . . .	26
5.3	Attributes . . . . .	28

<b>6</b>	<b>mpi4py.futures</b>	<b>34</b>
6.1	concurrent.futures . . . . .	34
6.2	MPIPoolExecutor . . . . .	34
6.3	MPICommExecutor . . . . .	37
6.4	Command line . . . . .	38
6.5	Examples . . . . .	38
<b>7</b>	<b>mpi4py.util</b>	<b>40</b>
7.1	mpi4py.util.pkl5 . . . . .	40
7.2	mpi4py.util.dtlb . . . . .	46
<b>8</b>	<b>mpi4py.run</b>	<b>47</b>
8.1	Interface options . . . . .	48
<b>9</b>	<b>Reference</b>	<b>48</b>
9.1	mpi4py.MPI . . . . .	48
<b>10</b>	<b>Citation</b>	<b>197</b>
<b>11</b>	<b>Installation</b>	<b>197</b>
11.1	Requirements . . . . .	197
11.2	Using <b>pip</b> . . . . .	198
11.3	Using <b>distutils</b> . . . . .	198
11.4	Testing . . . . .	200
<b>12</b>	<b>Appendix</b>	<b>200</b>
12.1	MPI-enabled Python interpreter . . . . .	200
12.2	Building MPI from sources . . . . .	201
	<b>References</b>	<b>202</b>
	<b>Python Module Index</b>	<b>204</b>
	<b>Index</b>	<b>205</b>

## Abstract

This document describes the *MPI for Python* package. *MPI for Python* provides Python bindings for the *Message Passing Interface* (MPI) standard, allowing Python applications to exploit multiple processors on workstations, clusters and supercomputers.

This package builds on the MPI specification and provides an object oriented interface resembling the MPI-2 C++ bindings. It supports point-to-point (sends, receives) and collective (broadcasts, scatters, gathers) communication of any *pickleable* Python object, as well as efficient communication of Python objects exposing the Python buffer interface (e.g. NumPy arrays and builtin bytes/array/memoryview objects).

# 1 Introduction

Over the last years, high performance computing has become an affordable resource to many more researchers in the scientific community than ever before. The conjunction of quality open source software and commodity hardware strongly influenced the now widespread popularity of [Beowulf](#) class clusters and cluster of workstations.

Among many parallel computational models, message-passing has proven to be an effective one. This paradigm is specially suited for (but not limited to) distributed memory architectures and is used in today's most demanding scientific and engineering application related to modeling, simulation, design, and signal processing. However, portable message-passing parallel programming used to be a nightmare in the past because of the many incompatible options developers were faced to. Fortunately, this situation definitely changed after the MPI Forum released its standard specification.

High performance computing is traditionally associated with software development using compiled languages. However, in typical applications programs, only a small part of the code is time-critical enough to require the efficiency of compiled languages. The rest of the code is generally related to memory management, error handling, input/output, and user interaction, and those are usually the most error prone and time-consuming lines of code to write and debug in the whole development process. Interpreted high-level languages can be really advantageous for this kind of tasks.

For implementing general-purpose numerical computations, MATLAB<sup>1</sup> is the dominant interpreted programming language. In the open source side, Octave and Scilab are well known, freely distributed software packages providing compatibility with the MATLAB language. In this work, we present MPI for Python, a new package enabling applications to exploit multiple processors using standard MPI “look and feel” in Python scripts.

## 1.1 What is MPI?

MPI, [\[mpi-using\]](#) [\[mpi-ref\]](#) the *Message Passing Interface*, is a standardized and portable message-passing system designed to function on a wide variety of parallel computers. The standard defines the syntax and semantics of library routines and allows users to write portable programs in the main scientific programming languages (Fortran, C, or C++).

Since its release, the MPI specification [\[mpi-std1\]](#) [\[mpi-std2\]](#) has become the leading standard for message-passing libraries for parallel computers. Implementations are available from vendors of high-performance computers and from well known open source projects like [MPICH](#) [\[mpi-mpich\]](#) and [Open MPI](#) [\[mpi-openmpi\]](#).

## 1.2 What is Python?

[Python](#) is a modern, easy to learn, powerful programming language. It has efficient high-level data structures and a simple but effective approach to object-oriented programming with dynamic typing and dynamic binding. It supports modules and packages, which encourages program modularity and code reuse. Python's elegant syntax, together with its interpreted nature, make it an ideal language for scripting and rapid application development in many areas on most platforms.

The Python interpreter and the extensive standard library are available in source or binary form without charge for all major platforms, and can be freely distributed. It is easily extended with new functions and data types implemented in C or C++. Python is also suitable as an extension language for customizable applications.

Python is an ideal candidate for writing the higher-level parts of large-scale scientific applications [\[Hinsen97\]](#) and driving simulations in parallel architectures [\[Beazley97\]](#) like clusters of PC's or SMP's. Python codes are quickly developed, easily maintained, and can achieve a high degree of integration with other libraries written in compiled languages.

---

<sup>1</sup> MATLAB is a registered trademark of The MathWorks, Inc.

## 1.3 Related Projects

As this work started and evolved, some ideas were borrowed from well known MPI and Python related open source projects from the Internet.

- **OOMPI**
  - It has no relation with Python, but is an excellent object oriented approach to MPI.
  - It is a C++ class library specification layered on top of the C bindings that encapsulates MPI into a functional class hierarchy.
  - It provides a flexible and intuitive interface by adding some abstractions, like *Ports* and *Messages*, which enrich and simplify the syntax.
- **Pympar**
  - Its interface is rather minimal. There is no support for communicators or process topologies.
  - It does not require the Python interpreter to be modified or recompiled, but does not permit interactive parallel runs.
  - General (*picklable*) Python objects of any type can be communicated. There is good support for numeric arrays, practically full MPI bandwidth can be achieved.
- **pyMPI**
  - It rebuilds the Python interpreter providing a built-in module for message passing. It does permit interactive parallel runs, which are useful for learning and debugging.
  - It provides an interface suitable for basic parallel programming. There is not full support for defining new communicators or process topologies.
  - General (*picklable*) Python objects can be messaged between processors. There is not support for numeric arrays.
- **Scientific Python**
  - It provides a collection of Python modules that are useful for scientific computing.
  - There is an interface to MPI and BSP (*Bulk Synchronous Parallel programming*).
  - The interface is simple but incomplete and does not resemble the MPI specification. There is support for numeric arrays.

Additionally, we would like to mention some available tools for scientific computing and software development with Python.

- **NumPy** is a package that provides array manipulation and computational capabilities similar to those found in IDL, MATLAB, or Octave. Using NumPy, it is possible to write many efficient numerical data processing applications directly in Python without using any C, C++ or Fortran code.
- **SciPy** is an open source library of scientific tools for Python, gathering a variety of high level science and engineering modules together as a single package. It includes modules for graphics and plotting, optimization, integration, special functions, signal and image processing, genetic algorithms, ODE solvers, and others.
- **Cython** is a language that makes writing C extensions for the Python language as easy as Python itself. The Cython language is very close to the Python language, but Cython additionally supports calling C functions and declaring C types on variables and class attributes. This allows the compiler to generate very efficient C code from Cython code. This makes Cython the ideal language for wrapping for external C libraries, and for fast C modules that speed up the execution of Python code.

- **SWIG** is a software development tool that connects programs written in C and C++ with a variety of high-level programming languages like Perl, Tcl/Tk, Ruby and Python. Issuing header files to SWIG is the simplest approach to interfacing C/C++ libraries from a Python module.

## 2 Overview

MPI for Python provides an object oriented approach to message passing which grounds on the standard MPI-2 C++ bindings. The interface was designed with focus in translating MPI syntax and semantics of standard MPI-2 bindings for C++ to Python. Any user of the standard C/C++ MPI bindings should be able to use this module without need of learning a new interface.

### 2.1 Communicating Python Objects and Array Data

The Python standard library supports different mechanisms for data persistence. Many of them rely on disk storage, but *pickling* and *marshaling* can also work with memory buffers.

The **pickle** modules provide user-extensible facilities to serialize general Python objects using ASCII or binary formats. The **marshal** module provides facilities to serialize built-in Python objects using a binary format specific to Python, but independent of machine architecture issues.

*MPI for Python* can communicate any built-in or user-defined Python object taking advantage of the features provided by the **pickle** module. These facilities will be routinely used to build binary representations of objects to communicate (at sending processes), and restoring them back (at receiving processes).

Although simple and general, the serialization approach (i.e., *pickling* and *unpickling*) previously discussed imposes important overheads in memory as well as processor usage, especially in the scenario of objects with large memory footprints being communicated. Pickling general Python objects, ranging from primitive or container built-in types to user-defined classes, necessarily requires computer resources. Processing is also needed for dispatching the appropriate serialization method (that depends on the type of the object) and doing the actual packing. Additional memory is always needed, and if its total amount is not known *a priori*, many reallocations can occur. Indeed, in the case of large numeric arrays, this is certainly unacceptable and precludes communication of objects occupying half or more of the available memory resources.

*MPI for Python* supports direct communication of any object exporting the single-segment buffer interface. This interface is a standard Python mechanism provided by some types (e.g., strings and numeric arrays), allowing access in the C side to a contiguous memory buffer (i.e., address and length) containing the relevant data. This feature, in conjunction with the capability of constructing user-defined MPI datatypes describing complicated memory layouts, enables the implementation of many algorithms involving multidimensional numeric arrays (e.g., image processing, fast Fourier transforms, finite difference schemes on structured Cartesian grids) directly in Python, with negligible overhead, and almost as fast as compiled Fortran, C, or C++ codes.

### 2.2 Communicators

In *MPI for Python*, **Comm** is the base class of communicators. The **Intracomm** and **Intercomm** classes are subclasses of the **Comm** class. The **Comm.Is\_inter** method (and **Comm.Is\_intra**, provided for convenience but not part of the MPI specification) is defined for communicator objects and can be used to determine the particular communicator class.

The two predefined intracommunicator instances are available: **COMM\_SELF** and **COMM\_WORLD**. From them, new communicators can be created as needed.

The number of processes in a communicator and the calling process rank can be respectively obtained with methods **Comm.GetSize** and **Comm.GetRank**. The associated process group can be retrieved from a communicator by calling the **Comm.GetGroup** method, which returns an instance of the **Group** class. Set operations with **Group** objects like

like `Group.Union`, `Group.Intersection` and `Group.Difference` are fully supported, as well as the creation of new communicators from these groups using `Comm.Create` and `Comm.Create_group`.

New communicator instances can be obtained with the `Comm.Clone`, `Comm.Dup` and `Comm.Split` methods, as well methods `Intracomm.Create_intercomm` and `Intercomm.Merge`.

Virtual topologies (`Cartcomm`, `Graphcomm` and `Distgraphcomm` classes, which are specializations of the `Intracomm` class) are fully supported. New instances can be obtained from intracommunicator instances with factory methods `Intracomm.Create_cart` and `Intracomm.Create_graph`.

## 2.3 Point-to-Point Communications

Point to point communication is a fundamental capability of message passing systems. This mechanism enables the transmission of data between a pair of processes, one side sending, the other receiving.

MPI provides a set of *send* and *receive* functions allowing the communication of *typed* data with an associated *tag*. The type information enables the conversion of data representation from one architecture to another in the case of heterogeneous computing environments; additionally, it allows the representation of non-contiguous data layouts and user-defined datatypes, thus avoiding the overhead of (otherwise unavoidable) packing/unpacking operations. The tag information allows selectivity of messages at the receiving end.

### Blocking Communications

MPI provides basic send and receive functions that are *blocking*. These functions block the caller until the data buffers involved in the communication can be safely reused by the application program.

In *MPI for Python*, the `Comm.Send`, `Comm.Recv` and `Comm.Sendrecv` methods of communicator objects provide support for blocking point-to-point communications within `Intracomm` and `Intercomm` instances. These methods can communicate memory buffers. The variants `Comm.send`, `Comm.recv` and `Comm.sendrecv` can communicate general Python objects.

### Nonblocking Communications

On many systems, performance can be significantly increased by overlapping communication and computation. This is particularly true on systems where communication can be executed autonomously by an intelligent, dedicated communication controller.

MPI provides *nonblocking* send and receive functions. They allow the possible overlap of communication and computation. Non-blocking communication always come in two parts: posting functions, which begin the requested operation; and test-for-completion functions, which allow to discover whether the requested operation has completed.

In *MPI for Python*, the `Comm.Isend` and `Comm.Irecv` methods initiate send and receive operations, respectively. These methods return a `Request` instance, uniquely identifying the started operation. Its completion can be managed using the `Request.Test`, `Request.Wait` and `Request.Cancel` methods. The management of `Request` objects and associated memory buffers involved in communication requires a careful, rather low-level coordination. Users must ensure that objects exposing their memory buffers are not accessed at the Python level while they are involved in nonblocking message-passing operations.

## Persistent Communications

Often a communication with the same argument list is repeatedly executed within an inner loop. In such cases, communication can be further optimized by using persistent communication, a particular case of nonblocking communication allowing the reduction of the overhead between processes and communication controllers. Furthermore, this kind of optimization can also alleviate the extra call overheads associated to interpreted, dynamic languages like Python.

In *MPI for Python*, the `Comm.Send_init` and `Comm.Recv_init` methods create persistent requests for a send and receive operation, respectively. These methods return an instance of the `Prequest` class, a subclass of the `Request` class. The actual communication can be effectively started using the `Prequest.Start` method, and its completion can be managed as previously described.

## 2.4 Collective Communications

Collective communications allow the transmittal of data between multiple processes of a group simultaneously. The syntax and semantics of collective functions is consistent with point-to-point communication. Collective functions communicate *typed* data, but messages are not paired with an associated *tag*; selectivity of messages is implied in the calling order. Additionally, collective functions come in blocking versions only.

The more commonly used collective communication operations are the following.

- Barrier synchronization across all group members.
- Global communication functions
  - Broadcast data from one member to all members of a group.
  - Gather data from all members to one member of a group.
  - Scatter data from one member to all members of a group.
- Global reduction operations such as sum, maximum, minimum, etc.

In *MPI for Python*, the `Comm.Bcast`, `Comm.Scatter`, `Comm.Gather`, `Comm.Allgather`, `Comm.Alltoall` methods provide support for collective communications of memory buffers. The lower-case variants `Comm.bcast`, `Comm.scatter`, `Comm.gather`, `Comm.allgather` and `Comm.alltoall` can communicate general Python objects. The vector variants (which can communicate different amounts of data to each process) `Comm.Scatterv`, `Comm.Gatherv`, `Comm.Allgatherv`, `Comm.Alltoallv` and `Comm.Alltoallw` are also supported, they can only communicate objects exposing memory buffers.

Global reduction operations on memory buffers are accessible through the `Comm.Reduce`, `Comm.Reduce_scatter`, `Comm.Allreduce`, `IntraComm.Scan` and `IntraComm.Exscan` methods. The lower-case variants `Comm.reduce`, `Comm.allreduce`, `IntraComm.scan` and `IntraComm.exscan` can communicate general Python objects; however, the actual required reduction computations are performed sequentially at some process. All the predefined (i.e., `SUM`, `PROD`, `MAX`, etc.) reduction operations can be applied.

## 2.5 Support for GPU-aware MPI

Several MPI implementations, including Open MPI and MVAPICH, support passing GPU pointers to MPI calls to avoid explicit data movement between the host and the device. On the Python side, GPU arrays have been implemented by many libraries that need GPU computation, such as CuPy, Numba, PyTorch, and PyArrow. In order to increase library interoperability, two kinds of zero-copy data exchange protocols are defined and agreed upon: `DLPack` and `CUDA Array Interface`. For example, a CuPy array can be passed to a Numba CUDA-jit kernel.

*MPI for Python* provides an experimental support for GPU-aware MPI. This feature requires:

1. mpi4py is built against a GPU-aware MPI library.
2. The Python GPU arrays are compliant with either of the protocols.



See the [Tutorial](#) section for further information. We note that

- Whether or not a MPI call can work for GPU arrays depends on the underlying MPI implementation, not on `mpi4py`.
- This support is currently experimental and subject to change in the future.

## 2.6 Dynamic Process Management

In the context of the MPI-1 specification, a parallel application is static; that is, no processes can be added to or deleted from a running application after it has been started. Fortunately, this limitation was addressed in MPI-2. The new specification added a process management model providing a basic interface between an application and external resources and process managers.

This MPI-2 extension can be really useful, especially for sequential applications built on top of parallel modules, or parallel applications with a client/server model. The MPI-2 process model provides a mechanism to create new processes and establish communication between them and the existing MPI application. It also provides mechanisms to establish communication between two existing MPI applications, even when one did not *start* the other.

In *MPI for Python*, new independent process groups can be created by calling the [Intracomm.Spawn](#) method within an intracommunicator. This call returns a new intercommunicator (i.e., an [Intercomm](#) instance) at the parent process group. The child process group can retrieve the matching intercommunicator by calling the [Comm.Get\\_parent](#) class method. At each side, the new intercommunicator can be used to perform point to point and collective communications between the parent and child groups of processes.

Alternatively, disjoint groups of processes can establish communication using a client/server approach. Any server application must first call the [Open\\_port](#) function to open a *port* and the [Publish\\_name](#) function to publish a provided *service*, and next call the [Intracomm.Accept](#) method. Any client applications can first find a published *service* by calling the [Lookup\\_name](#) function, which returns the *port* where a server can be contacted; and next call the [Intracomm.Connect](#) method. Both [Intracomm.Accept](#) and [Intracomm.Connect](#) methods return an [Intercomm](#) instance. When connection between client/server processes is no longer needed, all of them must cooperatively call the [Comm.Disconnect](#) method. Additionally, server applications should release resources by calling the [Unpublish\\_name](#) and [Close\\_port](#) functions.

## 2.7 One-Sided Communications

One-sided communications (also called *Remote Memory Access*, *RMA*) supplements the traditional two-sided, send/receive based MPI communication model with a one-sided, put/get based interface. One-sided communication that can take advantage of the capabilities of highly specialized network hardware. Additionally, this extension lowers latency and software overhead in applications written using a shared-memory-like paradigm.

The MPI specification revolves around the use of objects called *windows*; they intuitively specify regions of a process's memory that have been made available for remote read and write operations. The published memory blocks can be accessed through three functions for put (remote send), get (remote write), and accumulate (remote update or reduction) data items. A much larger number of functions support different synchronization styles; the semantics of these synchronization operations are fairly complex.

In *MPI for Python*, one-sided operations are available by using instances of the [Win](#) class. New window objects are created by calling the [Win.Create](#) method at all processes within a communicator and specifying a memory buffer. When a window instance is no longer needed, the [Win.Free](#) method should be called.

The three one-sided MPI operations for remote write, read and reduction are available through calling the methods [Win.Put](#), [Win.Get](#), and [Win.Accumulate](#) respectively within a [Win](#) instance. These methods need an integer rank identifying the target process and an integer offset relative the base address of the remote memory block being accessed.

The one-sided operations read, write, and reduction are implicitly nonblocking, and must be synchronized by using two primary modes. Active target synchronization requires the origin process to call the [Win.Start](#) and [Win.Complete](#)



methods at the origin process, and target process cooperates by calling the *Win.Post* and *Win.Wait* methods. There is also a collective variant provided by the *Win.Fence* method. Passive target synchronization is more lenient, only the origin process calls the *Win.Lock* and *Win.Unlock* methods. Locks are used to protect remote accesses to the locked remote window and to protect local load/store accesses to a locked local window.

## 2.8 Parallel Input/Output

The POSIX standard provides a model of a widely portable file system. However, the optimization needed for parallel input/output cannot be achieved with this generic interface. In order to ensure efficiency and scalability, the underlying parallel input/output system must provide a high-level interface supporting partitioning of file data among processes and a collective interface supporting complete transfers of global data structures between process memories and files. Additionally, further efficiencies can be gained via support for asynchronous input/output, strided accesses to data, and control over physical file layout on storage devices. This scenario motivated the inclusion in the MPI-2 standard of a custom interface in order to support more elaborated parallel input/output operations.

The MPI specification for parallel input/output revolves around the use objects called *files*. As defined by MPI, files are not just contiguous byte streams. Instead, they are regarded as ordered collections of *typed* data items. MPI supports sequential or random access to any integral set of these items. Furthermore, files are opened collectively by a group of processes.

The common patterns for accessing a shared file (broadcast, scatter, gather, reduction) is expressed by using user-defined datatypes. Compared to the communication patterns of point-to-point and collective communications, this approach has the advantage of added flexibility and expressiveness. Data access operations (read and write) are defined for different kinds of positioning (using explicit offsets, individual file pointers, and shared file pointers), coordination (non-collective and collective), and synchronism (blocking, nonblocking, and split collective with begin/end phases).

In *MPI for Python*, all MPI input/output operations are performed through instances of the *File* class. File handles are obtained by calling the *File.Open* method at all processes within a communicator and providing a file name and the intended access mode. After use, they must be closed by calling the *File.Close* method. Files even can be deleted by calling method *File.Delete*.

After creation, files are typically associated with a per-process *view*. The view defines the current set of data visible and accessible from an open file as an ordered set of elementary datatypes. This data layout can be set and queried with the *File.Set\_view* and *File.Get\_view* methods respectively.

Actual input/output operations are achieved by many methods combining read and write calls with different behavior regarding positioning, coordination, and synchronism. Summing up, *MPI for Python* provides the thirty (30) methods defined in MPI-2 for reading from or writing to files using explicit offsets or file pointers (individual or shared), in blocking or nonblocking and collective or noncollective versions.

## 2.9 Environmental Management

### Initialization and Exit

Module functions *Init* or *Init\_thread* and *Finalize* provide MPI initialization and finalization respectively. Module functions *Is\_initialized* and *Is\_finalized* provide the respective tests for initialization and finalization.

---

**Note:** *MPI\_Init()* or *MPI\_Init\_thread()* is actually called when you import the *MPI* module from the *mpi4py* package, but only if MPI is not already initialized. In such case, calling *Init* or *Init\_thread* from Python is expected to generate an MPI error, and in turn an exception will be raised.

---

---

**Note:** *MPI\_Finalize()* is registered (by using Python C/API function *Py\_AtExit()*) for being automatically called when Python processes exit, but only if *mpi4py* actually initialized MPI. Therefore, there is no need to call *Finalize*

---

from Python to ensure MPI finalization.

---

## Implementation Information

- The MPI version number can be retrieved from module function `Get_version`. It returns a two-integer tuple (version, subversion).
- The `Get_processor_name` function can be used to access the processor name.
- The values of predefined attributes attached to the world communicator can be obtained by calling the `Comm.Get_attr` method within the `COMM_WORLD` instance.

## Timers

MPI timer functionalities are available through the `Wtime` and `Wtick` functions.

## Error Handling

In order facilitate handle sharing with other Python modules interfacing MPI-based parallel libraries, the predefined MPI error handlers `ERRORS_RETURN` and `ERRORS_ARE_FATAL` can be assigned to and retrieved from communicators using methods `Comm.Set_errhandler` and `Comm.Get_errhandler`, and similarly for windows and files.

When the predefined error handler `ERRORS_RETURN` is set, errors returned from MPI calls within Python code will raise an instance of the exception class `Exception`, which is a subclass of the standard Python exception `RuntimeError`.

---

**Note:** After import, mpi4py overrides the default MPI rules governing inheritance of error handlers. The `ERRORS_RETURN` error handler is set in the predefined `COMM_SELF` and `COMM_WORLD` communicators, as well as any new `Comm`, `Win`, or `File` instance created through mpi4py. If you ever pass such handles to C/C++/Fortran library code, it is recommended to set the `ERRORS_ARE_FATAL` error handler on them to ensure MPI errors do not pass silently.

---

**Warning:** Importing with `from mpi4py.MPI import *` will cause a name clashing with the standard Python `Exception` base class.

## 3 Tutorial

**Warning:** Under construction. Contributions very welcome!

---

**Tip:** Rolf Rabenseifner at HLRS developed a comprehensive MPI-3.1/4.0 course with slides and a large set of exercises including solutions. This material is [available online](#) for self-study. The slides and exercises show the C, Fortran, and Python (mpi4py) interfaces. For performance reasons, most Python exercises use NumPy arrays and communication routines involving buffer-like objects.

---

---

**Tip:** Victor Eijkhout at TACC authored the book *Parallel Programming for Science and Engineering*. This book is available online in [PDF](#) and [HTML](#) formats. The book covers parallel programming with MPI and OpenMP in C/C++ and Fortran, and MPI in Python using `mpi4py`.

---

*MPI for Python* supports convenient, *pickle*-based communication of generic Python object as well as fast, near C-speed, direct array data communication of buffer-provider objects (e.g., NumPy arrays).

- Communication of generic Python objects

You have to use methods with **all-lowercase** names, like `Comm.send`, `Comm.recv`, `Comm.bcast`, `Comm.scatter`, `Comm.gather`. An object to be sent is passed as a parameter to the communication call, and the received object is simply the return value.

The `Comm.isend` and `Comm.irecv` methods return `Request` instances; completion of these methods can be managed using the `Request.test` and `Request.wait` methods.

The `Comm.recv` and `Comm.irecv` methods may be passed a buffer object that can be repeatedly used to receive messages avoiding internal memory allocation. This buffer must be sufficiently large to accommodate the transmitted messages; hence, any buffer passed to `Comm.recv` or `Comm.irecv` must be at least as long as the *pickled* data transmitted to the receiver.

Collective calls like `Comm.scatter`, `Comm.gather`, `Comm.allgather`, `Comm.alltoall` expect a single value or a sequence of `Comm.size` elements at the root or all process. They return a single value, a list of `Comm.size` elements, or `None`.

---

**Note:** *MPI for Python* uses the **highest protocol version** available in the Python runtime (see the `HIGHEST_PROTOCOL` constant in the `pickle` module). The default protocol can be changed at import time by setting the `MPI4PY_PICKLE_PROTOCOL` environment variable, or at runtime by assigning a different value to the `PROTOCOL` attribute of the *pickle* object within the *MPI* module.

---

- Communication of buffer-like objects

You have to use method names starting with an **upper-case** letter, like `Comm.Send`, `Comm.Recv`, `Comm.Bcast`, `Comm.Scatter`, `Comm.Gather`.

In general, buffer arguments to these calls must be explicitly specified by using a 2/3-list/tuple like `[data, MPI.DOUBLE]`, or `[data, count, MPI.DOUBLE]` (the former one uses the byte-size of `data` and the extent of the MPI datatype to define `count`).

For vector collectives communication operations like `Comm.Scatterv` and `Comm.Gatherv`, buffer arguments are specified as `[data, count, displ, datatype]`, where `count` and `displ` are sequences of integral values.

Automatic MPI datatype discovery for NumPy/GPU arrays and PEP-3118 buffers is supported, but limited to basic C types (all C/C99-native signed/unsigned integral types and single/double precision real/complex floating types) and availability of matching datatypes in the underlying MPI implementation. In this case, the buffer-provider object can be passed directly as a buffer argument, the count and MPI datatype will be inferred.

If `mpi4py` is built against a GPU-aware MPI implementation, GPU arrays can be passed to upper-case methods as long as they have either the `__dlpack__` and `__dlpack_device__` methods or the `__cuda_array_interface__` attribute that are compliant with the respective standard specifications. Moreover, only C-contiguous or Fortran-contiguous GPU arrays are supported. It is important to note that GPU buffers must be fully ready before any MPI routines operate on them to avoid race conditions. This can be ensured by using the synchronization API of your array library. `mpi4py` does not have access to any GPU-specific functionality and thus cannot perform this operation automatically for users.

### 3.1 Running Python scripts with MPI

Most MPI programs can be run with the command **mpiexec**. In practice, running Python programs looks like:

```
$ mpiexec -n 4 python script.py
```

to run the program with 4 processors.

### 3.2 Point-to-Point Communication

- Python objects (*pickle* under the hood):

```
from mpi4py import MPI

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

if rank == 0:
    data = {'a': 7, 'b': 3.14}
    comm.send(data, dest=1, tag=11)
elif rank == 1:
    data = comm.recv(source=0, tag=11)
```

- Python objects with non-blocking communication:

```
from mpi4py import MPI

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

if rank == 0:
    data = {'a': 7, 'b': 3.14}
    req = comm.isend(data, dest=1, tag=11)
    req.wait()
elif rank == 1:
    req = comm.irecv(source=0, tag=11)
    data = req.wait()
```

- NumPy arrays (the fast way!):

```
from mpi4py import MPI
import numpy

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

# passing MPI datatypes explicitly
if rank == 0:
    data = numpy.arange(1000, dtype='i')
    comm.Send([data, MPI.INT], dest=1, tag=77)
elif rank == 1:
    data = numpy.empty(1000, dtype='i')
    comm.Recv([data, MPI.INT], source=0, tag=77)
```

(continues on next page)

```
# automatic MPI datatype discovery
if rank == 0:
    data = numpy.arange(100, dtype=numpy.float64)
    comm.Send(data, dest=1, tag=13)
elif rank == 1:
    data = numpy.empty(100, dtype=numpy.float64)
    comm.Recv(data, source=0, tag=13)
```

### 3.3 Collective Communication

- Broadcasting a Python dictionary:

```
from mpi4py import MPI

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

if rank == 0:
    data = {'key1' : [7, 2.72, 2+3j],
           'key2' : ('abc', 'xyz')}
else:
    data = None
data = comm.bcast(data, root=0)
```

- Scattering Python objects:

```
from mpi4py import MPI

comm = MPI.COMM_WORLD
size = comm.Get_size()
rank = comm.Get_rank()

if rank == 0:
    data = [(i+1)**2 for i in range(size)]
else:
    data = None
data = comm.scatter(data, root=0)
assert data == (rank+1)**2
```

- Gathering Python objects:

```
from mpi4py import MPI

comm = MPI.COMM_WORLD
size = comm.Get_size()
rank = comm.Get_rank()

data = (rank+1)**2
data = comm.gather(data, root=0)
if rank == 0:
```

(continues on next page)

(continued from previous page)

```
    for i in range(size):
        assert data[i] == (i+1)**2
else:
    assert data is None
```

- Broadcasting a NumPy array:

```
from mpi4py import MPI
import numpy as np

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

if rank == 0:
    data = np.arange(100, dtype='i')
else:
    data = np.empty(100, dtype='i')
comm.Bcast(data, root=0)
for i in range(100):
    assert data[i] == i
```

- Scattering NumPy arrays:

```
from mpi4py import MPI
import numpy as np

comm = MPI.COMM_WORLD
size = comm.Get_size()
rank = comm.Get_rank()

sendbuf = None
if rank == 0:
    sendbuf = np.empty([size, 100], dtype='i')
    sendbuf.T[:, :] = range(size)
recvbuf = np.empty(100, dtype='i')
comm.Scatter(sendbuf, recvbuf, root=0)
assert np.allclose(recvbuf, rank)
```

- Gathering NumPy arrays:

```
from mpi4py import MPI
import numpy as np

comm = MPI.COMM_WORLD
size = comm.Get_size()
rank = comm.Get_rank()

sendbuf = np.zeros(100, dtype='i') + rank
recvbuf = None
if rank == 0:
    recvbuf = np.empty([size, 100], dtype='i')
comm.Gather(sendbuf, recvbuf, root=0)
if rank == 0:
```

(continues on next page)

(continued from previous page)

```
for i in range(size):
    assert np.allclose(recvbuf[i,:], i)
```

- Parallel matrix-vector product:

```
from mpi4py import MPI
import numpy

def matvec(comm, A, x):
    m = A.shape[0] # local rows
    p = comm.Get_size()
    xg = numpy.zeros(m*p, dtype='d')
    comm.Allgather([x, MPI.DOUBLE],
                  [xg, MPI.DOUBLE])
    y = numpy.dot(A, xg)
    return y
```

## 3.4 MPI-IO

- Collective I/O with NumPy arrays:

```
from mpi4py import MPI
import numpy as np

amode = MPI.MODE_WRONLY | MPI.MODE_CREATE
comm = MPI.COMM_WORLD
fh = MPI.File.Open(comm, "./datafile.contig", amode)

buffer = np.empty(10, dtype=np.int)
buffer[:] = comm.Get_rank()

offset = comm.Get_rank()*buffer.nbytes
fh.Write_at_all(offset, buffer)

fh.Close()
```

- Non-contiguous Collective I/O with NumPy arrays and datatypes:

```
from mpi4py import MPI
import numpy as np

comm = MPI.COMM_WORLD
rank = comm.Get_rank()
size = comm.Get_size()

amode = MPI.MODE_WRONLY | MPI.MODE_CREATE
fh = MPI.File.Open(comm, "./datafile.noncontig", amode)

item_count = 10

buffer = np.empty(item_count, dtype='i')
```

(continues on next page)



(continued from previous page)

```
buffer[:] = rank

filetype = MPI.INT.Create_vector(item_count, 1, size)
filetype.Commit()

displacement = MPI.INT.Get_size()*rank
fh.Set_view(displacement, filetype=filetype)

fh.Write_all(buffer)
filetype.Free()
fh.Close()
```

### 3.5 Dynamic Process Management

- Compute Pi - Master (or parent, or client) side:

```
#!/usr/bin/env python
from mpi4py import MPI
import numpy
import sys

comm = MPI.COMM_SELF.Spawn(sys.executable,
                           args=['cpi.py'],
                           maxprocs=5)

N = numpy.array(100, 'i')
comm.Bcast([N, MPI.INT], root=MPI.ROOT)
PI = numpy.array(0.0, 'd')
comm.Reduce(None, [PI, MPI.DOUBLE],
            op=MPI.SUM, root=MPI.ROOT)
print(PI)

comm.Disconnect()
```

- Compute Pi - Worker (or child, or server) side:

```
#!/usr/bin/env python
from mpi4py import MPI
import numpy

comm = MPI.Comm.Get_parent()
size = comm.Get_size()
rank = comm.Get_rank()

N = numpy.array(0, dtype='i')
comm.Bcast([N, MPI.INT], root=0)
h = 1.0 / N; s = 0.0
for i in range(rank, N, size):
    x = h * (i + 0.5)
    s += 4.0 / (1.0 + x**2)
PI = numpy.array(s * h, dtype='d')
```

(continues on next page)

(continued from previous page)

```
comm.Reduce([PI, MPI.DOUBLE], None,  
            op=MPI.SUM, root=0)  
  
comm.Disconnect()
```

### 3.6 CUDA-aware MPI + Python GPU arrays

- Reduce-to-all CuPy arrays:

```
from mpi4py import MPI  
import cupy as cp  
  
comm = MPI.COMM_WORLD  
size = comm.Get_size()  
rank = comm.Get_rank()  
  
sendbuf = cp.arange(10, dtype='i')  
recvbuf = cp.empty_like(sendbuf)  
assert hasattr(sendbuf, '__cuda_array_interface__')  
assert hasattr(recvbuf, '__cuda_array_interface__')  
cp.cuda.get_current_stream().synchronize()  
comm.Allreduce(sendbuf, recvbuf)  
  
assert cp.allclose(recvbuf, sendbuf*size)
```

### 3.7 One-Sided Communications

- Read from (write to) the entire RMA window:

```
import numpy as np  
from mpi4py import MPI  
from mpi4py.util import dtlib  
  
comm = MPI.COMM_WORLD  
rank = comm.Get_rank()  
  
datatype = MPI.FLOAT  
np_dtype = dtlib.to_numpy_dtype(datatype)  
itemsize = datatype.Get_size()  
  
N = 10  
win_size = N * itemsize if rank == 0 else 0  
win = MPI.Win.Allocate(win_size, comm=comm)  
  
buf = np.empty(N, dtype=np_dtype)  
if rank == 0:  
    buf.fill(42)  
    win.Lock(rank=0)  
    win.Put(buf, target_rank=0)  
    win.Unlock(rank=0)
```

(continues on next page)

(continued from previous page)

```
comm.Barrier()
else:
    comm.Barrier()
    win.Lock(rank=0)
    win.Get(buf, target_rank=0)
    win.Unlock(rank=0)
    assert np.all(buf == 42)
```

- Accessing a part of the RMA window using the target argument, which is defined as (offset, count, datatype):

```
import numpy as np
from mpi4py import MPI
from mpi4py.util import dtlib

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

datatype = MPI.FLOAT
np_dtype = dtlib.to_numpy_dtype(datatype)
itemsz = datatype.Get_size()

N = comm.Get_size() + 1
win_size = N * itemsz if rank == 0 else 0
win = MPI.Win.Allocate(
    size=win_size,
    disp_unit=itemsz,
    comm=comm,
)
if rank == 0:
    mem = np.frombuffer(win, dtype=np_dtype)
    mem[:] = np.arange(len(mem), dtype=np_dtype)
comm.Barrier()

buf = np.zeros(3, dtype=np_dtype)
target = (rank, 2, datatype)
win.Lock(rank=0)
win.Get(buf, target_rank=0, target=target)
win.Unlock(rank=0)
assert np.all(buf == [rank, rank+1, 0])
```

### 3.8 Wrapping with SWIG

- C source:

```
/* file: helloworld.c */
void sayhello(MPI_Comm comm)
{
    int size, rank;
    MPI_Comm_size(comm, &size);
    MPI_Comm_rank(comm, &rank);
```

(continues on next page)

(continued from previous page)

```
printf("Hello, World! "  
      "I am process %d of %d.\n",  
      rank, size);  
}
```

- SWIG interface file:

```
// file: helloworld.i  
%module helloworld  
%{  
#include <mpi.h>  
#include "helloworld.c"  
}%  
  
%include mpi4py/mpi4py.i  
%mpi4py_map_type(Comm, MPI_Comm);  
void sayhello(MPI_Comm comm);
```

- Try it in the Python prompt:

```
>>> from mpi4py import MPI  
>>> import helloworld  
>>> helloworld.sayhello(MPI.COMM_WORLD)  
Hello, World! I am process 0 of 1.
```

### 3.9 Wrapping with F2Py

- Fortran 90 source:

```
! file: helloworld.f90  
subroutine sayhello(comm)  
  use mpi  
  implicit none  
  integer :: comm, rank, size, ierr  
  call MPI_Comm_size(comm, size, ierr)  
  call MPI_Comm_rank(comm, rank, ierr)  
  print *, 'Hello, World! I am process ',rank,' of ',size,'.'  
end subroutine sayhello
```

- Compiling example using f2py

```
$ f2py -c --f90exec=mpif90 helloworld.f90 -m helloworld
```

- Try it in the Python prompt:

```
>>> from mpi4py import MPI  
>>> import helloworld  
>>> fcomm = MPI.COMM_WORLD.py2f()  
>>> helloworld.sayhello(fcomm)  
Hello, World! I am process 0 of 1.
```

## 4 mpi4py

This is the **MPI for Python** package.

The *Message Passing Interface* (MPI) is a standardized and portable message-passing system designed to function on a wide variety of parallel computers. The MPI standard defines the syntax and semantics of library routines and allows users to write portable programs in the main scientific programming languages (Fortran, C, or C++). Since its release, the MPI specification has become the leading standard for message-passing libraries for parallel computers.

*MPI for Python* provides MPI bindings for the Python programming language, allowing any Python program to exploit multiple processors. This package build on the MPI specification and provides an object oriented interface which closely follows MPI-2 C++ bindings.

### 4.1 Runtime configuration options

`mpi4py.rc`

This object has attributes exposing runtime configuration options that become effective at import time of the *MPI* module.

#### Attributes Summary

<code>initialize</code>	Automatic MPI initialization at import
<code>threads</code>	Request initialization with thread support
<code>thread_level</code>	Level of thread support to request
<code>finalize</code>	Automatic MPI finalization at exit
<code>fast_reduce</code>	Use tree-based reductions for objects
<code>recv_mprobe</code>	Use matched probes to receive objects
<code>errors</code>	Error handling policy

#### Attributes Documentation

`mpi4py.rc.initialize`

Automatic MPI initialization at import.

**Type**

`bool`

**Default**

`True`

**See also:**

`MPI4PY_RC_INITIALIZE`

`mpi4py.rc.threads`

Request initialization with thread support.

**Type**

`bool`

**Default**

`True`

**See also:**

*MPI4PY\_RC\_THREADS*

**mpi4py.rc.thread\_level**

Level of thread support to request.

**Type**

`str`

**Default**

"multiple"

**Choices**

"multiple", "serialized", "funneled", "single"

**See also:**

*MPI4PY\_RC\_THREAD\_LEVEL*

**mpi4py.rc.finalize**

Automatic MPI finalization at exit.

**Type**

`None` or `bool`

**Default**

`None`

**See also:**

*MPI4PY\_RC\_FINALIZE*

**mpi4py.rc.fast\_reduce**

Use tree-based reductions for objects.

**Type**

`bool`

**Default**

`True`

**See also:**

*MPI4PY\_RC\_FAST\_REDUCE*

**mpi4py.rc.recv\_mprobe**

Use matched probes to receive objects.

**Type**

`bool`

**Default**

`True`

**See also:**

*MPI4PY\_RC\_RECV\_MPROBE*

**mpi4py.rc.errors**

Error handling policy.

**Type**

`str`

**Default**`"exception"`**Choices**`"exception", "default", "fatal"`**See also:**`MPI4PY_RC_ERRORS`

## Example

MPI for Python features automatic initialization and finalization of the MPI execution environment. By using the `mpi4py.rc` object, MPI initialization and finalization can be handled programmatically:

```
import mpi4py
mpi4py.rc.initialize = False # do not initialize MPI automatically
mpi4py.rc.finalize = False  # do not finalize MPI automatically

from mpi4py import MPI # import the 'MPI' module

MPI.Init()      # manual initialization of the MPI environment
...             # your finest code here ...
MPI.Finalize()  # manual finalization of the MPI environment
```

## 4.2 Environment variables

The following environment variables override the corresponding attributes of the `mpi4py.rc` and `MPI.pickle` objects at import time of the `MPI` module.

---

**Note:** For variables of boolean type, accepted values are 0 and 1 (interpreted as `False` and `True`, respectively), and strings specifying a `YAML boolean` value (case-insensitive).

---

### MPI4PY\_RC\_INITIALIZE

**Type**`bool`**Default**`True`

Whether to automatically initialize MPI at import time of the `mpi4py.MPI` module.

**See also:**`mpi4py.rc.initialize`

Added in version 3.1.0.

### MPI4PY\_RC\_FINALIZE

**Type**`None | bool`**Default**`None`



**Choices**

`None, True, False`

Whether to automatically finalize MPI at exit time of the Python process.

**See also:**

`mpi4py.rc.finalize`

Added in version 3.1.0.

**MPI4PY\_RC\_THREADS****Type**

`bool`

**Default**

`True`

Whether to initialize MPI with thread support.

**See also:**

`mpi4py.rc.threads`

Added in version 3.1.0.

**MPI4PY\_RC\_THREAD\_LEVEL****Default**

`"multiple"`

**Choices**

`"single", "funneled", "serialized", "multiple"`

The level of required thread support.

**See also:**

`mpi4py.rc.thread_level`

Added in version 3.1.0.

**MPI4PY\_RC\_FAST\_REDUCE****Type**

`bool`

**Default**

`True`

Whether to use tree-based reductions for objects.

**See also:**

`mpi4py.rc.fast_reduce`

Added in version 3.1.0.

**MPI4PY\_RC\_RECV\_MPROBE****Type**

`bool`

**Default**

`True`

Whether to use matched probes to receive objects.

**See also:**

[\*mpi4py.rc.recv\\_mprobe\*](#)

## **MPI4PY\_RC\_ERRORS**

**Default**

"exception"

**Choices**

"exception", "default", "fatal"

Controls default MPI error handling policy.

**See also:**

[\*mpi4py.rc.errors\*](#)

Added in version 3.1.0.

## **MPI4PY\_PICKLE\_PROTOCOL**

**Type**

`int`

**Default**

`pickle.HIGHEST_PROTOCOL`

Controls the default pickle protocol to use when communicating Python objects.

**See also:**

`PROTOCOL` attribute of the [\*MPI.pickle\*](#) object within the [\*MPI\*](#) module.

Added in version 3.1.0.

## **MPI4PY\_PICKLE\_THRESHOLD**

**Type**

`int`

**Default**

262144

Controls the default buffer size threshold for switching from in-band to out-of-band buffer handling when using pickle protocol version 5 or higher.

**See also:**

Module [\*mpi4py.util.pkl5\*](#).

Added in version 3.1.2.

## 4.3 Miscellaneous functions

`mpi4py.profile(name, *, path=None, logfile=None)`

Support for the MPI profiling interface.

### Parameters

- **name** (`str`) – Name of the profiler library to load.
- **path** (`sequence` of `str`, *optional*) – Additional paths to search for the profiler.
- **logfile** (`str`, *optional*) – Filename prefix for dumping profiler output.

### Return type

`None`

`mpi4py.get_config()`

Return a dictionary with information about MPI.

### Return type

`Dict[str, str]`

`mpi4py.get_include()`

Return the directory in the package that contains header files.

Extension modules that need to compile against mpi4py should use this function to locate the appropriate include directory. Using Python distutils (or perhaps NumPy distutils):

```
import mpi4py
Extension('extension_name', ...
        include_dirs=[..., mpi4py.get_include()])
```

### Return type

`str`

## 5 mpi4py.MPI

### 5.1 Classes

#### Ancillary

<code>Datatype</code> ([datatype])	Datatype object
<code>Status</code> ([status])	Status object
<code>Request</code> ([request])	Request handle
<code>Prerequest</code> ([request])	Persistent request handle
<code>Grerequest</code> ([request])	Generalized request handle
<code>Op</code> ([op])	Operation object
<code>Group</code> ([group])	Group of processes
<code>Info</code> ([info])	Info object

## Communication

<i>Comm</i> ([comm])	Communicator
<i>Intracomm</i> ([comm])	Intracommunicator
<i>Topocomm</i> ([comm])	Topology intracommunicator
<i>Cartcomm</i> ([comm])	Cartesian topology intracommunicator
<i>Graphcomm</i> ([comm])	General graph topology intracommunicator
<i>Distgraphcomm</i> ([comm])	Distributed graph topology intracommunicator
<i>Intercomm</i> ([comm])	Intercommunicator
<i>Message</i> ([message])	Matched message handle

## One-sided operations

<i>Win</i> ([win])	Window handle
--------------------	---------------

## Input/Output

<i>File</i> ([file])	File handle
----------------------	-------------

## Error handling

<i>Errhandler</i> ([errhandler])	Error handler
<i>Exception</i> ([ierr])	Exception class

## Auxiliary

<i>Pickle</i> ([dumps, loads, protocol])	Pickle/unpickle Python objects
<i>memory</i> (buf)	Memory buffer

## 5.2 Functions

### Version inquiry

<i>Get_version</i> ()	Obtain the version number of the MPI standard supported by the implementation as a tuple (version, subversion)
<i>Get_library_version</i> ()	Obtain the version string of the MPI library

## Initialization and finalization

<i>Init()</i>	Initialize the MPI execution environment
<i>Init_thread</i> ([required])	Initialize the MPI execution environment
<i>Finalize</i> ()	Terminate the MPI execution environment
<i>Is_initialized</i> ()	Indicates whether <i>Init</i> has been called
<i>Is_finalized</i> ()	Indicates whether <i>Finalize</i> has completed
<i>Query_thread</i> ()	Return the level of thread support provided by the MPI library
<i>Is_thread_main</i> ()	Indicate whether this thread called <i>Init</i> or <i>Init_thread</i>

## Memory allocation

<i>Alloc_mem</i> (size[, info])	Allocate memory for message passing and RMA
<i>Free_mem</i> (mem)	Free memory allocated with <i>Alloc_mem</i> ()

## Address manipulation

<i>Get_address</i> (location)	Get the address of a location in memory
<i>Aint_add</i> (base, disp)	Return the sum of base address and displacement
<i>Aint_diff</i> (addr1, addr2)	Return the difference between absolute addresses

## Timer

<i>Wtick</i> ()	Return the resolution of <i>Wtime</i>
<i>Wtime</i> ()	Return an elapsed time on the calling processor

## Error handling

<i>Get_error_class</i> (errorcode)	Convert an <i>error code</i> into an <i>error class</i>
<i>Get_error_string</i> (errorcode)	Return the <i>error string</i> for a given <i>error class</i> or <i>error code</i>
<i>Add_error_class</i> ()	Add an <i>error class</i> to the known error classes
<i>Add_error_code</i> (errorclass)	Add an <i>error code</i> to an <i>error class</i>
<i>Add_error_string</i> (errorcode, string)	Associate an <i>error string</i> with an <i>error class</i> or <i>error-code</i>

## Dynamic process management

<i>Open_port</i> ([info])	Return an address that can be used to establish connections between groups of MPI processes
<i>Close_port</i> (port_name)	Close a port
<i>Publish_name</i> (service_name, port_name[, info])	Publish a service name
<i>Unpublish_name</i> (service_name, port_name[, info])	Unpublish a service name
<i>Lookup_name</i> (service_name[, info])	Lookup a port name given a service name

## Miscellanea

<i>Attach_buffer</i> (buf)	Attach a user-provided buffer for sending in buffered mode
<i>Detach_buffer</i> ()	Remove an existing attached buffer
<i>Compute_dims</i> (nnodes, dims)	Return a balanced distribution of processes per coordinate direction
<i>Get_processor_name</i> ()	Obtain the name of the calling processor
<i>Register_datarep</i> (datarep, read_fn, write_fn, ...)	Register user-defined data representations
<i>Pcontrol</i> (level)	Control profiling

## Utilities

<i>get_vendor</i> ()	Information about the underlying MPI implementation
----------------------	---

## 5.3 Attributes

<i>UNDEFINED</i>	<i>int</i> UNDEFINED
<i>ANY_SOURCE</i>	<i>int</i> ANY_SOURCE
<i>ANY_TAG</i>	<i>int</i> ANY_TAG
<i>PROC_NULL</i>	<i>int</i> PROC_NULL
<i>ROOT</i>	<i>int</i> ROOT
<i>BOTTOM</i>	Bottom BOTTOM
<i>IN_PLACE</i>	InPlace IN_PLACE
<i>KEYVAL_INVALID</i>	<i>int</i> KEYVAL_INVALID
<i>TAG_UB</i>	<i>int</i> TAG_UB
<i>HOST</i>	<i>int</i> HOST
<i>IO</i>	<i>int</i> IO
<i>WTIME_IS_GLOBAL</i>	<i>int</i> WTIME_IS_GLOBAL
<i>UNIVERSE_SIZE</i>	<i>int</i> UNIVERSE_SIZE
<i>APPNUM</i>	<i>int</i> APPNUM
<i>LASTUSED</i>	<i>int</i> LASTUSED
<i>WIN_BASE</i>	<i>int</i> WIN_BASE
<i>WIN_SIZE</i>	<i>int</i> WIN_SIZE
<i>WIN_DISP_UNIT</i>	<i>int</i> WIN_DISP_UNIT
<i>WIN_CREATE_FLAVOR</i>	<i>int</i> WIN_CREATE_FLAVOR

continues on next page

Table 1 – continued from previous page

WIN_FLAVOR	int WIN_FLAVOR
WIN_MODEL	int WIN_MODEL
SUCCESS	int SUCCESS
ERR_LASTCODE	int ERR_LASTCODE
ERR_COMM	int ERR_COMM
ERR_GROUP	int ERR_GROUP
ERR_TYPE	int ERR_TYPE
ERR_REQUEST	int ERR_REQUEST
ERR_OP	int ERR_OP
ERR_BUFFER	int ERR_BUFFER
ERR_COUNT	int ERR_COUNT
ERR_TAG	int ERR_TAG
ERR_RANK	int ERR_RANK
ERR_ROOT	int ERR_ROOT
ERR_TRUNCATE	int ERR_TRUNCATE
ERR_IN_STATUS	int ERR_IN_STATUS
ERR_PENDING	int ERR_PENDING
ERR_TOPOLOGY	int ERR_TOPOLOGY
ERR_DIMS	int ERR_DIMS
ERR_ARG	int ERR_ARG
ERR_OTHER	int ERR_OTHER
ERR_UNKNOWN	int ERR_UNKNOWN
ERR_INTERN	int ERR_INTERN
ERR_INFO	int ERR_INFO
ERR_FILE	int ERR_FILE
ERR_WIN	int ERR_WIN
ERR_KEYVAL	int ERR_KEYVAL
ERR_INFO_KEY	int ERR_INFO_KEY
ERR_INFO_VALUE	int ERR_INFO_VALUE
ERR_INFO_NOKEY	int ERR_INFO_NOKEY
ERR_ACCESS	int ERR_ACCESS
ERR_AMODE	int ERR_AMODE
ERR_BAD_FILE	int ERR_BAD_FILE
ERR_FILE_EXISTS	int ERR_FILE_EXISTS
ERR_FILE_IN_USE	int ERR_FILE_IN_USE
ERR_NO_SPACE	int ERR_NO_SPACE
ERR_NO_SUCH_FILE	int ERR_NO_SUCH_FILE
ERR_IO	int ERR_IO
ERR_READ_ONLY	int ERR_READ_ONLY
ERR_CONVERSION	int ERR_CONVERSION
ERR_DUP_DATAREP	int ERR_DUP_DATAREP
ERR_UNSUPPORTED_DATAREP	int ERR_UNSUPPORTED_DATAREP
ERR_UNSUPPORTED_OPERATION	int ERR_UNSUPPORTED_OPERATION
ERR_NAME	int ERR_NAME
ERR_NO_MEM	int ERR_NO_MEM
ERR_NOT_SAME	int ERR_NOT_SAME
ERR_PORT	int ERR_PORT
ERR_QUOTA	int ERR_QUOTA
ERR_SERVICE	int ERR_SERVICE
ERR_SPAWN	int ERR_SPAWN
ERR_BASE	int ERR_BASE
ERR_SIZE	int ERR_SIZE

continues on next page



Table 1 – continued from previous page

ERR_DISP	int ERR_DISP
ERR_ASSERT	int ERR_ASSERT
ERR_LOCKTYPE	int ERR_LOCKTYPE
ERR_RMA_CONFLICT	int ERR_RMA_CONFLICT
ERR_RMA_SYNC	int ERR_RMA_SYNC
ERR_RMA_RANGE	int ERR_RMA_RANGE
ERR_RMA_ATTACH	int ERR_RMA_ATTACH
ERR_RMA_SHARED	int ERR_RMA_SHARED
ERR_RMA_FLAVOR	int ERR_RMA_FLAVOR
ORDER_C	int ORDER_C
ORDER_F	int ORDER_F
ORDER_FORTRAN	int ORDER_FORTRAN
TYPECLASS_INTEGER	int TYPECLASS_INTEGER
TYPECLASS_REAL	int TYPECLASS_REAL
TYPECLASS_COMPLEX	int TYPECLASS_COMPLEX
DISTRIBUTE_NONE	int DISTRIBUTE_NONE
DISTRIBUTE_BLOCK	int DISTRIBUTE_BLOCK
DISTRIBUTE_CYCLIC	int DISTRIBUTE_CYCLIC
DISTRIBUTE_DFLT_DARG	int DISTRIBUTE_DFLT_DARG
COMBINER_NAMED	int COMBINER_NAMED
COMBINER_DUP	int COMBINER_DUP
COMBINER_CONTIGUOUS	int COMBINER_CONTIGUOUS
COMBINER_VECTOR	int COMBINER_VECTOR
COMBINER_HVECTOR	int COMBINER_HVECTOR
COMBINER_INDEXED	int COMBINER_INDEXED
COMBINER_HINDEXED	int COMBINER_HINDEXED
COMBINER_INDEXED_BLOCK	int COMBINER_INDEXED_BLOCK
COMBINER_HINDEXED_BLOCK	int COMBINER_HINDEXED_BLOCK
COMBINER_STRUCT	int COMBINER_STRUCT
COMBINER_SUBARRAY	int COMBINER_SUBARRAY
COMBINER_DARRAY	int COMBINER_DARRAY
COMBINER_RESIZED	int COMBINER_RESIZED
COMBINER_F90_REAL	int COMBINER_F90_REAL
COMBINER_F90_COMPLEX	int COMBINER_F90_COMPLEX
COMBINER_F90_INTEGER	int COMBINER_F90_INTEGER
IDENT	int IDENT
CONGRUENT	int CONGRUENT
SIMILAR	int SIMILAR
UNEQUAL	int UNEQUAL
CART	int CART
GRAPH	int GRAPH
DIST_GRAPH	int DIST_GRAPH
UNWEIGHTED	int UNWEIGHTED
WEIGHTS_EMPTY	int WEIGHTS_EMPTY
COMM_TYPE_SHARED	int COMM_TYPE_SHARED
BSEND_OVERHEAD	int BSEND_OVERHEAD
WIN_FLAVOR_CREATE	int WIN_FLAVOR_CREATE
WIN_FLAVOR_ALLOCATE	int WIN_FLAVOR_ALLOCATE
WIN_FLAVOR_DYNAMIC	int WIN_FLAVOR_DYNAMIC
WIN_FLAVOR_SHARED	int WIN_FLAVOR_SHARED
WIN_SEPARATE	int WIN_SEPARATE
WIN_UNIFIED	int WIN_UNIFIED

continues on next page

Table 1 – continued from previous page

MODE_NOCHECK	int MODE_NOCHECK
MODE_NOSTORE	int MODE_NOSTORE
MODE_NOPUT	int MODE_NOPUT
MODE_NOPRECEDE	int MODE_NOPRECEDE
MODE_NOSUCCEED	int MODE_NOSUCCEED
LOCK_EXCLUSIVE	int LOCK_EXCLUSIVE
LOCK_SHARED	int LOCK_SHARED
MODE_RDONLY	int MODE_RDONLY
MODE_WRONLY	int MODE_WRONLY
MODE_RDWR	int MODE_RDWR
MODE_CREATE	int MODE_CREATE
MODE_EXCL	int MODE_EXCL
MODE_DELETE_ON_CLOSE	int MODE_DELETE_ON_CLOSE
MODE_UNIQUE_OPEN	int MODE_UNIQUE_OPEN
MODE_SEQUENTIAL	int MODE_SEQUENTIAL
MODE_APPEND	int MODE_APPEND
SEEK_SET	int SEEK_SET
SEEK_CUR	int SEEK_CUR
SEEK_END	int SEEK_END
DISPLACEMENT_CURRENT	int DISPLACEMENT_CURRENT
DISP_CUR	int DISP_CUR
THREAD_SINGLE	int THREAD_SINGLE
THREAD_FUNNELED	int THREAD_FUNNELED
THREAD_SERIALIZED	int THREAD_SERIALIZED
THREAD_MULTIPLE	int THREAD_MULTIPLE
VERSION	int VERSION
SUBVERSION	int SUBVERSION
MAX_PROCESSOR_NAME	int MAX_PROCESSOR_NAME
MAX_ERROR_STRING	int MAX_ERROR_STRING
MAX_PORT_NAME	int MAX_PORT_NAME
MAX_INFO_KEY	int MAX_INFO_KEY
MAX_INFO_VAL	int MAX_INFO_VAL
MAX_OBJECT_NAME	int MAX_OBJECT_NAME
MAX_DATAREP_STRING	int MAX_DATAREP_STRING
MAX_LIBRARY_VERSION_STRING	int MAX_LIBRARY_VERSION_STRING
DATATYPE_NULL	Datatype DATATYPE_NULL
UB	Datatype UB
LB	Datatype LB
PACKED	Datatype PACKED
BYTE	Datatype BYTE
AINT	Datatype AINT
OFFSET	Datatype OFFSET
COUNT	Datatype COUNT
CHAR	Datatype CHAR
WCHAR	Datatype WCHAR
SIGNED_CHAR	Datatype SIGNED_CHAR
SHORT	Datatype SHORT
INT	Datatype INT
LONG	Datatype LONG
LONG_LONG	Datatype LONG_LONG
UNSIGNED_CHAR	Datatype UNSIGNED_CHAR
UNSIGNED_SHORT	Datatype UNSIGNED_SHORT

continues on next page

Table 1 – continued from previous page

UNSIGNED	Datatype UNSIGNED
UNSIGNED_LONG	Datatype UNSIGNED_LONG
UNSIGNED_LONG_LONG	Datatype UNSIGNED_LONG_LONG
FLOAT	Datatype FLOAT
DOUBLE	Datatype DOUBLE
LONG_DOUBLE	Datatype LONG_DOUBLE
C_BOOL	Datatype C_BOOL
INT8_T	Datatype INT8_T
INT16_T	Datatype INT16_T
INT32_T	Datatype INT32_T
INT64_T	Datatype INT64_T
UINT8_T	Datatype UINT8_T
UINT16_T	Datatype UINT16_T
UINT32_T	Datatype UINT32_T
UINT64_T	Datatype UINT64_T
C_COMPLEX	Datatype C_COMPLEX
C_FLOAT_COMPLEX	Datatype C_FLOAT_COMPLEX
C_DOUBLE_COMPLEX	Datatype C_DOUBLE_COMPLEX
C_LONG_DOUBLE_COMPLEX	Datatype C_LONG_DOUBLE_COMPLEX
CXX_BOOL	Datatype CXX_BOOL
CXX_FLOAT_COMPLEX	Datatype CXX_FLOAT_COMPLEX
CXX_DOUBLE_COMPLEX	Datatype CXX_DOUBLE_COMPLEX
CXX_LONG_DOUBLE_COMPLEX	Datatype CXX_LONG_DOUBLE_COMPLEX
SHORT_INT	Datatype SHORT_INT
INT_INT	Datatype INT_INT
TWOINT	Datatype TWOINT
LONG_INT	Datatype LONG_INT
FLOAT_INT	Datatype FLOAT_INT
DOUBLE_INT	Datatype DOUBLE_INT
LONG_DOUBLE_INT	Datatype LONG_DOUBLE_INT
CHARACTER	Datatype CHARACTER
LOGICAL	Datatype LOGICAL
INTEGER	Datatype INTEGER
REAL	Datatype REAL
DOUBLE_PRECISION	Datatype DOUBLE_PRECISION
COMPLEX	Datatype COMPLEX
DOUBLE_COMPLEX	Datatype DOUBLE_COMPLEX
LOGICAL1	Datatype LOGICAL1
LOGICAL2	Datatype LOGICAL2
LOGICAL4	Datatype LOGICAL4
LOGICAL8	Datatype LOGICAL8
INTEGER1	Datatype INTEGER1
INTEGER2	Datatype INTEGER2
INTEGER4	Datatype INTEGER4
INTEGER8	Datatype INTEGER8
INTEGER16	Datatype INTEGER16
REAL2	Datatype REAL2
REAL4	Datatype REAL4
REAL8	Datatype REAL8
REAL16	Datatype REAL16
COMPLEX4	Datatype COMPLEX4
COMPLEX8	Datatype COMPLEX8

continues on next page

Table 1 – continued from previous page

COMPLEX16	<i>Datatype</i> COMPLEX16
COMPLEX32	<i>Datatype</i> COMPLEX32
UNSIGNED_INT	<i>Datatype</i> UNSIGNED_INT
SIGNED_SHORT	<i>Datatype</i> SIGNED_SHORT
SIGNED_INT	<i>Datatype</i> SIGNED_INT
SIGNED_LONG	<i>Datatype</i> SIGNED_LONG
SIGNED_LONG_LONG	<i>Datatype</i> SIGNED_LONG_LONG
BOOL	<i>Datatype</i> BOOL
SINT8_T	<i>Datatype</i> SINT8_T
SINT16_T	<i>Datatype</i> SINT16_T
SINT32_T	<i>Datatype</i> SINT32_T
SINT64_T	<i>Datatype</i> SINT64_T
F_BOOL	<i>Datatype</i> F_BOOL
F_INT	<i>Datatype</i> F_INT
F_FLOAT	<i>Datatype</i> F_FLOAT
F_DOUBLE	<i>Datatype</i> F_DOUBLE
F_COMPLEX	<i>Datatype</i> F_COMPLEX
F_FLOAT_COMPLEX	<i>Datatype</i> F_FLOAT_COMPLEX
F_DOUBLE_COMPLEX	<i>Datatype</i> F_DOUBLE_COMPLEX
REQUEST_NULL	<i>Request</i> REQUEST_NULL
MESSAGE_NULL	<i>Message</i> MESSAGE_NULL
MESSAGE_NO_PROC	<i>Message</i> MESSAGE_NO_PROC
OP_NULL	<i>Op</i> OP_NULL
MAX	<i>Op</i> MAX
MIN	<i>Op</i> MIN
SUM	<i>Op</i> SUM
PROD	<i>Op</i> PROD
LAND	<i>Op</i> LAND
BAND	<i>Op</i> BAND
LOR	<i>Op</i> LOR
BOR	<i>Op</i> BOR
LXOR	<i>Op</i> LXOR
BXOR	<i>Op</i> BXOR
MAXLOC	<i>Op</i> MAXLOC
MINLOC	<i>Op</i> MINLOC
REPLACE	<i>Op</i> REPLACE
NO_OP	<i>Op</i> NO_OP
GROUP_NULL	<i>Group</i> GROUP_NULL
GROUP_EMPTY	<i>Group</i> GROUP_EMPTY
INFO_NULL	<i>Info</i> INFO_NULL
INFO_ENV	<i>Info</i> INFO_ENV
ERRHANDLER_NULL	<i>Errhandler</i> ERRHANDLER_NULL
ERRORS_RETURN	<i>Errhandler</i> ERRORS_RETURN
ERRORS_ARE_FATAL	<i>Errhandler</i> ERRORS_ARE_FATAL
COMM_NULL	<i>Comm</i> COMM_NULL
COMM_SELF	<i>Intracomm</i> COMM_SELF
COMM_WORLD	<i>Intracomm</i> COMM_WORLD
WIN_NULL	<i>Win</i> WIN_NULL
FILE_NULL	<i>File</i> FILE_NULL
pickle	<i>Pickle</i> pickle

## 6 mpi4py.futures

Added in version 3.0.0.

This package provides a high-level interface for asynchronously executing callables on a pool of worker processes using MPI for inter-process communication.

### 6.1 concurrent.futures

The `mpi4py.futures` package is based on `concurrent.futures` from the Python standard library. More precisely, `mpi4py.futures` provides the `MPIPoolExecutor` class as a concrete implementation of the abstract class `Executor`. The `submit()` interface schedules a callable to be executed asynchronously and returns a `Future` object representing the execution of the callable. `Future` instances can be queried for the call result or exception. Sets of `Future` instances can be passed to the `wait()` and `as_completed()` functions.

---

**Note:** The `concurrent.futures` package was introduced in Python 3.2. A `backport` targeting Python 2.7 is available on PyPI. The `mpi4py.futures` package uses `concurrent.futures` if available, either from the Python 3 standard library or the Python 2.7 backport if installed. Otherwise, `mpi4py.futures` uses a bundled copy of core functionality backported from Python 3.5 to work with Python 2.7.

---

See also:

Module `concurrent.futures`

Documentation of the `concurrent.futures` standard module.

### 6.2 MPIPoolExecutor

The `MPIPoolExecutor` class uses a pool of MPI processes to execute calls asynchronously. By performing computations in separate processes, it allows to side-step the `global interpreter lock` but also means that only picklable objects can be executed and returned. The `__main__` module must be importable by worker processes, thus `MPIPoolExecutor` instances may not work in the interactive interpreter.

`MPIPoolExecutor` takes advantage of the dynamic process management features introduced in the MPI-2 standard. In particular, the `MPI.Intracomm.Spawn` method of `MPI.COMM_SELF` is used in the master (or parent) process to spawn new worker (or child) processes running a Python interpreter. The master process uses a separate thread (one for each `MPIPoolExecutor` instance) to communicate back and forth with the workers. The worker processes serve the execution of tasks in the main (and only) thread until they are signaled for completion.

---

**Note:** The worker processes must import the main script in order to *unpickle* any callable defined in the `__main__` module and submitted from the master process. Furthermore, the callables may need access to other global variables. At the worker processes, `mpi4py.futures` executes the main script code (using the `runpy` module) under the `__worker__` namespace to define the `__main__` module. The `__main__` and `__worker__` modules are added to `sys.modules` (both at the master and worker processes) to ensure proper *pickling* and *unpickling*.

---

**Warning:** During the initial import phase at the workers, the main script cannot create and use new `MPIPoolExecutor` instances. Otherwise, each worker would attempt to spawn a new pool of workers, leading to infinite recursion. `mpi4py.futures` detects such recursive attempts to spawn new workers and aborts the MPI execution environment. As the main script code is run under the `__worker__` namespace, the easiest way to avoid spawn recursion is using the idiom `if __name__ == '__main__': ...` in the main script.

**class** `mpi4py.futures.MPIPoolExecutor`(*max\_workers=None, initializer=None, initargs=(), \*\*kwargs*)

An `Executor` subclass that executes calls asynchronously using a pool of at most *max\_workers* processes. If *max\_workers* is `None` or not given, its value is determined from the `MPI4PY_FUTURES_MAX_WORKERS` environment variable if set, or the MPI universe size if set, otherwise a single worker process is spawned. If *max\_workers* is lower than or equal to 0, then a `ValueError` will be raised.

*initializer* is an optional callable that is called at the start of each worker process before executing any tasks; *initargs* is a tuple of arguments passed to the initializer. If *initializer* raises an exception, all pending tasks and any attempt to submit new tasks to the pool will raise a `BrokenExecutor` exception.

Other parameters:

- *python\_exe*: Path to the Python interpreter executable used to spawn worker processes, otherwise `sys.executable` is used.
- *python\_args*: `list` or iterable with additional command line flags to pass to the Python executable. Command line flags determined from inspection of `sys.flags`, `sys.warnoptions` and `sys.xoptions` in are passed unconditionally.
- *mpi\_info*: `dict` or iterable yielding (key, value) pairs. These (key, value) pairs are passed (through an `MPI.Info` object) to the `MPI.Intracomm.Spawn` call used to spawn worker processes. This mechanism allows telling the MPI runtime system where and how to start the processes. Check the documentation of the backend MPI implementation about the set of keys it interprets and the corresponding format for values.
- *globals*: `dict` or iterable yielding (name, value) pairs to initialize the main module namespace in worker processes.
- *main*: If set to `False`, do not import the `__main__` module in worker processes. Setting *main* to `False` prevents worker processes from accessing definitions in the parent `__main__` namespace.
- *path*: `list` or iterable with paths to append to `sys.path` in worker processes to extend the module search path.
- *wdir*: Path to set the current working directory in worker processes using `os.chdir()`. The initial working directory is set by the MPI implementation. Quality MPI implementations should honor a *wdir* info key passed through *mpi\_info*, although such feature is not mandatory.
- *env*: `dict` or iterable yielding (name, value) pairs with environment variables to update `os.environ` in worker processes. The initial environment is set by the MPI implementation. MPI implementations may allow setting the initial environment through *mpi\_info*, however such feature is not required nor recommended by the MPI standard.

**submit**(*func, \*args, \*\*kwargs*)

Schedule the callable, *func*, to be executed as `func(*args, **kwargs)` and returns a `Future` object representing the execution of the callable.

```
executor = MPIPoolExecutor(max_workers=1)
future = executor.submit(pow, 321, 1234)
print(future.result())
```

**map**(*func, \*iterables, timeout=None, chunksize=1, \*\*kwargs*)

Equivalent to `map(func, *iterables)` except *func* is executed asynchronously and several calls to *func* may be made concurrently, out-of-order, in separate processes. The returned iterator raises a `TimeoutError` if `__next__()` is called and the result isn't available after *timeout* seconds from the original call to `map()`. *timeout* can be an int or a float. If *timeout* is not specified or `None`, there is no limit to the wait time. If a call raises an exception, then that exception will be raised when its value is retrieved from the iterator. This method chops *iterables* into a number of chunks which it submits to the pool as separate tasks. The (approximate) size of these chunks can be specified by setting *chunksize* to a positive integer. For very long iterables, using a large value for *chunksize* can significantly improve performance compared

to the default size of one. By default, the returned iterator yields results in-order, waiting for successive tasks to complete. This behavior can be changed by passing the keyword argument `unordered` as `True`, then the result iterator will yield a result as soon as any of the tasks complete.

```
executor = MPIPoolExecutor(max_workers=3)
for result in executor.map(pow, [2]*32, range(32)):
    print(result)
```

**starmap**(*func, iterable, timeout=None, chunksize=1, \*\*kwargs*)

Equivalent to `itertools.starmap(func, iterable)`. Used instead of `map()` when argument parameters are already grouped in tuples from a single iterable (the data has been “pre-zipped”). `map(func, *iterable)` is equivalent to `starmap(func, zip(*iterable))`.

```
executor = MPIPoolExecutor(max_workers=3)
iterable = ((2, n) for n in range(32))
for result in executor.starmap(pow, iterable):
    print(result)
```

**shutdown**(*wait=True, cancel\_futures=False*)

Signal the executor that it should free any resources that it is using when the currently pending futures are done executing. Calls to `submit()` and `map()` made after `shutdown()` will raise `RuntimeError`.

If `wait` is `True` then this method will not return until all the pending futures are done executing and the resources associated with the executor have been freed. If `wait` is `False` then this method will return immediately and the resources associated with the executor will be freed when all pending futures are done executing. Regardless of the value of `wait`, the entire Python program will not exit until all pending futures are done executing.

If `cancel_futures` is `True`, this method will cancel all pending futures that the executor has not started running. Any futures that are completed or running won’t be cancelled, regardless of the value of `cancel_futures`.

You can avoid having to call this method explicitly if you use the `with` statement, which will shutdown the executor instance (waiting as if `shutdown()` were called with `wait` set to `True`).

```
import time
with MPIPoolExecutor(max_workers=1) as executor:
    future = executor.submit(time.sleep, 2)
assert future.done()
```

**bootup**(*wait=True*)

Signal the executor that it should allocate eagerly any required resources (in particular, MPI worker processes). If `wait` is `True`, then `bootup()` will not return until the executor resources are ready to process submissions. Resources are automatically allocated in the first call to `submit()`, thus calling `bootup()` explicitly is seldom needed.

## **MPI4PY\_FUTURES\_MAX\_WORKERS**

If the `max_workers` parameter to `MPIPoolExecutor` is `None` or not given, the `MPI4PY_FUTURES_MAX_WORKERS` environment variable provides fallback value for the maximum number of MPI worker processes to spawn.

---

**Note:** As the master process uses a separate thread to perform MPI communication with the workers, the backend MPI implementation should provide support for `MPI.THREAD_MULTIPLE`. However, some popular MPI implementations do not support yet concurrent MPI calls from multiple threads. Additionally, users may decide to initialize MPI with a lower level of thread support. If the level of thread support in the backend MPI is less than `MPI`.



`THREAD_MULTIPLE`, `mpi4py.futures` will use a global lock to serialize MPI calls. If the level of thread support is less than `MPI.THREAD_SERIALIZED`, `mpi4py.futures` will emit a `RuntimeWarning`.

**Warning:** If the level of thread support in the backend MPI is less than `MPI.THREAD_SERIALIZED` (i.e., it is either `MPI.THREAD_SINGLE` or `MPI.THREAD_FUNNELED`), in theory `mpi4py.futures` cannot be used. Rather than raising an exception, `mpi4py.futures` emits a warning and takes a “cross-fingers” attitude to continue execution in the hope that serializing MPI calls with a global lock will actually work.

## 6.3 MPICommExecutor

Legacy MPI-1 implementations (as well as some vendor MPI-2 implementations) do not support the dynamic process management features introduced in the MPI-2 standard. Additionally, job schedulers and batch systems in supercomputing facilities may pose additional complications to applications using the `MPI_Comm_spawn()` routine.

With these issues in mind, `mpi4py.futures` supports an additional, more traditional, SPMD-like usage pattern requiring MPI-1 calls only. Python applications are started the usual way, e.g., using the `mpiexec` command. Python code should make a collective call to the `MPICommExecutor` context manager to partition the set of MPI processes within a MPI communicator in one master processes and many workers processes. The master process gets access to an `MPIPoolExecutor` instance to submit tasks. Meanwhile, the worker process follow a different execution path and team-up to execute the tasks submitted from the master.

Besides alleviating the lack of dynamic process management features in legacy MPI-1 or partial MPI-2 implementations, the `MPICommExecutor` context manager may be useful in classic MPI-based Python applications willing to take advantage of the simple, task-based, master/worker approach available in the `mpi4py.futures` package.

**class** `mpi4py.futures.MPICommExecutor(comm=None, root=0)`

Context manager for `MPIPoolExecutor`. This context manager splits a MPI (intra)communicator `comm` (defaults to `MPI.COMM_WORLD` if not provided or `None`) in two disjoint sets: a single master process (with rank `root` in `comm`) and the remaining worker processes. These sets are then connected through an intercommunicator. The target of the `with` statement is assigned either an `MPIPoolExecutor` instance (at the master) or `None` (at the workers).

```
from mpi4py import MPI
from mpi4py.futures import MPICommExecutor

with MPICommExecutor(MPI.COMM_WORLD, root=0) as executor:
    if executor is not None:
        future = executor.submit(abs, -42)
        assert future.result() == 42
        answer = set(executor.map(abs, [-42, 42]))
        assert answer == {42}
```

**Warning:** If `MPICommExecutor` is passed a communicator of size one (e.g., `MPI.COMM_SELF`), then the executor instance assigned to the target of the `with` statement will execute all submitted tasks in a single worker thread, thus ensuring that task execution still progress asynchronously. However, the `GIL` will prevent the main and worker threads from running concurrently in multicore processors. Moreover, the thread context switching may harm noticeably the performance of CPU-bound tasks. In case of I/O-bound tasks, the `GIL` is not usually an issue, however, as a single worker thread is used, it progress one task at a time. We advice against using `MPICommExecutor` with communicators of size one and suggest refactoring your code to use instead a `ThreadPoolExecutor`.

## 6.4 Command line

Recalling the issues related to the lack of support for dynamic process management features in MPI implementations, `mpi4py.futures` supports an alternative usage pattern where Python code (either from scripts, modules, or zip files) is run under command line control of the `mpi4py.futures` package by passing `-m mpi4py.futures` to the **python** executable. The `mpi4py.futures` invocation should be passed a *pyfile* path to a script (or a zipfile/directory containing a `__main__.py` file). Additionally, `mpi4py.futures` accepts `-m mod` to execute a module named *mod*, `-c cmd` to execute a command string *cmd*, or even `-` to read commands from standard input (`sys.stdin`). Summarizing, `mpi4py.futures` can be invoked in the following ways:

- `$ mpiexec -n numprocs python -m mpi4py.futures pyfile [arg] ...`
- `$ mpiexec -n numprocs python -m mpi4py.futures -m mod [arg] ...`
- `$ mpiexec -n numprocs python -m mpi4py.futures -c cmd [arg] ...`
- `$ mpiexec -n numprocs python -m mpi4py.futures - [arg] ...`

Before starting the main script execution, `mpi4py.futures` splits `MPI.COMM_WORLD` in one master (the process with rank 0 in `MPI.COMM_WORLD`) and `numprocs - 1` workers and connects them through an MPI intercommunicator. Afterwards, the master process proceeds with the execution of the user script code, which eventually creates `MPIPoolExecutor` instances to submit tasks. Meanwhile, the worker processes follow a different execution path to serve the master. Upon successful termination of the main script at the master, the entire MPI execution environment exists gracefully. In case of any unhandled exception in the main script, the master process calls `MPI.COMM_WORLD.Abort(1)` to prevent deadlocks and force termination of entire MPI execution environment.

**Warning:** Running scripts under command line control of `mpi4py.futures` is quite similar to executing a single-process application that spawn additional workers as required. However, there is a very important difference users should be aware of. All `MPIPoolExecutor` instances created at the master will share the pool of workers. Tasks submitted at the master from many different executors will be scheduled for execution in random order as soon as a worker is idle. Any executor can easily starve all the workers (e.g., by calling `MPIPoolExecutor.map()` with long iterables). If that ever happens, submissions from other executors will not be serviced until free workers are available.

See also:

### Command line

Documentation on Python command line interface.

## 6.5 Examples

The following `julia.py` script computes the **Julia set** and dumps an image to disk in binary **PGM** format. The code starts by importing `MPIPoolExecutor` from the `mpi4py.futures` package. Next, some global constants and functions implement the computation of the Julia set. The computations are protected with the standard `if __name__ == '__main__':...` idiom. The image is computed by whole scanlines submitting all these tasks at once using the `map` method. The result iterator yields scanlines in-order as the tasks complete. Finally, each scanline is dumped to disk.

Listing 1: `julia.py`

```
1 from mpi4py.futures import MPIPoolExecutor
2
3 x0, x1, w = -2.0, +2.0, 640*2
4 y0, y1, h = -1.5, +1.5, 480*2
5 dx = (x1 - x0) / w
```

(continues on next page)

```

6  dy = (y1 - y0) / h
7
8  c = complex(0, 0.65)
9
10 def julia(x, y):
11     z = complex(x, y)
12     n = 255
13     while abs(z) < 3 and n > 1:
14         z = z**2 + c
15         n -= 1
16     return n
17
18 def julia_line(k):
19     line = bytearray(w)
20     y = y1 - k * dy
21     for j in range(w):
22         x = x0 + j * dx
23         line[j] = julia(x, y)
24     return line
25
26 if __name__ == '__main__':
27
28     with MPIPoolExecutor() as executor:
29         image = executor.map(julia_line, range(h))
30     with open('julia.pgm', 'wb') as f:
31         f.write(b'P5 %d %d %d\n' % (w, h, 255))
32         for line in image:
33             f.write(line)

```

The recommended way to execute the script is by using the **mpiexec** command specifying one MPI process (master) and (optional but recommended) the desired MPI universe size, which determines the number of additional dynamically spawned processes (workers). The MPI universe size is provided either by a batch system or set by the user via command-line arguments to **mpiexec** or environment variables. Below we provide examples for MPICH and Open MPI implementations<sup>1</sup>. In all of these examples, the **mpiexec** command launches a single master process running the Python interpreter and executing the main script. When required, *mpi4py.futures* spawns the pool of 16 worker processes. The master submits tasks to the workers and waits for the results. The workers receive incoming tasks, execute them, and send back the results to the master.

When using MPICH implementation or its derivatives based on the Hydra process manager, users can set the MPI universe size via the **-usize** argument to **mpiexec**:

```
$ mpiexec -n 1 -usize 17 python julia.py
```

or, alternatively, by setting the **MPIEXEC\_UNIVERSE\_SIZE** environment variable:

```
$ MPIEXEC_UNIVERSE_SIZE=17 mpiexec -n 1 python julia.py
```

In the Open MPI implementation, the MPI universe size can be set via the **-host** argument to **mpiexec**:

```
$ mpiexec -n 1 -host <hostname>:17 python julia.py
```

<sup>1</sup> When using an MPI implementation other than MPICH or Open MPI, please check the documentation of the implementation and/or batch system for the ways to specify the desired MPI universe size.

Another way to specify the number of workers is to use the `mpi4py.futures`-specific environment variable `MPI4PY_FUTURES_MAX_WORKERS`:

```
$ MPI4PY_FUTURES_MAX_WORKERS=16 mpiexec -n 1 python julia.py
```

Note that in this case, the MPI universe size is ignored.

Alternatively, users may decide to execute the script in a more traditional way, that is, all the MPI processes are started at once. The user script is run under command-line control of `mpi4py.futures` passing the `-m` flag to the `python` executable:

```
$ mpiexec -n 17 python -m mpi4py.futures julia.py
```

As explained previously, the 17 processes are partitioned in one master and 16 workers. The master process executes the main script while the workers execute the tasks submitted by the master.

## GIL

See [global interpreter lock](#).

## 7 mpi4py.util

Added in version 3.1.0.

The `mpi4py.util` package collects miscellaneous utilities within the intersection of Python and MPI.

### 7.1 mpi4py.util.pkl5

Added in version 3.1.0.

`pickle` protocol 5 (see [PEP 574](#)) introduced support for out-of-band buffers, allowing for more efficient handling of certain object types with large memory footprints.

MPI for Python uses the traditional in-band handling of buffers. This approach is appropriate for communicating non-buffer Python objects, or buffer-like objects with small memory footprints. For point-to-point communication, in-band buffer handling allows for the communication of a pickled stream with a single MPI message, at the expense of additional CPU and memory overhead in the pickling and unpickling steps.

The `mpi4py.util.pkl5` module provides communicator wrapper classes reimplementing pickle-based point-to-point communication methods using pickle protocol 5. Handling out-of-band buffers necessarily involve multiple MPI messages, thus increasing latency and hurting performance in case of small size data. However, in case of large size data, the zero-copy savings of out-of-band buffer handling more than offset the extra latency costs. Additionally, these wrapper methods overcome the infamous 2 GiB message count limit (MPI-1 to MPI-3).

---

**Note:** Support for pickle protocol 5 is available in the `pickle` module within the Python standard library since Python 3.8. Previous Python 3 releases can use the `pickle5` backport, which is available on [PyPI](#) and can be installed with:

```
python -m pip install pickle5
```

---

```
class mpi4py.util.pkl5.Request(request=None)
```

Request.

Custom request class for nonblocking communications.

---

**Note:** *Request* is not a subclass of *mpi4py.MPI.Request*

---

**Parameters**

**request** (*Iterable*[*MPI.Request*])

**Return type**

*Request*

**Free()**

Free a communication request.

**Return type**

None

**cancel()**

Cancel a communication request.

**Return type**

None

**get\_status(status=None)**

Non-destructive test for the completion of a request.

**Parameters**

**status** (*Optional*[*Status*])

**Return type**

bool

**test(status=None)**

Test for the completion of a request.

**Parameters**

**status** (*Optional*[*Status*])

**Return type**

Tuple[bool, *Optional*[Any]]

**wait(status=None)**

Wait for a request to complete.

**Parameters**

**status** (*Optional*[*Status*])

**Return type**

Any

**classmethod testall(requests, statuses=None)**

Test for the completion of all requests.

**Classmethod**

**classmethod waitall(requests, statuses=None)**

Wait for all requests to complete.

**Classmethod**

**class** mpi4py.util.pkl5.**Message**(*message=None*)

Message.

Custom message class for matching probes.

---

**Note:** *Message* is not a subclass of *mpi4py.MPI.Message*

---

**Parameters**

**message** (*Iterable*[*MPI.Message*])

**Return type**

*Message*

**recv**(*status=None*)

Blocking receive of matched message.

**Parameters**

**status** (*Optional*[*Status*])

**Return type**

Any

**irecv**()

Nonblocking receive of matched message.

**Return type**

*Request*

**classmethod probe**(*comm, source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Blocking test for a matched message.

**Classmethod**

**classmethod iprobe**(*comm, source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Nonblocking test for a matched message.

**Classmethod**

**class** mpi4py.util.pkl5.**Comm**

Communicator.

Base communicator wrapper class.

**send**(*obj, dest, tag=0*)

Blocking send in standard mode.

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

**b**send(*obj*, *dest*, *tag*=0)

Blocking send in buffered mode.

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

**s**send(*obj*, *dest*, *tag*=0)

Blocking send in synchronous mode.

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

**i**send(*obj*, *dest*, *tag*=0)

Nonblocking send in standard mode.

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**i**bsend(*obj*, *dest*, *tag*=0)

Nonblocking send in buffered mode.

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**i**ssend(*obj*, *dest*, *tag*=0)

Nonblocking send in synchronous mode.

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type***Request***recv**(buf=None, source=ANY\_SOURCE, tag=ANY\_TAG, status=None)

Blocking receive.

**Parameters**

- **buf** (*Optional[Buffer]*)
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

Any

**irecv**(buf=None, source=ANY\_SOURCE, tag=ANY\_TAG)

Nonblocking receive.

**Warning:** This method cannot be supported reliably and raises *RuntimeError*.**Parameters**

- **buf** (*Optional[Buffer]*)
- **source** (*int*)
- **tag** (*int*)

**Return type***Request***sendrecv**(sendobj, dest, sendtag=0, recvbuf=None, source=ANY\_SOURCE, recvtag=ANY\_TAG, status=None)

Send and receive.

**Parameters**

- **sendobj** (*Any*)
- **dest** (*int*)
- **sendtag** (*int*)
- **recvbuf** (*Optional[Buffer]*)
- **source** (*int*)
- **recvtag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

Any

**mprobe**(source=ANY\_SOURCE, tag=ANY\_TAG, status=None)

Blocking test for a matched message.

**Parameters**



- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

*Message*

**improbe**(*source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Nonblocking test for a matched message.

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

*Optional[Message]*

**bcast**(*obj, root=0*)

Broadcast.

**Parameters**

- **obj** (*Any*)
- **root** (*int*)

**Return type**

*Any*

**class** `mpi4py.util.pkl5.Intracomm`

Intracommunicator.

Intracommunicator wrapper class.

**class** `mpi4py.util.pkl5.Intercomm`

Intercommunicator.

Intercommunicator wrapper class.

## Examples

Listing 2: test-pkl5-1.py

```

1 import numpy as np
2 from mpi4py import MPI
3 from mpi4py.util import pkl5
4
5 comm = pkl5.Intracomm(MPI.COMM_WORLD) # comm wrapper
6 size = comm.Get_size()
7 rank = comm.Get_rank()
8 dst = (rank + 1) % size
9 src = (rank - 1) % size
10
11 sobj = np.full(1024**3, rank, dtype='i4') # > 4 GiB

```

(continues on next page)

(continued from previous page)

```
12 sreq = comm.isend(sobj, dst, tag=42)
13 robj = comm.recv (None, src, tag=42)
14 sreq.Free()
15
16 assert np.min(robj) == src
17 assert np.max(robj) == src
```

Listing 3: test-pkl5-2.py

```
1 import numpy as np
2 from mpi4py import MPI
3 from mpi4py.util import pkl5
4
5 comm = pkl5.IntraComm(MPI.COMM_WORLD) # comm wrapper
6 size = comm.Get_size()
7 rank = comm.Get_rank()
8 dst = (rank + 1) % size
9 src = (rank - 1) % size
10
11 sobj = np.full(1024**3, rank, dtype='i4') # > 4 GiB
12 sreq = comm.isend(sobj, dst, tag=42)
13
14 status = MPI.Status()
15 rmsg = comm.mprobe(status=status)
16 assert status.Get_source() == src
17 assert status.Get_tag() == 42
18 rreq = rmsg.irecv()
19 robj = rreq.wait()
20
21 sreq.Free()
22 assert np.max(robj) == src
23 assert np.min(robj) == src
```

## 7.2 mpi4py.util.dtlb

Added in version 3.1.0.

The `mpi4py.util.dtlb` module provides converter routines between NumPy and MPI datatypes.

`mpi4py.util.dtlb.from_numpy_dtype(dtype)`

Convert NumPy datatype to MPI datatype.

### Parameters

**dtype** (`numpy.typing.DTypeLike`) – NumPy dtype-like object.

### Return type

*Datatype*

`mpi4py.util.dtlb.to_numpy_dtype(datatype)`

Convert MPI datatype to NumPy datatype.

### Parameters

**datatype** (*Datatype*) – MPI datatype.

**Return type**  
`numpy.dtype`

## 8 mpi4py.run

Added in version 3.0.0.

At import time, `mpi4py` initializes the MPI execution environment calling `MPI_Init_thread()` and installs an exit hook to automatically call `MPI_Finalize()` just before the Python process terminates. Additionally, `mpi4py` overrides the default `ERRORS_ARE_FATAL` error handler in favor of `ERRORS_RETURN`, which allows translating MPI errors in Python exceptions. These departures from standard MPI behavior may be controversial, but are quite convenient within the highly dynamic Python programming environment. Third-party code using `mpi4py` can just `from mpi4py import MPI` and perform MPI calls without the tedious initialization/finalization handling. MPI errors, once translated automatically to Python exceptions, can be dealt with the common `try...except...finally` clauses; unhandled MPI exceptions will print a traceback which helps in locating problems in source code.

Unfortunately, the interplay of automatic MPI finalization and unhandled exceptions may lead to deadlocks. In unattended runs, these deadlocks will drain the battery of your laptop, or burn precious allocation hours in your supercomputing facility.

Consider the following snippet of Python code. Assume this code is stored in a standard Python script file and run with `mpiexec` in two or more processes.

```
from mpi4py import MPI
assert MPI.COMM_WORLD.Get_size() > 1
rank = MPI.COMM_WORLD.Get_rank()
if rank == 0:
    1/0
    MPI.COMM_WORLD.send(None, dest=1, tag=42)
elif rank == 1:
    MPI.COMM_WORLD.recv(source=0, tag=42)
```

Process 0 raises `ZeroDivisionError` exception before performing a send call to process 1. As the exception is not handled, the Python interpreter running in process 0 will proceed to exit with non-zero status. However, as `mpi4py` installed a finalizer hook to call `MPI_Finalize()` before exit, process 0 will block waiting for other processes to also enter the `MPI_Finalize()` call. Meanwhile, process 1 will block waiting for a message to arrive from process 0, thus never reaching to `MPI_Finalize()`. The whole MPI execution environment is irremediably in a deadlock state.

To alleviate this issue, `mpi4py` offers a simple, alternative command line execution mechanism based on using the `-m` flag and implemented with the `runpy` module. To use this features, Python code should be run passing `-m mpi4py` in the command line invoking the Python interpreter. In case of unhandled exceptions, the finalizer hook will call `MPI_Abort()` on the `MPI_COMM_WORLD` communicator, thus effectively aborting the MPI execution environment.

**Warning:** When a process is forced to abort, resources (e.g. open files) are not cleaned-up and any registered finalizers (either with the `atexit` module, the Python C/API function `Py_AtExit()`, or even the C standard library function `atexit()`) will not be executed. Thus, aborting execution is an extremely impolite way of ensuring process termination. However, MPI provides no other mechanism to recover from a deadlock state.

## 8.1 Interface options

The use of `-m mpi4py` to execute Python code on the command line resembles that of the Python interpreter.

- `mpiexec -n numprocs python -m mpi4py pyfile [arg] ...`
- `mpiexec -n numprocs python -m mpi4py -m mod [arg] ...`
- `mpiexec -n numprocs python -m mpi4py -c cmd [arg] ...`
- `mpiexec -n numprocs python -m mpi4py - [arg] ...`

### <pyfile>

Execute the Python code contained in *pyfile*, which must be a filesystem path referring to either a Python file, a directory containing a `__main__.py` file, or a zipfile containing a `__main__.py` file.

### -m <mod>

Search `sys.path` for the named module *mod* and execute its contents.

### -c <cmd>

Execute the Python code in the *cmd* string command.

-

Read commands from standard input (`sys.stdin`).

See also:

### Command line

Documentation on Python command line interface.

## 9 Reference

---

*mpi4py.MPI*

Message Passing Interface.

---

### 9.1 mpi4py.MPI

Message Passing Interface.

## Classes

<i>Cartcomm</i> ([comm])	Cartesian topology intracommunicator
<i>Comm</i> ([comm])	Communicator
<i>Datatype</i> ([datatype])	Datatype object
<i>Distgraphcomm</i> ([comm])	Distributed graph topology intracommunicator
<i>Errhandler</i> ([errhandler])	Error handler
<i>File</i> ([file])	File handle
<i>Graphcomm</i> ([comm])	General graph topology intracommunicator
<i>Grequest</i> ([request])	Generalized request handle
<i>Group</i> ([group])	Group of processes
<i>Info</i> ([info])	Info object
<i>Intercomm</i> ([comm])	Intercommunicator
<i>Intracomm</i> ([comm])	Intracommunicator
<i>Message</i> ([message])	Matched message handle
<i>Op</i> ([op])	Operation object
<i>Pickle</i> ([dumps, loads, protocol])	Pickle/unpickle Python objects
<i>Prequest</i> ([request])	Persistent request handle
<i>Request</i> ([request])	Request handle
<i>Status</i> ([status])	Status object
<i>Topocomm</i> ([comm])	Topology intracommunicator
<i>Win</i> ([win])	Window handle
<i>memory</i> (buf)	Memory buffer

### mpi4py.MPI.Cartcomm

**class** mpi4py.MPI.**Cartcomm**(comm=None)

Bases: *Topocomm*

Cartesian topology intracommunicator

#### Parameters

**comm** (*Optional*[*Cartcomm*])

#### Return type

*Cartcomm*

**static** **\_\_new\_\_**(cls, comm=None)

#### Parameters

**comm** (*Optional*[*Cartcomm*])

#### Return type

*Cartcomm*

## Methods Summary

<code>Get_cart_rank(coords)</code>	Translate logical coordinates to ranks
<code>Get_coords(rank)</code>	Translate ranks to logical coordinates
<code>Get_dim()</code>	Return number of dimensions
<code>Get_topo()</code>	Return information on the cartesian topology
<code>Shift(direction, disp)</code>	Return a tuple (source, dest) of process ranks for data shifting with <code>Comm.Sendrecv()</code>
<code>Sub(remain_dims)</code>	Return cartesian communicators that form lower-dimensional subgrids

## Attributes Summary

<code>coords</code>	coordinates
<code>dim</code>	number of dimensions
<code>dims</code>	dimensions
<code>ndim</code>	number of dimensions
<code>periods</code>	periodicity
<code>topo</code>	topology information

## Methods Documentation

### `Get_cart_rank(coords)`

Translate logical coordinates to ranks

#### Parameters

**coords** (*Sequence*[*int*])

#### Return type

*int*

### `Get_coords(rank)`

Translate ranks to logical coordinates

#### Parameters

**rank** (*int*)

#### Return type

*List*[*int*]

### `Get_dim()`

Return number of dimensions

#### Return type

*int*

### `Get_topo()`

Return information on the cartesian topology

#### Return type

*Tuple*[*List*[*int*], *List*[*int*], *List*[*int*]]

**Shift**(*direction*, *disp*)

Return a tuple (source, dest) of process ranks for data shifting with Comm.Sendrecv()

**Parameters**

- **direction** (*int*)
- **disp** (*int*)

**Return type**

Tuple[int, int]

**Sub**(*remain\_dims*)

Return cartesian communicators that form lower-dimensional subgrids

**Parameters**

**remain\_dims** (*Sequence[bool]*)

**Return type**

*Cartcomm*

## Attributes Documentation

**coords**

coordinates

**dim**

number of dimensions

**dims**

dimensions

**ndim**

number of dimensions

**periods**

periodicity

**topo**

topology information

## mpi4py.MPI.Comm

**class** mpi4py.MPI.**Comm**(*comm=None*)

Bases: *object*

Communicator

**Parameters**

**comm** (*Optional[Comm]*)

**Return type**

*Comm*

**static** **\_\_new\_\_**(*cls, comm=None*)

**Parameters**

**comm** (*Optional[Comm]*)

**Return type**  
*Comm*

## Methods Summary

<i>Abort</i> ([errorcode])	Terminate MPI execution environment
<i>Allgather</i> (sendbuf, recvbuf)	Gather to All, gather data from all processes and distribute it to all other processes in a group
<i>Allgatherv</i> (sendbuf, recvbuf)	Gather to All Vector, gather data from all processes and distribute it to all other processes in a group providing different amount of data and displacements
<i>Allreduce</i> (sendbuf, recvbuf[, op])	Reduce to All
<i>Alltoall</i> (sendbuf, recvbuf)	All to All Scatter/Gather, send data from all to all processes in a group
<i>Alltoallv</i> (sendbuf, recvbuf)	All to All Scatter/Gather Vector, send data from all to all processes in a group providing different amount of data and displacements
<i>Alltoallw</i> (sendbuf, recvbuf)	Generalized All-to-All communication allowing different counts, displacements and datatypes for each partner
<i>Barrier</i> ()	Barrier synchronization
<i>Bcast</i> (buf[, root])	Broadcast a message from one process to all other processes in a group
<i>Bsend</i> (buf, dest[, tag])	Blocking send in buffered mode
<i>Bsend_init</i> (buf, dest[, tag])	Persistent request for a send in buffered mode
<i>Call_errhandler</i> (errorcode)	Call the error handler installed on a communicator
<i>Clone</i> ()	Clone an existing communicator
<i>Compare</i> (comm1, comm2)	Compare two communicators
<i>Create</i> (group)	Create communicator from group
<i>Create_group</i> (group[, tag])	Create communicator from group
<i>Create_keyval</i> ([copy_fn, delete_fn, nopython])	Create a new attribute key for communicators
<i>Delete_attr</i> (keyval)	Delete attribute value associated with a key
<i>Disconnect</i> ()	Disconnect from a communicator
<i>Dup</i> ([info])	Duplicate an existing communicator
<i>Dup_with_info</i> (info)	Duplicate an existing communicator
<i>Free</i> ()	Free a communicator
<i>Free_keyval</i> (keyval)	Free an attribute key for communicators
<i>Gather</i> (sendbuf, recvbuf[, root])	Gather together values from a group of processes
<i>Gatherv</i> (sendbuf, recvbuf[, root])	Gather Vector, gather data to one process from all other processes in a group providing different amount of data and displacements at the receiving sides
<i>Get_attr</i> (keyval)	Retrieve attribute value by key
<i>Get_errhandler</i> ()	Get the error handler for a communicator
<i>Get_group</i> ()	Access the group associated with a communicator
<i>Get_info</i> ()	Return the hints for a communicator that are currently in use
<i>Get_name</i> ()	Get the print name for this communicator
<i>Get_parent</i> ()	Return the parent intercommunicator for this process
<i>Get_rank</i> ()	Return the rank of this process in a communicator
<i>Get_size</i> ()	Return the number of processes in a communicator

continues on next page



Table 2 – continued from previous page

<i>Get_topology()</i>	Determine the type of topology (if any) associated with a communicator
<i>Iallgather</i> (sendbuf, recvbuf)	Nonblocking Gather to All
<i>Iallgatherv</i> (sendbuf, recvbuf)	Nonblocking Gather to All Vector
<i>Iallreduce</i> (sendbuf, recvbuf[, op])	Nonblocking Reduce to All
<i>Ialltoall</i> (sendbuf, recvbuf)	Nonblocking All to All Scatter/Gather
<i>Ialltoallv</i> (sendbuf, recvbuf)	Nonblocking All to All Scatter/Gather Vector
<i>Ialltoallw</i> (sendbuf, recvbuf)	Nonblocking Generalized All-to-All
<i>Ibarrier</i> ()	Nonblocking Barrier
<i>Ibcast</i> (buf[, root])	Nonblocking Broadcast
<i>Ibsend</i> (buf, dest[, tag])	Nonblocking send in buffered mode
<i>Idup</i> ()	Nonblocking duplicate an existing communicator
<i>Igather</i> (sendbuf, recvbuf[, root])	Nonblocking Gather
<i>Igatherv</i> (sendbuf, recvbuf[, root])	Nonblocking Gather Vector
<i>Improbe</i> ([source, tag, status])	Nonblocking test for a matched message
<i>Iprobe</i> ([source, tag, status])	Nonblocking test for a message
<i>Irecv</i> (buf[, source, tag])	Nonblocking receive
<i>Ireduce</i> (sendbuf, recvbuf[, op, root])	Nonblocking Reduce to Root
<i>Ireduce_scatter</i> (sendbuf, recvbuf[, ...])	Nonblocking Reduce-Scatter (vector version)
<i>Ireduce_scatter_block</i> (sendbuf, recvbuf[, op])	Nonblocking Reduce-Scatter Block (regular, non-vector version)
<i>Irsend</i> (buf, dest[, tag])	Nonblocking send in ready mode
<i>Is_inter</i> ()	Test to see if a comm is an intercommunicator
<i>Is_intra</i> ()	Test to see if a comm is an intracommunicator
<i>Isctest</i> (sendbuf, recvbuf[, root])	Nonblocking Scatter
<i>Isctestv</i> (sendbuf, recvbuf[, root])	Nonblocking Scatter Vector
<i>Isend</i> (buf, dest[, tag])	Nonblocking send
<i>Issend</i> (buf, dest[, tag])	Nonblocking send in synchronous mode
<i>Join</i> (fd)	Create a intercommunicator by joining two processes connected by a socket
<i>Mprobe</i> ([source, tag, status])	Blocking test for a matched message
<i>Probe</i> ([source, tag, status])	Blocking test for a message
<i>Recv</i> (buf[, source, tag, status])	Blocking receive
<i>Recv_init</i> (buf[, source, tag])	Create a persistent request for a receive
<i>Reduce</i> (sendbuf, recvbuf[, op, root])	Reduce to Root
<i>Reduce_scatter</i> (sendbuf, recvbuf[, ...])	Reduce-Scatter (vector version)
<i>Reduce_scatter_block</i> (sendbuf, recvbuf[, op])	Reduce-Scatter Block (regular, non-vector version)
<i>Rsend</i> (buf, dest[, tag])	Blocking send in ready mode
<i>Rsend_init</i> (buf, dest[, tag])	Persistent request for a send in ready mode
<i>Scatter</i> (sendbuf, recvbuf[, root])	Scatter data from one process to all other processes in a group
<i>Scatterv</i> (sendbuf, recvbuf[, root])	Scatter Vector, scatter data from one process to all other processes in a group providing different amount of data and displacements at the sending side
<i>Send</i> (buf, dest[, tag])	Blocking send
<i>Send_init</i> (buf, dest[, tag])	Create a persistent request for a standard send
<i>Sendrecv</i> (sendbuf, dest[, sendtag, recvbuf, ...])	Send and receive a message
<i>Sendrecv_replace</i> (buf, dest[, sendtag, ...])	Send and receive a message
<i>Set_attr</i> (keyval, attrval)	Store attribute value associated with a key
<i>Set_errhandler</i> (errhandler)	Set the error handler for a communicator
<i>Set_info</i> (info)	Set new values for the hints associated with a communicator

continues on next page

Table 2 – continued from previous page

<i>Set_name</i> (name)	Set the print name for this communicator
<i>Split</i> ([color, key])	Split communicator by color and key
<i>Split_type</i> (split_type[, key, info])	Split communicator by split type
<i>Ssend</i> (buf, dest[, tag])	Blocking send in synchronous mode
<i>Ssend_init</i> (buf, dest[, tag])	Persistent request for a send in synchronous mode
<i>allgather</i> (sendobj)	Gather to All
<i>allreduce</i> (sendobj[, op])	Reduce to All
<i>alltoall</i> (sendobj)	All to All Scatter/Gather
<i>barrier</i> ()	Barrier
<i>bcast</i> (obj[, root])	Broadcast
<i>bsend</i> (obj, dest[, tag])	Send in buffered mode
<i>f2py</i> (arg)	
<i>gather</i> (sendobj[, root])	Gather
<i>ibsend</i> (obj, dest[, tag])	Nonblocking send in buffered mode
<i>improbe</i> ([source, tag, status])	Nonblocking test for a matched message
<i>iprobe</i> ([source, tag, status])	Nonblocking test for a message
<i>irecv</i> ([buf, source, tag])	Nonblocking receive
<i>isend</i> (obj, dest[, tag])	Nonblocking send
<i>issend</i> (obj, dest[, tag])	Nonblocking send in synchronous mode
<i>mprobe</i> ([source, tag, status])	Blocking test for a matched message
<i>probe</i> ([source, tag, status])	Blocking test for a message
<i>py2f</i> ()	
<i>recv</i> ([buf, source, tag, status])	Receive
<i>reduce</i> (sendobj[, op, root])	Reduce to Root
<i>scatter</i> (sendobj[, root])	Scatter
<i>send</i> (obj, dest[, tag])	Send
<i>sendrecv</i> (sendobj, dest[, sendtag, recvbuf, ...])	Send and Receive
<i>ssend</i> (obj, dest[, tag])	Send in synchronous mode

### Attributes Summary

<i>group</i>	communicator group
<i>info</i>	communicator info
<i>is_inter</i>	is intercommunicator
<i>is_intra</i>	is intracommunicator
<i>is_topo</i>	is a topology communicator
<i>name</i>	communicator name
<i>rank</i>	rank of this process in communicator
<i>size</i>	number of processes in communicator
<i>topology</i>	communicator topology type

## Methods Documentation

### **Abort**(*errorcode=0*)

Terminate MPI execution environment

**Warning:** This is a direct call, use it with care!!!.

#### **Parameters**

**errorcode** (*int*)

#### **Return type**

NoReturn

### **Allgather**(*sendbuf, recvbuf*)

Gather to All, gather data from all processes and distribute it to all other processes in a group

#### **Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpecB*)

#### **Return type**

None

### **Allgatherv**(*sendbuf, recvbuf*)

Gather to All Vector, gather data from all processes and distribute it to all other processes in a group providing different amount of data and displacements

#### **Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpecV*)

#### **Return type**

None

### **Allreduce**(*sendbuf, recvbuf, op=SUM*)

Reduce to All

#### **Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpec*)
- **op** (*Op*)

#### **Return type**

None

### **Alltoall**(*sendbuf, recvbuf*)

All to All Scatter/Gather, send data from all to all processes in a group

#### **Parameters**

- **sendbuf** (*Union[BufSpecB, InPlace]*)
- **recvbuf** (*BufSpecB*)

**Return type**

None

**Alltoallv**(*sendbuf*, *recvbuf*)

All to All Scatter/Gather Vector, send data from all to all processes in a group providing different amount of data and displacements

**Parameters**

- **sendbuf** (*Union[BufSpecV, InPlace]*)
- **recvbuf** (*BufSpecV*)

**Return type**

None

**Alltoallw**(*sendbuf*, *recvbuf*)

Generalized All-to-All communication allowing different counts, displacements and datatypes for each partner

**Parameters**

- **sendbuf** (*Union[BufSpecW, InPlace]*)
- **recvbuf** (*BufSpecW*)

**Return type**

None

**Barrier**()

Barrier synchronization

**Return type**

None

**Bcast**(*buf*, *root=0*)

Broadcast a message from one process to all other processes in a group

**Parameters**

- **buf** (*BufSpec*)
- **root** (*int*)

**Return type**

None

**Bsend**(*buf*, *dest*, *tag=0*)

Blocking send in buffered mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

**Bsend\_init**(*buf*, *dest*, *tag=0*)

Persistent request for a send in buffered mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**Call\_errhandler**(*errorcode*)

Call the error handler installed on a communicator

**Parameters**

**errorcode** (*int*)

**Return type**

None

**Clone**()

Clone an existing communicator

**Return type**

*Comm*

**classmethod Compare**(*comm1*, *comm2*)

Compare two communicators

**Parameters**

- **comm1** (*Comm*)
- **comm2** (*Comm*)

**Return type**

*int*

**Create**(*group*)

Create communicator from group

**Parameters**

**group** (*Group*)

**Return type**

*Comm*

**Create\_group**(*group*, *tag=0*)

Create communicator from group

**Parameters**

- **group** (*Group*)
- **tag** (*int*)

**Return type**

*Comm*

**classmethod Create\_keyval**(*copy\_fn=None*, *delete\_fn=None*, *nopython=False*)

Create a new attribute key for communicators

**Parameters**

- **copy\_fn** (*Optional[Callable[[Comm, int, Any], Any]]*)
- **delete\_fn** (*Optional[Callable[[Comm, int, Any], None]]*)

- **nopython** (*bool*)

**Return type**

*int*

**Delete\_attr**(*keyval*)

Delete attribute value associated with a key

**Parameters**

**keyval** (*int*)

**Return type**

None

**Disconnect**()

Disconnect from a communicator

**Return type**

None

**Dup**(*info=None*)

Duplicate an existing communicator

**Parameters**

**info** (*Optional[Info]*)

**Return type**

*Comm*

**Dup\_with\_info**(*info*)

Duplicate an existing communicator

**Parameters**

**info** (*Info*)

**Return type**

*Comm*

**Free**()

Free a communicator

**Return type**

None

**classmethod Free\_keyval**(*keyval*)

Free an attribute key for communicators

**Parameters**

**keyval** (*int*)

**Return type**

*int*

**Gather**(*sendbuf, recvbuf, root=0*)

Gather together values from a group of processes

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)

- **recvbuf** (*Optional[BufSpecB]*)

- **root** (*int*)

**Return type**

None

**Gatherv**(*sendbuf*, *recvbuf*, *root*=0)

Gather Vector, gather data to one process from all other processes in a group providing different amount of data and displacements at the receiving sides

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*Optional[BufSpecV]*)
- **root** (*int*)

**Return type**

None

**Get\_attr**(*keyval*)

Retrieve attribute value by key

**Parameters**

**keyval** (*int*)

**Return type**

*Optional[Union[int, Any]]*

**Get\_errhandler**()

Get the error handler for a communicator

**Return type**

*Errhandler*

**Get\_group**()

Access the group associated with a communicator

**Return type**

*Group*

**Get\_info**()

Return the hints for a communicator that are currently in use

**Return type**

*Info*

**Get\_name**()

Get the print name for this communicator

**Return type**

*str*

**classmethod Get\_parent**()

Return the parent intercommunicator for this process

**Return type**

*Intercomm*

**Get\_rank**()

Return the rank of this process in a communicator

**Return type**

*int*

**Get\_size()**

Return the number of processes in a communicator

**Return type**

*int*

**Get\_topology()**

Determine the type of topology (if any) associated with a communicator

**Return type**

*int*

**Iallgather**(*sendbuf*, *recvbuf*)

Nonblocking Gather to All

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpecB*)

**Return type**

*Request*

**Iallgatherv**(*sendbuf*, *recvbuf*)

Nonblocking Gather to All Vector

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpecV*)

**Return type**

*Request*

**Iallreduce**(*sendbuf*, *recvbuf*, *op=SUM*)

Nonblocking Reduce to All

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpec*)
- **op** (*Op*)

**Return type**

*Request*

**Ialltoall**(*sendbuf*, *recvbuf*)

Nonblocking All to All Scatter/Gather

**Parameters**

- **sendbuf** (*Union[BufSpecB, InPlace]*)
- **recvbuf** (*BufSpecB*)

**Return type**

*Request*



**Ialltoallv**(*sendbuf*, *recvbuf*)

Nonblocking All to All Scatter/Gather Vector

**Parameters**

- **sendbuf** (*Union*[*BufSpecV*, *InPlace*])
- **recvbuf** (*BufSpecV*)

**Return type**

*Request*

**Ialltoallw**(*sendbuf*, *recvbuf*)

Nonblocking Generalized All-to-All

**Parameters**

- **sendbuf** (*Union*[*BufSpecW*, *InPlace*])
- **recvbuf** (*BufSpecW*)

**Return type**

*Request*

**Ibarrier**()

Nonblocking Barrier

**Return type**

*Request*

**Ibcast**(*buf*, *root*=0)

Nonblocking Broadcast

**Parameters**

- **buf** (*BufSpec*)
- **root** (*int*)

**Return type**

*Request*

**Ibsend**(*buf*, *dest*, *tag*=0)

Nonblocking send in buffered mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**Idup**()

Nonblocking duplicate an existing communicator

**Return type**

*Tuple*[*Comm*, *Request*]

**Igather**(*sendbuf*, *recvbuf*, *root*=0)

Nonblocking Gather

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*Optional*[*BufSpecB*])
- **root** (*int*)

**Return type**

*Request*

**Igatherv**(*sendbuf*, *recvbuf*, *root*=0)

Nonblocking Gather Vector

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*Optional*[*BufSpecV*])
- **root** (*int*)

**Return type**

*Request*

**Improbe**(*source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*, *status*=*None*)

Nonblocking test for a matched message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional*[*Status*])

**Return type**

*Optional*[*Message*]

**Iprobe**(*source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*, *status*=*None*)

Nonblocking test for a message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional*[*Status*])

**Return type**

*bool*

**Irecv**(*buf*, *source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*)

Nonblocking receive

**Parameters**

- **buf** (*BufSpec*)
- **source** (*int*)
- **tag** (*int*)

**Return type***Request***Ireduce**(*sendbuf*, *recvbuf*, *op*=SUM, *root*=0)

Nonblocking Reduce to Root

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*Optional*[*BufSpec*])
- **op** (*Op*)
- **root** (*int*)

**Return type***Request***Ireduce\_scatter**(*sendbuf*, *recvbuf*, *recvcounts*=None, *op*=SUM)

Nonblocking Reduce-Scatter (vector version)

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*BufSpec*)
- **recvcounts** (*Optional*[*Sequence*[*int*]])
- **op** (*Op*)

**Return type***Request***Ireduce\_scatter\_block**(*sendbuf*, *recvbuf*, *op*=SUM)

Nonblocking Reduce-Scatter Block (regular, non-vector version)

**Parameters**

- **sendbuf** (*Union*[*BufSpecB*, *InPlace*])
- **recvbuf** (*Union*[*BufSpec*, *BufSpecB*])
- **op** (*Op*)

**Return type***Request***Irsend**(*buf*, *dest*, *tag*=0)

Nonblocking send in ready mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type***Request*

**Is\_inter()**

Test to see if a comm is an intercommunicator

**Return type**

`bool`

**Is\_intra()**

Test to see if a comm is an intracommunicator

**Return type**

`bool`

**Iscatter**(*sendbuf*, *recvbuf*, *root=0*)

Nonblocking Scatter

**Parameters**

- **sendbuf** (*Optional*[*BufSpecB*])
- **recvbuf** (*Union*[*BufSpec*, *InPlace*])
- **root** (*int*)

**Return type**

*Request*

**Iscatterv**(*sendbuf*, *recvbuf*, *root=0*)

Nonblocking Scatter Vector

**Parameters**

- **sendbuf** (*Optional*[*BufSpecV*])
- **recvbuf** (*Union*[*BufSpec*, *InPlace*])
- **root** (*int*)

**Return type**

*Request*

**Isend**(*buf*, *dest*, *tag=0*)

Nonblocking send

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**Issend**(*buf*, *dest*, *tag=0*)

Nonblocking send in synchronous mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type***Request***classmethod** **Join**(*fd*)

Create a intercommunicator by joining two processes connected by a socket

**Parameters****fd** (*int*)**Return type***Intercomm***Mprobe**(*source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Blocking test for a matched message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type***Message***Probe**(*source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Blocking test for a message

---

**Note:** This function blocks until the message arrives.

---

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type***Literal[True]***Recv**(*buf, source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Blocking receive

---

**Note:** This function blocks until the message is received

---

**Parameters**

- **buf** (*BufSpec*)
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type***None*

**Recv\_init**(*buf*, *source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*)

Create a persistent request for a receive

**Parameters**

- **buf** (*BufSpec*)
- **source** (*int*)
- **tag** (*int*)

**Return type**

*Prequest*

**Reduce**(*sendbuf*, *recvbuf*, *op*=*SUM*, *root*=0)

Reduce to Root

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*Optional[BufSpec]*)
- **op** (*Op*)
- **root** (*int*)

**Return type**

None

**Reduce\_scatter**(*sendbuf*, *recvbuf*, *recvcounts*=*None*, *op*=*SUM*)

Reduce-Scatter (vector version)

**Parameters**

- **sendbuf** (*Union[BufSpec, InPlace]*)
- **recvbuf** (*BufSpec*)
- **recvcounts** (*Optional[Sequence[int]]*)
- **op** (*Op*)

**Return type**

None

**Reduce\_scatter\_block**(*sendbuf*, *recvbuf*, *op*=*SUM*)

Reduce-Scatter Block (regular, non-vector version)

**Parameters**

- **sendbuf** (*Union[BufSpecB, InPlace]*)
- **recvbuf** (*Union[BufSpec, BufSpecB]*)
- **op** (*Op*)

**Return type**

None

**Rsend**(*buf*, *dest*, *tag*=0)

Blocking send in ready mode

**Parameters**

- **buf** (*BufSpec*)

- **dest** (*int*)

- **tag** (*int*)

**Return type**

None

**Rsend\_init**(*buf, dest, tag=0*)

Persistent request for a send in ready mode

**Parameters**

- **buf** (*BufSpec*)

- **dest** (*int*)

- **tag** (*int*)

**Return type**

*Request*

**Scatter**(*sendbuf, recvbuf, root=0*)

Scatter data from one process to all other processes in a group

**Parameters**

- **sendbuf** (*Optional[BufSpecB]*)

- **recvbuf** (*Union[BufSpec, InPlace]*)

- **root** (*int*)

**Return type**

None

**Scatterv**(*sendbuf, recvbuf, root=0*)

Scatter Vector, scatter data from one process to all other processes in a group providing different amount of data and displacements at the sending side

**Parameters**

- **sendbuf** (*Optional[BufSpecV]*)

- **recvbuf** (*Union[BufSpec, InPlace]*)

- **root** (*int*)

**Return type**

None

**Send**(*buf, dest, tag=0*)

Blocking send

---

**Note:** This function may block until the message is received. Whether or not *Send* blocks depends on several factors and is implementation dependent

---

**Parameters**

- **buf** (*BufSpec*)

- **dest** (*int*)

- **tag** (*int*)

**Return type**

None

**Send\_init**(*buf*, *dest*, *tag=0*)

Create a persistent request for a standard send

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type***Prequest***Sendrecv**(*sendbuf*, *dest*, *sendtag=0*, *recvbuf=None*, *source=ANY\_SOURCE*, *recvtag=ANY\_TAG*, *status=None*)

Send and receive a message

---

**Note:** This function is guaranteed not to deadlock in situations where pairs of blocking sends and receives may deadlock.

---

**Caution:** A common mistake when using this function is to mismatch the tags with the source and destination ranks, which can result in deadlock.

**Parameters**

- **sendbuf** (*BufSpec*)
- **dest** (*int*)
- **sendtag** (*int*)
- **recvbuf** (*BufSpec*)
- **source** (*int*)
- **recvtag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

None

**Sendrecv\_replace**(*buf*, *dest*, *sendtag=0*, *source=ANY\_SOURCE*, *recvtag=ANY\_TAG*, *status=None*)

Send and receive a message

---

**Note:** This function is guaranteed not to deadlock in situations where pairs of blocking sends and receives may deadlock.

---

**Caution:** A common mistake when using this function is to mismatch the tags with the source and destination ranks, which can result in deadlock.



#### Parameters

- **buf** (*BufSpec*)
- **dest** (*int*)
- **sendtag** (*int*)
- **source** (*int*)
- **recvtag** (*int*)
- **status** (*Optional[Status]*)

#### Return type

None

#### **Set\_attr**(*keyval, attrval*)

Store attribute value associated with a key

#### Parameters

- **keyval** (*int*)
- **attrval** (*Any*)

#### Return type

None

#### **Set\_errhandler**(*errhandler*)

Set the error handler for a communicator

#### Parameters

**errhandler** (*Errhandler*)

#### Return type

None

#### **Set\_info**(*info*)

Set new values for the hints associated with a communicator

#### Parameters

**info** (*Info*)

#### Return type

None

#### **Set\_name**(*name*)

Set the print name for this communicator

#### Parameters

**name** (*str*)

#### Return type

None

#### **Split**(*color=0, key=0*)

Split communicator by color and key

#### Parameters

- **color** (*int*)
- **key** (*int*)

**Return type***Comm***Split\_type**(*split\_type*, *key*=0, *info*=INFO\_NULL)

Split communicator by split type

**Parameters**

- **split\_type** (*int*)
- **key** (*int*)
- **info** (*Info*)

**Return type***Comm***Ssend**(*buf*, *dest*, *tag*=0)

Blocking send in synchronous mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

**Ssend\_init**(*buf*, *dest*, *tag*=0)

Persistent request for a send in synchronous mode

**Parameters**

- **buf** (*BufSpec*)
- **dest** (*int*)
- **tag** (*int*)

**Return type***Request***allgather**(*sendobj*)

Gather to All

**Parameters****sendobj** (*Any*)**Return type**List[*Any*]**allreduce**(*sendobj*, *op*=SUM)

Reduce to All

**Parameters**

- **sendobj** (*Any*)
- **op** (*Union*[*Op*, *Callable*[[*Any*, *Any*], *Any*]])

**Return type***Any*

**alltoall**(*sendobj*)

All to All Scatter/Gather

**Parameters**

**sendobj** (*Sequence*[*Any*])

**Return type**

List[*Any*]

**barrier**()

Barrier

**Return type**

None

**bcast**(*obj*, *root*=0)

Broadcast

**Parameters**

- **obj** (*Any*)
- **root** (*int*)

**Return type**

*Any*

**bsend**(*obj*, *dest*, *tag*=0)

Send in buffered mode

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

**classmethod f2py**(*arg*)

**Parameters**

**arg** (*int*)

**Return type**

*Comm*

**gather**(*sendobj*, *root*=0)

Gather

**Parameters**

- **sendobj** (*Any*)
- **root** (*int*)

**Return type**

Optional[List[*Any*]]

**ibsend**(*obj*, *dest*, *tag*=0)

Nonblocking send in buffered mode

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**improbe**(*source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Nonblocking test for a matched message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

*Optional[Message]*

**iprobe**(*source=ANY\_SOURCE, tag=ANY\_TAG, status=None*)

Nonblocking test for a message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

*bool*

**irecv**(*buf=None, source=ANY\_SOURCE, tag=ANY\_TAG*)

Nonblocking receive

**Parameters**

- **buf** (*Optional[Buffer]*)
- **source** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**isend**(*obj, dest, tag=0*)

Nonblocking send

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**issend**(*obj*, *dest*, *tag*=0)

Nonblocking send in synchronous mode

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*Request*

**mprobe**(*source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*, *status*=*None*)

Blocking test for a matched message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional*[*Status*])

**Return type**

*Message*

**probe**(*source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*, *status*=*None*)

Blocking test for a message

**Parameters**

- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional*[*Status*])

**Return type**

*Literal*[*True*]

**py2f**()

**Return type**

*int*

**recv**(*buf*=*None*, *source*=*ANY\_SOURCE*, *tag*=*ANY\_TAG*, *status*=*None*)

Receive

**Parameters**

- **buf** (*Optional*[*Buffer*])
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional*[*Status*])

**Return type**

*Any*

**reduce**(*sendobj*, *op*=*SUM*, *root*=0)

Reduce to Root

**Parameters**

- **sendobj** (*Any*)
- **op** (*Union*[*Op*, *Callable*[[*Any*, *Any*], *Any*]])
- **root** (*int*)

**Return type**

*Optional*[*Any*]

**scatter**(*sendobj*, *root*=0)

Scatter

**Parameters**

- **sendobj** (*Sequence*[*Any*])
- **root** (*int*)

**Return type**

*Any*

**send**(*obj*, *dest*, *tag*=0)

Send

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

*None*

**sendrecv**(*sendobj*, *dest*, *sendtag*=0, *recvbuf*=*None*, *source*=*ANY\_SOURCE*, *recvtag*=*ANY\_TAG*,  
*status*=*None*)

Send and Receive

**Parameters**

- **sendobj** (*Any*)
- **dest** (*int*)
- **sendtag** (*int*)
- **recvbuf** (*Optional*[*Buffer*])
- **source** (*int*)
- **recvtag** (*int*)
- **status** (*Optional*[*Status*])

**Return type**

*Any*

**ssend**(*obj*, *dest*, *tag=0*)

Send in synchronous mode

**Parameters**

- **obj** (*Any*)
- **dest** (*int*)
- **tag** (*int*)

**Return type**

None

## Attributes Documentation

**group**

communicator group

**info**

communicator info

**is\_inter**

is intercommunicator

**is\_intra**

is intracommunicator

**is\_topo**

is a topology communicator

**name**

communicator name

**rank**

rank of this process in communicator

**size**

number of processes in communicator

**topology**

communicator topology type

## mpi4py.MPI.Datatype

**class** `mpi4py.MPI.Datatype`(*datatype=None*)

Bases: `object`

Datatype object

**Parameters**

**datatype** (*Optional* [`Datatype`])

**Return type**

*Datatype*

**static** `__new__(cls, datatype=None)`

**Parameters**

**datatype** (*Optional*[Datatype])

**Return type**

*Datatype*

## Methods Summary

<code>Commit()</code>	Commit the datatype
<code>Create_contiguous(count)</code>	Create a contiguous datatype
<code>Create_darray(size, rank, gsizes, distribs, ...)</code>	Create a datatype representing an HPF-like distributed array on Cartesian process grids
<code>Create_f90_complex(p, r)</code>	Return a bounded complex datatype
<code>Create_f90_integer(r)</code>	Return a bounded integer datatype
<code>Create_f90_real(p, r)</code>	Return a bounded real datatype
<code>Create_hindexed(blocklengths, displacements)</code>	Create an indexed datatype with displacements in bytes
<code>Create_hindexed_block(blocklength, displacements)</code>	Create an indexed datatype with constant-sized blocks and displacements in bytes
<code>Create_hvector(count, blocklength, stride)</code>	Create a vector (strided) datatype
<code>Create_indexed(blocklengths, displacements)</code>	Create an indexed datatype
<code>Create_indexed_block(blocklength, displacements)</code>	Create an indexed datatype with constant-sized blocks
<code>Create_keyval([copy_fn, delete_fn, nopython])</code>	Create a new attribute key for datatypes
<code>Create_resized(lb, extent)</code>	Create a datatype with a new lower bound and extent
<code>Create_struct(blocklengths, displacements, ...)</code>	Create an datatype from a general set of block sizes, displacements and datatypes
<code>Create_subarray(sizes, subsizes, starts[, order])</code>	Create a datatype for a subarray of a regular, multidimensional array
<code>Create_vector(count, blocklength, stride)</code>	Create a vector (strided) datatype
<code>Delete_attr(keyval)</code>	Delete attribute value associated with a key
<code>Dup()</code>	Duplicate a datatype
<code>Free()</code>	Free the datatype
<code>Free_keyval(keyval)</code>	Free an attribute key for datatypes
<code>Get_attr(keyval)</code>	Retrieve attribute value by key
<code>Get_contents()</code>	Retrieve the actual arguments used in the call that created a datatype
<code>Get_envelope()</code>	Return information on the number and type of input arguments used in the call that created a datatype
<code>Get_extent()</code>	Return lower bound and extent of datatype
<code>Get_name()</code>	Get the print name for this datatype
<code>Get_size()</code>	Return the number of bytes occupied by entries in the datatype
<code>Get_true_extent()</code>	Return the true lower bound and extent of a datatype
<code>Match_size(typeclass, size)</code>	Find a datatype matching a specified size in bytes
<code>Pack(inbuf, outbuf, position, comm)</code>	Pack into contiguous memory according to datatype.
<code>Pack_external(datarep, inbuf, outbuf, position)</code>	Pack into contiguous memory according to datatype, using a portable data representation ( <b>external32</b> ).

continues on next page



Table 3 – continued from previous page

<i>Pack_external_size</i> (datarep, count)	Return the upper bound on the amount of space (in bytes) needed to pack a message according to datatype, using a portable data representation ( <b>external32</b> ).
<i>Pack_size</i> (count, comm)	Return the upper bound on the amount of space (in bytes) needed to pack a message according to datatype.
<i>Set_attr</i> (keyval, attrval)	Store attribute value associated with a key
<i>Set_name</i> (name)	Set the print name for this datatype
<i>Unpack</i> (inbuf, position, outbuf, comm)	Unpack from contiguous memory according to datatype.
<i>Unpack_external</i> (datarep, inbuf, position, outbuf)	Unpack from contiguous memory according to datatype, using a portable data representation ( <b>external32</b> ).
<i>decode</i> ()	Convenience method for decoding a datatype
<i>f2py</i> (arg)	
<i>py2f</i> ()	

## Attributes Summary

<i>combiner</i>	datatype combiner
<i>contents</i>	datatype contents
<i>envelope</i>	datatype envelope
<i>extent</i>	
<i>is_named</i>	is a named datatype
<i>is_predefined</i>	is a predefined datatype
<i>lb</i>	lower bound
<i>name</i>	datatype name
<i>size</i>	
<i>true_extent</i>	true extent
<i>true_lb</i>	true lower bound
<i>true_ub</i>	true upper bound
<i>ub</i>	upper bound

## Methods Documentation

### **Commit()**

Commit the datatype

#### **Return type**

*Datatype*

### **Create\_contiguous(count)**

Create a contiguous datatype

#### **Parameters**

**count** (*int*)

**Return type***Datatype***Create\_darray**(*size, rank, gsizes, distribs, dargs, psize, order=ORDER\_C*)

Create a datatype representing an HPF-like distributed array on Cartesian process grids

**Parameters**

- **size** (*int*)
- **rank** (*int*)
- **gsizes** (*Sequence[int]*)
- **distribs** (*Sequence[int]*)
- **dargs** (*Sequence[int]*)
- **psize** (*Sequence[int]*)
- **order** (*int*)

**Return type***Datatype***classmethod Create\_f90\_complex**(*p, r*)

Return a bounded complex datatype

**Parameters**

- **p** (*int*)
- **r** (*int*)

**Return type***Datatype***classmethod Create\_f90\_integer**(*r*)

Return a bounded integer datatype

**Parameters****r** (*int*)**Return type***Datatype***classmethod Create\_f90\_real**(*p, r*)

Return a bounded real datatype

**Parameters**

- **p** (*int*)
- **r** (*int*)

**Return type***Datatype***Create\_hindexed**(*blocklengths, displacements*)

Create an indexed datatype with displacements in bytes

**Parameters**

- **blocklengths** (*Sequence[int]*)
- **displacements** (*Sequence[int]*)

**Return type***Datatype***Create\_indexed\_block**(*blocklength, displacements*)

Create an indexed datatype with constant-sized blocks and displacements in bytes

**Parameters**

- **blocklength** (*int*)
- **displacements** (*Sequence[int]*)

**Return type***Datatype***Create\_hvector**(*count, blocklength, stride*)

Create a vector (strided) datatype

**Parameters**

- **count** (*int*)
- **blocklength** (*int*)
- **stride** (*int*)

**Return type***Datatype***Create\_indexed**(*blocklengths, displacements*)

Create an indexed datatype

**Parameters**

- **blocklengths** (*Sequence[int]*)
- **displacements** (*Sequence[int]*)

**Return type***Datatype***Create\_indexed\_block**(*blocklength, displacements*)

Create an indexed datatype with constant-sized blocks

**Parameters**

- **blocklength** (*int*)
- **displacements** (*Sequence[int]*)

**Return type***Datatype***classmethod Create\_keyval**(*copy\_fn=None, delete\_fn=None, nopython=False*)

Create a new attribute key for datatypes

**Parameters**

- **copy\_fn** (*Optional[Callable[[Datatype, int, Any], Any]]*)
- **delete\_fn** (*Optional[Callable[[Datatype, int, Any], None]]*)
- **nopython** (*bool*)

**Return type***int*

**Create\_resized**(*lb, extent*)

Create a datatype with a new lower bound and extent

**Parameters**

- **lb** (*int*)
- **extent** (*int*)

**Return type**

*Datatype*

**classmethod Create\_struct**(*blocklengths, displacements, datatypes*)

Create an datatype from a general set of block sizes, displacements and datatypes

**Parameters**

- **blocklengths** (*Sequence[int]*)
- **displacements** (*Sequence[int]*)
- **datatypes** (*Sequence[Datatype]*)

**Return type**

*Datatype*

**Create\_subarray**(*sizes, subsizes, starts, order=ORDER\_C*)

Create a datatype for a subarray of a regular, multidimensional array

**Parameters**

- **sizes** (*Sequence[int]*)
- **subsizes** (*Sequence[int]*)
- **starts** (*Sequence[int]*)
- **order** (*int*)

**Return type**

*Datatype*

**Create\_vector**(*count, blocklength, stride*)

Create a vector (strided) datatype

**Parameters**

- **count** (*int*)
- **blocklength** (*int*)
- **stride** (*int*)

**Return type**

*Datatype*

**Delete\_attr**(*keyval*)

Delete attribute value associated with a key

**Parameters**

**keyval** (*int*)

**Return type**

None

**Dup()**

Duplicate a datatype

**Return type**

*Datatype*

**Free()**

Free the datatype

**Return type**

None

**classmethod Free\_keyval**(*keyval*)

Free an attribute key for datatypes

**Parameters**

**keyval** (*int*)

**Return type**

*int*

**Get\_attr**(*keyval*)

Retrieve attribute value by key

**Parameters**

**keyval** (*int*)

**Return type**

Optional[Union[*int*, Any]]

**Get\_contents()**

Retrieve the actual arguments used in the call that created a datatype

**Return type**

Tuple[List[*int*], List[*int*], List[*Datatype*]]

**Get\_envelope()**

Return information on the number and type of input arguments used in the call that created a datatype

**Return type**

Tuple[*int*, *int*, *int*, *int*]

**Get\_extent()**

Return lower bound and extent of datatype

**Return type**

Tuple[*int*, *int*]

**Get\_name()**

Get the print name for this datatype

**Return type**

*str*

**Get\_size()**

Return the number of bytes occupied by entries in the datatype

**Return type**

*int*

**Get\_true\_extent()**

Return the true lower bound and extent of a datatype

**Return type**

Tuple[int, int]

**classmethod Match\_size(*typeclass, size*)**

Find a datatype matching a specified size in bytes

**Parameters**

- **typeclass** (*int*)
- **size** (*int*)

**Return type**

*Datatype*

**Pack(*inbuf, outbuf, position, comm*)**

Pack into contiguous memory according to datatype.

**Parameters**

- **inbuf** (*BufSpec*)
- **outbuf** (*BufSpec*)
- **position** (*int*)
- **comm** (*Comm*)

**Return type**

*int*

**Pack\_external(*datarep, inbuf, outbuf, position*)**

Pack into contiguous memory according to datatype, using a portable data representation (**external32**).

**Parameters**

- **datarep** (*str*)
- **inbuf** (*BufSpec*)
- **outbuf** (*BufSpec*)
- **position** (*int*)

**Return type**

*int*

**Pack\_external\_size(*datarep, count*)**

Return the upper bound on the amount of space (in bytes) needed to pack a message according to datatype, using a portable data representation (**external32**).

**Parameters**

- **datarep** (*str*)
- **count** (*int*)

**Return type**

*int*

**Pack\_size**(*count*, *comm*)

Return the upper bound on the amount of space (in bytes) needed to pack a message according to datatype.

**Parameters**

- **count** (*int*)
- **comm** (*Comm*)

**Return type**

*int*

**Set\_attr**(*keyval*, *attrval*)

Store attribute value associated with a key

**Parameters**

- **keyval** (*int*)
- **attrval** (*Any*)

**Return type**

*None*

**Set\_name**(*name*)

Set the print name for this datatype

**Parameters**

**name** (*str*)

**Return type**

*None*

**Unpack**(*inbuf*, *position*, *outbuf*, *comm*)

Unpack from contiguous memory according to datatype.

**Parameters**

- **inbuf** (*BufSpec*)
- **position** (*int*)
- **outbuf** (*BufSpec*)
- **comm** (*Comm*)

**Return type**

*int*

**Unpack\_external**(*datarep*, *inbuf*, *position*, *outbuf*)

Unpack from contiguous memory according to datatype, using a portable data representation (**external32**).

**Parameters**

- **datarep** (*str*)
- **inbuf** (*BufSpec*)
- **position** (*int*)
- **outbuf** (*BufSpec*)

**Return type**

*int*

**decode()**

Convenience method for decoding a datatype

**Return type**

Tuple[*Datatype*, str, Dict[str, Any]]

**classmethod f2py(arg)**

**Parameters**

**arg** (*int*)

**Return type**

*Datatype*

**py2f()**

**Return type**

*int*

## Attributes Documentation

**combiner**

datatype combiner

**contents**

datatype contents

**envelope**

datatype envelope

**extent**

**is\_named**

is a named datatype

**is\_predefined**

is a predefined datatype

**lb**

lower bound

**name**

datatype name

**size**

**true\_extent**

true extent

**true\_lb**

true lower bound

**true\_ub**

true upper bound

**ub**

upper bound



## mpi4py.MPI.Distgraphcomm

**class** mpi4py.MPI.Distgraphcomm(comm=None)

Bases: *Topocomm*

Distributed graph topology intracommunicator

### Parameters

**comm** (*Optional*[*Distgraphcomm*])

### Return type

*Distgraphcomm*

**static** \_\_new\_\_(cls, comm=None)

### Parameters

**comm** (*Optional*[*Distgraphcomm*])

### Return type

*Distgraphcomm*

## Methods Summary

<i>Get_dist_neighbors()</i>	Return adjacency information for a distributed graph topology
<i>Get_dist_neighbors_count()</i>	Return adjacency information for a distributed graph topology

## Methods Documentation

### Get\_dist\_neighbors()

Return adjacency information for a distributed graph topology

### Return type

Tuple[List[int], List[int], *Optional*[Tuple[List[int], List[int]]]]

### Get\_dist\_neighbors\_count()

Return adjacency information for a distributed graph topology

### Return type

int

## mpi4py.MPI.Errhandler

**class** mpi4py.MPI.Errhandler(errhandler=None)

Bases: *object*

Error handler

### Parameters

**errhandler** (*Optional*[*Errhandler*])

### Return type

*Errhandler*

**static** `__new__(cls, errhandler=None)`

**Parameters**

**errhandler** (*Optional*[[Errhandler](#)])

**Return type**

*Errhandler*

## Methods Summary

<a href="#">Free()</a>	Free an error handler
<a href="#">f2py(arg)</a>	
<a href="#">py2f()</a>	

## Methods Documentation

### **Free()**

Free an error handler

**Return type**

None

### **classmethod** `f2py(arg)`

**Parameters**

**arg** (*int*)

**Return type**

*Errhandler*

### **py2f()**

**Return type**

*int*

## **mpi4py.MPI.File**

**class** `mpi4py.MPI.File(file=None)`

Bases: [object](#)

File handle

**Parameters**

**file** (*Optional*[[File](#)])

**Return type**

*File*

**static** `__new__(cls, file=None)`

**Parameters**

**file** (*Optional*[[File](#)])

## Return type

*File*

## Methods Summary

<i>Call_errhandler</i> (errorcode)	Call the error handler installed on a file
<i>Close</i> ()	Close a file
<i>Delete</i> (filename[, info])	Delete a file
<i>Get_amode</i> ()	Return the file access mode
<i>Get_atomicsity</i> ()	Return the atomicity mode
<i>Get_byte_offset</i> (offset)	Return the absolute byte position in the file corresponding to 'offset' etypes relative to the current view
<i>Get_errhandler</i> ()	Get the error handler for a file
<i>Get_group</i> ()	Return the group of processes that opened the file
<i>Get_info</i> ()	Return the hints for a file that that are currently in use
<i>Get_position</i> ()	Return the current position of the individual file pointer in etype units relative to the current view
<i>Get_position_shared</i> ()	Return the current position of the shared file pointer in etype units relative to the current view
<i>Get_size</i> ()	Return the file size
<i>Get_type_extent</i> (datatype)	Return the extent of datatype in the file
<i>Get_view</i> ()	Return the file view
<i>Iread</i> (buf)	Nonblocking read using individual file pointer
<i>Iread_all</i> (buf)	Nonblocking collective read using individual file pointer
<i>Iread_at</i> (offset, buf)	Nonblocking read using explicit offset
<i>Iread_at_all</i> (offset, buf)	Nonblocking collective read using explicit offset
<i>Iread_shared</i> (buf)	Nonblocking read using shared file pointer
<i>Iwrite</i> (buf)	Nonblocking write using individual file pointer
<i>Iwrite_all</i> (buf)	Nonblocking collective write using individual file pointer
<i>Iwrite_at</i> (offset, buf)	Nonblocking write using explicit offset
<i>Iwrite_at_all</i> (offset, buf)	Nonblocking collective write using explicit offset
<i>Iwrite_shared</i> (buf)	Nonblocking write using shared file pointer
<i>Open</i> (comm, filename[, amode, info])	Open a file
<i>Preallocate</i> (size)	Preallocate storage space for a file
<i>Read</i> (buf[, status])	Read using individual file pointer
<i>Read_all</i> (buf[, status])	Collective read using individual file pointer
<i>Read_all_begin</i> (buf)	Start a split collective read using individual file pointer
<i>Read_all_end</i> (buf[, status])	Complete a split collective read using individual file pointer
<i>Read_at</i> (offset, buf[, status])	Read using explicit offset
<i>Read_at_all</i> (offset, buf[, status])	Collective read using explicit offset
<i>Read_at_all_begin</i> (offset, buf)	Start a split collective read using explicit offset
<i>Read_at_all_end</i> (buf[, status])	Complete a split collective read using explicit offset
<i>Read_ordered</i> (buf[, status])	Collective read using shared file pointer
<i>Read_ordered_begin</i> (buf)	Start a split collective read using shared file pointer
<i>Read_ordered_end</i> (buf[, status])	Complete a split collective read using shared file pointer
<i>Read_shared</i> (buf[, status])	Read using shared file pointer

continues on next page

Table 4 – continued from previous page

<i>Seek</i> (offset[, whence])	Update the individual file pointer
<i>Seek_shared</i> (offset[, whence])	Update the shared file pointer
<i>Set_atomics</i> (flag)	Set the atomicity mode
<i>Set_errhandler</i> (errhandler)	Set the error handler for a file
<i>Set_info</i> (info)	Set new values for the hints associated with a file
<i>Set_size</i> (size)	Sets the file size
<i>Set_view</i> ([disp, etype, filetype, datarep, info])	Set the file view
<i>Sync</i> ()	Causes all previous writes to be transferred to the storage device
<i>Write</i> (buf[, status])	Write using individual file pointer
<i>Write_all</i> (buf[, status])	Collective write using individual file pointer
<i>Write_all_begin</i> (buf)	Start a split collective write using individual file pointer
<i>Write_all_end</i> (buf[, status])	Complete a split collective write using individual file pointer
<i>Write_at</i> (offset, buf[, status])	Write using explicit offset
<i>Write_at_all</i> (offset, buf[, status])	Collective write using explicit offset
<i>Write_at_all_begin</i> (offset, buf)	Start a split collective write using explicit offset
<i>Write_at_all_end</i> (buf[, status])	Complete a split collective write using explicit offset
<i>Write_ordered</i> (buf[, status])	Collective write using shared file pointer
<i>Write_ordered_begin</i> (buf)	Start a split collective write using shared file pointer
<i>Write_ordered_end</i> (buf[, status])	Complete a split collective write using shared file pointer
<i>Write_shared</i> (buf[, status])	Write using shared file pointer
<i>f2py</i> (arg)	
<i>py2f</i> ()	

## Attributes Summary

<i>amode</i>	file access mode
<i>atomicity</i>	
<i>group</i>	file group
<i>info</i>	file info
<i>size</i>	file size

## Methods Documentation

### **Call\_errhandler**(*errorcode*)

Call the error handler installed on a file

#### **Parameters**

**errorcode** (*int*)

#### **Return type**

None

### **Close**()

Close a file

**Return type**

None

**classmethod Delete**(*filename*, *info=INFO\_NULL*)

Delete a file

**Parameters**

- **filename** (*str*)
- **info** (*Info*)

**Return type**

None

**Get\_amode**()

Return the file access mode

**Return type**

*int*

**Get\_atomicity**()

Return the atomicity mode

**Return type**

*bool*

**Get\_byte\_offset**(*offset*)

Return the absolute byte position in the file corresponding to 'offset' etypes relative to the current view

**Parameters**

**offset** (*int*)

**Return type**

*int*

**Get\_errhandler**()

Get the error handler for a file

**Return type**

*Errhandler*

**Get\_group**()

Return the group of processes that opened the file

**Return type**

*Group*

**Get\_info**()

Return the hints for a file that that are currently in use

**Return type**

*Info*

**Get\_position**()

Return the current position of the individual file pointer in etype units relative to the current view

**Return type**

*int*

**Get\_position\_shared()**

Return the current position of the shared file pointer in etype units relative to the current view

**Return type**

*int*

**Get\_size()**

Return the file size

**Return type**

*int*

**Get\_type\_extent(*datatype*)**

Return the extent of datatype in the file

**Parameters**

**datatype** (*Datatype*)

**Return type**

*int*

**Get\_view()**

Return the file view

**Return type**

Tuple[*int*, *Datatype*, *Datatype*, str]

**Iread(*buf*)**

Nonblocking read using individual file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

*Request*

**Iread\_all(*buf*)**

Nonblocking collective read using individual file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

*Request*

**Iread\_at(*offset*, *buf*)**

Nonblocking read using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)

**Return type**

*Request*

**Iread\_at\_all(*offset*, *buf*)**

Nonblocking collective read using explicit offset

**Parameters**

- **offset** (*int*)

- **buf** (*BufSpec*)

**Return type**

*Request*

**Iread\_shared(buf)**

Nonblocking read using shared file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

*Request*

**Iwrite(buf)**

Nonblocking write using individual file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

*Request*

**Iwrite\_all(buf)**

Nonblocking collective write using individual file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

*Request*

**Iwrite\_at(offset, buf)**

Nonblocking write using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)

**Return type**

*Request*

**Iwrite\_at\_all(offset, buf)**

Nonblocking collective write using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)

**Return type**

*Request*

**Iwrite\_shared(buf)**

Nonblocking write using shared file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

*Request*

**classmethod** **Open**(*comm, filename, amode=MODE\_RDONLY, info=INFO\_NULL*)

Open a file

**Parameters**

- **comm** ([IntraComm](#))
- **filename** ([str](#))
- **amode** ([int](#))
- **info** ([Info](#))

**Return type**

[File](#)

**Preallocate**(*size*)

Preallocate storage space for a file

**Parameters**

**size** ([int](#))

**Return type**

None

**Read**(*buf, status=None*)

Read using individual file pointer

**Parameters**

- **buf** ([BufSpec](#))
- **status** ([Optional\[Status\]](#))

**Return type**

None

**Read\_all**(*buf, status=None*)

Collective read using individual file pointer

**Parameters**

- **buf** ([BufSpec](#))
- **status** ([Optional\[Status\]](#))

**Return type**

None

**Read\_all\_begin**(*buf*)

Start a split collective read using individual file pointer

**Parameters**

**buf** ([BufSpec](#))

**Return type**

None

**Read\_all\_end**(*buf, status=None*)

Complete a split collective read using individual file pointer

**Parameters**

- **buf** ([BufSpec](#))
- **status** ([Optional\[Status\]](#))



**Return type**

None

**Read\_at**(*offset*, *buf*, *status=None*)

Read using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Read\_at\_all**(*offset*, *buf*, *status=None*)

Collective read using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Read\_at\_all\_begin**(*offset*, *buf*)

Start a split collective read using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)

**Return type**

None

**Read\_at\_all\_end**(*buf*, *status=None*)

Complete a split collective read using explicit offset

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Read\_ordered**(*buf*, *status=None*)

Collective read using shared file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Read\_ordered\_begin(buf)**

Start a split collective read using shared file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

None

**Read\_ordered\_end(buf, status=None)**

Complete a split collective read using shared file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Read\_shared(buf, status=None)**

Read using shared file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Seek(offset, whence=SEEK\_SET)**

Update the individual file pointer

**Parameters**

- **offset** (*int*)
- **whence** (*int*)

**Return type**

None

**Seek\_shared(offset, whence=SEEK\_SET)**

Update the shared file pointer

**Parameters**

- **offset** (*int*)
- **whence** (*int*)

**Return type**

None

**Set\_atomicity(flag)**

Set the atomicity mode

**Parameters**

**flag** (*bool*)

**Return type**

None

**Set\_errhandler**(*errhandler*)

Set the error handler for a file

**Parameters**

**errhandler** ([Errhandler](#))

**Return type**

None

**Set\_info**(*info*)

Set new values for the hints associated with a file

**Parameters**

**info** ([Info](#))

**Return type**

None

**Set\_size**(*size*)

Sets the file size

**Parameters**

**size** ([int](#))

**Return type**

None

**Set\_view**(*disp=0, etype=BYTE, filetype=None, datarep='native', info=INFO\_NULL*)

Set the file view

**Parameters**

- **disp** ([int](#))
- **etype** ([Datatype](#))
- **filetype** (*Optional* [[Datatype](#)])
- **datarep** ([str](#))
- **info** ([Info](#))

**Return type**

None

**Sync**()

Causes all previous writes to be transferred to the storage device

**Return type**

None

**Write**(*buf, status=None*)

Write using individual file pointer

**Parameters**

- **buf** ([BufSpec](#))
- **status** (*Optional* [[Status](#)])

**Return type**

None

**Write\_all**(*buf*, *status=None*)

Collective write using individual file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_all\_begin**(*buf*)

Start a split collective write using individual file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

None

**Write\_all\_end**(*buf*, *status=None*)

Complete a split collective write using individual file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_at**(*offset*, *buf*, *status=None*)

Write using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_at\_all**(*offset*, *buf*, *status=None*)

Collective write using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_at\_all\_begin**(*offset*, *buf*)

Start a split collective write using explicit offset

**Parameters**

- **offset** (*int*)
- **buf** (*BufSpec*)

**Return type**

None

**Write\_at\_all\_end**(*buf, status=None*)

Complete a split collective write using explicit offset

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_ordered**(*buf, status=None*)

Collective write using shared file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_ordered\_begin**(*buf*)

Start a split collective write using shared file pointer

**Parameters**

**buf** (*BufSpec*)

**Return type**

None

**Write\_ordered\_end**(*buf, status=None*)

Complete a split collective write using shared file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**Write\_shared**(*buf, status=None*)

Write using shared file pointer

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**classmethod** `f2py(arg)`

**Parameters**

**arg** (*int*)

**Return type**

*File*

**py2f()**

**Return type**

*int*

## Attributes Documentation

**amode**

file access mode

**atomicity**

**group**

file group

**info**

file info

**size**

file size

## mpi4py.MPI.Graphcomm

**class** `mpi4py.MPI.Graphcomm(comm=None)`

Bases: *Topocomm*

General graph topology intracommunicator

**Parameters**

**comm** (*Optional[Graphcomm]*)

**Return type**

*Graphcomm*

**static** `__new__(cls, comm=None)`

**Parameters**

**comm** (*Optional[Graphcomm]*)

**Return type**

*Graphcomm*

## Methods Summary

<i>Get_dims()</i>	Return the number of nodes and edges
<i>Get_neighbors(rank)</i>	Return list of neighbors of a process
<i>Get_neighbors_count(rank)</i>	Return number of neighbors of a process
<i>Get_topo()</i>	Return index and edges

## Attributes Summary

<i>dims</i>	number of nodes and edges
<i>edges</i>	
<i>index</i>	
<i>nedges</i>	number of edges
<i>neighbors</i>	
<i>nneighbors</i>	number of neighbors
<i>nodes</i>	number of nodes
<i>topo</i>	topology information

## Methods Documentation

### **Get\_dims()**

Return the number of nodes and edges

#### **Return type**

Tuple[int, int]

### **Get\_neighbors(rank)**

Return list of neighbors of a process

#### **Parameters**

**rank** (*int*)

#### **Return type**

List[int]

### **Get\_neighbors\_count(rank)**

Return number of neighbors of a process

#### **Parameters**

**rank** (*int*)

#### **Return type**

int

### **Get\_topo()**

Return index and edges

#### **Return type**

Tuple[List[int], List[int]]

## Attributes Documentation

### **dims**

number of nodes and edges

### **edges**

### **index**

### **nedges**

number of edges

### **neighbors**

### **nneighbors**

number of neighbors

### **nnodes**

number of nodes

### **topo**

topology information

## **mpi4py.MPI.Grequest**

**class** `mpi4py.MPI.Grequest`(*request=None*)

Bases: [\*Request\*](#)

Generalized request handle

#### **Parameters**

**request** (*Optional* [[\*Grequest\*](#)])

#### **Return type**

[\*Grequest\*](#)

**static** `__new__`(*cls, request=None*)

#### **Parameters**

**request** (*Optional* [[\*Grequest\*](#)])

#### **Return type**

[\*Grequest\*](#)

## Methods Summary

<a href="#"><i>Complete</i></a> ()	Notify that a user-defined request is complete
<a href="#"><i>Start</i></a> ( <i>query_fn, free_fn, cancel_fn[, args, ...]</i> )	Create and return a user-defined request



## Methods Documentation

### **Complete()**

Notify that a user-defined request is complete

#### **Return type**

None

### **classmethod Start**(*query\_fn, free\_fn, cancel\_fn, args=None, kargs=None*)

Create and return a user-defined request

#### **Parameters**

- **query\_fn** (*Callable*[..., None])
- **free\_fn** (*Callable*[..., None])
- **cancel\_fn** (*Callable*[..., None])
- **args** (*Optional*[*Tuple*[Any]])
- **kargs** (*Optional*[*Dict*[*str*, Any]])

#### **Return type**

*Grequest*

## **mpi4py.MPI.Group**

### **class** `mpi4py.MPI.Group`(*group=None*)

Bases: `object`

Group of processes

#### **Parameters**

**group** (*Optional*[`Group`])

#### **Return type**

*Group*

### **static** `__new__`(*cls, group=None*)

#### **Parameters**

**group** (*Optional*[`Group`])

#### **Return type**

*Group*

## Methods Summary

<i>Compare</i> (group1, group2)	Compare two groups
<i>Difference</i> (group1, group2)	Produce a group from the difference of two existing groups
<i>Dup</i> ()	Duplicate a group
<i>Excl</i> (ranks)	Produce a group by reordering an existing group and taking only unlisted members
<i>Free</i> ()	Free a group
<i>Get_rank</i> ()	Return the rank of this process in a group
<i>Get_size</i> ()	Return the size of a group
<i>Incl</i> (ranks)	Produce a group by reordering an existing group and taking only listed members
<i>Intersection</i> (group1, group2)	Produce a group as the intersection of two existing groups
<i>Range_excl</i> (ranks)	Create a new group by excluding ranges of processes from an existing group
<i>Range_incl</i> (ranks)	Create a new group from ranges of of ranks in an existing group
<i>Translate_ranks</i> (group1, ranks1[, group2])	Translate the ranks of processes in one group to those in another group
<i>Union</i> (group1, group2)	Produce a group by combining two existing groups
<i>f2py</i> (arg)	
<i>py2f</i> ()	

## Attributes Summary

<i>rank</i>	rank of this process in group
<i>size</i>	number of processes in group

## Methods Documentation

**classmethod** *Compare*(group1, group2)

Compare two groups

### Parameters

- **group1** (Group)
- **group2** (Group)

### Return type

int

**classmethod** *Difference*(group1, group2)

Produce a group from the difference of two existing groups

### Parameters

- **group1** (Group)

- **group2** (*Group*)

**Return type**

*Group*

**Dup()**

Duplicate a group

**Return type**

*Group*

**Excl(ranks)**

Produce a group by reordering an existing group and taking only unlisted members

**Parameters**

**ranks** (*Sequence* [*int*])

**Return type**

*Group*

**Free()**

Free a group

**Return type**

None

**Get\_rank()**

Return the rank of this process in a group

**Return type**

*int*

**Get\_size()**

Return the size of a group

**Return type**

*int*

**Incl(ranks)**

Produce a group by reordering an existing group and taking only listed members

**Parameters**

**ranks** (*Sequence* [*int*])

**Return type**

*Group*

**classmethod Intersection(group1, group2)**

Produce a group as the intersection of two existing groups

**Parameters**

- **group1** (*Group*)

- **group2** (*Group*)

**Return type**

*Group*

**Range\_excl(ranks)**

Create a new group by excluding ranges of processes from an existing group

**Parameters**

**ranks** (*Sequence*[*Tuple*[*int*, *int*, *int*]])

**Return type**

*Group*

**Range\_incl**(*ranks*)

Create a new group from ranges of of ranks in an existing group

**Parameters**

**ranks** (*Sequence*[*Tuple*[*int*, *int*, *int*]])

**Return type**

*Group*

**classmethod Translate\_ranks**(*group1*, *ranks1*, *group2=None*)

Translate the ranks of processes in one group to those in another group

**Parameters**

- **group1** (*Group*)
- **ranks1** (*Sequence*[*int*])
- **group2** (*Optional*[*Group*])

**Return type**

*List*[*int*]

**classmethod Union**(*group1*, *group2*)

Produce a group by combining two existing groups

**Parameters**

- **group1** (*Group*)
- **group2** (*Group*)

**Return type**

*Group*

**classmethod f2py**(*arg*)

**Parameters**

**arg** (*int*)

**Return type**

*Group*

**py2f**()

**Return type**

*int*

## Attributes Documentation

### **rank**

rank of this process in group

### **size**

number of processes in group

## **mpi4py.MPI.Info**

**class** `mpi4py.MPI.Info`(*info=None*)

Bases: `object`

Info object

### **Parameters**

**info** (*Optional*[`Info`])

### **Return type**

*Info*

**static** `__new__`(*cls, info=None*)

### **Parameters**

**info** (*Optional*[`Info`])

### **Return type**

*Info*

## Methods Summary

<i>Create()</i>	Create a new, empty info object
<i>Delete</i> (key)	Remove a (key, value) pair from info
<i>Dup</i> ()	Duplicate an existing info object, creating a new object, with the same (key, value) pairs and the same ordering of keys
<i>Free</i> ()	Free a info object
<i>Get</i> (key[, maxlen])	Retrieve the value associated with a key
<i>Get_nkeys</i> ()	Return the number of currently defined keys in info
<i>Get_nthkey</i> (n)	Return the nth defined key in info.
<i>Set</i> (key, value)	Add the (key, value) pair to info, and overrides the value if a value for the same key was previously set
<i>clear</i> ()	info clear
<i>copy</i> ()	info copy
<i>f2py</i> (arg)	
<i>get</i> (key[, default])	info get
<i>items</i> ()	info items
<i>keys</i> ()	info keys
<i>pop</i> (key, *default)	info pop
<i>popitem</i> ()	info popitem
<i>py2f</i> ()	
<i>update</i> ([other])	info update
<i>values</i> ()	info values

## Methods Documentation

### **classmethod** **Create()**

Create a new, empty info object

#### **Return type**

*Info*

### **Delete**(key)

Remove a (key, value) pair from info

#### **Parameters**

**key** (*str*)

#### **Return type**

None

### **Dup**()

Duplicate an existing info object, creating a new object, with the same (key, value) pairs and the same ordering of keys

#### **Return type**

*Info*

### **Free**()

Free a info object

**Return type**

None

**Get**(*key*, *maxlen=-1*)

Retrieve the value associated with a key

**Parameters**

- **key** (*str*)
- **maxlen** (*int*)

**Return type**

Optional[*str*]

**Get\_nkeys**()

Return the number of currently defined keys in info

**Return type**

*int*

**Get\_nthkey**(*n*)

Return the *n*th defined key in info. Keys are numbered in the range [0, N) where N is the value returned by [Info.Get\\_nkeys\(\)](#)

**Parameters**

**n** (*int*)

**Return type**

*str*

**Set**(*key*, *value*)

Add the (key, value) pair to info, and overrides the value if a value for the same key was previously set

**Parameters**

- **key** (*str*)
- **value** (*str*)

**Return type**

None

**clear**()

info clear

**Return type**

None

**copy**()

info copy

**Return type**

*Info*

**classmethod f2py**(*arg*)

**Parameters**

**arg** (*int*)

**Return type**

*Info*

**get**(*key*, *default=None*)

info get

**Parameters**

- **key** (*str*)
- **default** (*Optional[str]*)

**Return type**

*Optional[str]*

**items**()

info items

**Return type**

*List[Tuple[str, str]]*

**keys**()

info keys

**Return type**

*List[str]*

**pop**(*key*, *\*default*)

info pop

**Parameters**

- **key** (*str*)
- **default** (*str*)

**Return type**

*str*

**popitem**()

info popitem

**Return type**

*Tuple[str, str]*

**py2f**()

**Return type**

*int*

**update**(*other=()*, *\*\*kws*)

info update

**Parameters**

- **other** (*Union[Info, Mapping[str, str], Iterable[Tuple[str, str]]]*)
- **kws** (*str*)

**Return type**

*None*

**values**()

info values

**Return type**

*List[str]*



## mpi4py.MPI.Intercomm

**class** mpi4py.MPI.**Intercomm**(comm=None)

Bases: *Comm*

Intercommunicator

### Parameters

**comm** (*Optional*[*Intercomm*])

### Return type

*Intercomm*

**static** **\_\_new\_\_**(cls, comm=None)

### Parameters

**comm** (*Optional*[*Intercomm*])

### Return type

*Intercomm*

## Methods Summary

<i>Get_remote_group</i> ()	Access the remote group associated with the inter-communicator
<i>Get_remote_size</i> ()	Intercommunicator remote size
<i>Merge</i> ([high])	Merge intercommunicator

## Attributes Summary

<i>remote_group</i>	remote group
<i>remote_size</i>	number of remote processes

## Methods Documentation

### **Get\_remote\_group**()

Access the remote group associated with the inter-communicator

### Return type

*Group*

### **Get\_remote\_size**()

Intercommunicator remote size

### Return type

*int*

### **Merge**(high=False)

Merge intercommunicator

### Parameters

**high** (*bool*)

**Return type**  
*Intracomm*

## Attributes Documentation

**remote\_group**

remote group

**remote\_size**

number of remote processes

## mpi4py.MPI.Intracomm

**class** mpi4py.MPI.Intracomm(comm=None)

Bases: *Comm*

Intracommunicator

### Parameters

**comm** (*Optional*[*Intracomm*])

### Return type

*Intracomm*

**static** \_\_new\_\_(cls, comm=None)

### Parameters

**comm** (*Optional*[*Intracomm*])

### Return type

*Intracomm*

## Methods Summary

<a href="#"><i>Accept</i></a> (port_name[, info, root])	Accept a request to form a new intercommunicator
<a href="#"><i>Cart_map</i></a> (dims[, periods])	Return an optimal placement for the calling process on the physical machine
<a href="#"><i>Connect</i></a> (port_name[, info, root])	Make a request to form a new intercommunicator
<a href="#"><i>Create_cart</i></a> (dims[, periods, reorder])	Create cartesian communicator
<a href="#"><i>Create_dist_graph</i></a> (sources, degrees, destinations)	Create distributed graph communicator
<a href="#"><i>Create_dist_graph_adjacent</i></a> (sources, destinations)	Create distributed graph communicator
<a href="#"><i>Create_graph</i></a> (index, edges[, reorder])	Create graph communicator
<a href="#"><i>Create_intercomm</i></a> (local_leader, peer_comm, ...)	Create intercommunicator
<a href="#"><i>Exscan</i></a> (sendbuf, recvbuf[, op])	Exclusive Scan
<a href="#"><i>Graph_map</i></a> (index, edges)	Return an optimal placement for the calling process on the physical machine
<a href="#"><i>Iexscan</i></a> (sendbuf, recvbuf[, op])	Inclusive Scan
<a href="#"><i>Iscan</i></a> (sendbuf, recvbuf[, op])	Inclusive Scan
<a href="#"><i>Scan</i></a> (sendbuf, recvbuf[, op])	Inclusive Scan
<a href="#"><i>Spawn</i></a> (command[, args, maxprocs, info, root, ...])	Spawn instances of a single MPI application
<a href="#"><i>Spawn_multiple</i></a> (command[, args, maxprocs, ...])	Spawn instances of multiple MPI applications
<a href="#"><i>exscan</i></a> (sendobj[, op])	Exclusive Scan
<a href="#"><i>scan</i></a> (sendobj[, op])	Inclusive Scan

## Methods Documentation

**Accept**(port\_name, info=INFO\_NULL, root=0)

Accept a request to form a new intercommunicator

### Parameters

- **port\_name** (*str*)
- **info** (*Info*)
- **root** (*int*)

### Return type

*Intercomm*

**Cart\_map**(dims, periods=None)

Return an optimal placement for the calling process on the physical machine

### Parameters

- **dims** (*Sequence[int]*)
- **periods** (*Optional[Sequence[bool]]*)

### Return type

*int*

**Connect**(port\_name, info=INFO\_NULL, root=0)

Make a request to form a new intercommunicator

### Parameters

- **port\_name** (*str*)

- **info** ([Info](#))

- **root** ([int](#))

**Return type**

[Intercomm](#)

**Create\_cart**(*dims, periods=None, reorder=False*)

Create cartesian communicator

**Parameters**

- **dims** ([Sequence](#)[[int](#)])

- **periods** ([Optional](#)[[Sequence](#)[[bool](#)]])

- **reorder** ([bool](#))

**Return type**

[Cartcomm](#)

**Create\_dist\_graph**(*sources, degrees, destinations, weights=None, info=INFO\_NULL, reorder=False*)

Create distributed graph communicator

**Parameters**

- **sources** ([Sequence](#)[[int](#)])

- **degrees** ([Sequence](#)[[int](#)])

- **destinations** ([Sequence](#)[[int](#)])

- **weights** ([Optional](#)[[Sequence](#)[[int](#)]])

- **info** ([Info](#))

- **reorder** ([bool](#))

**Return type**

[Distgraphcomm](#)

**Create\_dist\_graph\_adjacent**(*sources, destinations, sourceweights=None, destweights=None, info=INFO\_NULL, reorder=False*)

Create distributed graph communicator

**Parameters**

- **sources** ([Sequence](#)[[int](#)])

- **destinations** ([Sequence](#)[[int](#)])

- **sourceweights** ([Optional](#)[[Sequence](#)[[int](#)]])

- **destweights** ([Optional](#)[[Sequence](#)[[int](#)]])

- **info** ([Info](#))

- **reorder** ([bool](#))

**Return type**

[Distgraphcomm](#)

**Create\_graph**(*index, edges, reorder=False*)

Create graph communicator

**Parameters**

- **index** (*Sequence*[*int*])
- **edges** (*Sequence*[*int*])
- **reorder** (*bool*)

**Return type**

*Graphcomm*

**Create\_intercomm**(*local\_leader*, *peer\_comm*, *remote\_leader*, *tag=0*)

Create intercommunicator

**Parameters**

- **local\_leader** (*int*)
- **peer\_comm** (*Intracomm*)
- **remote\_leader** (*int*)
- **tag** (*int*)

**Return type**

*Intercomm*

**Exscan**(*sendbuf*, *recvbuf*, *op=SUM*)

Exclusive Scan

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*BufSpec*)
- **op** (*Op*)

**Return type**

None

**Graph\_map**(*index*, *edges*)

Return an optimal placement for the calling process on the physical machine

**Parameters**

- **index** (*Sequence*[*int*])
- **edges** (*Sequence*[*int*])

**Return type**

*int*

**Iexscan**(*sendbuf*, *recvbuf*, *op=SUM*)

Inclusive Scan

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*BufSpec*)
- **op** (*Op*)

**Return type**

*Request*

**Iscan**(*sendbuf*, *recvbuf*, *op*=*SUM*)

Inclusive Scan

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*BufSpec*)
- **op** (*Op*)

**Return type**

*Request*

**Scan**(*sendbuf*, *recvbuf*, *op*=*SUM*)

Inclusive Scan

**Parameters**

- **sendbuf** (*Union*[*BufSpec*, *InPlace*])
- **recvbuf** (*BufSpec*)
- **op** (*Op*)

**Return type**

*None*

**Spawn**(*command*, *args*=*None*, *maxprocs*=*1*, *info*=*INFO\_NULL*, *root*=*0*, *errcodes*=*None*)

Spawn instances of a single MPI application

**Parameters**

- **command** (*str*)
- **args** (*Optional*[*Sequence*[*str*]])
- **maxprocs** (*int*)
- **info** (*Info*)
- **root** (*int*)
- **errcodes** (*Optional*[*list*])

**Return type**

*Intercomm*

**Spawn\_multiple**(*command*, *args*=*None*, *maxprocs*=*None*, *info*=*INFO\_NULL*, *root*=*0*, *errcodes*=*None*)

Spawn instances of multiple MPI applications

**Parameters**

- **command** (*Sequence*[*str*])
- **args** (*Optional*[*Sequence*[*Sequence*[*str*]]])
- **maxprocs** (*Optional*[*Sequence*[*int*]])
- **info** (*Union*[*Info*, *Sequence*[*Info*]])
- **root** (*int*)
- **errcodes** (*Optional*[*list*])

**Return type**

*Intercomm*

**exscan**(*sendobj*, *op*=*SUM*)

Exclusive Scan

**Parameters**

- **sendobj** (*Any*)
- **op** (*Union*[*Op*, *Callable*[[*Any*, *Any*], *Any*]])

**Return type**

*Any*

**scan**(*sendobj*, *op*=*SUM*)

Inclusive Scan

**Parameters**

- **sendobj** (*Any*)
- **op** (*Union*[*Op*, *Callable*[[*Any*, *Any*], *Any*]])

**Return type**

*Any*

## **mpi4py.MPI.Message**

**class** `mpi4py.MPI.Message`(*message*=*None*)

Bases: `object`

Matched message handle

**Parameters**

**message** (*Optional*[`Message`])

**Return type**

`Message`

**static** `__new__`(*cls*, *message*=*None*)

**Parameters**

**message** (*Optional*[`Message`])

**Return type**

`Message`

## Methods Summary

<i>Iprobe</i> (comm[, source, tag, status])	Nonblocking test for a matched message
<i>Irecv</i> (buf)	Nonblocking receive of matched message
<i>Probe</i> (comm[, source, tag, status])	Blocking test for a matched message
<i>Recv</i> (buf[, status])	Blocking receive of matched message
<i>f2py</i> (arg)	
<i>iprobe</i> (comm[, source, tag, status])	Nonblocking test for a matched message
<i>irecv</i> ()	Nonblocking receive of matched message
<i>probe</i> (comm[, source, tag, status])	Blocking test for a matched message
<i>py2f</i> ()	
<i>recv</i> ([status])	Blocking receive of matched message

## Methods Documentation

**classmethod** *Iprobe*(comm, source=ANY\_SOURCE, tag=ANY\_TAG, status=None)

Nonblocking test for a matched message

### Parameters

- **comm** (*Comm*)
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

### Return type

*Optional[Message]*

**Irecv**(buf)

Nonblocking receive of matched message

### Parameters

**buf** (*BufSpec*)

### Return type

*Request*

**classmethod** *Probe*(comm, source=ANY\_SOURCE, tag=ANY\_TAG, status=None)

Blocking test for a matched message

### Parameters

- **comm** (*Comm*)
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

### Return type

*Message*



**Recv**(*buf*, *status=None*)

Blocking receive of matched message

**Parameters**

- **buf** (*BufSpec*)
- **status** (*Optional[Status]*)

**Return type**

None

**classmethod f2py**(*arg*)

**Parameters**

**arg** (*int*)

**Return type**

*Message*

**classmethod iprobe**(*comm*, *source=ANY\_SOURCE*, *tag=ANY\_TAG*, *status=None*)

Nonblocking test for a matched message

**Parameters**

- **comm** (*Comm*)
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

*Optional[Message]*

**irecv**()

Nonblocking receive of matched message

**Return type**

*Request*

**classmethod probe**(*comm*, *source=ANY\_SOURCE*, *tag=ANY\_TAG*, *status=None*)

Blocking test for a matched message

**Parameters**

- **comm** (*Comm*)
- **source** (*int*)
- **tag** (*int*)
- **status** (*Optional[Status]*)

**Return type**

*Message*

**py2f**()

**Return type**

*int*

**recv**(*status=None*)

Blocking receive of matched message

**Parameters**

**status** (*Optional*[*Status*])

**Return type**

Any

## mpi4py.MPI.Op

**class** mpi4py.MPI.**Op**(*op=None*)

Bases: *object*

Operation object

**Parameters**

**op** (*Optional*[*Op*])

**Return type**

*Op*

**static** **\_\_new\_\_**(*cls, op=None*)

**Parameters**

**op** (*Optional*[*Op*])

**Return type**

*Op*

## Methods Summary

<i>Create</i> (function[, commute])	Create a user-defined operation
<i>Free</i> ()	Free the operation
<i>Is_commutative</i> ()	Query reduction operations for their commutativity
<i>Reduce_local</i> (inbuf, inoutbuf)	Apply a reduction operator to local data
<i>f2py</i> (arg)	
<i>py2f</i> ()	

## Attributes Summary

<i>is_commutative</i>	is commutative
<i>is_predefined</i>	is a predefined operation

## Methods Documentation

**classmethod** `Create(function, commute=False)`

Create a user-defined operation

**Parameters**

- **function** (*Callable*[[*Buffer*, *Buffer*, *Datatype*], *None*])
- **commute** (*bool*)

**Return type**

*Op*

**Free()**

Free the operation

**Return type**

*None*

**Is\_commutative()**

Query reduction operations for their commutativity

**Return type**

*bool*

**Reduce\_local(inbuf, inoutbuf)**

Apply a reduction operator to local data

**Parameters**

- **inbuf** (*BufSpec*)
- **inoutbuf** (*BufSpec*)

**Return type**

*None*

**classmethod** `f2py(arg)`

**Parameters**

**arg** (*int*)

**Return type**

*Op*

**py2f()**

**Return type**

*int*

## Attributes Documentation

**is\_commutative**

is commutative

**is\_predefined**

is a predefined operation

## mpi4py.MPI.Pickle

**class** mpi4py.MPI.Pickle(*dumps=None, loads=None, protocol=None*)

Bases: `object`

Pickle/unpickle Python objects

### Parameters

- **dumps** (*Optional*[*Callable*[[*Any*, *int*], *bytes*]])
- **loads** (*Optional*[*Callable*[[*Buffer*], *Any*]])
- **protocol** (*Optional*[*int*])

**\_\_init\_\_** (*dumps=None, loads=None, protocol=None*)

### Parameters

- **dumps** (*Optional*[*Callable*[[*Any*, *int*], *bytes*]])
- **loads** (*Optional*[*Callable*[[*Buffer*], *Any*]])
- **protocol** (*Optional*[*int*])

### Return type

*None*

## Methods Summary

<i>dumps</i> (obj[, buffer_callback])	Serialize object to pickle data stream.
<i>loads</i> (data[, buffers])	Deserialize object from pickle data stream.

## Attributes Summary

<i>PROTOCOL</i>	pickle protocol
-----------------	-----------------

## Methods Documentation

**dumps** (*obj, buffer\_callback=None*)

Serialize object to pickle data stream.

### Parameters

- **obj** (*Any*)
- **buffer\_callback** (*Optional*[*Callable*[[*Buffer*], *Any*]])

### Return type

*bytes*

**loads** (*data, buffers=None*)

Deserialize object from pickle data stream.

### Parameters

- **data** (*Buffer*)

- **buffers** (*Optional*[*Iterable*[*Buffer*]])

**Return type**  
Any

## Attributes Documentation

### PROTOCOL

pickle protocol

## mpi4py.MPI.Prerequest

**class** `mpi4py.MPI.Prerequest(request=None)`

Bases: *Request*

Persistent request handle

### Parameters

**request** (*Optional*[*Prerequest*])

### Return type

*Prerequest*

**static** `__new__(cls, request=None)`

### Parameters

**request** (*Optional*[*Prerequest*])

### Return type

*Prerequest*

## Methods Summary

<i>Start</i> ()	Initiate a communication with a persistent request
<i>Startall</i> (requests)	Start a collection of persistent requests

## Methods Documentation

### Start()

Initiate a communication with a persistent request

### Return type

None

**classmethod** `Startall(requests)`

Start a collection of persistent requests

### Parameters

**requests** (*List*[*Prerequest*])

### Return type

None

## mpi4py.MPI.Request

**class** mpi4py.MPI.Request(*request=None*)

Bases: `object`

Request handle

### Parameters

**request** (*Optional* [`Request`])

### Return type

*Request*

**static** `__new__`(*cls*, *request=None*)

### Parameters

**request** (*Optional* [`Request`])

### Return type

*Request*

## Methods Summary

<code>Cancel()</code>	Cancel a communication request
<code>Free()</code>	Free a communication request
<code>Get_status([status])</code>	Non-destructive test for the completion of a request
<code>Test([status])</code>	Test for the completion of a send or receive
<code>Testall(requests[, statuses])</code>	Test for completion of all previously initiated requests
<code>Testany(requests[, status])</code>	Test for completion of any previously initiated request
<code>Testsome(requests[, statuses])</code>	Test for completion of some previously initiated requests
<code>Wait([status])</code>	Wait for a send or receive to complete
<code>Waitall(requests[, statuses])</code>	Wait for all previously initiated requests to complete
<code>Waitany(requests[, status])</code>	Wait for any previously initiated request to complete
<code>Waitsome(requests[, statuses])</code>	Wait for some previously initiated requests to complete
<code>cancel()</code>	Cancel a communication request
<code>f2py(arg)</code>	
<code>get_status([status])</code>	Non-destructive test for the completion of a request
<code>py2f()</code>	
<code>test([status])</code>	Test for the completion of a send or receive
<code>testall(requests[, statuses])</code>	Test for completion of all previously initiated requests
<code>testany(requests[, status])</code>	Test for completion of any previously initiated request
<code>testsome(requests[, statuses])</code>	Test for completion of some previously initiated requests
<code>wait([status])</code>	Wait for a send or receive to complete
<code>waitall(requests[, statuses])</code>	Wait for all previously initiated requests to complete
<code>waitany(requests[, status])</code>	Wait for any previously initiated request to complete
<code>waitsome(requests[, statuses])</code>	Wait for some previously initiated requests to complete

## Methods Documentation

### **Cancel()**

Cancel a communication request

#### **Return type**

None

### **Free()**

Free a communication request

#### **Return type**

None

### **Get\_status(status=None)**

Non-destructive test for the completion of a request

#### **Parameters**

**status** (*Optional* [*Status*])

#### **Return type**

bool

### **Test(status=None)**

Test for the completion of a send or receive

#### **Parameters**

**status** (*Optional* [*Status*])

#### **Return type**

bool

### **classmethod Testall(requests, statuses=None)**

Test for completion of all previously initiated requests

#### **Parameters**

- **requests** (*Sequence* [*Request*])
- **statuses** (*Optional* [*List* [*Status*]])

#### **Return type**

bool

### **classmethod Testany(requests, status=None)**

Test for completion of any previously initiated request

#### **Parameters**

- **requests** (*Sequence* [*Request*])
- **status** (*Optional* [*Status*])

#### **Return type**

Tuple[int, bool]

### **classmethod Testsome(requests, statuses=None)**

Test for completion of some previously initiated requests

#### **Parameters**

- **requests** (*Sequence* [*Request*])
- **statuses** (*Optional* [*List* [*Status*]])

**Return type**  
Optional[List[int]]

**Wait**(*status=None*)

Wait for a send or receive to complete

**Parameters**  
**status** (Optional[Status])

**Return type**  
Literal[True]

**classmethod Waitall**(*requests, statuses=None*)

Wait for all previously initiated requests to complete

**Parameters**

- **requests** (Sequence[Request])
- **statuses** (Optional[List[Status]])

**Return type**  
Literal[True]

**classmethod Waitany**(*requests, status=None*)

Wait for any previously initiated request to complete

**Parameters**

- **requests** (Sequence[Request])
- **status** (Optional[Status])

**Return type**  
int

**classmethod Waitsome**(*requests, statuses=None*)

Wait for some previously initiated requests to complete

**Parameters**

- **requests** (Sequence[Request])
- **statuses** (Optional[List[Status]])

**Return type**  
Optional[List[int]]

**cancel**()

Cancel a communication request

**Return type**  
None

**classmethod f2py**(*arg*)

**Parameters**  
**arg** (int)

**Return type**  
Request



**get\_status**(*status=None*)

Non-destructive test for the completion of a request

**Parameters**

**status** (*Optional*[[Status](#)])

**Return type**

[bool](#)

**py2f**()

**Return type**

[int](#)

**test**(*status=None*)

Test for the completion of a send or receive

**Parameters**

**status** (*Optional*[[Status](#)])

**Return type**

Tuple[[bool](#), *Optional*[*Any*]]

**classmethod testall**(*requests, statuses=None*)

Test for completion of all previously initiated requests

**Parameters**

- **requests** (*Sequence*[[Request](#)])
- **statuses** (*Optional*[*List*[[Status](#)]])

**Return type**

Tuple[[bool](#), *Optional*[*List*[*Any*]]]

**classmethod testany**(*requests, status=None*)

Test for completion of any previously initiated request

**Parameters**

- **requests** (*Sequence*[[Request](#)])
- **status** (*Optional*[[Status](#)])

**Return type**

Tuple[[int](#), [bool](#), *Optional*[*Any*]]

**classmethod testsome**(*requests, statuses=None*)

Test for completion of some previously initiated requests

**Parameters**

- **requests** (*Sequence*[[Request](#)])
- **statuses** (*Optional*[*List*[[Status](#)]])

**Return type**

Tuple[*Optional*[*List*[[int](#)]], *Optional*[*List*[*Any*]]]

**wait**(*status=None*)

Wait for a send or receive to complete

**Parameters**

**status** (*Optional*[[Status](#)])

**Return type**

Any

**classmethod** **waitall**(*requests*, *statuses=None*)

Wait for all previously initiated requests to complete

**Parameters**

- **requests** (*Sequence*[[Request](#)])
- **statuses** (*Optional*[*List*[[Status](#)]])

**Return type**

*List*[Any]

**classmethod** **waitany**(*requests*, *status=None*)

Wait for any previously initiated request to complete

**Parameters**

- **requests** (*Sequence*[[Request](#)])
- **status** (*Optional*[[Status](#)])

**Return type**

*Tuple*[[int](#), Any]

**classmethod** **waitsome**(*requests*, *statuses=None*)

Wait for some previously initiated requests to complete

**Parameters**

- **requests** (*Sequence*[[Request](#)])
- **statuses** (*Optional*[*List*[[Status](#)]])

**Return type**

*Tuple*[*Optional*[*List*[[int](#)]], *Optional*[*List*[Any]]]

**[mpi4py.MPI.Status](#)**

**class** [mpi4py.MPI.Status](#)(*status=None*)

Bases: [object](#)

Status object

**Parameters**

**status** (*Optional*[[Status](#)])

**Return type**

[Status](#)

**static** **\_\_new\_\_**(*cls*, *status=None*)

**Parameters**

**status** (*Optional*[[Status](#)])

**Return type**

[Status](#)

## Methods Summary

<code>Get_count([datatype])</code>	Get the number of <i>top level</i> elements
<code>Get_elements(datatype)</code>	Get the number of basic elements in a datatype
<code>Get_error()</code>	Get message error
<code>Get_source()</code>	Get message source
<code>Get_tag()</code>	Get message tag
<code>Is_cancelled()</code>	Test to see if a request was cancelled
<code>Set_cancelled(flag)</code>	Set the cancelled state associated with a status
<code>Set_elements(datatype, count)</code>	Set the number of elements in a status
<code>Set_error(error)</code>	Set message error
<code>Set_source(source)</code>	Set message source
<code>Set_tag(tag)</code>	Set message tag
<code>f2py(arg)</code>	
<code>py2f()</code>	

## Attributes Summary

<code>cancelled</code>	cancelled state
<code>count</code>	byte count
<code>error</code>	
<code>source</code>	
<code>tag</code>	

## Methods Documentation

### **Get\_count**(*datatype*=*BYTE*)

Get the number of *top level* elements

#### **Parameters**

**datatype** (*Datatype*)

#### **Return type**

*int*

### **Get\_elements**(*datatype*)

Get the number of basic elements in a datatype

#### **Parameters**

**datatype** (*Datatype*)

#### **Return type**

*int*

### **Get\_error**()

Get message error

**Return type**

`int`

**Get\_source()**

Get message source

**Return type**

`int`

**Get\_tag()**

Get message tag

**Return type**

`int`

**Is\_cancelled()**

Test to see if a request was cancelled

**Return type**

`bool`

**Set\_cancelled(*flag*)**

Set the cancelled state associated with a status

---

**Note:** This should be only used when implementing query callback functions for generalized requests

---

**Parameters**

**flag** (`bool`)

**Return type**

None

**Set\_elements(*datatype*, *count*)**

Set the number of elements in a status

---

**Note:** This should be only used when implementing query callback functions for generalized requests

---

**Parameters**

- **datatype** (`Datatype`)

- **count** (`int`)

**Return type**

None

**Set\_error(*error*)**

Set message error

**Parameters**

**error** (`int`)

**Return type**

None

**Set\_source**(*source*)

Set message source

**Parameters**

**source** (*int*)

**Return type**

None

**Set\_tag**(*tag*)

Set message tag

**Parameters**

**tag** (*int*)

**Return type**

None

**classmethod** **f2py**(*arg*)

**Parameters**

**arg** (*List[int]*)

**Return type**

*Status*

**py2f**()

**Return type**

*List[int]*

## Attributes Documentation

**cancelled**

cancelled state

**count**

byte count

**error**

**source**

**tag**

## mpi4py.MPI.Topocomm

**class** `mpi4py.MPI.Topocomm`(*comm=None*)

Bases: *Intracomm*

Topology intracommunicator

**Parameters**

**comm** (*Optional[Topocomm]*)

**Return type**

*Topocomm*

**static** `__new__(cls, comm=None)`

**Parameters**

**comm** (*Optional*[`Topocomm`])

**Return type**

*Topocomm*

## Methods Summary

<i>Ineighbor_allgather</i> (sendbuf, recvbuf)	Nonblocking Neighbor Gather to All
<i>Ineighbor_allgatherv</i> (sendbuf, recvbuf)	Nonblocking Neighbor Gather to All Vector
<i>Ineighbor_alltoall</i> (sendbuf, recvbuf)	Nonblocking Neighbor All-to-All
<i>Ineighbor_alltoallv</i> (sendbuf, recvbuf)	Nonblocking Neighbor All-to-All Vector
<i>Ineighbor_alltoallw</i> (sendbuf, recvbuf)	Nonblocking Neighbor All-to-All Generalized
<i>Neighbor_allgather</i> (sendbuf, recvbuf)	Neighbor Gather to All
<i>Neighbor_allgatherv</i> (sendbuf, recvbuf)	Neighbor Gather to All Vector
<i>Neighbor_alltoall</i> (sendbuf, recvbuf)	Neighbor All-to-All
<i>Neighbor_alltoallv</i> (sendbuf, recvbuf)	Neighbor All-to-All Vector
<i>Neighbor_alltoallw</i> (sendbuf, recvbuf)	Neighbor All-to-All Generalized
<i>neighbor_allgather</i> (sendobj)	Neighbor Gather to All
<i>neighbor_alltoall</i> (sendobj)	Neighbor All to All Scatter/Gather

## Attributes Summary

<i>degrees</i>	number of incoming and outgoing neighbors
<i>indegree</i>	number of incoming neighbors
<i>inedges</i>	incoming neighbors
<i>inoutedges</i>	incoming and outgoing neighbors
<i>outdegree</i>	number of outgoing neighbors
<i>outedges</i>	outgoing neighbors

## Methods Documentation

***Ineighbor\_allgather***(*sendbuf*, *recvbuf*)

Nonblocking Neighbor Gather to All

**Parameters**

- **sendbuf** (*BufSpec*)
- **recvbuf** (*BufSpecB*)

**Return type**

*Request*

***Ineighbor\_allgatherv***(*sendbuf*, *recvbuf*)

Nonblocking Neighbor Gather to All Vector

**Parameters**

- **sendbuf** (*BufSpec*)

- **recvbuf** (*BufSpecV*)

**Return type**

*Request*

**Ineighbor\_alltoall**(*sendbuf, recvbuf*)

Nonblocking Neighbor All-to-All

**Parameters**

- **sendbuf** (*BufSpecB*)
- **recvbuf** (*BufSpecB*)

**Return type**

*Request*

**Ineighbor\_alltoallv**(*sendbuf, recvbuf*)

Nonblocking Neighbor All-to-All Vector

**Parameters**

- **sendbuf** (*BufSpecV*)
- **recvbuf** (*BufSpecV*)

**Return type**

*Request*

**Ineighbor\_alltoallw**(*sendbuf, recvbuf*)

Nonblocking Neighbor All-to-All Generalized

**Parameters**

- **sendbuf** (*BufSpecW*)
- **recvbuf** (*BufSpecW*)

**Return type**

*Request*

**Neighbor\_allgather**(*sendbuf, recvbuf*)

Neighbor Gather to All

**Parameters**

- **sendbuf** (*BufSpec*)
- **recvbuf** (*BufSpecB*)

**Return type**

None

**Neighbor\_allgatherv**(*sendbuf, recvbuf*)

Neighbor Gather to All Vector

**Parameters**

- **sendbuf** (*BufSpec*)
- **recvbuf** (*BufSpecV*)

**Return type**

None

**Neighbor\_alltoall**(*sendbuf*, *recvbuf*)

Neighbor All-to-All

**Parameters**

- **sendbuf** (*BufSpecB*)
- **recvbuf** (*BufSpecB*)

**Return type**

None

**Neighbor\_alltoallv**(*sendbuf*, *recvbuf*)

Neighbor All-to-All Vector

**Parameters**

- **sendbuf** (*BufSpecV*)
- **recvbuf** (*BufSpecV*)

**Return type**

None

**Neighbor\_alltoallw**(*sendbuf*, *recvbuf*)

Neighbor All-to-All Generalized

**Parameters**

- **sendbuf** (*BufSpecW*)
- **recvbuf** (*BufSpecW*)

**Return type**

None

**neighbor\_allgather**(*sendobj*)

Neighbor Gather to All

**Parameters**

**sendobj** (*Any*)

**Return type**

List[*Any*]

**neighbor\_alltoall**(*sendobj*)

Neighbor All to All Scatter/Gather

**Parameters**

**sendobj** (*List[Any]*)

**Return type**

List[*Any*]



## Attributes Documentation

### degrees

number of incoming and outgoing neighbors

### indegree

number of incoming neighbors

### inedges

incoming neighbors

### inoutedges

incoming and outgoing neighbors

### outdegree

number of outgoing neighbors

### outedges

outgoing neighbors

## mpi4py.MPI.Win

**class** `mpi4py.MPI.Win`(*win=None*)

Bases: `object`

Window handle

#### Parameters

**win** (*Optional* [`Win`])

#### Return type

`Win`

**static** `__new__`(*cls*, *win=None*)

#### Parameters

**win** (*Optional* [`Win`])

#### Return type

`Win`

## Methods Summary

<code>Accumulate</code> ( <i>origin</i> , <i>target_rank</i> [, <i>target</i> , <i>op</i> ])	Accumulate data into the target process
<code>Allocate</code> ( <i>size</i> [, <i>disp_unit</i> , <i>info</i> , <i>comm</i> ])	Create an window object for one-sided communication
<code>Allocate_shared</code> ( <i>size</i> [, <i>disp_unit</i> , <i>info</i> , <i>comm</i> ])	Create an window object for one-sided communication
<code>Attach</code> ( <i>memory</i> )	Attach a local memory region
<code>Call_errhandler</code> ( <i>errorcode</i> )	Call the error handler installed on a window
<code>Compare_and_swap</code> ( <i>origin</i> , <i>compare</i> , <i>result</i> , ...)	Perform one-sided atomic compare-and-swap
<code>Complete</code> ()	Completes an RMA operations begun after an <code>Win.Start()</code>

continues on next page

Table 5 – continued from previous page

<i>Create</i> (memory[, disp_unit, info, comm])	Create an window object for one-sided communication
<i>Create_dynamic</i> ([info, comm])	Create an window object for one-sided communication
<i>Create_keyval</i> ([copy_fn, delete_fn, nopython])	Create a new attribute key for windows
<i>Delete_attr</i> (keyval)	Delete attribute value associated with a key
<i>Detach</i> (memory)	Detach a local memory region
<i>Fence</i> ([assertion])	Perform an MPI fence synchronization on a window
<i>Fetch_and_op</i> (origin, result, target_rank[, ...])	Perform one-sided read-modify-write
<i>Flush</i> (rank)	Complete all outstanding RMA operations at the given target
<i>Flush_all</i> ()	Complete all outstanding RMA operations at all targets
<i>Flush_local</i> (rank)	Complete locally all outstanding RMA operations at the given target
<i>Flush_local_all</i> ()	Complete locally all outstanding RMA operations at all targets
<i>Free</i> ()	Free a window
<i>Free_keyval</i> (keyval)	Free an attribute key for windows
<i>Get</i> (origin, target_rank[, target])	Get data from a memory window on a remote process.
<i>Get_accumulate</i> (origin, result, target_rank)	Fetch-and-accumulate data into the target process
<i>Get_attr</i> (keyval)	Retrieve attribute value by key
<i>Get_errhandler</i> ()	Get the error handler for a window
<i>Get_group</i> ()	Return a duplicate of the group of the communicator used to create the window
<i>Get_info</i> ()	Return the hints for a windows that are currently in use
<i>Get_name</i> ()	Get the print name associated with the window
<i>Lock</i> (rank[, lock_type, assertion])	Begin an RMA access epoch at the target process
<i>Lock_all</i> ([assertion])	Begin an RMA access epoch at all processes
<i>Post</i> (group[, assertion])	Start an RMA exposure epoch
<i>Put</i> (origin, target_rank[, target])	Put data into a memory window on a remote process.
<i>Raccumulate</i> (origin, target_rank[, target, op])	Fetch-and-accumulate data into the target process
<i>Rget</i> (origin, target_rank[, target])	Get data from a memory window on a remote process.
<i>Rget_accumulate</i> (origin, result, target_rank)	Accumulate data into the target process using remote memory access.
<i>Rput</i> (origin, target_rank[, target])	Put data into a memory window on a remote process.
<i>Set_attr</i> (keyval, attrval)	Store attribute value associated with a key
<i>Set_errhandler</i> (errhandler)	Set the error handler for a window
<i>Set_info</i> (info)	Set new values for the hints associated with a window
<i>Set_name</i> (name)	Set the print name associated with the window
<i>Shared_query</i> (rank)	Query the process-local address for remote memory segments created with <i>Win.Allocate_shared()</i>
<i>Start</i> (group[, assertion])	Start an RMA access epoch for MPI
<i>Sync</i> ()	Synchronize public and private copies of the given window
<i>Test</i> ()	Test whether an RMA exposure epoch has completed
<i>Unlock</i> (rank)	Complete an RMA access epoch at the target process
<i>Unlock_all</i> ()	Complete an RMA access epoch at all processes
<i>Wait</i> ()	Complete an RMA exposure epoch begun with <i>Win.Post()</i>

continues on next page

Table 5 – continued from previous page

<code>f2py(arg)</code>	
<code>py2f()</code>	
<code>tomemory()</code>	Return window memory buffer

## Attributes Summary

<code>attrs</code>	window attributes
<code>flavor</code>	window create flavor
<code>group</code>	window group
<code>info</code>	window info
<code>model</code>	window memory model
<code>name</code>	window name

## Methods Documentation

**Accumulate**(*origin*, *target\_rank*, *target=None*, *op=SUM*)

Accumulate data into the target process

### Parameters

- **origin** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)
- **op** (*Op*)

### Return type

None

**classmethod Allocate**(*size*, *disp\_unit=1*, *info=INFO\_NULL*, *comm=COMM\_SELF*)

Create an window object for one-sided communication

### Parameters

- **size** (*int*)
- **disp\_unit** (*int*)
- **info** (*Info*)
- **comm** (*Intracomm*)

### Return type

*Win*

**classmethod Allocate\_shared**(*size*, *disp\_unit=1*, *info=INFO\_NULL*, *comm=COMM\_SELF*)

Create an window object for one-sided communication

### Parameters

- **size** (*int*)
- **disp\_unit** (*int*)

- **info** ([Info](#))
- **comm** ([Intracomm](#))

**Return type**

[Win](#)

**Attach**(*memory*)

Attach a local memory region

**Parameters**

**memory** (*Buffer*)

**Return type**

None

**Call\_errhandler**(*errorcode*)

Call the error handler installed on a window

**Parameters**

**errorcode** (*int*)

**Return type**

None

**Compare\_and\_swap**(*origin, compare, result, target\_rank, target\_disp=0*)

Perform one-sided atomic compare-and-swap

**Parameters**

- **origin** (*BufSpec*)
- **compare** (*BufSpec*)
- **result** (*BufSpec*)
- **target\_rank** (*int*)
- **target\_disp** (*int*)

**Return type**

None

**Complete**()

Completes an RMA operations begun after an [Win.Start\(\)](#)

**Return type**

None

**classmethod Create**(*memory, disp\_unit=1, info=INFO\_NULL, comm=COMM\_SELF*)

Create an window object for one-sided communication

**Parameters**

- **memory** (*Union[Buffer, Bottom, None]*)
- **disp\_unit** (*int*)
- **info** ([Info](#))
- **comm** ([Intracomm](#))

**Return type**

[Win](#)

**classmethod** **Create\_dynamic**(*info=INFO\_NULL, comm=COMM\_SELF*)

Create an window object for one-sided communication

**Parameters**

- **info** ([Info](#))
- **comm** ([Intracomm](#))

**Return type**

[Win](#)

**classmethod** **Create\_keyval**(*copy\_fn=None, delete\_fn=None, nopython=False*)

Create a new attribute key for windows

**Parameters**

- **copy\_fn** (*Optional*[*Callable*[[[Win](#), [int](#), *Any*], *Any*]])
- **delete\_fn** (*Optional*[*Callable*[[[Win](#), [int](#), *Any*], *None*]])
- **nopython** (*bool*)

**Return type**

[int](#)

**Delete\_attr**(*keyval*)

Delete attribute value associated with a key

**Parameters**

**keyval** ([int](#))

**Return type**

*None*

**Detach**(*memory*)

Detach a local memory region

**Parameters**

**memory** (*Buffer*)

**Return type**

*None*

**Fence**(*assertion=0*)

Perform an MPI fence synchronization on a window

**Parameters**

**assertion** ([int](#))

**Return type**

*None*

**Fetch\_and\_op**(*origin, result, target\_rank, target\_disp=0, op=SUM*)

Perform one-sided read-modify-write

**Parameters**

- **origin** (*BufSpec*)
- **result** (*BufSpec*)
- **target\_rank** ([int](#))
- **target\_disp** ([int](#))

- **op** (*Op*)

**Return type**

None

**Flush**(*rank*)

Complete all outstanding RMA operations at the given target

**Parameters**

**rank** (*int*)

**Return type**

None

**Flush\_all**()

Complete all outstanding RMA operations at all targets

**Return type**

None

**Flush\_local**(*rank*)

Complete locally all outstanding RMA operations at the given target

**Parameters**

**rank** (*int*)

**Return type**

None

**Flush\_local\_all**()

Complete locally all outstanding RMA operations at all targets

**Return type**

None

**Free**()

Free a window

**Return type**

None

**classmethod Free\_keyval**(*keyval*)

Free an attribute key for windows

**Parameters**

**keyval** (*int*)

**Return type**

*int*

**Get**(*origin*, *target\_rank*, *target=None*)

Get data from a memory window on a remote process.

**Parameters**

- **origin** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)

**Return type**

None

**Get\_accumulate**(*origin, result, target\_rank, target=None, op=SUM*)

Fetch-and-accumulate data into the target process

**Parameters**

- **origin** (*BufSpec*)
- **result** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)
- **op** (*Op*)

**Return type**

None

**Get\_attr**(*keyval*)

Retrieve attribute value by key

**Parameters**

**keyval** (*int*)

**Return type**

Optional[Union[*int*, Any]]

**Get\_errhandler**()

Get the error handler for a window

**Return type**

*Errhandler*

**Get\_group**()

Return a duplicate of the group of the communicator used to create the window

**Return type**

*Group*

**Get\_info**()

Return the hints for a windows that are currently in use

**Return type**

*Info*

**Get\_name**()

Get the print name associated with the window

**Return type**

*str*

**Lock**(*rank, lock\_type=LOCK\_EXCLUSIVE, assertion=0*)

Begin an RMA access epoch at the target process

**Parameters**

- **rank** (*int*)
- **lock\_type** (*int*)
- **assertion** (*int*)

**Return type**

None

**Lock\_all**(*assertion=0*)

Begin an RMA access epoch at all processes

**Parameters**

**assertion** (*int*)

**Return type**

None

**Post**(*group, assertion=0*)

Start an RMA exposure epoch

**Parameters**

- **group** (*Group*)
- **assertion** (*int*)

**Return type**

None

**Put**(*origin, target\_rank, target=None*)

Put data into a memory window on a remote process.

**Parameters**

- **origin** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)

**Return type**

None

**Raccumulate**(*origin, target\_rank, target=None, op=SUM*)

Fetch-and-accumulate data into the target process

**Parameters**

- **origin** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)
- **op** (*Op*)

**Return type**

*Request*

**Rget**(*origin, target\_rank, target=None*)

Get data from a memory window on a remote process.

**Parameters**

- **origin** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)

**Return type**

*Request*



**Rget\_accumulate**(*origin, result, target\_rank, target=None, op=SUM*)

Accumulate data into the target process using remote memory access.

**Parameters**

- **origin** (*BufSpec*)
- **result** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)
- **op** (*Op*)

**Return type**

*Request*

**Rput**(*origin, target\_rank, target=None*)

Put data into a memory window on a remote process.

**Parameters**

- **origin** (*BufSpec*)
- **target\_rank** (*int*)
- **target** (*Optional[TargetSpec]*)

**Return type**

*Request*

**Set\_attr**(*keyval, attrval*)

Store attribute value associated with a key

**Parameters**

- **keyval** (*int*)
- **attrval** (*Any*)

**Return type**

None

**Set\_errhandler**(*errhandler*)

Set the error handler for a window

**Parameters**

**errhandler** (*Errhandler*)

**Return type**

None

**Set\_info**(*info*)

Set new values for the hints associated with a window

**Parameters**

**info** (*Info*)

**Return type**

None

**Set\_name**(*name*)

Set the print name associated with the window

**Parameters**

**name** (*str*)

**Return type**

None

**Shared\_query**(*rank*)

Query the process-local address for remote memory segments created with *Win.Allocate\_shared()*

**Parameters**

**rank** (*int*)

**Return type**

Tuple[*memory*, int]

**Start**(*group*, *assertion=0*)

Start an RMA access epoch for MPI

**Parameters**

- **group** (*Group*)
- **assertion** (*int*)

**Return type**

None

**Sync**()

Synchronize public and private copies of the given window

**Return type**

None

**Test**()

Test whether an RMA exposure epoch has completed

**Return type**

bool

**Unlock**(*rank*)

Complete an RMA access epoch at the target process

**Parameters**

**rank** (*int*)

**Return type**

None

**Unlock\_all**()

Complete an RMA access epoch at all processes

**Return type**

None

**Wait**()

Complete an RMA exposure epoch begun with *Win.Post()*

**Return type**

Literal[True]

**classmethod** **f2py**(*arg*)

**Parameters**

**arg** (*int*)

**Return type**

*Win*

**py2f**()

**Return type**

*int*

**tomemory**()

Return window memory buffer

**Return type**

*memory*

## Attributes Documentation

**attrs**

window attributes

**flavor**

window create flavor

**group**

window group

**info**

window info

**model**

window memory model

**name**

window name

## mpi4py.MPI.memory

**class** **mpi4py.MPI.memory**(*buf*)

Bases: *object*

Memory buffer

**Parameters**

**buf** (*Buffer*)

**Return type**

*memory*

**static** **\_\_new\_\_**(*cls, buf*)

**Parameters**

**buf** (*Buffer*)

**Return type**

*memory*

## Methods Summary

<code>allocate(nbytes[, clear])</code>	Memory allocation
<code>fromaddress(address, nbytes[, readonly])</code>	Memory from address and size in bytes
<code>frombuffer(obj[, readonly])</code>	Memory from buffer-like object
<code>release()</code>	Release the underlying buffer exposed by the memory object
<code>tobytes([order])</code>	Return the data in the buffer as a byte string
<code>toreadonly()</code>	Return a readonly version of the memory object

## Attributes Summary

<code>address</code>	Memory address
<code>format</code>	A string with the format of each element
<code>itemsize</code>	The size in bytes of each element
<code>nbytes</code>	Memory size (in bytes)
<code>obj</code>	The underlying object of the memory
<code>readonly</code>	Boolean indicating whether the memory is read-only

## Methods Documentation

**static** `allocate(nbytes, clear=False)`

Memory allocation

### Parameters

- **nbytes** (*int*)
- **clear** (*bool*)

### Return type

*memory*

**static** `fromaddress(address, nbytes, readonly=False)`

Memory from address and size in bytes

### Parameters

- **address** (*int*)
- **nbytes** (*int*)
- **readonly** (*bool*)

### Return type

*memory*

**static** `frombuffer(obj, readonly=False)`

Memory from buffer-like object

### Parameters

- **obj** (*Buffer*)
- **readonly** (*bool*)

**Return type***memory***release()**

Release the underlying buffer exposed by the memory object

**Return type**

None

**tobytes**(*order=None*)

Return the data in the buffer as a byte string

**Parameters****order** (*Optional*[*str*])**Return type***bytes***toreadonly()**

Return a readonly version of the memory object

**Return type***memory***Attributes Documentation****address**

Memory address

**format**

A string with the format of each element

**itemsize**

The size in bytes of each element

**nbytes**

Memory size (in bytes)

**obj**

The underlying object of the memory

**readonly**

Boolean indicating whether the memory is read-only

**Exceptions***Exception*(*[ierr]*)

Exception class

## mpi4py.MPI.Exception

**exception** `mpi4py.MPI.Exception(ierr=SUCCESS)`

Bases: `RuntimeError`

Exception class

### Parameters

**ierr** (*int*)

### Return type

*Exception*

**static** `__new__(cls, ierr=SUCCESS)`

### Parameters

**ierr** (*int*)

### Return type

*Exception*

## Methods Summary

<code>Get_error_class()</code>	Error class
<code>Get_error_code()</code>	Error code
<code>Get_error_string()</code>	Error string

## Attributes Summary

<code>error_class</code>	error class
<code>error_code</code>	error code
<code>error_string</code>	error string

## Methods Documentation

**Get\_error\_class()**

Error class

### Return type

*int*

**Get\_error\_code()**

Error code

### Return type

*int*

**Get\_error\_string()**

Error string

### Return type

*str*

## Attributes Documentation

### **error\_class**

error class

### **error\_code**

error code

### **error\_string**

error string

## Functions

<a href="#"><i>Add_error_class()</i></a>	Add an <i>error class</i> to the known error classes
<a href="#"><i>Add_error_code</i>(errorclass)</a>	Add an <i>error code</i> to an <i>error class</i>
<a href="#"><i>Add_error_string</i>(errorcode, string)</a>	Associate an <i>error string</i> with an <i>error class</i> or <i>error-code</i>
<a href="#"><i>Aint_add</i>(base, disp)</a>	Return the sum of base address and displacement
<a href="#"><i>Aint_diff</i>(addr1, addr2)</a>	Return the difference between absolute addresses
<a href="#"><i>Alloc_mem</i>(size[, info])</a>	Allocate memory for message passing and RMA
<a href="#"><i>Attach_buffer</i>(buf)</a>	Attach a user-provided buffer for sending in buffered mode
<a href="#"><i>Close_port</i>(port_name)</a>	Close a port
<a href="#"><i>Compute_dims</i>(nnodes, dims)</a>	Return a balanced distribution of processes per coordinate direction
<a href="#"><i>Detach_buffer</i>()</a>	Remove an existing attached buffer
<a href="#"><i>Finalize</i>()</a>	Terminate the MPI execution environment
<a href="#"><i>Free_mem</i>(mem)</a>	Free memory allocated with <a href="#"><i>Alloc_mem()</i></a>
<a href="#"><i>Get_address</i>(location)</a>	Get the address of a location in memory
<a href="#"><i>Get_error_class</i>(errorcode)</a>	Convert an <i>error code</i> into an <i>error class</i>
<a href="#"><i>Get_error_string</i>(errorcode)</a>	Return the <i>error string</i> for a given <i>error class</i> or <i>error code</i>
<a href="#"><i>Get_library_version</i>()</a>	Obtain the version string of the MPI library
<a href="#"><i>Get_processor_name</i>()</a>	Obtain the name of the calling processor
<a href="#"><i>Get_version</i>()</a>	Obtain the version number of the MPI standard supported by the implementation as a tuple (version, subversion)
<a href="#"><i>Init</i>()</a>	Initialize the MPI execution environment
<a href="#"><i>Init_thread</i>([required])</a>	Initialize the MPI execution environment
<a href="#"><i>Is_finalized</i>()</a>	Indicates whether <a href="#"><i>Finalize</i></a> has completed
<a href="#"><i>Is_initialized</i>()</a>	Indicates whether <a href="#"><i>Init</i></a> has been called
<a href="#"><i>Is_thread_main</i>()</a>	Indicate whether this thread called <a href="#"><i>Init</i></a> or <a href="#"><i>Init_thread</i></a>
<a href="#"><i>Lookup_name</i>(service_name[, info])</a>	Lookup a port name given a service name
<a href="#"><i>Open_port</i>([info])</a>	Return an address that can be used to establish connections between groups of MPI processes
<a href="#"><i>Pcontrol</i>(level)</a>	Control profiling
<a href="#"><i>Publish_name</i>(service_name, port_name[, info])</a>	Publish a service name
<a href="#"><i>Query_thread</i>()</a>	Return the level of thread support provided by the MPI library
<a href="#"><i>Register_datarep</i>(datarep, read_fn, write_fn, ...)</a>	Register user-defined data representations

continues on next page

Table 6 – continued from previous page

<code>Unpublish_name(service_name, port_name[, info])</code>	Unpublish a service name
<code>Wtick()</code>	Return the resolution of <code>Wtime</code>
<code>Wtime()</code>	Return an elapsed time on the calling processor
<code>get_vendor()</code>	Information about the underlying MPI implementation

### `mpi4py.MPI.Add_error_class`

`mpi4py.MPI.Add_error_class()`

Add an *error class* to the known error classes

**Return type**

`int`

### `mpi4py.MPI.Add_error_code`

`mpi4py.MPI.Add_error_code(errorclass)`

Add an *error code* to an *error class*

**Parameters**

**errorclass** (`int`)

**Return type**

`int`

### `mpi4py.MPI.Add_error_string`

`mpi4py.MPI.Add_error_string(errorcode, string)`

Associate an *error string* with an *error class* or *errorcode*

**Parameters**

- **errorcode** (`int`)
- **string** (`str`)

**Return type**

`None`

### `mpi4py.MPI.Aint_add`

`mpi4py.MPI.Aint_add(base, disp)`

Return the sum of base address and displacement

**Parameters**

- **base** (`int`)
- **disp** (`int`)

**Return type**

`int`



### **mpi4py.MPI.Aint\_diff**

`mpi4py.MPI.Aint_diff(addr1, addr2)`

Return the difference between absolute addresses

#### **Parameters**

- **addr1** (*int*)
- **addr2** (*int*)

#### **Return type**

*int*

### **mpi4py.MPI.Alloc\_mem**

`mpi4py.MPI.Alloc_mem(size, info=INFO_NULL)`

Allocate memory for message passing and RMA

#### **Parameters**

- **size** (*int*)
- **info** (*Info*)

#### **Return type**

*memory*

### **mpi4py.MPI.Attach\_buffer**

`mpi4py.MPI.Attach_buffer(buf)`

Attach a user-provided buffer for sending in buffered mode

#### **Parameters**

**buf** (*Buffer*)

#### **Return type**

*None*

### **mpi4py.MPI.Close\_port**

`mpi4py.MPI.Close_port(port_name)`

Close a port

#### **Parameters**

**port\_name** (*str*)

#### **Return type**

*None*

### **mpi4py.MPI.Compute\_dims**

`mpi4py.MPI.Compute_dims(nnodes, dims)`

Return a balanced distribution of processes per coordinate direction

#### **Parameters**

- **nnodes** (*int*)
- **dims** (*Union[int, Sequence[int]]*)

#### **Return type**

*List[int]*

### **mpi4py.MPI.Detach\_buffer**

`mpi4py.MPI.Detach_buffer()`

Remove an existing attached buffer

#### **Return type**

*Buffer*

### **mpi4py.MPI.Finalize**

`mpi4py.MPI.Finalize()`

Terminate the MPI execution environment

#### **Return type**

*None*

### **mpi4py.MPI.Free\_mem**

`mpi4py.MPI.Free_mem(mem)`

Free memory allocated with *Alloc\_mem()*

#### **Parameters**

**mem** (*memory*)

#### **Return type**

*None*

### **mpi4py.MPI.Get\_address**

`mpi4py.MPI.Get_address(location)`

Get the address of a location in memory

#### **Parameters**

**location** (*Union[Buffer, Bottom]*)

#### **Return type**

*int*

### **mpi4py.MPI.Get\_error\_class**

`mpi4py.MPI.Get_error_class(errorcode)`  
Convert an *error code* into an *error class*

**Parameters**

**errorcode** (*int*)

**Return type**

*int*

### **mpi4py.MPI.Get\_error\_string**

`mpi4py.MPI.Get_error_string(errorcode)`  
Return the *error string* for a given *error class* or *error code*

**Parameters**

**errorcode** (*int*)

**Return type**

*str*

### **mpi4py.MPI.Get\_library\_version**

`mpi4py.MPI.Get_library_version()`  
Obtain the version string of the MPI library

**Return type**

*str*

### **mpi4py.MPI.Get\_processor\_name**

`mpi4py.MPI.Get_processor_name()`  
Obtain the name of the calling processor

**Return type**

*str*

### **mpi4py.MPI.Get\_version**

`mpi4py.MPI.Get_version()`  
Obtain the version number of the MPI standard supported by the implementation as a tuple (*version*, *subversion*)

**Return type**

Tuple[*int*, *int*]

## **mpi4py.MPI.Init**

`mpi4py.MPI.Init()`

Initialize the MPI execution environment

### **Return type**

None

## **mpi4py.MPI.Init\_thread**

`mpi4py.MPI.Init_thread(required=THREAD_MULTIPLE)`

Initialize the MPI execution environment

### **Parameters**

**required** (*int*)

### **Return type**

*int*

## **mpi4py.MPI.Is\_finalized**

`mpi4py.MPI.Is_finalized()`

Indicates whether *Finalize* has completed

### **Return type**

*bool*

## **mpi4py.MPI.Is\_initialized**

`mpi4py.MPI.Is_initialized()`

Indicates whether *Init* has been called

### **Return type**

*bool*

## **mpi4py.MPI.Is\_thread\_main**

`mpi4py.MPI.Is_thread_main()`

Indicate whether this thread called *Init* or *Init\_thread*

### **Return type**

*bool*

## **mpi4py.MPI.Lookup\_name**

`mpi4py.MPI.Lookup_name(service_name, info=INFO_NULL)`

Lookup a port name given a service name

### **Parameters**

- **service\_name** (*str*)
- **info** (*Info*)

**Return type**

str

**mpi4py.MPI.Open\_port**

`mpi4py.MPI.Open_port(info=INFO_NULL)`

Return an address that can be used to establish connections between groups of MPI processes

**Parameters**

**info** ([Info](#))

**Return type**

str

**mpi4py.MPI.Pcontrol**

`mpi4py.MPI.Pcontrol(level)`

Control profiling

**Parameters**

**level** ([int](#))

**Return type**

None

**mpi4py.MPI.Publish\_name**

`mpi4py.MPI.Publish_name(service_name, port_name, info=INFO_NULL)`

Publish a service name

**Parameters**

- **service\_name** ([str](#))
- **port\_name** ([str](#))
- **info** ([Info](#))

**Return type**

None

**mpi4py.MPI.Query\_thread**

`mpi4py.MPI.Query_thread()`

Return the level of thread support provided by the MPI library

**Return type**

int

### **mpi4py.MPI.Register\_datarep**

`mpi4py.MPI.Register_datarep(datarep, read_fn, write_fn, extent_fn)`

Register user-defined data representations

#### **Parameters**

- **datarep** (*str*)
- **read\_fn** (*Callable*[[*Buffer*, *Datatype*, *int*, *Buffer*, *int*], *None*])
- **write\_fn** (*Callable*[[*Buffer*, *Datatype*, *int*, *Buffer*, *int*], *None*])
- **extent\_fn** (*Callable*[[*Datatype*], *int*])

#### **Return type**

*None*

### **mpi4py.MPI.Unpublish\_name**

`mpi4py.MPI.Unpublish_name(service_name, port_name, info=INFO_NULL)`

Unpublish a service name

#### **Parameters**

- **service\_name** (*str*)
- **port\_name** (*str*)
- **info** (*Info*)

#### **Return type**

*None*

### **mpi4py.MPI.Wtick**

`mpi4py.MPI.Wtick()`

Return the resolution of *Wtime*

#### **Return type**

*float*

### **mpi4py.MPI.Wtime**

`mpi4py.MPI.Wtime()`

Return an elapsed time on the calling processor

#### **Return type**

*float*

## mpi4py.MPI.get\_vendor

mpi4py.MPI.get\_vendor()

Information about the underlying MPI implementation

### Returns

- a string with the name of the MPI implementation
- an integer 3-tuple version (major, minor, micro)

### Return type

Tuple[str, Tuple[int, int, int]]

## Attributes

UNDEFINED	int UNDEFINED
ANY_SOURCE	int ANY_SOURCE
ANY_TAG	int ANY_TAG
PROC_NULL	int PROC_NULL
ROOT	int ROOT
BOTTOM	Bottom BOTTOM
IN_PLACE	InPlace IN_PLACE
KEYVAL_INVALID	int KEYVAL_INVALID
TAG_UB	int TAG_UB
HOST	int HOST
IO	int IO
WTIME_IS_GLOBAL	int WTIME_IS_GLOBAL
UNIVERSE_SIZE	int UNIVERSE_SIZE
APPNUM	int APPNUM
LASTUSED	int LASTUSED
WIN_BASE	int WIN_BASE
WIN_SIZE	int WIN_SIZE
WIN_DISP_UNIT	int WIN_DISP_UNIT
WIN_CREATE_FLAVOR	int WIN_CREATE_FLAVOR
WIN_FLAVOR	int WIN_FLAVOR
WIN_MODEL	int WIN_MODEL
SUCCESS	int SUCCESS
ERR_LASTCODE	int ERR_LASTCODE
ERR_COMM	int ERR_COMM
ERR_GROUP	int ERR_GROUP
ERR_TYPE	int ERR_TYPE
ERR_REQUEST	int ERR_REQUEST
ERR_OP	int ERR_OP
ERR_BUFFER	int ERR_BUFFER
ERR_COUNT	int ERR_COUNT
ERR_TAG	int ERR_TAG
ERR_RANK	int ERR_RANK
ERR_ROOT	int ERR_ROOT
ERR_TRUNCATE	int ERR_TRUNCATE
ERR_IN_STATUS	int ERR_IN_STATUS
ERR_PENDING	int ERR_PENDING
ERR_TOPOLOGY	int ERR_TOPOLOGY

continues on next page

Table 7 – continued from previous page

<code>ERR_DIMS</code>	<code>int ERR_DIMS</code>
<code>ERR_ARG</code>	<code>int ERR_ARG</code>
<code>ERR_OTHER</code>	<code>int ERR_OTHER</code>
<code>ERR_UNKNOWN</code>	<code>int ERR_UNKNOWN</code>
<code>ERR_INTERN</code>	<code>int ERR_INTERN</code>
<code>ERR_INFO</code>	<code>int ERR_INFO</code>
<code>ERR_FILE</code>	<code>int ERR_FILE</code>
<code>ERR_WIN</code>	<code>int ERR_WIN</code>
<code>ERR_KEYVAL</code>	<code>int ERR_KEYVAL</code>
<code>ERR_INFO_KEY</code>	<code>int ERR_INFO_KEY</code>
<code>ERR_INFO_VALUE</code>	<code>int ERR_INFO_VALUE</code>
<code>ERR_INFO_NOKEY</code>	<code>int ERR_INFO_NOKEY</code>
<code>ERR_ACCESS</code>	<code>int ERR_ACCESS</code>
<code>ERR_AMODE</code>	<code>int ERR_AMODE</code>
<code>ERR_BAD_FILE</code>	<code>int ERR_BAD_FILE</code>
<code>ERR_FILE_EXISTS</code>	<code>int ERR_FILE_EXISTS</code>
<code>ERR_FILE_IN_USE</code>	<code>int ERR_FILE_IN_USE</code>
<code>ERR_NO_SPACE</code>	<code>int ERR_NO_SPACE</code>
<code>ERR_NO_SUCH_FILE</code>	<code>int ERR_NO_SUCH_FILE</code>
<code>ERR_IO</code>	<code>int ERR_IO</code>
<code>ERR_READ_ONLY</code>	<code>int ERR_READ_ONLY</code>
<code>ERR_CONVERSION</code>	<code>int ERR_CONVERSION</code>
<code>ERR_DUP_DATAREP</code>	<code>int ERR_DUP_DATAREP</code>
<code>ERR_UNSUPPORTED_DATAREP</code>	<code>int ERR_UNSUPPORTED_DATAREP</code>
<code>ERR_UNSUPPORTED_OPERATION</code>	<code>int ERR_UNSUPPORTED_OPERATION</code>
<code>ERR_NAME</code>	<code>int ERR_NAME</code>
<code>ERR_NO_MEM</code>	<code>int ERR_NO_MEM</code>
<code>ERR_NOT_SAME</code>	<code>int ERR_NOT_SAME</code>
<code>ERR_PORT</code>	<code>int ERR_PORT</code>
<code>ERR_QUOTA</code>	<code>int ERR_QUOTA</code>
<code>ERR_SERVICE</code>	<code>int ERR_SERVICE</code>
<code>ERR_SPAWN</code>	<code>int ERR_SPAWN</code>
<code>ERR_BASE</code>	<code>int ERR_BASE</code>
<code>ERR_SIZE</code>	<code>int ERR_SIZE</code>
<code>ERR_DISP</code>	<code>int ERR_DISP</code>
<code>ERR_ASSERT</code>	<code>int ERR_ASSERT</code>
<code>ERR_LOCKTYPE</code>	<code>int ERR_LOCKTYPE</code>
<code>ERR_RMA_CONFLICT</code>	<code>int ERR_RMA_CONFLICT</code>
<code>ERR_RMA_SYNC</code>	<code>int ERR_RMA_SYNC</code>
<code>ERR_RMA_RANGE</code>	<code>int ERR_RMA_RANGE</code>
<code>ERR_RMA_ATTACH</code>	<code>int ERR_RMA_ATTACH</code>
<code>ERR_RMA_SHARED</code>	<code>int ERR_RMA_SHARED</code>
<code>ERR_RMA_FLAVOR</code>	<code>int ERR_RMA_FLAVOR</code>
<code>ORDER_C</code>	<code>int ORDER_C</code>
<code>ORDER_FORTRAN</code>	<code>int ORDER_FORTRAN</code>
<code>ORDER_F</code>	<code>int ORDER_F</code>
<code>TYPECLASS_INTEGER</code>	<code>int TYPECLASS_INTEGER</code>
<code>TYPECLASS_REAL</code>	<code>int TYPECLASS_REAL</code>
<code>TYPECLASS_COMPLEX</code>	<code>int TYPECLASS_COMPLEX</code>
<code>DISTRIBUTE_NONE</code>	<code>int DISTRIBUTE_NONE</code>
<code>DISTRIBUTE_BLOCK</code>	<code>int DISTRIBUTE_BLOCK</code>
<code>DISTRIBUTE_CYCLIC</code>	<code>int DISTRIBUTE_CYCLIC</code>

continues on next page



Table 7 – continued from previous page

<i>DISTRIBUTE_DFLT_DARG</i>	<i>int</i> <i>DISTRIBUTE_DFLT_DARG</i>
<i>COMBINER_NAMED</i>	<i>int</i> <i>COMBINER_NAMED</i>
<i>COMBINER_DUP</i>	<i>int</i> <i>COMBINER_DUP</i>
<i>COMBINER_CONTIGUOUS</i>	<i>int</i> <i>COMBINER_CONTIGUOUS</i>
<i>COMBINER_VECTOR</i>	<i>int</i> <i>COMBINER_VECTOR</i>
<i>COMBINER_HVECTOR</i>	<i>int</i> <i>COMBINER_HVECTOR</i>
<i>COMBINER_INDEXED</i>	<i>int</i> <i>COMBINER_INDEXED</i>
<i>COMBINER_HINDEXED</i>	<i>int</i> <i>COMBINER_HINDEXED</i>
<i>COMBINER_INDEXED_BLOCK</i>	<i>int</i> <i>COMBINER_INDEXED_BLOCK</i>
<i>COMBINER_HINDEXED_BLOCK</i>	<i>int</i> <i>COMBINER_HINDEXED_BLOCK</i>
<i>COMBINER_STRUCT</i>	<i>int</i> <i>COMBINER_STRUCT</i>
<i>COMBINER_SUBARRAY</i>	<i>int</i> <i>COMBINER_SUBARRAY</i>
<i>COMBINER_DARRAY</i>	<i>int</i> <i>COMBINER_DARRAY</i>
<i>COMBINER_RESIZED</i>	<i>int</i> <i>COMBINER_RESIZED</i>
<i>COMBINER_F90_REAL</i>	<i>int</i> <i>COMBINER_F90_REAL</i>
<i>COMBINER_F90_COMPLEX</i>	<i>int</i> <i>COMBINER_F90_COMPLEX</i>
<i>COMBINER_F90_INTEGER</i>	<i>int</i> <i>COMBINER_F90_INTEGER</i>
<i>IDENT</i>	<i>int</i> <i>IDENT</i>
<i>CONGRUENT</i>	<i>int</i> <i>CONGRUENT</i>
<i>SIMILAR</i>	<i>int</i> <i>SIMILAR</i>
<i>UNEQUAL</i>	<i>int</i> <i>UNEQUAL</i>
<i>CART</i>	<i>int</i> <i>CART</i>
<i>GRAPH</i>	<i>int</i> <i>GRAPH</i>
<i>DIST_GRAPH</i>	<i>int</i> <i>DIST_GRAPH</i>
<i>UNWEIGHTED</i>	<i>int</i> <i>UNWEIGHTED</i>
<i>WEIGHTS_EMPTY</i>	<i>int</i> <i>WEIGHTS_EMPTY</i>
<i>COMM_TYPE_SHARED</i>	<i>int</i> <i>COMM_TYPE_SHARED</i>
<i>BSEND_OVERHEAD</i>	<i>int</i> <i>BSEND_OVERHEAD</i>
<i>WIN_FLAVOR_CREATE</i>	<i>int</i> <i>WIN_FLAVOR_CREATE</i>
<i>WIN_FLAVOR_ALLOCATE</i>	<i>int</i> <i>WIN_FLAVOR_ALLOCATE</i>
<i>WIN_FLAVOR_DYNAMIC</i>	<i>int</i> <i>WIN_FLAVOR_DYNAMIC</i>
<i>WIN_FLAVOR_SHARED</i>	<i>int</i> <i>WIN_FLAVOR_SHARED</i>
<i>WIN_SEPARATE</i>	<i>int</i> <i>WIN_SEPARATE</i>
<i>WIN_UNIFIED</i>	<i>int</i> <i>WIN_UNIFIED</i>
<i>MODE_NOCHECK</i>	<i>int</i> <i>MODE_NOCHECK</i>
<i>MODE_NOSTORE</i>	<i>int</i> <i>MODE_NOSTORE</i>
<i>MODE_NOPUT</i>	<i>int</i> <i>MODE_NOPUT</i>
<i>MODE_NOPRECEDE</i>	<i>int</i> <i>MODE_NOPRECEDE</i>
<i>MODE_NOSUCCEED</i>	<i>int</i> <i>MODE_NOSUCCEED</i>
<i>LOCK_EXCLUSIVE</i>	<i>int</i> <i>LOCK_EXCLUSIVE</i>
<i>LOCK_SHARED</i>	<i>int</i> <i>LOCK_SHARED</i>
<i>MODE_RDONLY</i>	<i>int</i> <i>MODE_RDONLY</i>
<i>MODE_WRONLY</i>	<i>int</i> <i>MODE_WRONLY</i>
<i>MODE_RDWR</i>	<i>int</i> <i>MODE_RDWR</i>
<i>MODE_CREATE</i>	<i>int</i> <i>MODE_CREATE</i>
<i>MODE_EXCL</i>	<i>int</i> <i>MODE_EXCL</i>
<i>MODE_DELETE_ON_CLOSE</i>	<i>int</i> <i>MODE_DELETE_ON_CLOSE</i>
<i>MODE_UNIQUE_OPEN</i>	<i>int</i> <i>MODE_UNIQUE_OPEN</i>
<i>MODE_SEQUENTIAL</i>	<i>int</i> <i>MODE_SEQUENTIAL</i>
<i>MODE_APPEND</i>	<i>int</i> <i>MODE_APPEND</i>
<i>SEEK_SET</i>	<i>int</i> <i>SEEK_SET</i>
<i>SEEK_CUR</i>	<i>int</i> <i>SEEK_CUR</i>

continues on next page

Table 7 – continued from previous page

SEEK_END	int SEEK_END
DISPLACEMENT_CURRENT	int DISPLACEMENT_CURRENT
DISP_CUR	int DISP_CUR
THREAD_SINGLE	int THREAD_SINGLE
THREAD_FUNNELED	int THREAD_FUNNELED
THREAD_SERIALIZED	int THREAD_SERIALIZED
THREAD_MULTIPLE	int THREAD_MULTIPLE
VERSION	int VERSION
SUBVERSION	int SUBVERSION
MAX_PROCESSOR_NAME	int MAX_PROCESSOR_NAME
MAX_ERROR_STRING	int MAX_ERROR_STRING
MAX_PORT_NAME	int MAX_PORT_NAME
MAX_INFO_KEY	int MAX_INFO_KEY
MAX_INFO_VAL	int MAX_INFO_VAL
MAX_OBJECT_NAME	int MAX_OBJECT_NAME
MAX_DATAREP_STRING	int MAX_DATAREP_STRING
MAX_LIBRARY_VERSION_STRING	int MAX_LIBRARY_VERSION_STRING
DATATYPE_NULL	Datatype DATATYPE_NULL
UB	Datatype UB
LB	Datatype LB
PACKED	Datatype PACKED
BYTE	Datatype BYTE
AINT	Datatype AINT
OFFSET	Datatype OFFSET
COUNT	Datatype COUNT
CHAR	Datatype CHAR
WCHAR	Datatype WCHAR
SIGNED_CHAR	Datatype SIGNED_CHAR
SHORT	Datatype SHORT
INT	Datatype INT
LONG	Datatype LONG
LONG_LONG	Datatype LONG_LONG
UNSIGNED_CHAR	Datatype UNSIGNED_CHAR
UNSIGNED_SHORT	Datatype UNSIGNED_SHORT
UNSIGNED	Datatype UNSIGNED
UNSIGNED_LONG	Datatype UNSIGNED_LONG
UNSIGNED_LONG_LONG	Datatype UNSIGNED_LONG_LONG
FLOAT	Datatype FLOAT
DOUBLE	Datatype DOUBLE
LONG_DOUBLE	Datatype LONG_DOUBLE
C_BOOL	Datatype C_BOOL
INT8_T	Datatype INT8_T
INT16_T	Datatype INT16_T
INT32_T	Datatype INT32_T
INT64_T	Datatype INT64_T
UINT8_T	Datatype UINT8_T
UINT16_T	Datatype UINT16_T
UINT32_T	Datatype UINT32_T
UINT64_T	Datatype UINT64_T
C_COMPLEX	Datatype C_COMPLEX
C_FLOAT_COMPLEX	Datatype C_FLOAT_COMPLEX
C_DOUBLE_COMPLEX	Datatype C_DOUBLE_COMPLEX

continues on next page

Table 7 – continued from previous page

<i>C_LONG_DOUBLE_COMPLEX</i>	<i>Datatype</i> C_LONG_DOUBLE_COMPLEX
<i>CXX_BOOL</i>	<i>Datatype</i> CXX_BOOL
<i>CXX_FLOAT_COMPLEX</i>	<i>Datatype</i> CXX_FLOAT_COMPLEX
<i>CXX_DOUBLE_COMPLEX</i>	<i>Datatype</i> CXX_DOUBLE_COMPLEX
<i>CXX_LONG_DOUBLE_COMPLEX</i>	<i>Datatype</i> CXX_LONG_DOUBLE_COMPLEX
<i>SHORT_INT</i>	<i>Datatype</i> SHORT_INT
<i>INT_INT</i>	<i>Datatype</i> INT_INT
<i>TWOINT</i>	<i>Datatype</i> TWOINT
<i>LONG_INT</i>	<i>Datatype</i> LONG_INT
<i>FLOAT_INT</i>	<i>Datatype</i> FLOAT_INT
<i>DOUBLE_INT</i>	<i>Datatype</i> DOUBLE_INT
<i>LONG_DOUBLE_INT</i>	<i>Datatype</i> LONG_DOUBLE_INT
<i>CHARACTER</i>	<i>Datatype</i> CHARACTER
<i>LOGICAL</i>	<i>Datatype</i> LOGICAL
<i>INTEGER</i>	<i>Datatype</i> INTEGER
<i>REAL</i>	<i>Datatype</i> REAL
<i>DOUBLE_PRECISION</i>	<i>Datatype</i> DOUBLE_PRECISION
<i>COMPLEX</i>	<i>Datatype</i> COMPLEX
<i>DOUBLE_COMPLEX</i>	<i>Datatype</i> DOUBLE_COMPLEX
<i>LOGICAL1</i>	<i>Datatype</i> LOGICAL1
<i>LOGICAL2</i>	<i>Datatype</i> LOGICAL2
<i>LOGICAL4</i>	<i>Datatype</i> LOGICAL4
<i>LOGICAL8</i>	<i>Datatype</i> LOGICAL8
<i>INTEGER1</i>	<i>Datatype</i> INTEGER1
<i>INTEGER2</i>	<i>Datatype</i> INTEGER2
<i>INTEGER4</i>	<i>Datatype</i> INTEGER4
<i>INTEGER8</i>	<i>Datatype</i> INTEGER8
<i>INTEGER16</i>	<i>Datatype</i> INTEGER16
<i>REAL2</i>	<i>Datatype</i> REAL2
<i>REAL4</i>	<i>Datatype</i> REAL4
<i>REAL8</i>	<i>Datatype</i> REAL8
<i>REAL16</i>	<i>Datatype</i> REAL16
<i>COMPLEX4</i>	<i>Datatype</i> COMPLEX4
<i>COMPLEX8</i>	<i>Datatype</i> COMPLEX8
<i>COMPLEX16</i>	<i>Datatype</i> COMPLEX16
<i>COMPLEX32</i>	<i>Datatype</i> COMPLEX32
<i>UNSIGNED_INT</i>	<i>Datatype</i> UNSIGNED_INT
<i>SIGNED_SHORT</i>	<i>Datatype</i> SIGNED_SHORT
<i>SIGNED_INT</i>	<i>Datatype</i> SIGNED_INT
<i>SIGNED_LONG</i>	<i>Datatype</i> SIGNED_LONG
<i>SIGNED_LONG_LONG</i>	<i>Datatype</i> SIGNED_LONG_LONG
<i>BOOL</i>	<i>Datatype</i> BOOL
<i>SINT8_T</i>	<i>Datatype</i> SINT8_T
<i>SINT16_T</i>	<i>Datatype</i> SINT16_T
<i>SINT32_T</i>	<i>Datatype</i> SINT32_T
<i>SINT64_T</i>	<i>Datatype</i> SINT64_T
<i>F_BOOL</i>	<i>Datatype</i> F_BOOL
<i>F_INT</i>	<i>Datatype</i> F_INT
<i>F_FLOAT</i>	<i>Datatype</i> F_FLOAT
<i>F_DOUBLE</i>	<i>Datatype</i> F_DOUBLE
<i>F_COMPLEX</i>	<i>Datatype</i> F_COMPLEX
<i>F_FLOAT_COMPLEX</i>	<i>Datatype</i> F_FLOAT_COMPLEX

continues on next page

Table 7 – continued from previous page

<i>F_DOUBLE_COMPLEX</i>	<i>Datatype</i> F_DOUBLE_COMPLEX
<i>REQUEST_NULL</i>	<i>Request</i> REQUEST_NULL
<i>MESSAGE_NULL</i>	<i>Message</i> MESSAGE_NULL
<i>MESSAGE_NO_PROC</i>	<i>Message</i> MESSAGE_NO_PROC
<i>OP_NULL</i>	<i>Op</i> OP_NULL
<i>MAX</i>	<i>Op</i> MAX
<i>MIN</i>	<i>Op</i> MIN
<i>SUM</i>	<i>Op</i> SUM
<i>PROD</i>	<i>Op</i> PROD
<i>LAND</i>	<i>Op</i> LAND
<i>BAND</i>	<i>Op</i> BAND
<i>LOR</i>	<i>Op</i> LOR
<i>BOR</i>	<i>Op</i> BOR
<i>LXOR</i>	<i>Op</i> LXOR
<i>BXOR</i>	<i>Op</i> BXOR
<i>MAXLOC</i>	<i>Op</i> MAXLOC
<i>MINLOC</i>	<i>Op</i> MINLOC
<i>REPLACE</i>	<i>Op</i> REPLACE
<i>NO_OP</i>	<i>Op</i> NO_OP
<i>GROUP_NULL</i>	<i>Group</i> GROUP_NULL
<i>GROUP_EMPTY</i>	<i>Group</i> GROUP_EMPTY
<i>INFO_NULL</i>	<i>Info</i> INFO_NULL
<i>INFO_ENV</i>	<i>Info</i> INFO_ENV
<i>ERRHANDLER_NULL</i>	<i>Errhandler</i> ERRHANDLER_NULL
<i>ERRORS_RETURN</i>	<i>Errhandler</i> ERRORS_RETURN
<i>ERRORS_ARE_FATAL</i>	<i>Errhandler</i> ERRORS_ARE_FATAL
<i>COMM_NULL</i>	<i>Comm</i> COMM_NULL
<i>COMM_SELF</i>	<i>Intracomm</i> COMM_SELF
<i>COMM_WORLD</i>	<i>Intracomm</i> COMM_WORLD
<i>WIN_NULL</i>	<i>Win</i> WIN_NULL
<i>FILE_NULL</i>	<i>File</i> FILE_NULL
<i>pickle</i>	<i>Pickle</i> pickle

**mpi4py.MPI.UNDEFINED**

```
mpi4py.MPI.UNDEFINED: int = UNDEFINED
    int UNDEFINED
```

### **mpi4py.MPI.ANY\_SOURCE**

```
mpi4py.MPI.ANY_SOURCE: int = ANY_SOURCE  
int ANY_SOURCE
```

### **mpi4py.MPI.ANY\_TAG**

```
mpi4py.MPI.ANY_TAG: int = ANY_TAG  
int ANY_TAG
```

### **mpi4py.MPI.PROC\_NULL**

```
mpi4py.MPI.PROC_NULL: int = PROC_NULL  
int PROC_NULL
```

### **mpi4py.MPI.ROOT**

```
mpi4py.MPI.ROOT: int = ROOT  
int ROOT
```

### **mpi4py.MPI.BOTTOM**

```
mpi4py.MPI.BOTTOM: Bottom = BOTTOM  
Bottom BOTTOM
```

### **mpi4py.MPI.IN\_PLACE**

```
mpi4py.MPI.IN_PLACE: InPlace = IN_PLACE  
InPlace IN_PLACE
```

### **mpi4py.MPI.KEYVAL\_INVALID**

```
mpi4py.MPI.KEYVAL_INVALID: int = KEYVAL_INVALID  
int KEYVAL_INVALID
```

### **mpi4py.MPI.TAG\_UB**

```
mpi4py.MPI.TAG_UB: int = TAG_UB  
int TAG_UB
```

### **mpi4py.MPI.HOST**

```
mpi4py.MPI.HOST: int = HOST  
    int HOST
```

### **mpi4py.MPI.IO**

```
mpi4py.MPI.IO: int = IO  
    int IO
```

### **mpi4py.MPI.WTIME\_IS\_GLOBAL**

```
mpi4py.MPI.WTIME_IS_GLOBAL: int = WTIME_IS_GLOBAL  
    int WTIME_IS_GLOBAL
```

### **mpi4py.MPI.UNIVERSE\_SIZE**

```
mpi4py.MPI.UNIVERSE_SIZE: int = UNIVERSE_SIZE  
    int UNIVERSE_SIZE
```

### **mpi4py.MPI.APPNUM**

```
mpi4py.MPI.APPNUM: int = APPNUM  
    int APPNUM
```

### **mpi4py.MPI.LASTUSEDCODE**

```
mpi4py.MPI.LASTUSEDCODE: int = LASTUSEDCODE  
    int LASTUSEDCODE
```

### **mpi4py.MPI.WIN\_BASE**

```
mpi4py.MPI.WIN_BASE: int = WIN_BASE  
    int WIN_BASE
```

### **mpi4py.MPI.WIN\_SIZE**

```
mpi4py.MPI.WIN_SIZE: int = WIN_SIZE  
    int WIN_SIZE
```

### **mpi4py.MPI.WIN\_DISP\_UNIT**

```
mpi4py.MPI.WIN_DISP_UNIT: int = WIN_DISP_UNIT
    int WIN_DISP_UNIT
```

### **mpi4py.MPI.WIN\_CREATE\_FLAVOR**

```
mpi4py.MPI.WIN_CREATE_FLAVOR: int = WIN_CREATE_FLAVOR
    int WIN_CREATE_FLAVOR
```

### **mpi4py.MPI.WIN\_FLAVOR**

```
mpi4py.MPI.WIN_FLAVOR: int = WIN_FLAVOR
    int WIN_FLAVOR
```

### **mpi4py.MPI.WIN\_MODEL**

```
mpi4py.MPI.WIN_MODEL: int = WIN_MODEL
    int WIN_MODEL
```

### **mpi4py.MPI.SUCCESS**

```
mpi4py.MPI.SUCCESS: int = SUCCESS
    int SUCCESS
```

### **mpi4py.MPI.ERR\_LASTCODE**

```
mpi4py.MPI.ERR_LASTCODE: int = ERR_LASTCODE
    int ERR_LASTCODE
```

### **mpi4py.MPI.ERR\_COMM**

```
mpi4py.MPI.ERR_COMM: int = ERR_COMM
    int ERR_COMM
```

### **mpi4py.MPI.ERR\_GROUP**

```
mpi4py.MPI.ERR_GROUP: int = ERR_GROUP
    int ERR_GROUP
```

### **mpi4py.MPI.ERR\_TYPE**

```
mpi4py.MPI.ERR_TYPE: int = ERR_TYPE  
    int ERR_TYPE
```

### **mpi4py.MPI.ERR\_REQUEST**

```
mpi4py.MPI.ERR_REQUEST: int = ERR_REQUEST  
    int ERR_REQUEST
```

### **mpi4py.MPI.ERR\_OP**

```
mpi4py.MPI.ERR_OP: int = ERR_OP  
    int ERR_OP
```

### **mpi4py.MPI.ERR\_BUFFER**

```
mpi4py.MPI.ERR_BUFFER: int = ERR_BUFFER  
    int ERR_BUFFER
```

### **mpi4py.MPI.ERR\_COUNT**

```
mpi4py.MPI.ERR_COUNT: int = ERR_COUNT  
    int ERR_COUNT
```

### **mpi4py.MPI.ERR\_TAG**

```
mpi4py.MPI.ERR_TAG: int = ERR_TAG  
    int ERR_TAG
```

### **mpi4py.MPI.ERR\_RANK**

```
mpi4py.MPI.ERR_RANK: int = ERR_RANK  
    int ERR_RANK
```

### **mpi4py.MPI.ERR\_ROOT**

```
mpi4py.MPI.ERR_ROOT: int = ERR_ROOT  
    int ERR_ROOT
```



### **mpi4py.MPI.ERR\_TRUNCATE**

```
mpi4py.MPI.ERR_TRUNCATE: int = ERR_TRUNCATE  
int ERR_TRUNCATE
```

### **mpi4py.MPI.ERR\_IN\_STATUS**

```
mpi4py.MPI.ERR_IN_STATUS: int = ERR_IN_STATUS  
int ERR_IN_STATUS
```

### **mpi4py.MPI.ERR\_PENDING**

```
mpi4py.MPI.ERR_PENDING: int = ERR_PENDING  
int ERR_PENDING
```

### **mpi4py.MPI.ERR\_TOPOLOGY**

```
mpi4py.MPI.ERR_TOPOLOGY: int = ERR_TOPOLOGY  
int ERR_TOPOLOGY
```

### **mpi4py.MPI.ERR\_DIMS**

```
mpi4py.MPI.ERR_DIMS: int = ERR_DIMS  
int ERR_DIMS
```

### **mpi4py.MPI.ERR\_ARG**

```
mpi4py.MPI.ERR_ARG: int = ERR_ARG  
int ERR_ARG
```

### **mpi4py.MPI.ERR\_OTHER**

```
mpi4py.MPI.ERR_OTHER: int = ERR_OTHER  
int ERR_OTHER
```

### **mpi4py.MPI.ERR\_UNKNOWN**

```
mpi4py.MPI.ERR_UNKNOWN: int = ERR_UNKNOWN  
int ERR_UNKNOWN
```

### **mpi4py.MPI.ERR\_INTERN**

```
mpi4py.MPI.ERR_INTERN: int = ERR_INTERN  
int ERR_INTERN
```

### **mpi4py.MPI.ERR\_INFO**

```
mpi4py.MPI.ERR_INFO: int = ERR_INFO  
int ERR_INFO
```

### **mpi4py.MPI.ERR\_FILE**

```
mpi4py.MPI.ERR_FILE: int = ERR_FILE  
int ERR_FILE
```

### **mpi4py.MPI.ERR\_WIN**

```
mpi4py.MPI.ERR_WIN: int = ERR_WIN  
int ERR_WIN
```

### **mpi4py.MPI.ERR\_KEYVAL**

```
mpi4py.MPI.ERR_KEYVAL: int = ERR_KEYVAL  
int ERR_KEYVAL
```

### **mpi4py.MPI.ERR\_INFO\_KEY**

```
mpi4py.MPI.ERR_INFO_KEY: int = ERR_INFO_KEY  
int ERR_INFO_KEY
```

### **mpi4py.MPI.ERR\_INFO\_VALUE**

```
mpi4py.MPI.ERR_INFO_VALUE: int = ERR_INFO_VALUE  
int ERR_INFO_VALUE
```

### **mpi4py.MPI.ERR\_INFO\_NOKEY**

```
mpi4py.MPI.ERR_INFO_NOKEY: int = ERR_INFO_NOKEY  
int ERR_INFO_NOKEY
```

### **mpi4py.MPI.ERR\_ACCESS**

```
mpi4py.MPI.ERR_ACCESS: int = ERR_ACCESS  
int ERR_ACCESS
```

### **mpi4py.MPI.ERR\_AMODE**

```
mpi4py.MPI.ERR_AMODE: int = ERR_AMODE  
int ERR_AMODE
```

### **mpi4py.MPI.ERR\_BAD\_FILE**

```
mpi4py.MPI.ERR_BAD_FILE: int = ERR_BAD_FILE  
int ERR_BAD_FILE
```

### **mpi4py.MPI.ERR\_FILE\_EXISTS**

```
mpi4py.MPI.ERR_FILE_EXISTS: int = ERR_FILE_EXISTS  
int ERR_FILE_EXISTS
```

### **mpi4py.MPI.ERR\_FILE\_IN\_USE**

```
mpi4py.MPI.ERR_FILE_IN_USE: int = ERR_FILE_IN_USE  
int ERR_FILE_IN_USE
```

### **mpi4py.MPI.ERR\_NO\_SPACE**

```
mpi4py.MPI.ERR_NO_SPACE: int = ERR_NO_SPACE  
int ERR_NO_SPACE
```

### **mpi4py.MPI.ERR\_NO\_SUCH\_FILE**

```
mpi4py.MPI.ERR_NO_SUCH_FILE: int = ERR_NO_SUCH_FILE  
int ERR_NO_SUCH_FILE
```

### **mpi4py.MPI.ERR\_IO**

```
mpi4py.MPI.ERR_IO: int = ERR_IO  
int ERR_IO
```

### **mpi4py.MPI.ERR\_READ\_ONLY**

```
mpi4py.MPI.ERR_READ_ONLY: int = ERR_READ_ONLY  
int ERR_READ_ONLY
```

### **mpi4py.MPI.ERR\_CONVERSION**

```
mpi4py.MPI.ERR_CONVERSION: int = ERR_CONVERSION  
int ERR_CONVERSION
```

### **mpi4py.MPI.ERR\_DUP\_DATAREP**

```
mpi4py.MPI.ERR_DUP_DATAREP: int = ERR_DUP_DATAREP  
int ERR_DUP_DATAREP
```

### **mpi4py.MPI.ERR\_UNSUPPORTED\_DATAREP**

```
mpi4py.MPI.ERR_UNSUPPORTED_DATAREP: int = ERR_UNSUPPORTED_DATAREP  
int ERR_UNSUPPORTED_DATAREP
```

### **mpi4py.MPI.ERR\_UNSUPPORTED\_OPERATION**

```
mpi4py.MPI.ERR_UNSUPPORTED_OPERATION: int = ERR_UNSUPPORTED_OPERATION  
int ERR_UNSUPPORTED_OPERATION
```

### **mpi4py.MPI.ERR\_NAME**

```
mpi4py.MPI.ERR_NAME: int = ERR_NAME  
int ERR_NAME
```

### **mpi4py.MPI.ERR\_NO\_MEM**

```
mpi4py.MPI.ERR_NO_MEM: int = ERR_NO_MEM  
int ERR_NO_MEM
```

### **mpi4py.MPI.ERR\_NOT\_SAME**

```
mpi4py.MPI.ERR_NOT_SAME: int = ERR_NOT_SAME  
int ERR_NOT_SAME
```

### **mpi4py.MPI.ERR\_PORT**

```
mpi4py.MPI.ERR_PORT: int = ERR_PORT  
    int ERR_PORT
```

### **mpi4py.MPI.ERR\_QUOTA**

```
mpi4py.MPI.ERR_QUOTA: int = ERR_QUOTA  
    int ERR_QUOTA
```

### **mpi4py.MPI.ERR\_SERVICE**

```
mpi4py.MPI.ERR_SERVICE: int = ERR_SERVICE  
    int ERR_SERVICE
```

### **mpi4py.MPI.ERR\_SPAWN**

```
mpi4py.MPI.ERR_SPAWN: int = ERR_SPAWN  
    int ERR_SPAWN
```

### **mpi4py.MPI.ERR\_BASE**

```
mpi4py.MPI.ERR_BASE: int = ERR_BASE  
    int ERR_BASE
```

### **mpi4py.MPI.ERR\_SIZE**

```
mpi4py.MPI.ERR_SIZE: int = ERR_SIZE  
    int ERR_SIZE
```

### **mpi4py.MPI.ERR\_DISP**

```
mpi4py.MPI.ERR_DISP: int = ERR_DISP  
    int ERR_DISP
```

### **mpi4py.MPI.ERR\_ASSERT**

```
mpi4py.MPI.ERR_ASSERT: int = ERR_ASSERT  
    int ERR_ASSERT
```

### **mpi4py.MPI.ERR\_LOCKTYPE**

```
mpi4py.MPI.ERR_LOCKTYPE: int = ERR_LOCKTYPE  
int ERR_LOCKTYPE
```

### **mpi4py.MPI.ERR\_RMA\_CONFLICT**

```
mpi4py.MPI.ERR_RMA_CONFLICT: int = ERR_RMA_CONFLICT  
int ERR_RMA_CONFLICT
```

### **mpi4py.MPI.ERR\_RMA\_SYNC**

```
mpi4py.MPI.ERR_RMA_SYNC: int = ERR_RMA_SYNC  
int ERR_RMA_SYNC
```

### **mpi4py.MPI.ERR\_RMA\_RANGE**

```
mpi4py.MPI.ERR_RMA_RANGE: int = ERR_RMA_RANGE  
int ERR_RMA_RANGE
```

### **mpi4py.MPI.ERR\_RMA\_ATTACH**

```
mpi4py.MPI.ERR_RMA_ATTACH: int = ERR_RMA_ATTACH  
int ERR_RMA_ATTACH
```

### **mpi4py.MPI.ERR\_RMA\_SHARED**

```
mpi4py.MPI.ERR_RMA_SHARED: int = ERR_RMA_SHARED  
int ERR_RMA_SHARED
```

### **mpi4py.MPI.ERR\_RMA\_FLAVOR**

```
mpi4py.MPI.ERR_RMA_FLAVOR: int = ERR_RMA_FLAVOR  
int ERR_RMA_FLAVOR
```

### **mpi4py.MPI.ORDER\_C**

```
mpi4py.MPI.ORDER_C: int = ORDER_C  
int ORDER_C
```

### **mpi4py.MPI.ORDER\_FORTRAN**

```
mpi4py.MPI.ORDER_FORTRAN: int = ORDER_FORTRAN
    int ORDER_FORTRAN
```

### **mpi4py.MPI.ORDER\_F**

```
mpi4py.MPI.ORDER_F: int = ORDER_F
    int ORDER_F
```

### **mpi4py.MPI.TYPECLASS\_INTEGER**

```
mpi4py.MPI.TYPECLASS_INTEGER: int = TYPECLASS_INTEGER
    int TYPECLASS_INTEGER
```

### **mpi4py.MPI.TYPECLASS\_REAL**

```
mpi4py.MPI.TYPECLASS_REAL: int = TYPECLASS_REAL
    int TYPECLASS_REAL
```

### **mpi4py.MPI.TYPECLASS\_COMPLEX**

```
mpi4py.MPI.TYPECLASS_COMPLEX: int = TYPECLASS_COMPLEX
    int TYPECLASS_COMPLEX
```

### **mpi4py.MPI.DISTRIBUTE\_NONE**

```
mpi4py.MPI.DISTRIBUTE_NONE: int = DISTRIBUTE_NONE
    int DISTRIBUTE_NONE
```

### **mpi4py.MPI.DISTRIBUTE\_BLOCK**

```
mpi4py.MPI.DISTRIBUTE_BLOCK: int = DISTRIBUTE_BLOCK
    int DISTRIBUTE_BLOCK
```

### **mpi4py.MPI.DISTRIBUTE\_CYCLIC**

```
mpi4py.MPI.DISTRIBUTE_CYCLIC: int = DISTRIBUTE_CYCLIC
    int DISTRIBUTE_CYCLIC
```

### **mpi4py.MPI.DISTRIBUTE\_DFLT\_DARG**

```
mpi4py.MPI.DISTRIBUTE_DFLT_DARG: int = DISTRIBUTE_DFLT_DARG
    int DISTRIBUTE_DFLT_DARG
```

### **mpi4py.MPI.COMBINER\_NAMED**

```
mpi4py.MPI.COMBINER_NAMED: int = COMBINER_NAMED
    int COMBINER_NAMED
```

### **mpi4py.MPI.COMBINER\_DUP**

```
mpi4py.MPI.COMBINER_DUP: int = COMBINER_DUP
    int COMBINER_DUP
```

### **mpi4py.MPI.COMBINER\_CONTIGUOUS**

```
mpi4py.MPI.COMBINER_CONTIGUOUS: int = COMBINER_CONTIGUOUS
    int COMBINER_CONTIGUOUS
```

### **mpi4py.MPI.COMBINER\_VECTOR**

```
mpi4py.MPI.COMBINER_VECTOR: int = COMBINER_VECTOR
    int COMBINER_VECTOR
```

### **mpi4py.MPI.COMBINER\_HVECTOR**

```
mpi4py.MPI.COMBINER_HVECTOR: int = COMBINER_HVECTOR
    int COMBINER_HVECTOR
```

### **mpi4py.MPI.COMBINER\_INDEXED**

```
mpi4py.MPI.COMBINER_INDEXED: int = COMBINER_INDEXED
    int COMBINER_INDEXED
```

### **mpi4py.MPI.COMBINER\_HINDEXED**

```
mpi4py.MPI.COMBINER_HINDEXED: int = COMBINER_HINDEXED
    int COMBINER_HINDEXED
```



### **mpi4py.MPI.COMBINER\_INDEXED\_BLOCK**

```
mpi4py.MPI.COMBINER_INDEXED_BLOCK: int = COMBINER_INDEXED_BLOCK  
    int COMBINER_INDEXED_BLOCK
```

### **mpi4py.MPI.COMBINER\_HINDEXED\_BLOCK**

```
mpi4py.MPI.COMBINER_HINDEXED_BLOCK: int = COMBINER_HINDEXED_BLOCK  
    int COMBINER_HINDEXED_BLOCK
```

### **mpi4py.MPI.COMBINER\_STRUCT**

```
mpi4py.MPI.COMBINER_STRUCT: int = COMBINER_STRUCT  
    int COMBINER_STRUCT
```

### **mpi4py.MPI.COMBINER\_SUBARRAY**

```
mpi4py.MPI.COMBINER_SUBARRAY: int = COMBINER_SUBARRAY  
    int COMBINER_SUBARRAY
```

### **mpi4py.MPI.COMBINER\_DARRAY**

```
mpi4py.MPI.COMBINER_DARRAY: int = COMBINER_DARRAY  
    int COMBINER_DARRAY
```

### **mpi4py.MPI.COMBINER\_RESIZED**

```
mpi4py.MPI.COMBINER_RESIZED: int = COMBINER_RESIZED  
    int COMBINER_RESIZED
```

### **mpi4py.MPI.COMBINER\_F90\_REAL**

```
mpi4py.MPI.COMBINER_F90_REAL: int = COMBINER_F90_REAL  
    int COMBINER_F90_REAL
```

### **mpi4py.MPI.COMBINER\_F90\_COMPLEX**

```
mpi4py.MPI.COMBINER_F90_COMPLEX: int = COMBINER_F90_COMPLEX  
    int COMBINER_F90_COMPLEX
```

### **mpi4py.MPI.COMBINER\_F90\_INTEGER**

```
mpi4py.MPI.COMBINER_F90_INTEGER: int = COMBINER_F90_INTEGER  
    int COMBINER_F90_INTEGER
```

### **mpi4py.MPI.IDENT**

```
mpi4py.MPI.IDENT: int = IDENT  
    int IDENT
```

### **mpi4py.MPI.CONGRUENT**

```
mpi4py.MPI.CONGRUENT: int = CONGRUENT  
    int CONGRUENT
```

### **mpi4py.MPI.SIMILAR**

```
mpi4py.MPI.SIMILAR: int = SIMILAR  
    int SIMILAR
```

### **mpi4py.MPI.UNEQUAL**

```
mpi4py.MPI.UNEQUAL: int = UNEQUAL  
    int UNEQUAL
```

### **mpi4py.MPI.CART**

```
mpi4py.MPI.CART: int = CART  
    int CART
```

### **mpi4py.MPI.GRAPH**

```
mpi4py.MPI.GRAPH: int = GRAPH  
    int GRAPH
```

### **mpi4py.MPI.DIST\_GRAPH**

```
mpi4py.MPI.DIST_GRAPH: int = DIST_GRAPH  
    int DIST_GRAPH
```

### **mpi4py.MPI.UNWEIGHTED**

```
mpi4py.MPI.UNWEIGHTED: int = UNWEIGHTED
int UNWEIGHTED
```

### **mpi4py.MPI.WEIGHTS\_EMPTY**

```
mpi4py.MPI.WEIGHTS_EMPTY: int = WEIGHTS_EMPTY
int WEIGHTS_EMPTY
```

### **mpi4py.MPI.COMM\_TYPE\_SHARED**

```
mpi4py.MPI.COMM_TYPE_SHARED: int = COMM_TYPE_SHARED
int COMM_TYPE_SHARED
```

### **mpi4py.MPI.BSEND\_OVERHEAD**

```
mpi4py.MPI.BSEND_OVERHEAD: int = BSEND_OVERHEAD
int BSEND_OVERHEAD
```

### **mpi4py.MPI.WIN\_FLAVOR\_CREATE**

```
mpi4py.MPI.WIN_FLAVOR_CREATE: int = WIN_FLAVOR_CREATE
int WIN_FLAVOR_CREATE
```

### **mpi4py.MPI.WIN\_FLAVOR\_ALLOCATE**

```
mpi4py.MPI.WIN_FLAVOR_ALLOCATE: int = WIN_FLAVOR_ALLOCATE
int WIN_FLAVOR_ALLOCATE
```

### **mpi4py.MPI.WIN\_FLAVOR\_DYNAMIC**

```
mpi4py.MPI.WIN_FLAVOR_DYNAMIC: int = WIN_FLAVOR_DYNAMIC
int WIN_FLAVOR_DYNAMIC
```

### **mpi4py.MPI.WIN\_FLAVOR\_SHARED**

```
mpi4py.MPI.WIN_FLAVOR_SHARED: int = WIN_FLAVOR_SHARED
int WIN_FLAVOR_SHARED
```

### **mpi4py.MPI.WIN\_SEPARATE**

```
mpi4py.MPI.WIN_SEPARATE: int = WIN_SEPARATE  
int WIN_SEPARATE
```

### **mpi4py.MPI.WIN\_UNIFIED**

```
mpi4py.MPI.WIN_UNIFIED: int = WIN_UNIFIED  
int WIN_UNIFIED
```

### **mpi4py.MPI.MODE\_NOCHECK**

```
mpi4py.MPI.MODE_NOCHECK: int = MODE_NOCHECK  
int MODE_NOCHECK
```

### **mpi4py.MPI.MODE\_NOSTORE**

```
mpi4py.MPI.MODE_NOSTORE: int = MODE_NOSTORE  
int MODE_NOSTORE
```

### **mpi4py.MPI.MODE\_NOPUT**

```
mpi4py.MPI.MODE_NOPUT: int = MODE_NOPUT  
int MODE_NOPUT
```

### **mpi4py.MPI.MODE\_NOPRECEDE**

```
mpi4py.MPI.MODE_NOPRECEDE: int = MODE_NOPRECEDE  
int MODE_NOPRECEDE
```

### **mpi4py.MPI.MODE\_NOSUCCEED**

```
mpi4py.MPI.MODE_NOSUCCEED: int = MODE_NOSUCCEED  
int MODE_NOSUCCEED
```

### **mpi4py.MPI.LOCK\_EXCLUSIVE**

```
mpi4py.MPI.LOCK_EXCLUSIVE: int = LOCK_EXCLUSIVE  
int LOCK_EXCLUSIVE
```

### **mpi4py.MPI.LOCK\_SHARED**

```
mpi4py.MPI.LOCK_SHARED: int = LOCK_SHARED  
int LOCK_SHARED
```

### **mpi4py.MPI.MODE\_RDONLY**

```
mpi4py.MPI.MODE_RDONLY: int = MODE_RDONLY  
int MODE_RDONLY
```

### **mpi4py.MPI.MODE\_WRONLY**

```
mpi4py.MPI.MODE_WRONLY: int = MODE_WRONLY  
int MODE_WRONLY
```

### **mpi4py.MPI.MODE\_RDWR**

```
mpi4py.MPI.MODE_RDWR: int = MODE_RDWR  
int MODE_RDWR
```

### **mpi4py.MPI.MODE\_CREATE**

```
mpi4py.MPI.MODE_CREATE: int = MODE_CREATE  
int MODE_CREATE
```

### **mpi4py.MPI.MODE\_EXCL**

```
mpi4py.MPI.MODE_EXCL: int = MODE_EXCL  
int MODE_EXCL
```

### **mpi4py.MPI.MODE\_DELETE\_ON\_CLOSE**

```
mpi4py.MPI.MODE_DELETE_ON_CLOSE: int = MODE_DELETE_ON_CLOSE  
int MODE_DELETE_ON_CLOSE
```

### **mpi4py.MPI.MODE\_UNIQUE\_OPEN**

```
mpi4py.MPI.MODE_UNIQUE_OPEN: int = MODE_UNIQUE_OPEN  
int MODE_UNIQUE_OPEN
```

### **mpi4py.MPI.MODE\_SEQUENTIAL**

```
mpi4py.MPI.MODE_SEQUENTIAL: int = MODE_SEQUENTIAL
int MODE_SEQUENTIAL
```

### **mpi4py.MPI.MODE\_APPEND**

```
mpi4py.MPI.MODE_APPEND: int = MODE_APPEND
int MODE_APPEND
```

### **mpi4py.MPI.SEEK\_SET**

```
mpi4py.MPI.SEEK_SET: int = SEEK_SET
int SEEK_SET
```

### **mpi4py.MPI.SEEK\_CUR**

```
mpi4py.MPI.SEEK_CUR: int = SEEK_CUR
int SEEK_CUR
```

### **mpi4py.MPI.SEEK\_END**

```
mpi4py.MPI.SEEK_END: int = SEEK_END
int SEEK_END
```

### **mpi4py.MPI.DISPLACEMENT\_CURRENT**

```
mpi4py.MPI.DISPLACEMENT_CURRENT: int = DISPLACEMENT_CURRENT
int DISPLACEMENT_CURRENT
```

### **mpi4py.MPI.DISP\_CUR**

```
mpi4py.MPI.DISP_CUR: int = DISP_CUR
int DISP_CUR
```

### **mpi4py.MPI.THREAD\_SINGLE**

```
mpi4py.MPI.THREAD_SINGLE: int = THREAD_SINGLE
int THREAD_SINGLE
```

### **mpi4py.MPI.THREAD\_FUNNELED**

```
mpi4py.MPI.THREAD_FUNNELED: int = THREAD_FUNNELED  
int THREAD_FUNNELED
```

### **mpi4py.MPI.THREAD\_SERIALIZED**

```
mpi4py.MPI.THREAD_SERIALIZED: int = THREAD_SERIALIZED  
int THREAD_SERIALIZED
```

### **mpi4py.MPI.THREAD\_MULTIPLE**

```
mpi4py.MPI.THREAD_MULTIPLE: int = THREAD_MULTIPLE  
int THREAD_MULTIPLE
```

### **mpi4py.MPI.VERSION**

```
mpi4py.MPI.VERSION: int = VERSION  
int VERSION
```

### **mpi4py.MPI.SUBVERSION**

```
mpi4py.MPI.SUBVERSION: int = SUBVERSION  
int SUBVERSION
```

### **mpi4py.MPI.MAX\_PROCESSOR\_NAME**

```
mpi4py.MPI.MAX_PROCESSOR_NAME: int = MAX_PROCESSOR_NAME  
int MAX_PROCESSOR_NAME
```

### **mpi4py.MPI.MAX\_ERROR\_STRING**

```
mpi4py.MPI.MAX_ERROR_STRING: int = MAX_ERROR_STRING  
int MAX_ERROR_STRING
```

### **mpi4py.MPI.MAX\_PORT\_NAME**

```
mpi4py.MPI.MAX_PORT_NAME: int = MAX_PORT_NAME  
int MAX_PORT_NAME
```

### **mpi4py.MPI.MAX\_INFO\_KEY**

```
mpi4py.MPI.MAX_INFO_KEY: int = MAX_INFO_KEY  
    int MAX_INFO_KEY
```

### **mpi4py.MPI.MAX\_INFO\_VAL**

```
mpi4py.MPI.MAX_INFO_VAL: int = MAX_INFO_VAL  
    int MAX_INFO_VAL
```

### **mpi4py.MPI.MAX\_OBJECT\_NAME**

```
mpi4py.MPI.MAX_OBJECT_NAME: int = MAX_OBJECT_NAME  
    int MAX_OBJECT_NAME
```

### **mpi4py.MPI.MAX\_DATAREP\_STRING**

```
mpi4py.MPI.MAX_DATAREP_STRING: int = MAX_DATAREP_STRING  
    int MAX_DATAREP_STRING
```

### **mpi4py.MPI.MAX\_LIBRARY\_VERSION\_STRING**

```
mpi4py.MPI.MAX_LIBRARY_VERSION_STRING: int = MAX_LIBRARY_VERSION_STRING  
    int MAX_LIBRARY_VERSION_STRING
```

### **mpi4py.MPI.DATATYPE\_NULL**

```
mpi4py.MPI.DATATYPE_NULL: Datatype = DATATYPE_NULL  
    Datatype DATATYPE_NULL
```

### **mpi4py.MPI.UB**

```
mpi4py.MPI.UB: Datatype = UB  
    Datatype UB
```

### **mpi4py.MPI.LB**

```
mpi4py.MPI.LB: Datatype = LB  
    Datatype LB
```



### **mpi4py.MPI.PACKED**

`mpi4py.MPI.PACKED: Datatype = PACKED`  
*Datatype* PACKED

### **mpi4py.MPI.BYTE**

`mpi4py.MPI.BYTE: Datatype = BYTE`  
*Datatype* BYTE

### **mpi4py.MPI.AINT**

`mpi4py.MPI.AINT: Datatype = AINT`  
*Datatype* AINT

### **mpi4py.MPI.OFFSET**

`mpi4py.MPI.OFFSET: Datatype = OFFSET`  
*Datatype* OFFSET

### **mpi4py.MPI.COUNT**

`mpi4py.MPI.COUNT: Datatype = COUNT`  
*Datatype* COUNT

### **mpi4py.MPI.CHAR**

`mpi4py.MPI.CHAR: Datatype = CHAR`  
*Datatype* CHAR

### **mpi4py.MPI.WCHAR**

`mpi4py.MPI.WCHAR: Datatype = WCHAR`  
*Datatype* WCHAR

### **mpi4py.MPI.SIGNED\_CHAR**

`mpi4py.MPI.SIGNED_CHAR: Datatype = SIGNED_CHAR`  
*Datatype* SIGNED\_CHAR

### **mpi4py.MPI.SHORT**

mpi4py.MPI.SHORT: *Datatype* = SHORT  
*Datatype* SHORT

### **mpi4py.MPI.INT**

mpi4py.MPI.INT: *Datatype* = INT  
*Datatype* INT

### **mpi4py.MPI.LONG**

mpi4py.MPI.LONG: *Datatype* = LONG  
*Datatype* LONG

### **mpi4py.MPI.LONG\_LONG**

mpi4py.MPI.LONG\_LONG: *Datatype* = LONG\_LONG  
*Datatype* LONG\_LONG

### **mpi4py.MPI.UNSIGNED\_CHAR**

mpi4py.MPI.UNSIGNED\_CHAR: *Datatype* = UNSIGNED\_CHAR  
*Datatype* UNSIGNED\_CHAR

### **mpi4py.MPI.UNSIGNED\_SHORT**

mpi4py.MPI.UNSIGNED\_SHORT: *Datatype* = UNSIGNED\_SHORT  
*Datatype* UNSIGNED\_SHORT

### **mpi4py.MPI.UNSIGNED**

mpi4py.MPI.UNSIGNED: *Datatype* = UNSIGNED  
*Datatype* UNSIGNED

### **mpi4py.MPI.UNSIGNED\_LONG**

mpi4py.MPI.UNSIGNED\_LONG: *Datatype* = UNSIGNED\_LONG  
*Datatype* UNSIGNED\_LONG

### **mpi4py.MPI.UNSIGNED\_LONG\_LONG**

mpi4py.MPI.UNSIGNED\_LONG\_LONG: *Datatype* = UNSIGNED\_LONG\_LONG  
*Datatype* UNSIGNED\_LONG\_LONG

### **mpi4py.MPI.FLOAT**

mpi4py.MPI.FLOAT: *Datatype* = FLOAT  
*Datatype* FLOAT

### **mpi4py.MPI.DOUBLE**

mpi4py.MPI.DOUBLE: *Datatype* = DOUBLE  
*Datatype* DOUBLE

### **mpi4py.MPI.LONG\_DOUBLE**

mpi4py.MPI.LONG\_DOUBLE: *Datatype* = LONG\_DOUBLE  
*Datatype* LONG\_DOUBLE

### **mpi4py.MPI.C\_BOOL**

mpi4py.MPI.C\_BOOL: *Datatype* = C\_BOOL  
*Datatype* C\_BOOL

### **mpi4py.MPI.INT8\_T**

mpi4py.MPI.INT8\_T: *Datatype* = INT8\_T  
*Datatype* INT8\_T

### **mpi4py.MPI.INT16\_T**

mpi4py.MPI.INT16\_T: *Datatype* = INT16\_T  
*Datatype* INT16\_T

### **mpi4py.MPI.INT32\_T**

mpi4py.MPI.INT32\_T: *Datatype* = INT32\_T  
*Datatype* INT32\_T

### **mpi4py.MPI.INT64\_T**

`mpi4py.MPI.INT64_T: Datatype = INT64_T`  
*Datatype* INT64\_T

### **mpi4py.MPI.UINT8\_T**

`mpi4py.MPI.UINT8_T: Datatype = UINT8_T`  
*Datatype* UINT8\_T

### **mpi4py.MPI.UINT16\_T**

`mpi4py.MPI.UINT16_T: Datatype = UINT16_T`  
*Datatype* UINT16\_T

### **mpi4py.MPI.UINT32\_T**

`mpi4py.MPI.UINT32_T: Datatype = UINT32_T`  
*Datatype* UINT32\_T

### **mpi4py.MPI.UINT64\_T**

`mpi4py.MPI.UINT64_T: Datatype = UINT64_T`  
*Datatype* UINT64\_T

### **mpi4py.MPI.C\_COMPLEX**

`mpi4py.MPI.C_COMPLEX: Datatype = C_COMPLEX`  
*Datatype* C\_COMPLEX

### **mpi4py.MPI.C\_FLOAT\_COMPLEX**

`mpi4py.MPI.C_FLOAT_COMPLEX: Datatype = C_FLOAT_COMPLEX`  
*Datatype* C\_FLOAT\_COMPLEX

### **mpi4py.MPI.C\_DOUBLE\_COMPLEX**

`mpi4py.MPI.C_DOUBLE_COMPLEX: Datatype = C_DOUBLE_COMPLEX`  
*Datatype* C\_DOUBLE\_COMPLEX

### **mpi4py.MPI.C\_LONG\_DOUBLE\_COMPLEX**

mpi4py.MPI.C\_LONG\_DOUBLE\_COMPLEX: *Datatype* = C\_LONG\_DOUBLE\_COMPLEX  
*Datatype* C\_LONG\_DOUBLE\_COMPLEX

### **mpi4py.MPI.CXX\_BOOL**

mpi4py.MPI.CXX\_BOOL: *Datatype* = CXX\_BOOL  
*Datatype* CXX\_BOOL

### **mpi4py.MPI.CXX\_FLOAT\_COMPLEX**

mpi4py.MPI.CXX\_FLOAT\_COMPLEX: *Datatype* = CXX\_FLOAT\_COMPLEX  
*Datatype* CXX\_FLOAT\_COMPLEX

### **mpi4py.MPI.CXX\_DOUBLE\_COMPLEX**

mpi4py.MPI.CXX\_DOUBLE\_COMPLEX: *Datatype* = CXX\_DOUBLE\_COMPLEX  
*Datatype* CXX\_DOUBLE\_COMPLEX

### **mpi4py.MPI.CXX\_LONG\_DOUBLE\_COMPLEX**

mpi4py.MPI.CXX\_LONG\_DOUBLE\_COMPLEX: *Datatype* = CXX\_LONG\_DOUBLE\_COMPLEX  
*Datatype* CXX\_LONG\_DOUBLE\_COMPLEX

### **mpi4py.MPI.SHORT\_INT**

mpi4py.MPI.SHORT\_INT: *Datatype* = SHORT\_INT  
*Datatype* SHORT\_INT

### **mpi4py.MPI.INT\_INT**

mpi4py.MPI.INT\_INT: *Datatype* = INT\_INT  
*Datatype* INT\_INT

### **mpi4py.MPI.TWOINT**

mpi4py.MPI.TWOINT: *Datatype* = TWOINT  
*Datatype* TWOINT

### **mpi4py.MPI.LONG\_INT**

`mpi4py.MPI.LONG_INT: Datatype = LONG_INT`  
`Datatype LONG_INT`

### **mpi4py.MPI.FLOAT\_INT**

`mpi4py.MPI.FLOAT_INT: Datatype = FLOAT_INT`  
`Datatype FLOAT_INT`

### **mpi4py.MPI.DOUBLE\_INT**

`mpi4py.MPI.DOUBLE_INT: Datatype = DOUBLE_INT`  
`Datatype DOUBLE_INT`

### **mpi4py.MPI.LONG\_DOUBLE\_INT**

`mpi4py.MPI.LONG_DOUBLE_INT: Datatype = LONG_DOUBLE_INT`  
`Datatype LONG_DOUBLE_INT`

### **mpi4py.MPI.CHARACTER**

`mpi4py.MPI.CHARACTER: Datatype = CHARACTER`  
`Datatype CHARACTER`

### **mpi4py.MPI.LOGICAL**

`mpi4py.MPI.LOGICAL: Datatype = LOGICAL`  
`Datatype LOGICAL`

### **mpi4py.MPI.INTEGER**

`mpi4py.MPI.INTEGER: Datatype = INTEGER`  
`Datatype INTEGER`

### **mpi4py.MPI.REAL**

`mpi4py.MPI.REAL: Datatype = REAL`  
`Datatype REAL`

### **mpi4py.MPI.DOUBLE\_PRECISION**

`mpi4py.MPI.DOUBLE_PRECISION: Datatype = DOUBLE_PRECISION`  
`Datatype DOUBLE_PRECISION`

### **mpi4py.MPI.COMPLEX**

`mpi4py.MPI.COMPLEX: Datatype = COMPLEX`  
`Datatype COMPLEX`

### **mpi4py.MPI.DOUBLE\_COMPLEX**

`mpi4py.MPI.DOUBLE_COMPLEX: Datatype = DOUBLE_COMPLEX`  
`Datatype DOUBLE_COMPLEX`

### **mpi4py.MPI.LOGICAL1**

`mpi4py.MPI.LOGICAL1: Datatype = LOGICAL1`  
`Datatype LOGICAL1`

### **mpi4py.MPI.LOGICAL2**

`mpi4py.MPI.LOGICAL2: Datatype = LOGICAL2`  
`Datatype LOGICAL2`

### **mpi4py.MPI.LOGICAL4**

`mpi4py.MPI.LOGICAL4: Datatype = LOGICAL4`  
`Datatype LOGICAL4`

### **mpi4py.MPI.LOGICAL8**

`mpi4py.MPI.LOGICAL8: Datatype = LOGICAL8`  
`Datatype LOGICAL8`

### **mpi4py.MPI.INTEGER1**

`mpi4py.MPI.INTEGER1: Datatype = INTEGER1`  
`Datatype INTEGER1`

### **mpi4py.MPI.INTEGER2**

`mpi4py.MPI.INTEGER2: Datatype = INTEGER2`  
*Datatype* INTEGER2

### **mpi4py.MPI.INTEGER4**

`mpi4py.MPI.INTEGER4: Datatype = INTEGER4`  
*Datatype* INTEGER4

### **mpi4py.MPI.INTEGER8**

`mpi4py.MPI.INTEGER8: Datatype = INTEGER8`  
*Datatype* INTEGER8

### **mpi4py.MPI.INTEGER16**

`mpi4py.MPI.INTEGER16: Datatype = INTEGER16`  
*Datatype* INTEGER16

### **mpi4py.MPI.REAL2**

`mpi4py.MPI.REAL2: Datatype = REAL2`  
*Datatype* REAL2

### **mpi4py.MPI.REAL4**

`mpi4py.MPI.REAL4: Datatype = REAL4`  
*Datatype* REAL4

### **mpi4py.MPI.REAL8**

`mpi4py.MPI.REAL8: Datatype = REAL8`  
*Datatype* REAL8

### **mpi4py.MPI.REAL16**

`mpi4py.MPI.REAL16: Datatype = REAL16`  
*Datatype* REAL16



### **mpi4py.MPI.COMPLEX4**

`mpi4py.MPI.COMPLEX4: Datatype = COMPLEX4`  
*Datatype* COMPLEX4

### **mpi4py.MPI.COMPLEX8**

`mpi4py.MPI.COMPLEX8: Datatype = COMPLEX8`  
*Datatype* COMPLEX8

### **mpi4py.MPI.COMPLEX16**

`mpi4py.MPI.COMPLEX16: Datatype = COMPLEX16`  
*Datatype* COMPLEX16

### **mpi4py.MPI.COMPLEX32**

`mpi4py.MPI.COMPLEX32: Datatype = COMPLEX32`  
*Datatype* COMPLEX32

### **mpi4py.MPI.UNSIGNED\_INT**

`mpi4py.MPI.UNSIGNED_INT: Datatype = UNSIGNED_INT`  
*Datatype* UNSIGNED\_INT

### **mpi4py.MPI.SIGNED\_SHORT**

`mpi4py.MPI.SIGNED_SHORT: Datatype = SIGNED_SHORT`  
*Datatype* SIGNED\_SHORT

### **mpi4py.MPI.SIGNED\_INT**

`mpi4py.MPI.SIGNED_INT: Datatype = SIGNED_INT`  
*Datatype* SIGNED\_INT

### **mpi4py.MPI.SIGNED\_LONG**

`mpi4py.MPI.SIGNED_LONG: Datatype = SIGNED_LONG`  
*Datatype* SIGNED\_LONG

### **mpi4py.MPI.SIGNED\_LONG\_LONG**

mpi4py.MPI.SIGNED\_LONG\_LONG: *Datatype* = SIGNED\_LONG\_LONG  
*Datatype* SIGNED\_LONG\_LONG

### **mpi4py.MPI.BOOL**

mpi4py.MPI.BOOL: *Datatype* = BOOL  
*Datatype* BOOL

### **mpi4py.MPI.SINT8\_T**

mpi4py.MPI.SINT8\_T: *Datatype* = SINT8\_T  
*Datatype* SINT8\_T

### **mpi4py.MPI.SINT16\_T**

mpi4py.MPI.SINT16\_T: *Datatype* = SINT16\_T  
*Datatype* SINT16\_T

### **mpi4py.MPI.SINT32\_T**

mpi4py.MPI.SINT32\_T: *Datatype* = SINT32\_T  
*Datatype* SINT32\_T

### **mpi4py.MPI.SINT64\_T**

mpi4py.MPI.SINT64\_T: *Datatype* = SINT64\_T  
*Datatype* SINT64\_T

### **mpi4py.MPI.F\_BOOL**

mpi4py.MPI.F\_BOOL: *Datatype* = F\_BOOL  
*Datatype* F\_BOOL

### **mpi4py.MPI.F\_INT**

mpi4py.MPI.F\_INT: *Datatype* = F\_INT  
*Datatype* F\_INT

### **mpi4py.MPI.F\_FLOAT**

mpi4py.MPI.F\_FLOAT: *Datatype* = F\_FLOAT  
*Datatype* F\_FLOAT

### **mpi4py.MPI.F\_DOUBLE**

mpi4py.MPI.F\_DOUBLE: *Datatype* = F\_DOUBLE  
*Datatype* F\_DOUBLE

### **mpi4py.MPI.F\_COMPLEX**

mpi4py.MPI.F\_COMPLEX: *Datatype* = F\_COMPLEX  
*Datatype* F\_COMPLEX

### **mpi4py.MPI.F\_FLOAT\_COMPLEX**

mpi4py.MPI.F\_FLOAT\_COMPLEX: *Datatype* = F\_FLOAT\_COMPLEX  
*Datatype* F\_FLOAT\_COMPLEX

### **mpi4py.MPI.F\_DOUBLE\_COMPLEX**

mpi4py.MPI.F\_DOUBLE\_COMPLEX: *Datatype* = F\_DOUBLE\_COMPLEX  
*Datatype* F\_DOUBLE\_COMPLEX

### **mpi4py.MPI.REQUEST\_NULL**

mpi4py.MPI.REQUEST\_NULL: *Request* = REQUEST\_NULL  
*Request* REQUEST\_NULL

### **mpi4py.MPI.MESSAGE\_NULL**

mpi4py.MPI.MESSAGE\_NULL: *Message* = MESSAGE\_NULL  
*Message* MESSAGE\_NULL

### **mpi4py.MPI.MESSAGE\_NO\_PROC**

mpi4py.MPI.MESSAGE\_NO\_PROC: *Message* = MESSAGE\_NO\_PROC  
*Message* MESSAGE\_NO\_PROC

## **mpi4py.MPI.OP\_NULL**

`mpi4py.MPI.OP_NULL: Op = OP_NULL`

*Op* OP\_NULL

### **Parameters**

- **x** (*Any*)
- **y** (*Any*)

### **Return type**

*Any*

## **mpi4py.MPI.MAX**

`mpi4py.MPI.MAX: Op = MAX`

*Op* MAX

### **Parameters**

- **x** (*Any*)
- **y** (*Any*)

### **Return type**

*Any*

## **mpi4py.MPI.MIN**

`mpi4py.MPI.MIN: Op = MIN`

*Op* MIN

### **Parameters**

- **x** (*Any*)
- **y** (*Any*)

### **Return type**

*Any*

## **mpi4py.MPI.SUM**

`mpi4py.MPI.SUM: Op = SUM`

*Op* SUM

### **Parameters**

- **x** (*Any*)
- **y** (*Any*)

### **Return type**

*Any*

## mpi4py.MPI.PROD

mpi4py.MPI.PROD: *Op* = PROD

*Op* PROD

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.LAND

mpi4py.MPI.LAND: *Op* = LAND

*Op* LAND

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.BAND

mpi4py.MPI.BAND: *Op* = BAND

*Op* BAND

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.LOR

mpi4py.MPI.LOR: *Op* = LOR

*Op* LOR

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.BOR

mpi4py.MPI.BOR: *Op* = BOR

*Op* BOR

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.LXOR

mpi4py.MPI.LXOR: *Op* = LXOR

*Op* LXOR

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.BXOR

mpi4py.MPI.BXOR: *Op* = BXOR

*Op* BXOR

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## mpi4py.MPI.MAXLOC

mpi4py.MPI.MAXLOC: *Op* = MAXLOC

*Op* MAXLOC

### Parameters

- *x* (Any)
- *y* (Any)

### Return type

Any

## **mpi4py.MPI.MINLOC**

`mpi4py.MPI.MINLOC: Op = MINLOC`  
*Op* MINLOC

### **Parameters**

- *x* (Any)
- *y* (Any)

**Return type**  
Any

## **mpi4py.MPI.REPLACE**

`mpi4py.MPI.REPLACE: Op = REPLACE`  
*Op* REPLACE

### **Parameters**

- *x* (Any)
- *y* (Any)

**Return type**  
Any

## **mpi4py.MPI.NO\_OP**

`mpi4py.MPI.NO_OP: Op = NO_OP`  
*Op* NO\_OP

### **Parameters**

- *x* (Any)
- *y* (Any)

**Return type**  
Any

## **mpi4py.MPI.GROUP\_NULL**

`mpi4py.MPI.GROUP_NULL: Group = GROUP_NULL`  
*Group* GROUP\_NULL

### **mpi4py.MPI.GROUP\_EMPTY**

mpi4py.MPI.GROUP\_EMPTY: *Group* = GROUP\_EMPTY  
*Group* GROUP\_EMPTY

### **mpi4py.MPI.INFO\_NULL**

mpi4py.MPI.INFO\_NULL: *Info* = INFO\_NULL  
*Info* INFO\_NULL

### **mpi4py.MPI.INFO\_ENV**

mpi4py.MPI.INFO\_ENV: *Info* = INFO\_ENV  
*Info* INFO\_ENV

### **mpi4py.MPI.ERRHANDLER\_NULL**

mpi4py.MPI.ERRHANDLER\_NULL: *Errhandler* = ERRHANDLER\_NULL  
*Errhandler* ERRHANDLER\_NULL

### **mpi4py.MPI.ERRORS\_RETURN**

mpi4py.MPI.ERRORS\_RETURN: *Errhandler* = ERRORS\_RETURN  
*Errhandler* ERRORS\_RETURN

### **mpi4py.MPI.ERRORS\_ARE\_FATAL**

mpi4py.MPI.ERRORS\_ARE\_FATAL: *Errhandler* = ERRORS\_ARE\_FATAL  
*Errhandler* ERRORS\_ARE\_FATAL

### **mpi4py.MPI.COMM\_NULL**

mpi4py.MPI.COMM\_NULL: *Comm* = COMM\_NULL  
*Comm* COMM\_NULL

### **mpi4py.MPI.COMM\_SELF**

mpi4py.MPI.COMM\_SELF: *Intracomm* = COMM\_SELF  
*Intracomm* COMM\_SELF



## mpi4py.MPI.COMM\_WORLD

```
mpi4py.MPI.COMM_WORLD: Intracomm = COMM_WORLD  
    Intracomm COMM_WORLD
```

## mpi4py.MPI.WIN\_NULL

```
mpi4py.MPI.WIN_NULL: Win = WIN_NULL  
    Win WIN_NULL
```

## mpi4py.MPI.FILE\_NULL

```
mpi4py.MPI.FILE_NULL: File = FILE_NULL  
    File FILE_NULL
```

## mpi4py.MPI.pickle

```
mpi4py.MPI.pickle: Pickle = <mpi4py.MPI.Pickle object>  
    Pickle pickle
```

# 10 Citation

If MPI for Python been significant to a project that leads to an academic publication, please acknowledge that fact by citing the project.

- L. Dalcin and Y.-L. L. Fang, *mpi4py: Status Update After 12 Years of Development*, Computing in Science & Engineering, 23(4):47-54, 2021. <https://doi.org/10.1109/MCSE.2021.3083216>
- L. Dalcin, P. Kler, R. Paz, and A. Cosimo, *Parallel Distributed Computing using Python*, Advances in Water Resources, 34(9):1124-1139, 2011. <https://doi.org/10.1016/j.advwatres.2011.04.013>
- L. Dalcin, R. Paz, M. Storti, and J. D’Elia, *MPI for Python: performance improvements and MPI-2 extensions*, Journal of Parallel and Distributed Computing, 68(5):655-662, 2008. <https://doi.org/10.1016/j.jpdc.2007.09.005>
- L. Dalcin, R. Paz, and M. Storti, *MPI for Python*, Journal of Parallel and Distributed Computing, 65(9):1108-1115, 2005. <https://doi.org/10.1016/j.jpdc.2005.03.010>

# 11 Installation

## 11.1 Requirements

You need to have the following software properly installed in order to build *MPI for Python*:

- A working MPI implementation, preferably supporting MPI-3 and built with shared/dynamic libraries.

---

**Note:** If you want to build some MPI implementation from sources, check the instructions at *Building MPI from sources* in the appendix.

---

- Python 2.7, 3.5 or above.

---

**Note:** Some MPI-1 implementations **do require** the actual command line arguments to be passed in `MPI_Init()`. In this case, you will need to use a rebuilt, MPI-enabled, Python interpreter executable. *MPI for Python* has some support for alleviating you from this task. Check the instructions at [MPI-enabled Python interpreter](#) in the appendix.

---

## 11.2 Using pip

If you already have a working MPI (either if you installed it from sources or by using a pre-built package from your favourite GNU/Linux distribution) and the **mpicc** compiler wrapper is on your search path, you can use **pip**:

```
$ python -m pip install mpi4py
```

**Note:** If the **mpicc** compiler wrapper is not on your search path (or if it has a different name) you can use **env** to pass the environment variable `MPICC` providing the full path to the MPI compiler wrapper executable:

```
$ env MPICC=/path/to/mpicc python -m pip install mpi4py
```

**Warning:** **pip** keeps previously built wheel files on its cache for future reuse. If you want to reinstall the *mpi4py* package using a different or updated MPI implementation, you have to either first remove the cached wheel file with:

```
$ python -m pip cache remove mpi4py
```

or ask **pip** to disable the cache:

```
$ python -m pip install --no-cache-dir mpi4py
```

## 11.3 Using distutils

The *MPI for Python* package is available for download at the project website generously hosted by GitHub. You can use **curl** or **wget** to get a release tarball.

- Using **curl**:

```
$ curl -O https://github.com/mpi4py/mpi4py/releases/download/X.Y.Z/mpi4py-X.Y.Z.tar.  
↪ gz
```

- Using **wget**:

```
$ wget https://github.com/mpi4py/mpi4py/releases/download/X.Y.Z/mpi4py-X.Y.Z.tar.gz
```

After unpacking the release tarball:

```
$ tar -zxf mpi4py-X.Y.Z.tar.gz  
$ cd mpi4py-X.Y.Z
```

the package is ready for building.

*MPI for Python* uses a standard distutils-based build system. However, some distutils commands (like *build*) have additional options:

**--mpicc=**

Lets you specify a special location or name for the **mpicc** compiler wrapper.

**--mpi=**

Lets you pass a section with MPI configuration within a special configuration file.

**--configure**

Runs exhaustive tests for checking about missing MPI types, constants, and functions. This option should be passed in order to build *MPI for Python* against old MPI-1 or MPI-2 implementations, possibly providing a subset of MPI-3.

If you use a MPI implementation providing a **mpicc** compiler wrapper (e.g., MPICH, Open MPI), it will be used for compilation and linking. This is the preferred and easiest way of building *MPI for Python*.

If **mpicc** is located somewhere in your search path, simply run the *build* command:

```
$ python setup.py build
```

If **mpicc** is not in your search path or the compiler wrapper has a different name, you can run the *build* command specifying its location:

```
$ python setup.py build --mpicc=/where/you/have/mpicc
```

Alternatively, you can provide all the relevant information about your MPI implementation by editing the file called *mpi.cfg*. You can use the default section *[mpi]* or add a new, custom section, for example *[other\_mpi]* (see the examples provided in the *mpi.cfg* file as a starting point to write your own section):

```
[mpi]

include_dirs      = /usr/local/mpi/include
libraries         = mpi
library_dirs      = /usr/local/mpi/lib
runtime_library_dirs = /usr/local/mpi/lib

[other_mpi]

include_dirs      = /opt/mpi/include ...
libraries         = mpi ...
library_dirs      = /opt/mpi/lib ...
runtime_library_dirs = /op/mpi/lib ...

...
```

and then run the *build* command, perhaps specifying you custom configuration section:

```
$ python setup.py build --mpi=other_mpi
```

After building, the package is ready for install.

If you have root privileges (either by log-in as the root user or by using **sudo**) and you want to install *MPI for Python* in your system for all users, just do:

```
$ python setup.py install
```

The previous steps will install the *mpi4py* package at standard location *prefix/lib/pythonX.X/site-packages*.

If you do not have root privileges or you want to install *MPI for Python* for your private use, just do:

```
$ python setup.py install --user
```

## 11.4 Testing

To quickly test the installation:

```
$ mpiexec -n 5 python -m mpi4py.bench helloworld
Hello, World! I am process 0 of 5 on localhost.
Hello, World! I am process 1 of 5 on localhost.
Hello, World! I am process 2 of 5 on localhost.
Hello, World! I am process 3 of 5 on localhost.
Hello, World! I am process 4 of 5 on localhost.
```

If you installed from source, issuing at the command line:

```
$ mpiexec -n 5 python demo/helloworld.py
```

or (in the case of ancient MPI-1 implementations):

```
$ mpirun -np 5 python `pwd`/demo/helloworld.py
```

will launch a five-process run of the Python interpreter and run the test script *demo/helloworld.py* from the source distribution.

You can also run all the *unittest* scripts:

```
$ mpiexec -n 5 python test/runtests.py
```

or, if you have *nose* unit testing framework installed:

```
$ mpiexec -n 5 nosetests -w test
```

or, if you have *py.test* unit testing framework installed:

```
$ mpiexec -n 5 py.test test/
```

## 12 Appendix

### 12.1 MPI-enabled Python interpreter

**Warning:** These days it is no longer required to use the MPI-enabled Python interpreter in most cases, and, therefore, it is not built by default anymore because it is too difficult to reliably build a Python interpreter across different distributions. If you know that you still **really** need it, see below on how to use the `build_exe` and `install_exe` commands.

Some MPI-1 implementations (notably, MPICH 1) **do require** the actual command line arguments to be passed at the time `MPI_Init()` is called. In this case, you will need to use a re-built, MPI-enabled, Python interpreter binary executable. A basic implementation (targeting Python 2.X) of what is required is shown below:

```
#include <Python.h>
#include <mpi.h>

int main(int argc, char *argv[])
{
    int status, flag;
    MPI_Init(&argc, &argv);
    status = Py_Main(argc, argv);
    MPI_Finalized(&flag);
    if (!flag) MPI_Finalize();
    return status;
}
```

The source code above is straightforward; compiling it should also be. However, the linking step is more tricky: special flags have to be passed to the linker depending on your platform. In order to alleviate you for such low-level details, *MPI for Python* provides some pure-distutils based support to build and install an MPI-enabled Python interpreter executable:

```
$ cd mpi4py-X.X.X
$ python setup.py build_exe [--mpi=<name>|--mpicc=/path/to/mpicc]
$ [sudo] python setup.py install_exe [--install-dir=$HOME/bin]
```

After the above steps you should have the MPI-enabled interpreter installed as *prefix/bin/pythonX.X-mpi* (or *\$HOME/bin/pythonX.X-mpi*). Assuming that *prefix/bin* (or *\$HOME/bin*) is listed on your *PATH*, you should be able to enter your MPI-enabled Python interactively, for example:

```
$ python2.7-mpi
Python 2.7.8 (default, Nov 10 2014, 08:19:18)
[GCC 4.9.2 20141101 (Red Hat 4.9.2-1)] on linux2
Type "help", "copyright", "credits" or "license" for more information.
>>> import sys
>>> sys.executable
'/usr/bin/python2.7-mpi'
>>>
```

## 12.2 Building MPI from sources

In the list below you have some executive instructions for building some of the open-source MPI implementations out there with support for shared/dynamic libraries on POSIX environments.

- *MPICH*

```
$ tar -zxf mpich-X.X.X.tar.gz
$ cd mpich-X.X.X
$ ./configure --enable-shared --prefix=/usr/local/mpich
$ make
$ make install
```

- *Open MPI*

```
$ tar -zxf openmpi-X.X.X tar.gz
$ cd openmpi-X.X.X
$ ./configure --prefix=/usr/local/openmpi
$ make all
$ make install
```

- *MPICH 1*

```
$ tar -zxf mpich-X.X.X.tar.gz
$ cd mpich-X.X.X
$ ./configure --enable-sharedlib --prefix=/usr/local/mpich1
$ make
$ make install
```

Perhaps you will need to set the `LD_LIBRARY_PATH` environment variable (using **export**, **setenv** or what applies to your system) pointing to the directory containing the MPI libraries . In case of getting runtime linking errors when running MPI programs, the following lines can be added to the user login shell script (`.profile`, `.bashrc`, etc.).

- *MPICH*

```
MPI_DIR=/usr/local/mpich
export LD_LIBRARY_PATH=$MPI_DIR/lib:$LD_LIBRARY_PATH
```

- *Open MPI*

```
MPI_DIR=/usr/local/openmpi
export LD_LIBRARY_PATH=$MPI_DIR/lib:$LD_LIBRARY_PATH
```

- *MPICH 1*

```
MPI_DIR=/usr/local/mpich1
export LD_LIBRARY_PATH=$MPI_DIR/lib/shared:$LD_LIBRARY_PATH:
export MPICH_USE_SHLIB=yes
```

**Warning:** MPICH 1 support for dynamic libraries is not completely transparent. Users should set the environment variable `MPICH_USE_SHLIB` to `yes` in order to avoid link problems when using the **mpicc** compiler wrapper.

## References

- [mpi-std1] MPI Forum. MPI: A Message Passing Interface Standard. International Journal of Supercomputer Applications, volume 8, number 3-4, pages 159-416, 1994.
- [mpi-std2] MPI Forum. MPI: A Message Passing Interface Standard. High Performance Computing Applications, volume 12, number 1-2, pages 1-299, 1998.
- [mpi-using] William Gropp, Ewing Lusk, and Anthony Skjellum. Using MPI: portable parallel programming with the message-passing interface. MIT Press, 1994.
- [mpi-ref] Mark Snir, Steve Otto, Steven Huss-Lederman, David Walker, and Jack Dongarra. MPI - The Complete Reference, volume 1, The MPI Core. MIT Press, 2nd. edition, 1998.

- [mpi-mpich] W. Gropp, E. Lusk, N. Doss, and A. Skjellum. A high-performance, portable implementation of the MPI message passing interface standard. *Parallel Computing*, 22(6):789-828, September 1996.
- [mpi-openmpi] Edgar Gabriel, Graham E. Fagg, George Bosilca, Thara Angskun, Jack J. Dongarra, Jeffrey M. Squyres, Vishal Sahay, Prabhanjan Kambadur, Brian Barrett, Andrew Lumsdaine, Ralph H. Castain, David J. Daniel, Richard L. Graham, and Timothy S. Woodall. Open MPI: Goals, Concept, and Design of a Next Generation MPI Implementation. In *Proceedings, 11th European PVM/MPI Users' Group Meeting*, Budapest, Hungary, September 2004.
- [Hinsen97] Konrad Hinsen. The Molecular Modelling Toolkit: a case study of a large scientific application in Python. In *Proceedings of the 6th International Python Conference*, pages 29-35, San Jose, Ca., October 1997.
- [Beazley97] David M. Beazley and Peter S. Lomdahl. Feeding a large-scale physics application to Python. In *Proceedings of the 6th International Python Conference*, pages 21-29, San Jose, Ca., October 1997.

## Python Module Index

### m

- `mpi4py`, [20](#)
- `mpi4py.futures`, [34](#)
- `mpi4py.MPI`, [48](#)
- `mpi4py.run`, [47](#)
- `mpi4py.util`, [40](#)
- `mpi4py.util.dtlb`, [46](#)
- `mpi4py.util.pkl5`, [40](#)



## Index

### Symbols

`__init__()` (*mpi4py.MPI.Pickle* method), 120  
`__new__()` (*mpi4py.MPI.Cartcomm* static method), 49  
`__new__()` (*mpi4py.MPI.Comm* static method), 51  
`__new__()` (*mpi4py.MPI.Datatype* static method), 75  
`__new__()` (*mpi4py.MPI.Distgraphcomm* static method), 85  
`__new__()` (*mpi4py.MPI.Errhandler* static method), 85  
`__new__()` (*mpi4py.MPI.Exception* static method), 146  
`__new__()` (*mpi4py.MPI.File* static method), 86  
`__new__()` (*mpi4py.MPI.Graphcomm* static method), 98  
`__new__()` (*mpi4py.MPI.Grequest* static method), 100  
`__new__()` (*mpi4py.MPI.Group* static method), 101  
`__new__()` (*mpi4py.MPI.Info* static method), 105  
`__new__()` (*mpi4py.MPI.Intercomm* static method), 109  
`__new__()` (*mpi4py.MPI.Intracomm* static method), 110  
`__new__()` (*mpi4py.MPI.Message* static method), 115  
`__new__()` (*mpi4py.MPI.Op* static method), 118  
`__new__()` (*mpi4py.MPI.Prerequest* static method), 121  
`__new__()` (*mpi4py.MPI.Request* static method), 122  
`__new__()` (*mpi4py.MPI.Status* static method), 126  
`__new__()` (*mpi4py.MPI.Topocomm* static method), 129  
`__new__()` (*mpi4py.MPI.Win* static method), 133  
`__new__()` (*mpi4py.MPI.memory* static method), 143  
`--configure`  
    command line option, 199  
`--mpi`  
    command line option, 199  
`--mpicc`  
    command line option, 199  
`-c`  
    command line option, 48  
`-m`  
    command line option, 48

### A

`Abort()` (*mpi4py.MPI.Comm* method), 55  
`Accept()` (*mpi4py.MPI.Intracomm* method), 111  
`Accumulate()` (*mpi4py.MPI.Win* method), 135  
`Add_error_class()` (in module *mpi4py.MPI*), 148  
`Add_error_code()` (in module *mpi4py.MPI*), 148  
`Add_error_string()` (in module *mpi4py.MPI*), 148  
`address` (*mpi4py.MPI.memory* attribute), 145  
`AINT` (in module *mpi4py.MPI*), 181  
`Aint_add()` (in module *mpi4py.MPI*), 148  
`Aint_diff()` (in module *mpi4py.MPI*), 149  
`Allgather()` (*mpi4py.MPI.Comm* method), 55  
`allgather()` (*mpi4py.MPI.Comm* method), 70  
`Allgatherv()` (*mpi4py.MPI.Comm* method), 55  
`Alloc_mem()` (in module *mpi4py.MPI*), 149

`allocate()` (*mpi4py.MPI.memory* static method), 144  
`Allocate()` (*mpi4py.MPI.Win* class method), 135  
`Allocate_shared()` (*mpi4py.MPI.Win* class method), 135  
`Allreduce()` (*mpi4py.MPI.Comm* method), 55  
`allreduce()` (*mpi4py.MPI.Comm* method), 70  
`Alltoall()` (*mpi4py.MPI.Comm* method), 55  
`alltoall()` (*mpi4py.MPI.Comm* method), 70  
`Alltoallv()` (*mpi4py.MPI.Comm* method), 56  
`Alltoallw()` (*mpi4py.MPI.Comm* method), 56  
`amode` (*mpi4py.MPI.File* attribute), 98  
`ANY_SOURCE` (in module *mpi4py.MPI*), 161  
`ANY_TAG` (in module *mpi4py.MPI*), 161  
`APPNUM` (in module *mpi4py.MPI*), 162  
`atomicity` (*mpi4py.MPI.File* attribute), 98  
`Attach()` (*mpi4py.MPI.Win* method), 136  
`Attach_buffer()` (in module *mpi4py.MPI*), 149  
`attrs` (*mpi4py.MPI.Win* attribute), 143

### B

`BAND` (in module *mpi4py.MPI*), 193  
`Barrier()` (*mpi4py.MPI.Comm* method), 56  
`barrier()` (*mpi4py.MPI.Comm* method), 71  
`Bcast()` (*mpi4py.MPI.Comm* method), 56  
`bcast()` (*mpi4py.MPI.Comm* method), 71  
`bcast()` (*mpi4py.util.pkl5.Comm* method), 45  
`BOOL` (in module *mpi4py.MPI*), 190  
`bootup()` (*mpi4py.futures.MPIPoolExecutor* method), 36  
`BOR` (in module *mpi4py.MPI*), 194  
`BOTTOM` (in module *mpi4py.MPI*), 161  
`Bsend()` (*mpi4py.MPI.Comm* method), 56  
`bsend()` (*mpi4py.MPI.Comm* method), 71  
`bsend()` (*mpi4py.util.pkl5.Comm* method), 42  
`Bsend_init()` (*mpi4py.MPI.Comm* method), 56  
`BSEND_OVERHEAD` (in module *mpi4py.MPI*), 175  
`BXOR` (in module *mpi4py.MPI*), 194  
`BYTE` (in module *mpi4py.MPI*), 181

### C

`C_BOOL` (in module *mpi4py.MPI*), 183  
`C_COMPLEX` (in module *mpi4py.MPI*), 184  
`C_DOUBLE_COMPLEX` (in module *mpi4py.MPI*), 184  
`C_FLOAT_COMPLEX` (in module *mpi4py.MPI*), 184  
`C_LONG_DOUBLE_COMPLEX` (in module *mpi4py.MPI*), 185  
`Call_errhandler()` (*mpi4py.MPI.Comm* method), 57  
`Call_errhandler()` (*mpi4py.MPI.File* method), 88  
`Call_errhandler()` (*mpi4py.MPI.Win* method), 136  
`Cancel()` (*mpi4py.MPI.Request* method), 123  
`cancel()` (*mpi4py.MPI.Request* method), 124  
`cancel()` (*mpi4py.util.pkl5.Request* method), 41

cancelled (*mpi4py.MPI.Status* attribute), 129  
 CART (in module *mpi4py.MPI*), 174  
 Cart\_map() (*mpi4py.MPI.Intracomm* method), 111  
 Cartcomm (class in *mpi4py.MPI*), 49  
 CHAR (in module *mpi4py.MPI*), 181  
 CHARACTER (in module *mpi4py.MPI*), 186  
 clear() (*mpi4py.MPI.Info* method), 107  
 Clone() (*mpi4py.MPI.Comm* method), 57  
 Close() (*mpi4py.MPI.File* method), 88  
 Close\_port() (in module *mpi4py.MPI*), 149  
 combiner (*mpi4py.MPI.Datatype* attribute), 84  
 COMBINER\_CONTIGUOUS (in module *mpi4py.MPI*), 172  
 COMBINER\_DARRAY (in module *mpi4py.MPI*), 173  
 COMBINER\_DUP (in module *mpi4py.MPI*), 172  
 COMBINER\_F90\_COMPLEX (in module *mpi4py.MPI*), 173  
 COMBINER\_F90\_INTEGER (in module *mpi4py.MPI*), 174  
 COMBINER\_F90\_REAL (in module *mpi4py.MPI*), 173  
 COMBINER\_HINDEXED (in module *mpi4py.MPI*), 172  
 COMBINER\_HINDEXED\_BLOCK (in module *mpi4py.MPI*), 173  
 COMBINER\_HVECTOR (in module *mpi4py.MPI*), 172  
 COMBINER\_INDEXED (in module *mpi4py.MPI*), 172  
 COMBINER\_INDEXED\_BLOCK (in module *mpi4py.MPI*), 173  
 COMBINER\_NAMED (in module *mpi4py.MPI*), 172  
 COMBINER\_RESIZED (in module *mpi4py.MPI*), 173  
 COMBINER\_STRUCT (in module *mpi4py.MPI*), 173  
 COMBINER\_SUBARRAY (in module *mpi4py.MPI*), 173  
 COMBINER\_VECTOR (in module *mpi4py.MPI*), 172  
 Comm (class in *mpi4py.MPI*), 51  
 Comm (class in *mpi4py.util.pkl5*), 42  
 COMM\_NULL (in module *mpi4py.MPI*), 196  
 COMM\_SELF (in module *mpi4py.MPI*), 196  
 COMM\_TYPE\_SHARED (in module *mpi4py.MPI*), 175  
 COMM\_WORLD (in module *mpi4py.MPI*), 197  
 command line option  
     --configure, 199  
     --mpi, 199  
     --mpicc, 199  
     -c, 48  
     -m, 48  
 Commit() (*mpi4py.MPI.Datatype* method), 77  
 Compare() (*mpi4py.MPI.Comm* class method), 57  
 Compare() (*mpi4py.MPI.Group* class method), 102  
 Compare\_and\_swap() (*mpi4py.MPI.Win* method), 136  
 Complete() (*mpi4py.MPI.Grequest* method), 101  
 Complete() (*mpi4py.MPI.Win* method), 136  
 COMPLEX (in module *mpi4py.MPI*), 187  
 COMPLEX16 (in module *mpi4py.MPI*), 189  
 COMPLEX32 (in module *mpi4py.MPI*), 189  
 COMPLEX4 (in module *mpi4py.MPI*), 189  
 COMPLEX8 (in module *mpi4py.MPI*), 189  
 Compute\_dims() (in module *mpi4py.MPI*), 150  
 CONGRUENT (in module *mpi4py.MPI*), 174  
 Connect() (*mpi4py.MPI.Intracomm* method), 111  
 contents (*mpi4py.MPI.Datatype* attribute), 84  
 coords (*mpi4py.MPI.Cartcomm* attribute), 51  
 copy() (*mpi4py.MPI.Info* method), 107  
 COUNT (in module *mpi4py.MPI*), 181  
 count (*mpi4py.MPI.Status* attribute), 129  
 Create() (*mpi4py.MPI.Comm* method), 57  
 Create() (*mpi4py.MPI.Info* class method), 106  
 Create() (*mpi4py.MPI.Op* class method), 119  
 Create() (*mpi4py.MPI.Win* class method), 136  
 Create\_cart() (*mpi4py.MPI.Intracomm* method), 112  
 Create\_contiguous() (*mpi4py.MPI.Datatype* method), 77  
 Create\_darray() (*mpi4py.MPI.Datatype* method), 78  
 Create\_dist\_graph() (*mpi4py.MPI.Intracomm* method), 112  
 Create\_dist\_graph\_adjacent() (*mpi4py.MPI.Intracomm* method), 112  
 Create\_dynamic() (*mpi4py.MPI.Win* class method), 136  
 Create\_f90\_complex() (*mpi4py.MPI.Datatype* class method), 78  
 Create\_f90\_integer() (*mpi4py.MPI.Datatype* class method), 78  
 Create\_f90\_real() (*mpi4py.MPI.Datatype* class method), 78  
 Create\_graph() (*mpi4py.MPI.Intracomm* method), 112  
 Create\_group() (*mpi4py.MPI.Comm* method), 57  
 Create\_hindexed() (*mpi4py.MPI.Datatype* method), 78  
 Create\_hindexed\_block() (*mpi4py.MPI.Datatype* method), 79  
 Create\_hvector() (*mpi4py.MPI.Datatype* method), 79  
 Create\_indexed() (*mpi4py.MPI.Datatype* method), 79  
 Create\_indexed\_block() (*mpi4py.MPI.Datatype* method), 79  
 Create\_intercomm() (*mpi4py.MPI.Intracomm* method), 113  
 Create\_keyval() (*mpi4py.MPI.Comm* class method), 57  
 Create\_keyval() (*mpi4py.MPI.Datatype* class method), 79  
 Create\_keyval() (*mpi4py.MPI.Win* class method), 137  
 Create\_resized() (*mpi4py.MPI.Datatype* method), 79  
 Create\_struct() (*mpi4py.MPI.Datatype* class method), 80  
 Create\_subarray() (*mpi4py.MPI.Datatype* method), 80  
 Create\_vector() (*mpi4py.MPI.Datatype* method), 80  
 CXX\_BOOL (in module *mpi4py.MPI*), 185  
 CXX\_DOUBLE\_COMPLEX (in module *mpi4py.MPI*), 185  
 CXX\_FLOAT\_COMPLEX (in module *mpi4py.MPI*), 185  
 CXX\_LONG\_DOUBLE\_COMPLEX (in module *mpi4py.MPI*), 185

## D

Datatype (class in *mpi4py.MPI*), 75  
DATATYPE\_NULL (in module *mpi4py.MPI*), 180  
decode() (*mpi4py.MPI.Datatype* method), 83  
degrees (*mpi4py.MPI.Topocomm* attribute), 133  
Delete() (*mpi4py.MPI.File* class method), 89  
Delete() (*mpi4py.MPI.Info* method), 106  
Delete\_attr() (*mpi4py.MPI.Comm* method), 58  
Delete\_attr() (*mpi4py.MPI.Datatype* method), 80  
Delete\_attr() (*mpi4py.MPI.Win* method), 137  
Detach() (*mpi4py.MPI.Win* method), 137  
Detach\_buffer() (in module *mpi4py.MPI*), 150  
Difference() (*mpi4py.MPI.Group* class method), 102  
dim (*mpi4py.MPI.Cartcomm* attribute), 51  
dims (*mpi4py.MPI.Cartcomm* attribute), 51  
dims (*mpi4py.MPI.Graphcomm* attribute), 100  
Disconnect() (*mpi4py.MPI.Comm* method), 58  
DISP\_CUR (in module *mpi4py.MPI*), 178  
DISPLACEMENT\_CURRENT (in module *mpi4py.MPI*), 178  
DIST\_GRAPH (in module *mpi4py.MPI*), 174  
Distgraphcomm (class in *mpi4py.MPI*), 85  
DISTRIBUTE\_BLOCK (in module *mpi4py.MPI*), 171  
DISTRIBUTE\_CYCLIC (in module *mpi4py.MPI*), 171  
DISTRIBUTE\_DFLT\_DARG (in module *mpi4py.MPI*), 172  
DISTRIBUTE\_NONE (in module *mpi4py.MPI*), 171  
DOUBLE (in module *mpi4py.MPI*), 183  
DOUBLE\_COMPLEX (in module *mpi4py.MPI*), 187  
DOUBLE\_INT (in module *mpi4py.MPI*), 186  
DOUBLE\_PRECISION (in module *mpi4py.MPI*), 187  
dumps() (*mpi4py.MPI.Pickle* method), 120  
Dup() (*mpi4py.MPI.Comm* method), 58  
Dup() (*mpi4py.MPI.Datatype* method), 80  
Dup() (*mpi4py.MPI.Group* method), 103  
Dup() (*mpi4py.MPI.Info* method), 106  
Dup\_with\_info() (*mpi4py.MPI.Comm* method), 58

## E

edges (*mpi4py.MPI.Graphcomm* attribute), 100  
envelope (*mpi4py.MPI.Datatype* attribute), 84  
environment variable  
LD\_LIBRARY\_PATH, 202  
MPI4PY\_FUTURES\_MAX\_WORKERS, 35, 36, 40  
MPI4PY\_PICKLE\_PROTOCOL, 11, 24  
MPI4PY\_PICKLE\_THRESHOLD, 24  
MPI4PY\_RC\_ERRORS, 22, 24  
MPI4PY\_RC\_FAST\_REDUCE, 21, 23  
MPI4PY\_RC\_FINALIZE, 21, 22  
MPI4PY\_RC\_INITIALIZE, 20, 22  
MPI4PY\_RC\_RECV\_MPROBE, 21, 23  
MPI4PY\_RC\_THREAD\_LEVEL, 21, 23  
MPI4PY\_RC\_THREADS, 21, 23  
MPICC, 198  
MPICH\_USE\_SHLIB, 202

MPIEXEC\_UNIVERSE\_SIZE, 39  
PATH, 201

ERR\_ACCESS (in module *mpi4py.MPI*), 167  
ERR\_AMODE (in module *mpi4py.MPI*), 167  
ERR\_ARG (in module *mpi4py.MPI*), 165  
ERR\_ASSERT (in module *mpi4py.MPI*), 169  
ERR\_BAD\_FILE (in module *mpi4py.MPI*), 167  
ERR\_BASE (in module *mpi4py.MPI*), 169  
ERR\_BUFFER (in module *mpi4py.MPI*), 164  
ERR\_COMM (in module *mpi4py.MPI*), 163  
ERR\_CONVERSION (in module *mpi4py.MPI*), 168  
ERR\_COUNT (in module *mpi4py.MPI*), 164  
ERR\_DIMS (in module *mpi4py.MPI*), 165  
ERR\_DISP (in module *mpi4py.MPI*), 169  
ERR\_DUP\_DATAREP (in module *mpi4py.MPI*), 168  
ERR\_FILE (in module *mpi4py.MPI*), 166  
ERR\_FILE\_EXISTS (in module *mpi4py.MPI*), 167  
ERR\_FILE\_IN\_USE (in module *mpi4py.MPI*), 167  
ERR\_GROUP (in module *mpi4py.MPI*), 163  
ERR\_IN\_STATUS (in module *mpi4py.MPI*), 165  
ERR\_INFO (in module *mpi4py.MPI*), 166  
ERR\_INFO\_KEY (in module *mpi4py.MPI*), 166  
ERR\_INFO\_NOKEY (in module *mpi4py.MPI*), 166  
ERR\_INFO\_VALUE (in module *mpi4py.MPI*), 166  
ERR\_INTERN (in module *mpi4py.MPI*), 166  
ERR\_IO (in module *mpi4py.MPI*), 167  
ERR\_KEYVAL (in module *mpi4py.MPI*), 166  
ERR\_LASTCODE (in module *mpi4py.MPI*), 163  
ERR\_LOCKTYPE (in module *mpi4py.MPI*), 170  
ERR\_NAME (in module *mpi4py.MPI*), 168  
ERR\_NO\_MEM (in module *mpi4py.MPI*), 168  
ERR\_NO\_SPACE (in module *mpi4py.MPI*), 167  
ERR\_NO\_SUCH\_FILE (in module *mpi4py.MPI*), 167  
ERR\_NOT\_SAME (in module *mpi4py.MPI*), 168  
ERR\_OP (in module *mpi4py.MPI*), 164  
ERR\_OTHER (in module *mpi4py.MPI*), 165  
ERR\_PENDING (in module *mpi4py.MPI*), 165  
ERR\_PORT (in module *mpi4py.MPI*), 169  
ERR\_QUOTA (in module *mpi4py.MPI*), 169  
ERR\_RANK (in module *mpi4py.MPI*), 164  
ERR\_READ\_ONLY (in module *mpi4py.MPI*), 168  
ERR\_REQUEST (in module *mpi4py.MPI*), 164  
ERR\_RMA\_ATTACH (in module *mpi4py.MPI*), 170  
ERR\_RMA\_CONFLICT (in module *mpi4py.MPI*), 170  
ERR\_RMA\_FLAVOR (in module *mpi4py.MPI*), 170  
ERR\_RMA\_RANGE (in module *mpi4py.MPI*), 170  
ERR\_RMA\_SHARED (in module *mpi4py.MPI*), 170  
ERR\_RMA\_SYNC (in module *mpi4py.MPI*), 170  
ERR\_ROOT (in module *mpi4py.MPI*), 164  
ERR\_SERVICE (in module *mpi4py.MPI*), 169  
ERR\_SIZE (in module *mpi4py.MPI*), 169  
ERR\_SPAWN (in module *mpi4py.MPI*), 169  
ERR\_TAG (in module *mpi4py.MPI*), 164  
ERR\_TOPOLOGY (in module *mpi4py.MPI*), 165



ERR\_TRUNCATE (in module *mpi4py.MPI*), 165  
 ERR\_TYPE (in module *mpi4py.MPI*), 164  
 ERR\_UNKNOWN (in module *mpi4py.MPI*), 165  
 ERR\_UNSUPPORTED\_DATAREP (in module *mpi4py.MPI*), 168  
 ERR\_UNSUPPORTED\_OPERATION (in module *mpi4py.MPI*), 168  
 ERR\_WIN (in module *mpi4py.MPI*), 166  
 Errhandler (class in *mpi4py.MPI*), 85  
 ERRHANDLER\_NULL (in module *mpi4py.MPI*), 196  
 error (*mpi4py.MPI.Status* attribute), 129  
 error\_class (*mpi4py.MPI.Exception* attribute), 147  
 error\_code (*mpi4py.MPI.Exception* attribute), 147  
 error\_string (*mpi4py.MPI.Exception* attribute), 147  
 errors (*mpi4py.mpi4py.rc* attribute), 21  
 ERRORS\_ARE\_FATAL (in module *mpi4py.MPI*), 196  
 ERRORS\_RETURN (in module *mpi4py.MPI*), 196  
 Exception, 146  
 Excl() (*mpi4py.MPI.Group* method), 103  
 Exscan() (*mpi4py.MPI.Intracomm* method), 113  
 exscan() (*mpi4py.MPI.Intracomm* method), 114  
 extent (*mpi4py.MPI.Datatype* attribute), 84

## F

f2py() (*mpi4py.MPI.Comm* class method), 71  
 f2py() (*mpi4py.MPI.Datatype* class method), 84  
 f2py() (*mpi4py.MPI.Errhandler* class method), 86  
 f2py() (*mpi4py.MPI.File* class method), 97  
 f2py() (*mpi4py.MPI.Group* class method), 104  
 f2py() (*mpi4py.MPI.Info* class method), 107  
 f2py() (*mpi4py.MPI.Message* class method), 117  
 f2py() (*mpi4py.MPI.Op* class method), 119  
 f2py() (*mpi4py.MPI.Request* class method), 124  
 f2py() (*mpi4py.MPI.Status* class method), 129  
 f2py() (*mpi4py.MPI.Win* class method), 142  
 F\_BOOL (in module *mpi4py.MPI*), 190  
 F\_COMPLEX (in module *mpi4py.MPI*), 191  
 F\_DOUBLE (in module *mpi4py.MPI*), 191  
 F\_DOUBLE\_COMPLEX (in module *mpi4py.MPI*), 191  
 F\_FLOAT (in module *mpi4py.MPI*), 191  
 F\_FLOAT\_COMPLEX (in module *mpi4py.MPI*), 191  
 F\_INT (in module *mpi4py.MPI*), 190  
 fast\_reduce (*mpi4py.mpi4py.rc* attribute), 21  
 Fence() (*mpi4py.MPI.Win* method), 137  
 Fetch\_and\_op() (*mpi4py.MPI.Win* method), 137  
 File (class in *mpi4py.MPI*), 86  
 FILE\_NULL (in module *mpi4py.MPI*), 197  
 finalize (*mpi4py.mpi4py.rc* attribute), 21  
 Finalize() (in module *mpi4py.MPI*), 150  
 flavor (*mpi4py.MPI.Win* attribute), 143  
 FLOAT (in module *mpi4py.MPI*), 183  
 FLOAT\_INT (in module *mpi4py.MPI*), 186  
 Flush() (*mpi4py.MPI.Win* method), 138  
 Flush\_all() (*mpi4py.MPI.Win* method), 138

Flush\_local() (*mpi4py.MPI.Win* method), 138  
 Flush\_local\_all() (*mpi4py.MPI.Win* method), 138  
 format (*mpi4py.MPI.memory* attribute), 145  
 Free() (*mpi4py.MPI.Comm* method), 58  
 Free() (*mpi4py.MPI.Datatype* method), 81  
 Free() (*mpi4py.MPI.Errhandler* method), 86  
 Free() (*mpi4py.MPI.Group* method), 103  
 Free() (*mpi4py.MPI.Info* method), 106  
 Free() (*mpi4py.MPI.Op* method), 119  
 Free() (*mpi4py.MPI.Request* method), 123  
 Free() (*mpi4py.MPI.Win* method), 138  
 Free() (*mpi4py.util.pkl5.Request* method), 41  
 Free\_keyval() (*mpi4py.MPI.Comm* class method), 58  
 Free\_keyval() (*mpi4py.MPI.Datatype* class method), 81  
 Free\_keyval() (*mpi4py.MPI.Win* class method), 138  
 Free\_mem() (in module *mpi4py.MPI*), 150  
 from\_numpy\_dtype() (in module *mpi4py.util.dtlb*), 46  
 fromaddress() (*mpi4py.MPI.memory* static method), 144  
 frombuffer() (*mpi4py.MPI.memory* static method), 144

## G

Gather() (*mpi4py.MPI.Comm* method), 58  
 gather() (*mpi4py.MPI.Comm* method), 71  
 Gatherv() (*mpi4py.MPI.Comm* method), 59  
 Get() (*mpi4py.MPI.Info* method), 107  
 get() (*mpi4py.MPI.Info* method), 107  
 Get() (*mpi4py.MPI.Win* method), 138  
 Get\_accumulate() (*mpi4py.MPI.Win* method), 138  
 Get\_address() (in module *mpi4py.MPI*), 150  
 Get\_amode() (*mpi4py.MPI.File* method), 89  
 Get\_atomicity() (*mpi4py.MPI.File* method), 89  
 Get\_attr() (*mpi4py.MPI.Comm* method), 59  
 Get\_attr() (*mpi4py.MPI.Datatype* method), 81  
 Get\_attr() (*mpi4py.MPI.Win* method), 139  
 Get\_byte\_offset() (*mpi4py.MPI.File* method), 89  
 Get\_cart\_rank() (*mpi4py.MPI.Cartcomm* method), 50  
 get\_config() (in module *mpi4py*), 25  
 Get\_contents() (*mpi4py.MPI.Datatype* method), 81  
 Get\_coords() (*mpi4py.MPI.Cartcomm* method), 50  
 Get\_count() (*mpi4py.MPI.Status* method), 127  
 Get\_dim() (*mpi4py.MPI.Cartcomm* method), 50  
 Get\_dims() (*mpi4py.MPI.Graphcomm* method), 99  
 Get\_dist\_neighbors() (*mpi4py.MPI.Distgraphcomm* method), 85  
 Get\_dist\_neighbors\_count() (*mpi4py.MPI.Distgraphcomm* method), 85  
 Get\_elements() (*mpi4py.MPI.Status* method), 127  
 Get\_envelope() (*mpi4py.MPI.Datatype* method), 81  
 Get\_errhandler() (*mpi4py.MPI.Comm* method), 59  
 Get\_errhandler() (*mpi4py.MPI.File* method), 89  
 Get\_errhandler() (*mpi4py.MPI.Win* method), 139  
 Get\_error() (*mpi4py.MPI.Status* method), 127

Get\_error\_class() (in module *mpi4py.MPI*), 151  
 Get\_error\_class() (*mpi4py.MPI.Exception* method), 146  
 Get\_error\_code() (*mpi4py.MPI.Exception* method), 146  
 Get\_error\_string() (in module *mpi4py.MPI*), 151  
 Get\_error\_string() (*mpi4py.MPI.Exception* method), 146  
 Get\_extent() (*mpi4py.MPI.Datatype* method), 81  
 Get\_group() (*mpi4py.MPI.Comm* method), 59  
 Get\_group() (*mpi4py.MPI.File* method), 89  
 Get\_group() (*mpi4py.MPI.Win* method), 139  
 get\_include() (in module *mpi4py*), 25  
 Get\_info() (*mpi4py.MPI.Comm* method), 59  
 Get\_info() (*mpi4py.MPI.File* method), 89  
 Get\_info() (*mpi4py.MPI.Win* method), 139  
 Get\_library\_version() (in module *mpi4py.MPI*), 151  
 Get\_name() (*mpi4py.MPI.Comm* method), 59  
 Get\_name() (*mpi4py.MPI.Datatype* method), 81  
 Get\_name() (*mpi4py.MPI.Win* method), 139  
 Get\_neighbors() (*mpi4py.MPI.Graphcomm* method), 99  
 Get\_neighbors\_count() (*mpi4py.MPI.Graphcomm* method), 99  
 Get\_nkeys() (*mpi4py.MPI.Info* method), 107  
 Get\_nthkey() (*mpi4py.MPI.Info* method), 107  
 Get\_parent() (*mpi4py.MPI.Comm* class method), 59  
 Get\_position() (*mpi4py.MPI.File* method), 89  
 Get\_position\_shared() (*mpi4py.MPI.File* method), 89  
 Get\_processor\_name() (in module *mpi4py.MPI*), 151  
 Get\_rank() (*mpi4py.MPI.Comm* method), 59  
 Get\_rank() (*mpi4py.MPI.Group* method), 103  
 Get\_remote\_group() (*mpi4py.MPI.Intercomm* method), 109  
 Get\_remote\_size() (*mpi4py.MPI.Intercomm* method), 109  
 Get\_size() (*mpi4py.MPI.Comm* method), 59  
 Get\_size() (*mpi4py.MPI.Datatype* method), 81  
 Get\_size() (*mpi4py.MPI.File* method), 90  
 Get\_size() (*mpi4py.MPI.Group* method), 103  
 Get\_source() (*mpi4py.MPI.Status* method), 128  
 Get\_status() (*mpi4py.MPI.Request* method), 123  
 get\_status() (*mpi4py.MPI.Request* method), 124  
 get\_status() (*mpi4py.util.pkl5.Request* method), 41  
 Get\_tag() (*mpi4py.MPI.Status* method), 128  
 Get\_topo() (*mpi4py.MPI.Cartcomm* method), 50  
 Get\_topo() (*mpi4py.MPI.Graphcomm* method), 99  
 Get\_topology() (*mpi4py.MPI.Comm* method), 60  
 Get\_true\_extent() (*mpi4py.MPI.Datatype* method), 81  
 Get\_type\_extent() (*mpi4py.MPI.File* method), 90  
 get\_vendor() (in module *mpi4py.MPI*), 155  
 Get\_version() (in module *mpi4py.MPI*), 151  
 Get\_view() (*mpi4py.MPI.File* method), 90  
 GIL, 40  
 GRAPH (in module *mpi4py.MPI*), 174  
 Graph\_map() (*mpi4py.MPI.Intracomm* method), 113  
 Graphcomm (class in *mpi4py.MPI*), 98  
 Grequest (class in *mpi4py.MPI*), 100  
 Group (class in *mpi4py.MPI*), 101  
 group (*mpi4py.MPI.Comm* attribute), 75  
 group (*mpi4py.MPI.File* attribute), 98  
 group (*mpi4py.MPI.Win* attribute), 143  
 GROUP\_EMPTY (in module *mpi4py.MPI*), 196  
 GROUP\_NULL (in module *mpi4py.MPI*), 195  

## H

 HOST (in module *mpi4py.MPI*), 162  

## I

 Iallgather() (*mpi4py.MPI.Comm* method), 60  
 Iallgatherv() (*mpi4py.MPI.Comm* method), 60  
 Iallreduce() (*mpi4py.MPI.Comm* method), 60  
 Ialltoall() (*mpi4py.MPI.Comm* method), 60  
 Ialltoallv() (*mpi4py.MPI.Comm* method), 60  
 Ialltoallw() (*mpi4py.MPI.Comm* method), 61  
 Ibarrier() (*mpi4py.MPI.Comm* method), 61  
 Ibcast() (*mpi4py.MPI.Comm* method), 61  
 Ibsend() (*mpi4py.MPI.Comm* method), 61  
 ibsend() (*mpi4py.MPI.Comm* method), 71  
 ibsend() (*mpi4py.util.pkl5.Comm* method), 43  
 IDENT (in module *mpi4py.MPI*), 174  
 Idup() (*mpi4py.MPI.Comm* method), 61  
 Iexscan() (*mpi4py.MPI.Intracomm* method), 113  
 Igather() (*mpi4py.MPI.Comm* method), 61  
 Igatherv() (*mpi4py.MPI.Comm* method), 62  
 Improbe() (*mpi4py.MPI.Comm* method), 62  
 improbe() (*mpi4py.MPI.Comm* method), 72  
 improbe() (*mpi4py.util.pkl5.Comm* method), 45  
 IN\_PLACE (in module *mpi4py.MPI*), 161  
 Incl() (*mpi4py.MPI.Group* method), 103  
 indegree (*mpi4py.MPI.Topocomm* attribute), 133  
 index (*mpi4py.MPI.Graphcomm* attribute), 100  
 inedges (*mpi4py.MPI.Topocomm* attribute), 133  
 Ineighbor\_allgather() (*mpi4py.MPI.Topocomm* method), 130  
 Ineighbor\_allgatherv() (*mpi4py.MPI.Topocomm* method), 130  
 Ineighbor\_alltoall() (*mpi4py.MPI.Topocomm* method), 131  
 Ineighbor\_alltoallv() (*mpi4py.MPI.Topocomm* method), 131  
 Ineighbor\_alltoallw() (*mpi4py.MPI.Topocomm* method), 131  
 Info (class in *mpi4py.MPI*), 105  
 info (*mpi4py.MPI.Comm* attribute), 75  
 info (*mpi4py.MPI.File* attribute), 98

info (*mpi4py.MPI.Win attribute*), 143  
 INFO\_ENV (*in module mpi4py.MPI*), 196  
 INFO\_NULL (*in module mpi4py.MPI*), 196  
 Init() (*in module mpi4py.MPI*), 152  
 Init\_thread() (*in module mpi4py.MPI*), 152  
 initialize (*mpi4py.mpi4py.rc attribute*), 20  
 inoutedges (*mpi4py.MPI.Topocomm attribute*), 133  
 INT (*in module mpi4py.MPI*), 182  
 INT16\_T (*in module mpi4py.MPI*), 183  
 INT32\_T (*in module mpi4py.MPI*), 183  
 INT64\_T (*in module mpi4py.MPI*), 184  
 INT8\_T (*in module mpi4py.MPI*), 183  
 INT\_INT (*in module mpi4py.MPI*), 185  
 INTEGER (*in module mpi4py.MPI*), 186  
 INTEGER1 (*in module mpi4py.MPI*), 187  
 INTEGER16 (*in module mpi4py.MPI*), 188  
 INTEGER2 (*in module mpi4py.MPI*), 188  
 INTEGER4 (*in module mpi4py.MPI*), 188  
 INTEGER8 (*in module mpi4py.MPI*), 188  
 Intercomm (*class in mpi4py.MPI*), 109  
 Intercomm (*class in mpi4py.util.pkl5*), 45  
 Intersection() (*mpi4py.MPI.Group class method*), 103  
 Intracomm (*class in mpi4py.MPI*), 110  
 Intracomm (*class in mpi4py.util.pkl5*), 45  
 IO (*in module mpi4py.MPI*), 162  
 Iprobe() (*mpi4py.MPI.Comm method*), 62  
 iprobe() (*mpi4py.MPI.Comm method*), 72  
 Iprobe() (*mpi4py.MPI.Message class method*), 116  
 iprobe() (*mpi4py.MPI.Message class method*), 117  
 iprobe() (*mpi4py.util.pkl5.Message class method*), 42  
 Iread() (*mpi4py.MPI.File method*), 90  
 Iread\_all() (*mpi4py.MPI.File method*), 90  
 Iread\_at() (*mpi4py.MPI.File method*), 90  
 Iread\_at\_all() (*mpi4py.MPI.File method*), 90  
 Iread\_shared() (*mpi4py.MPI.File method*), 91  
 Irecv() (*mpi4py.MPI.Comm method*), 62  
 irecv() (*mpi4py.MPI.Comm method*), 72  
 Irecv() (*mpi4py.MPI.Message method*), 116  
 irecv() (*mpi4py.MPI.Message method*), 117  
 irecv() (*mpi4py.util.pkl5.Comm method*), 44  
 irecv() (*mpi4py.util.pkl5.Message method*), 42  
 Ireduce() (*mpi4py.MPI.Comm method*), 63  
 Ireduce\_scatter() (*mpi4py.MPI.Comm method*), 63  
 Ireduce\_scatter\_block() (*mpi4py.MPI.Comm method*), 63  
 Irsend() (*mpi4py.MPI.Comm method*), 63  
 Is\_cancelled() (*mpi4py.MPI.Status method*), 128  
 is\_commutative (*mpi4py.MPI.Op attribute*), 119  
 Is\_commutative() (*mpi4py.MPI.Op method*), 119  
 Is\_finalized() (*in module mpi4py.MPI*), 152  
 Is\_initialized() (*in module mpi4py.MPI*), 152  
 is\_inter (*mpi4py.MPI.Comm attribute*), 75  
 Is\_inter() (*mpi4py.MPI.Comm method*), 63  
 is\_intra (*mpi4py.MPI.Comm attribute*), 75  
 Is\_intra() (*mpi4py.MPI.Comm method*), 64  
 is\_named (*mpi4py.MPI.Datatype attribute*), 84  
 is\_predefined (*mpi4py.MPI.Datatype attribute*), 84  
 is\_predefined (*mpi4py.MPI.Op attribute*), 119  
 Is\_thread\_main() (*in module mpi4py.MPI*), 152  
 is\_topo (*mpi4py.MPI.Comm attribute*), 75  
 Iscan() (*mpi4py.MPI.Intracomm method*), 113  
 Iscatter() (*mpi4py.MPI.Comm method*), 64  
 Iscatterv() (*mpi4py.MPI.Comm method*), 64  
 Isend() (*mpi4py.MPI.Comm method*), 64  
 isend() (*mpi4py.MPI.Comm method*), 72  
 isend() (*mpi4py.util.pkl5.Comm method*), 43  
 Issend() (*mpi4py.MPI.Comm method*), 64  
 issend() (*mpi4py.MPI.Comm method*), 72  
 issend() (*mpi4py.util.pkl5.Comm method*), 43  
 items() (*mpi4py.MPI.Info method*), 108  
 itemsize (*mpi4py.MPI.memory attribute*), 145  
 Iwrite() (*mpi4py.MPI.File method*), 91  
 Iwrite\_all() (*mpi4py.MPI.File method*), 91  
 Iwrite\_at() (*mpi4py.MPI.File method*), 91  
 Iwrite\_at\_all() (*mpi4py.MPI.File method*), 91  
 Iwrite\_shared() (*mpi4py.MPI.File method*), 91

## J

Join() (*mpi4py.MPI.Comm class method*), 65

## K

keys() (*mpi4py.MPI.Info method*), 108  
 KEYVAL\_INVALID (*in module mpi4py.MPI*), 161

## L

LAND (*in module mpi4py.MPI*), 193  
 LASTUSEDPCODE (*in module mpi4py.MPI*), 162  
 LB (*in module mpi4py.MPI*), 180  
 lb (*mpi4py.MPI.Datatype attribute*), 84  
 LD\_LIBRARY\_PATH, 202  
 loads() (*mpi4py.MPI.Pickle method*), 120  
 Lock() (*mpi4py.MPI.Win method*), 139  
 Lock\_all() (*mpi4py.MPI.Win method*), 139  
 LOCK\_EXCLUSIVE (*in module mpi4py.MPI*), 176  
 LOCK\_SHARED (*in module mpi4py.MPI*), 177  
 LOGICAL (*in module mpi4py.MPI*), 186  
 LOGICAL1 (*in module mpi4py.MPI*), 187  
 LOGICAL2 (*in module mpi4py.MPI*), 187  
 LOGICAL4 (*in module mpi4py.MPI*), 187  
 LOGICAL8 (*in module mpi4py.MPI*), 187  
 LONG (*in module mpi4py.MPI*), 182  
 LONG\_DOUBLE (*in module mpi4py.MPI*), 183  
 LONG\_DOUBLE\_INT (*in module mpi4py.MPI*), 186  
 LONG\_INT (*in module mpi4py.MPI*), 186  
 LONG\_LONG (*in module mpi4py.MPI*), 182  
 Lookup\_name() (*in module mpi4py.MPI*), 152

LOR (in module *mpi4py.MPI*), 193  
LXOR (in module *mpi4py.MPI*), 194

## M

map() (*mpi4py.futures.MPIPoolExecutor* method), 35  
Match\_size() (*mpi4py.MPI.Datatype* class method), 82  
MAX (in module *mpi4py.MPI*), 192  
MAX\_DATAREP\_STRING (in module *mpi4py.MPI*), 180  
MAX\_ERROR\_STRING (in module *mpi4py.MPI*), 179  
MAX\_INFO\_KEY (in module *mpi4py.MPI*), 180  
MAX\_INFO\_VAL (in module *mpi4py.MPI*), 180  
MAX\_LIBRARY\_VERSION\_STRING (in module *mpi4py.MPI*), 180  
MAX\_OBJECT\_NAME (in module *mpi4py.MPI*), 180  
MAX\_PORT\_NAME (in module *mpi4py.MPI*), 179  
MAX\_PROCESSOR\_NAME (in module *mpi4py.MPI*), 179  
MAXLOC (in module *mpi4py.MPI*), 194  
memory (class in *mpi4py.MPI*), 143  
Merge() (*mpi4py.MPI.Intercomm* method), 109  
Message (class in *mpi4py.MPI*), 115  
Message (class in *mpi4py.util.pkl5*), 41  
MESSAGE\_NO\_PROC (in module *mpi4py.MPI*), 191  
MESSAGE\_NULL (in module *mpi4py.MPI*), 191  
MIN (in module *mpi4py.MPI*), 192  
MINLOC (in module *mpi4py.MPI*), 195  
MODE\_APPEND (in module *mpi4py.MPI*), 178  
MODE\_CREATE (in module *mpi4py.MPI*), 177  
MODE\_DELETE\_ON\_CLOSE (in module *mpi4py.MPI*), 177  
MODE\_EXCL (in module *mpi4py.MPI*), 177  
MODE\_NOCHECK (in module *mpi4py.MPI*), 176  
MODE\_NOPRECEDE (in module *mpi4py.MPI*), 176  
MODE\_NOPUT (in module *mpi4py.MPI*), 176  
MODE\_NOSTORE (in module *mpi4py.MPI*), 176  
MODE\_NOSUCCEED (in module *mpi4py.MPI*), 176  
MODE\_RDONLY (in module *mpi4py.MPI*), 177  
MODE\_RDWR (in module *mpi4py.MPI*), 177  
MODE\_SEQUENTIAL (in module *mpi4py.MPI*), 178  
MODE\_UNIQUE\_OPEN (in module *mpi4py.MPI*), 177  
MODE\_WRONLY (in module *mpi4py.MPI*), 177  
model (*mpi4py.MPI.Win* attribute), 143  
module  
    *mpi4py*, 20  
    *mpi4py.futures*, 34  
    *mpi4py.MPI*, 48  
    *mpi4py.run*, 47  
    *mpi4py.util*, 40  
    *mpi4py.util.dtlb*, 46  
    *mpi4py.util.pkl5*, 40  
*mpi4py*  
    module, 20  
*mpi4py.futures*  
    module, 34  
*mpi4py.MPI*  
    module, 48

*mpi4py.rc* (in module *mpi4py*), 20  
*mpi4py.run*  
    module, 47  
*mpi4py.util*  
    module, 40  
*mpi4py.util.dtlb*  
    module, 46  
*mpi4py.util.pkl5*  
    module, 40  
MPI4PY\_FUTURES\_MAX\_WORKERS, 35, 36, 40  
MPI4PY\_PICKLE\_PROTOCOL, 11  
MPI4PY\_RC\_ERRORS, 22  
MPI4PY\_RC\_FAST\_REDUCE, 21  
MPI4PY\_RC\_FINALIZE, 21  
MPI4PY\_RC\_INITIALIZE, 20  
MPI4PY\_RC\_RECV\_MPROBE, 21  
MPI4PY\_RC\_THREAD\_LEVEL, 21  
MPI4PY\_RC\_THREADS, 21  
MPICC, 198  
MPICH\_USE\_SHLIB, 202  
MPICommExecutor (class in *mpi4py.futures*), 37  
MPIEXEC\_UNIVERSE\_SIZE, 39  
MPIPoolExecutor (class in *mpi4py.futures*), 34  
Mprobe() (*mpi4py.MPI.Comm* method), 65  
mprobe() (*mpi4py.MPI.Comm* method), 73  
mprobe() (*mpi4py.util.pkl5.Comm* method), 44

## N

name (*mpi4py.MPI.Comm* attribute), 75  
name (*mpi4py.MPI.Datatype* attribute), 84  
name (*mpi4py.MPI.Win* attribute), 143  
nbytes (*mpi4py.MPI.memory* attribute), 145  
ndim (*mpi4py.MPI.Cartcomm* attribute), 51  
nedges (*mpi4py.MPI.Graphcomm* attribute), 100  
Neighbor\_allgather() (*mpi4py.MPI.Topocomm* method), 131  
neighbor\_allgather() (*mpi4py.MPI.Topocomm* method), 132  
Neighbor\_allgatherv() (*mpi4py.MPI.Topocomm* method), 131  
Neighbor\_alltoall() (*mpi4py.MPI.Topocomm* method), 131  
neighbor\_alltoall() (*mpi4py.MPI.Topocomm* method), 132  
Neighbor\_alltoallv() (*mpi4py.MPI.Topocomm* method), 132  
Neighbor\_alltoallw() (*mpi4py.MPI.Topocomm* method), 132  
neighbors (*mpi4py.MPI.Graphcomm* attribute), 100  
nneighbors (*mpi4py.MPI.Graphcomm* attribute), 100  
nnodes (*mpi4py.MPI.Graphcomm* attribute), 100  
NO\_OP (in module *mpi4py.MPI*), 195



## O

obj (*mpi4py.MPI.memory attribute*), 145  
 OFFSET (in module *mpi4py.MPI*), 181  
 Op (class in *mpi4py.MPI*), 118  
 OP\_NULL (in module *mpi4py.MPI*), 192  
 Open() (*mpi4py.MPI.File class method*), 91  
 Open\_port() (in module *mpi4py.MPI*), 153  
 ORDER\_C (in module *mpi4py.MPI*), 170  
 ORDER\_F (in module *mpi4py.MPI*), 171  
 ORDER\_FORTRAN (in module *mpi4py.MPI*), 171  
 outdegree (*mpi4py.MPI.Topocomm attribute*), 133  
 outedges (*mpi4py.MPI.Topocomm attribute*), 133

## P

Pack() (*mpi4py.MPI.Datatype method*), 82  
 Pack\_external() (*mpi4py.MPI.Datatype method*), 82  
 Pack\_external\_size() (*mpi4py.MPI.Datatype method*), 82  
 Pack\_size() (*mpi4py.MPI.Datatype method*), 82  
 PACKED (in module *mpi4py.MPI*), 181  
 PATH, 201  
 Pcontrol() (in module *mpi4py.MPI*), 153  
 periods (*mpi4py.MPI.Cartcomm attribute*), 51  
 Pickle (class in *mpi4py.MPI*), 120  
 pickle (in module *mpi4py.MPI*), 197  
 pop() (*mpi4py.MPI.Info method*), 108  
 popitem() (*mpi4py.MPI.Info method*), 108  
 Post() (*mpi4py.MPI.Win method*), 140  
 Preallocate() (*mpi4py.MPI.File method*), 92  
 Prequest (class in *mpi4py.MPI*), 121  
 Probe() (*mpi4py.MPI.Comm method*), 65  
 probe() (*mpi4py.MPI.Comm method*), 73  
 Probe() (*mpi4py.MPI.Message class method*), 116  
 probe() (*mpi4py.MPI.Message class method*), 117  
 probe() (*mpi4py.util.pkl5.Message class method*), 42  
 PROC\_NULL (in module *mpi4py.MPI*), 161  
 PROD (in module *mpi4py.MPI*), 193  
 profile() (in module *mpi4py*), 25  
 PROTOCOL (*mpi4py.MPI.Pickle attribute*), 121  
 Publish\_name() (in module *mpi4py.MPI*), 153  
 Put() (*mpi4py.MPI.Win method*), 140  
 py2f() (*mpi4py.MPI.Comm method*), 73  
 py2f() (*mpi4py.MPI.Datatype method*), 84  
 py2f() (*mpi4py.MPI.Errhandler method*), 86  
 py2f() (*mpi4py.MPI.File method*), 98  
 py2f() (*mpi4py.MPI.Group method*), 104  
 py2f() (*mpi4py.MPI.Info method*), 108  
 py2f() (*mpi4py.MPI.Message method*), 117  
 py2f() (*mpi4py.MPI.Op method*), 119  
 py2f() (*mpi4py.MPI.Request method*), 125  
 py2f() (*mpi4py.MPI.Status method*), 129  
 py2f() (*mpi4py.MPI.Win method*), 143  
 Python Enhancement Proposals

PEP 574, 40

## Q

Query\_thread() (in module *mpi4py.MPI*), 153

## R

Raccumulate() (*mpi4py.MPI.Win method*), 140  
 Range\_excl() (*mpi4py.MPI.Group method*), 103  
 Range\_incl() (*mpi4py.MPI.Group method*), 104  
 rank (*mpi4py.MPI.Comm attribute*), 75  
 rank (*mpi4py.MPI.Group attribute*), 105  
 Read() (*mpi4py.MPI.File method*), 92  
 Read\_all() (*mpi4py.MPI.File method*), 92  
 Read\_all\_begin() (*mpi4py.MPI.File method*), 92  
 Read\_all\_end() (*mpi4py.MPI.File method*), 92  
 Read\_at() (*mpi4py.MPI.File method*), 93  
 Read\_at\_all() (*mpi4py.MPI.File method*), 93  
 Read\_at\_all\_begin() (*mpi4py.MPI.File method*), 93  
 Read\_at\_all\_end() (*mpi4py.MPI.File method*), 93  
 Read\_ordered() (*mpi4py.MPI.File method*), 93  
 Read\_ordered\_begin() (*mpi4py.MPI.File method*), 93  
 Read\_ordered\_end() (*mpi4py.MPI.File method*), 94  
 Read\_shared() (*mpi4py.MPI.File method*), 94  
 readonly (*mpi4py.MPI.memory attribute*), 145  
 REAL (in module *mpi4py.MPI*), 186  
 REAL16 (in module *mpi4py.MPI*), 188  
 REAL2 (in module *mpi4py.MPI*), 188  
 REAL4 (in module *mpi4py.MPI*), 188  
 REAL8 (in module *mpi4py.MPI*), 188  
 Recv() (*mpi4py.MPI.Comm method*), 65  
 recv() (*mpi4py.MPI.Comm method*), 73  
 Recv() (*mpi4py.MPI.Message method*), 116  
 recv() (*mpi4py.MPI.Message method*), 117  
 recv() (*mpi4py.util.pkl5.Comm method*), 44  
 recv() (*mpi4py.util.pkl5.Message method*), 42  
 Recv\_init() (*mpi4py.MPI.Comm method*), 65  
 recv\_mprobe (*mpi4py.mpi4py.rc attribute*), 21  
 Reduce() (*mpi4py.MPI.Comm method*), 66  
 reduce() (*mpi4py.MPI.Comm method*), 73  
 Reduce\_local() (*mpi4py.MPI.Op method*), 119  
 Reduce\_scatter() (*mpi4py.MPI.Comm method*), 66  
 Reduce\_scatter\_block() (*mpi4py.MPI.Comm method*), 66  
 Register\_datarep() (in module *mpi4py.MPI*), 154  
 release() (*mpi4py.MPI.memory method*), 145  
 remote\_group (*mpi4py.MPI.Intercomm attribute*), 110  
 remote\_size (*mpi4py.MPI.Intercomm attribute*), 110  
 REPLACE (in module *mpi4py.MPI*), 195  
 Request (class in *mpi4py.MPI*), 122  
 Request (class in *mpi4py.util.pkl5*), 40  
 REQUEST\_NULL (in module *mpi4py.MPI*), 191  
 Rget() (*mpi4py.MPI.Win method*), 140  
 Rget\_accumulate() (*mpi4py.MPI.Win method*), 140  
 ROOT (in module *mpi4py.MPI*), 161



Rput() (*mpi4py.MPI.Win method*), 141  
Rsend() (*mpi4py.MPI.Comm method*), 66  
Rsend\_init() (*mpi4py.MPI.Comm method*), 67

## S

Scan() (*mpi4py.MPI.Intracomm method*), 114  
scan() (*mpi4py.MPI.Intracomm method*), 115  
Scatter() (*mpi4py.MPI.Comm method*), 67  
scatter() (*mpi4py.MPI.Comm method*), 74  
Scatterv() (*mpi4py.MPI.Comm method*), 67  
Seek() (*mpi4py.MPI.File method*), 94  
SEEK\_CUR (in module *mpi4py.MPI*), 178  
SEEK\_END (in module *mpi4py.MPI*), 178  
SEEK\_SET (in module *mpi4py.MPI*), 178  
Seek\_shared() (*mpi4py.MPI.File method*), 94  
Send() (*mpi4py.MPI.Comm method*), 67  
send() (*mpi4py.MPI.Comm method*), 74  
send() (*mpi4py.util.pkl5.Comm method*), 42  
Send\_init() (*mpi4py.MPI.Comm method*), 68  
Sendrecv() (*mpi4py.MPI.Comm method*), 68  
sendrecv() (*mpi4py.MPI.Comm method*), 74  
sendrecv() (*mpi4py.util.pkl5.Comm method*), 44  
Sendrecv\_replace() (*mpi4py.MPI.Comm method*), 68  
Set() (*mpi4py.MPI.Info method*), 107  
Set\_atomicsity() (*mpi4py.MPI.File method*), 94  
Set\_attr() (*mpi4py.MPI.Comm method*), 69  
Set\_attr() (*mpi4py.MPI.Datatype method*), 83  
Set\_attr() (*mpi4py.MPI.Win method*), 141  
Set\_cancelled() (*mpi4py.MPI.Status method*), 128  
Set\_elements() (*mpi4py.MPI.Status method*), 128  
Set\_errhandler() (*mpi4py.MPI.Comm method*), 69  
Set\_errhandler() (*mpi4py.MPI.File method*), 94  
Set\_errhandler() (*mpi4py.MPI.Win method*), 141  
Set\_error() (*mpi4py.MPI.Status method*), 128  
Set\_info() (*mpi4py.MPI.Comm method*), 69  
Set\_info() (*mpi4py.MPI.File method*), 95  
Set\_info() (*mpi4py.MPI.Win method*), 141  
Set\_name() (*mpi4py.MPI.Comm method*), 69  
Set\_name() (*mpi4py.MPI.Datatype method*), 83  
Set\_name() (*mpi4py.MPI.Win method*), 141  
Set\_size() (*mpi4py.MPI.File method*), 95  
Set\_source() (*mpi4py.MPI.Status method*), 128  
Set\_tag() (*mpi4py.MPI.Status method*), 129  
Set\_view() (*mpi4py.MPI.File method*), 95  
Shared\_query() (*mpi4py.MPI.Win method*), 142  
Shift() (*mpi4py.MPI.Cartcomm method*), 50  
SHORT (in module *mpi4py.MPI*), 182  
SHORT\_INT (in module *mpi4py.MPI*), 185  
shutdown() (*mpi4py.futures.MPIPoolExecutor method*), 36  
SIGNED\_CHAR (in module *mpi4py.MPI*), 181  
SIGNED\_INT (in module *mpi4py.MPI*), 189  
SIGNED\_LONG (in module *mpi4py.MPI*), 189  
SIGNED\_LONG\_LONG (in module *mpi4py.MPI*), 190  
SIGNED\_SHORT (in module *mpi4py.MPI*), 189  
SIMILAR (in module *mpi4py.MPI*), 174  
SINT16\_T (in module *mpi4py.MPI*), 190  
SINT32\_T (in module *mpi4py.MPI*), 190  
SINT64\_T (in module *mpi4py.MPI*), 190  
SINT8\_T (in module *mpi4py.MPI*), 190  
size (*mpi4py.MPI.Comm attribute*), 75  
size (*mpi4py.MPI.Datatype attribute*), 84  
size (*mpi4py.MPI.File attribute*), 98  
size (*mpi4py.MPI.Group attribute*), 105  
source (*mpi4py.MPI.Status attribute*), 129  
Spawn() (*mpi4py.MPI.Intracomm method*), 114  
Spawn\_multiple() (*mpi4py.MPI.Intracomm method*), 114  
Split() (*mpi4py.MPI.Comm method*), 69  
Split\_type() (*mpi4py.MPI.Comm method*), 70  
Ssend() (*mpi4py.MPI.Comm method*), 70  
ssend() (*mpi4py.MPI.Comm method*), 74  
ssend() (*mpi4py.util.pkl5.Comm method*), 43  
Ssend\_init() (*mpi4py.MPI.Comm method*), 70  
starmap() (*mpi4py.futures.MPIPoolExecutor method*), 36  
Start() (*mpi4py.MPI.Grequest class method*), 101  
Start() (*mpi4py.MPI.Prequest method*), 121  
Start() (*mpi4py.MPI.Win method*), 142  
Startall() (*mpi4py.MPI.Prequest class method*), 121  
Status (class in *mpi4py.MPI*), 126  
Sub() (*mpi4py.MPI.Cartcomm method*), 51  
submit() (*mpi4py.futures.MPIPoolExecutor method*), 35  
SUBVERSION (in module *mpi4py.MPI*), 179  
SUCCESS (in module *mpi4py.MPI*), 163  
SUM (in module *mpi4py.MPI*), 192  
Sync() (*mpi4py.MPI.File method*), 95  
Sync() (*mpi4py.MPI.Win method*), 142

## T

tag (*mpi4py.MPI.Status attribute*), 129  
TAG\_UB (in module *mpi4py.MPI*), 161  
Test() (*mpi4py.MPI.Request method*), 123  
test() (*mpi4py.MPI.Request method*), 125  
Test() (*mpi4py.MPI.Win method*), 142  
test() (*mpi4py.util.pkl5.Request method*), 41  
Testall() (*mpi4py.MPI.Request class method*), 123  
testall() (*mpi4py.MPI.Request class method*), 125  
testall() (*mpi4py.util.pkl5.Request class method*), 41  
Testany() (*mpi4py.MPI.Request class method*), 123  
testany() (*mpi4py.MPI.Request class method*), 125  
Testsome() (*mpi4py.MPI.Request class method*), 123  
testsome() (*mpi4py.MPI.Request class method*), 125  
THREAD\_FUNNELED (in module *mpi4py.MPI*), 179  
thread\_level (*mpi4py.mpi4py.rc attribute*), 21  
THREAD\_MULTIPLE (in module *mpi4py.MPI*), 179  
THREAD\_SERIALIZED (in module *mpi4py.MPI*), 179  
THREAD\_SINGLE (in module *mpi4py.MPI*), 178

threads (*mpi4py.mpi4py.rc* attribute), 20  
 to\_numpy\_dtype() (in module *mpi4py.util.dtlb*), 46  
 tobytes() (*mpi4py.MPI.memory* method), 145  
 tomemory() (*mpi4py.MPI.Win* method), 143  
 topo (*mpi4py.MPI.Cartcomm* attribute), 51  
 topo (*mpi4py.MPI.Graphcomm* attribute), 100  
 Topocomm (class in *mpi4py.MPI*), 129  
 topology (*mpi4py.MPI.Comm* attribute), 75  
 toreadonly() (*mpi4py.MPI.memory* method), 145  
 Translate\_ranks() (*mpi4py.MPI.Group* class method), 104  
 true\_extent (*mpi4py.MPI.Datatype* attribute), 84  
 true\_lb (*mpi4py.MPI.Datatype* attribute), 84  
 true\_ub (*mpi4py.MPI.Datatype* attribute), 84  
 TWOINT (in module *mpi4py.MPI*), 185  
 TYPECLASS\_COMPLEX (in module *mpi4py.MPI*), 171  
 TYPECLASS\_INTEGER (in module *mpi4py.MPI*), 171  
 TYPECLASS\_REAL (in module *mpi4py.MPI*), 171

## U

UB (in module *mpi4py.MPI*), 180  
 ub (*mpi4py.MPI.Datatype* attribute), 84  
 UINT16\_T (in module *mpi4py.MPI*), 184  
 UINT32\_T (in module *mpi4py.MPI*), 184  
 UINT64\_T (in module *mpi4py.MPI*), 184  
 UINT8\_T (in module *mpi4py.MPI*), 184  
 UNDEFINED (in module *mpi4py.MPI*), 160  
 UNEQUAL (in module *mpi4py.MPI*), 174  
 Union() (*mpi4py.MPI.Group* class method), 104  
 UNIVERSE\_SIZE (in module *mpi4py.MPI*), 162  
 Unlock() (*mpi4py.MPI.Win* method), 142  
 Unlock\_all() (*mpi4py.MPI.Win* method), 142  
 Unpack() (*mpi4py.MPI.Datatype* method), 83  
 Unpack\_external() (*mpi4py.MPI.Datatype* method), 83  
 Unpublish\_name() (in module *mpi4py.MPI*), 154  
 UNSIGNED (in module *mpi4py.MPI*), 182  
 UNSIGNED\_CHAR (in module *mpi4py.MPI*), 182  
 UNSIGNED\_INT (in module *mpi4py.MPI*), 189  
 UNSIGNED\_LONG (in module *mpi4py.MPI*), 182  
 UNSIGNED\_LONG\_LONG (in module *mpi4py.MPI*), 183  
 UNSIGNED\_SHORT (in module *mpi4py.MPI*), 182  
 UNWEIGHTED (in module *mpi4py.MPI*), 175  
 update() (*mpi4py.MPI.Info* method), 108

## V

values() (*mpi4py.MPI.Info* method), 108  
 VERSION (in module *mpi4py.MPI*), 179

## W

Wait() (*mpi4py.MPI.Request* method), 124  
 wait() (*mpi4py.MPI.Request* method), 125  
 Wait() (*mpi4py.MPI.Win* method), 142

wait() (*mpi4py.util.pkl5.Request* method), 41  
 Waitall() (*mpi4py.MPI.Request* class method), 124  
 waitall() (*mpi4py.MPI.Request* class method), 126  
 waitall() (*mpi4py.util.pkl5.Request* class method), 41  
 Waitany() (*mpi4py.MPI.Request* class method), 124  
 waitany() (*mpi4py.MPI.Request* class method), 126  
 Waitsome() (*mpi4py.MPI.Request* class method), 124  
 waitsome() (*mpi4py.MPI.Request* class method), 126  
 WCHAR (in module *mpi4py.MPI*), 181  
 WEIGHTS\_EMPTY (in module *mpi4py.MPI*), 175  
 Win (class in *mpi4py.MPI*), 133  
 WIN\_BASE (in module *mpi4py.MPI*), 162  
 WIN\_CREATE\_FLAVOR (in module *mpi4py.MPI*), 163  
 WIN\_DISP\_UNIT (in module *mpi4py.MPI*), 163  
 WIN\_FLAVOR (in module *mpi4py.MPI*), 163  
 WIN\_FLAVOR\_ALLOCATE (in module *mpi4py.MPI*), 175  
 WIN\_FLAVOR\_CREATE (in module *mpi4py.MPI*), 175  
 WIN\_FLAVOR\_DYNAMIC (in module *mpi4py.MPI*), 175  
 WIN\_FLAVOR\_SHARED (in module *mpi4py.MPI*), 175  
 WIN\_MODEL (in module *mpi4py.MPI*), 163  
 WIN\_NULL (in module *mpi4py.MPI*), 197  
 WIN\_SEPARATE (in module *mpi4py.MPI*), 176  
 WIN\_SIZE (in module *mpi4py.MPI*), 162  
 WIN\_UNIFIED (in module *mpi4py.MPI*), 176  
 Write() (*mpi4py.MPI.File* method), 95  
 Write\_all() (*mpi4py.MPI.File* method), 95  
 Write\_all\_begin() (*mpi4py.MPI.File* method), 96  
 Write\_all\_end() (*mpi4py.MPI.File* method), 96  
 Write\_at() (*mpi4py.MPI.File* method), 96  
 Write\_at\_all() (*mpi4py.MPI.File* method), 96  
 Write\_at\_all\_begin() (*mpi4py.MPI.File* method), 96  
 Write\_at\_all\_end() (*mpi4py.MPI.File* method), 97  
 Write\_ordered() (*mpi4py.MPI.File* method), 97  
 Write\_ordered\_begin() (*mpi4py.MPI.File* method), 97  
 Write\_ordered\_end() (*mpi4py.MPI.File* method), 97  
 Write\_shared() (*mpi4py.MPI.File* method), 97  
 Wtick() (in module *mpi4py.MPI*), 154  
 Wtime() (in module *mpi4py.MPI*), 154  
 WTIME\_IS\_GLOBAL (in module *mpi4py.MPI*), 162