
OSMnx

Release 1.9.4

Geoff Boeing

Sep 30, 2024

CONTENTS

| | | |
|---|---------------------|-----|
| 1 | Citation | 3 |
| 2 | Getting Started | 5 |
| 3 | Installation | 7 |
| 4 | Support | 9 |
| 5 | License | 11 |
| 6 | Documentation | 13 |
| 7 | Indices | 135 |
| | Python Module Index | 137 |
| | Index | 139 |

OSMnx is a Python package to easily download, model, analyze, and visualize street networks and other geospatial features from OpenStreetMap. You can download and model walking, driving, or biking networks with a single line of code then analyze and visualize them. You can just as easily work with urban amenities/points of interest, building footprints, transit stops, elevation data, street orientations, speed/travel time, and routing.

OSMnx 2.0 is in beta: read the [migration guide](#).

CITATION

If you use OSMnx in your work, please cite the paper:

Boeing, G. (2024). [Modeling and Analyzing Urban Networks and Amenities with OSMnx](https://geoffboeing.com/publications/osmnx-paper/). Working paper. <https://geoffboeing.com/publications/osmnx-paper/>

GETTING STARTED

First read the *Getting Started* guide for an introduction to the package and FAQ.

Then work through the OSMnx [Examples Gallery](#) for step-by-step tutorials and sample code.

INSTALLATION

Follow the [Installation](#) guide to install OSMnx.

SUPPORT

If you have any trouble, consult the *User Reference*. The OSMnx repository is hosted on [GitHub](#). If you have a “how-to” or usage question, please ask it on [StackOverflow](#), as we reserve the repository’s issue tracker for bug tracking and feature development.

LICENSE

OSMnx is open source and licensed under the MIT license. OpenStreetMap's open data [license](#) requires that derivative works provide proper attribution. Refer to the [Getting Started](#) guide for usage limitations.

DOCUMENTATION

6.1 Getting Started

6.1.1 Get Started in 4 Steps

1. Install OSMnx by following the *Installation* guide.
2. Read “*Introducing OSMnx*” below on this page.
3. Work through the OSMnx *Examples Gallery* for step-by-step tutorials and sample code.
4. Consult the *User Reference* for complete details on using the package.

Finally, if you’re not already familiar with *NetworkX* and *GeoPandas*, make sure you read their user guides as OSMnx uses their data structures and functionality.

6.1.2 Introducing OSMnx

This quick introduction explains key concepts and the basic functionality of OSMnx.

Overview

OSMnx is pronounced as the initialism: “oh-ess-em-en-ex”. It is built on top of *NetworkX* and *GeoPandas*, and interacts with *OpenStreetMap* APIs to:

- Download and model street networks or other infrastructure anywhere in the world with a single line of code
- Download geospatial features (e.g., political boundaries, building footprints, grocery stores, transit stops) as a *GeoDataFrame*
- Query by city name, polygon, bounding box, or point/address + distance
- Model driving, walking, biking, and other travel modes
- Attach node elevations from a local raster file or web service and calculate edge grades
- Impute missing speeds and calculate graph edge travel times
- Simplify and correct the network’s topology to clean-up nodes and consolidate complex intersections
- Fast map-matching of points, routes, or trajectories to nearest graph edges or nodes
- Save/load network to/from disk as *GraphML*, *GeoPackage*, or *OSM XML* file
- Conduct topological and spatial analyses to automatically calculate dozens of indicators
- Calculate and visualize street bearings and orientations

- Calculate and visualize shortest-path routes that minimize distance, travel time, elevation, etc
- Explore street networks and geospatial features as a static map or interactive web map
- Visualize travel distance and travel time with isoline and isochrone maps
- Plot figure-ground diagrams of street networks and building footprints

The OSMnx [Examples Gallery](#) contains tutorials and demonstrations of all these features, and package usage is detailed in the [User Reference](#).

Configuration

You can configure OSMnx using the `settings` module. Here you can adjust logging behavior, caching, server end-points, and more. You can also configure OSMnx to retrieve historical snapshots of OpenStreetMap data as of a certain date. Refer to the FAQ below for server usage limitations.

Geocoding and Querying

OSMnx geocodes place names and addresses with the OpenStreetMap [Nominatim](#) API. You can use the `geocoder` module to geocode place names or addresses to lat-lon coordinates. Or, you can retrieve place boundaries or any other OpenStreetMap elements by name or ID.

Using the `features` and `graph` modules, as described below, you can download data by lat-lon point, address, bounding box, bounding polygon, or place name (e.g., neighborhood, city, county, etc).

Urban Amenities

Using OSMnx's `features` module, you can search for and download geospatial [features](#) (such as building footprints, grocery stores, schools, public parks, transit stops, etc) from the OpenStreetMap [Overpass](#) API as a GeoPandas GeoDataFrame. This uses OpenStreetMap [tags](#) to search for matching [elements](#).

Modeling a Network

Using OSMnx's `graph` module, you can retrieve any spatial network data (such as streets, paths, rail, canals, etc) from the Overpass API and model them as NetworkX [MultiDiGraphs](#).

MultiDiGraphs are nonplanar directed graphs with possible self-loops and parallel edges. Thus, a one-way street will be represented with a single directed edge from node u to node v , but a bidirectional street will be represented with two reciprocal directed edges (with identical geometries): one from node u to node v and another from v to u , to represent both possible directions of flow. Because these graphs are nonplanar, they correctly model the topology of interchanges, bridges, and tunnels. That is, edge crossings in a two-dimensional plane are not intersections in an OSMnx model unless they represent true junctions in the three-dimensional real world.

The `graph` module uses filters to query the Overpass API: you can either specify a built-in network type or provide your own custom filter with [Overpass QL](#). Refer to the `graph` module's documentation for more details. Under the hood, OSMnx does several things to generate the best possible model. It initially creates a 500m-buffered graph before truncating it to your desired query area, to ensure accurate streets-per-node stats and to attenuate graph perimeter effects. It also simplifies the graph topology as discussed below.

Topology Clean-Up

The `simplification` module automatically processes the network's topology from the original raw OpenStreetMap data, such that nodes represent intersections/dead-ends and edges represent the street segments that link them. This takes two primary forms: graph simplification and intersection consolidation.

Graph simplification cleans up the graph's topology so that nodes represent intersections or dead-ends and edges represent street segments. This is important because in OpenStreetMap raw data, ways comprise sets of straight-line segments between nodes: that is, nodes are vertices for streets' curving line geometries, not just intersections and dead-ends. By default, OSMnx simplifies this topology by discarding non-intersection/dead-end nodes while retaining the complete true edge geometry as an edge attribute. When multiple OpenStreetMap ways are merged into a single graph edge, the ways' attribute values can be aggregated into a single value.

Intersection consolidation is important because many real-world street networks feature complex intersections and traffic circles, resulting in a cluster of graph nodes where there is really just one true intersection as we would think of it in transportation or urban design. Similarly, divided roads are often represented by separate centerline edges: the intersection of two divided roads thus creates 4 nodes, representing where each edge intersects a perpendicular edge, but these 4 nodes represent a single intersection in the real world. OSMnx can consolidate such complex intersections into a single node and optionally rebuild the graph's edge topology accordingly. When multiple OpenStreetMap nodes are merged into a single graph node, the nodes' attribute values can be aggregated into a single value.

Converting, Projecting, Saving

OSMnx's `convert` module can convert a `MultiDiGraph` to a `MultiGraph` if you prefer an undirected representation of the network, or to a `DiGraph` if you prefer a directed representation without any parallel edges. It can also convert a `MultiDiGraph` to/from GeoPandas node and edge `GeoDataFrames`. The nodes `GeoDataFrame` is indexed by OSM ID and the edges `GeoDataFrame` is multi-indexed by `u`, `v`, `key` just like a `NetworkX` edge. This allows you to load arbitrary node/edge ShapeFiles or GeoPackage layers as `GeoDataFrames` then model them as a `MultiDiGraph` for graph analysis.

You can easily project your graph to different coordinate reference systems using the `projection` module. If you're unsure which `CRS` you want to project to, OSMnx can automatically determine an appropriate UTM CRS for you.

Using the `io` module, you can save your graph to disk as a GraphML file (to load into other network analysis software), a GeoPackage (to load into other GIS software), or an OSM XML file. Use the GraphML format whenever saving a graph for later work with OSMnx.

Working with Elevation

The `elevation` module lets you automatically attach elevations to the graph's nodes from a local raster file or a web service like the Google Maps `Elevation API`. You can also calculate edge grades (i.e., rise-over-run) and analyze the steepness of certain streets or routes.

Network Measures

You can use the `stats` module to calculate a variety of geometric and topological measures as well as street network bearing and orientation statistics. These measures define streets as the edges in an undirected representation of the graph to prevent double-counting bidirectional edges of a two-way street. You can easily generate common stats in transportation studies, urban design, and network science, including intersection density, circuitry, average node degree (connectedness), betweenness centrality, and much more.

You can also use `NetworkX` directly to calculate additional topological network measures.

Routing

The `distance` module can find the nearest node(s) or edge(s) to coordinates using a fast spatial index. The `routing` module can solve shortest paths for network routing, parallelized with multiprocessing, using different weights (e.g., distance, travel time, elevation change, etc). It can also impute missing speeds to the graph edges. This imputation can obviously be imprecise, so the user can override it by passing in arguments that define local speed limits. It can also calculate free-flow travel times for each edge.

Visualization

You can plot graphs, routes, network figure-ground diagrams, building footprints, and street network orientation rose diagrams (aka, polar histograms) with the `plot` module. You can also explore street networks, routes, or geospatial features as interactive [Folium](#) web maps.

6.1.3 More Info

All of this functionality is demonstrated step-by-step in the [OSMnx Examples Gallery](#), and usage is detailed in the [User Reference](#). More feature development details are in the [Changelog](#). Consult the [Further Reading](#) resources for additional technical details and research.

6.1.4 Frequently Asked Questions

How do I install OSMnx? Follow the [Installation](#) guide.

How do I use OSMnx? Check out the step-by-step tutorials in the [OSMnx Examples Gallery](#).

How does this or that function work? Consult the [User Reference](#).

What can I do with OSMnx? Check out recent [projects](#) that use OSMnx.

I have a usage question. Please ask it on [StackOverflow](#).

Are there any usage limitations? Yes. Refer to the [Nominatim Usage Policy](#) and [Overpass Commons](#) documentation for usage limitations and restrictions that you must adhere to at all times. If you use an alternative Nominatim/Overpass instance, ensure you understand and obey their usage policies. If you need to exceed these limitations, consider installing your own hosted instance and setting OSMnx to use it.

6.2 Installation

6.2.1 Conda

The official supported way to install OSMnx is with conda:

```
conda create -n ox -c conda-forge --strict-channel-priority osmnx
```

This creates a new conda environment and installs OSMnx into it, via the conda-forge channel. If you want other packages, such as `jupyterlab`, installed in this environment as well, just add their names after `osmnx` above.

To upgrade OSMnx to a newer release, remove the conda environment you created and then create a new one again, as above. Don't just run "conda update" or you could get package conflicts. See the [conda](#) and [conda-forge](#) documentation for more details.

6.2.2 Docker

You can run OSMnx + JupyterLab directly from the official OSMnx [Docker](#) image.

6.2.3 Pip

You may be able to install OSMnx with [pip](#) but this is not officially supported. OSMnx is written in pure Python and its installation alone is thus trivially simple if you already have all of its dependencies installed and tested on your system. OSMnx depends on other packages written in C, and installing those dependencies with pip is sometimes challenging depending on your specific system's configuration. Therefore, if you're not sure what you're doing, just follow the conda instructions above to avoid installation problems.

6.3 User Reference

This is the User Reference for the OSMnx package. If you are looking for an introduction to OSMnx, read the [Getting Started](#) guide. This guide describes the usage of OSMnx's public API.

OSMnx 2.0 is in beta: read the [migration guide](#).

6.3.1 osmnx.bearing module

Calculate graph edge bearings.

`osmnx.bearing.add_edge_bearings(G, precision=None)`

Add compass *bearing* attributes to all graph edges.

Vectorized function to calculate (initial) bearing from origin node to destination node for each edge in a directed, unprojected graph then add these bearings as new edge attributes. Bearing represents angle in degrees (clockwise) between north and the geodesic line from the origin node to the destination node. Ignores self-loop edges as their bearings are undefined.

Parameters

- **G** (*networkx.MultiDiGraph*) – unprojected graph
- **precision** (*int*) – deprecated, do not use

Returns

G – graph with edge bearing attributes

Return type

`networkx.MultiDiGraph`

`osmnx.bearing.calculate_bearing(lat1, lon1, lat2, lon2)`

Calculate the compass bearing(s) between pairs of lat-lon points.

Vectorized function to calculate initial bearings between two points' coordinates or between arrays of points' coordinates. Expects coordinates in decimal degrees. Bearing represents the clockwise angle in degrees between north and the geodesic line from (lat1, lon1) to (lat2, lon2).

Parameters

- **lat1** (*float or numpy.array of float*) – first point's latitude coordinate
- **lon1** (*float or numpy.array of float*) – first point's longitude coordinate
- **lat2** (*float or numpy.array of float*) – second point's latitude coordinate

- `lon2` (*float or numpy.array of float*) – second point’s longitude coordinate

Returns

bearing – the bearing(s) in decimal degrees

Return type

float or `numpy.array` of float

`osmnx.bearing.orientation_entropy(Gu, num_bins=36, min_length=0, weight=None)`

Calculate undirected graph’s orientation entropy.

Orientation entropy is the entropy of its edges’ bidirectional bearings across evenly spaced bins. Ignores self-loop edges as their bearings are undefined.

For more info see: Boeing, G. 2019. “Urban Spatial Order: Street Network Orientation, Configuration, and Entropy.” *Applied Network Science*, 4 (1), 67. <https://doi.org/10.1007/s41109-019-0189-1>

Parameters

- **Gu** (*networkx.MultiGraph*) – undirected, unprojected graph with *bearing* attributes on each edge
- **num_bins** (*int*) – number of bins; for example, if *num_bins=36* is provided, then each bin will represent 10 degrees around the compass
- **min_length** (*float*) – ignore edges with *length* attributes less than *min_length*; useful to ignore the noise of many very short edges
- **weight** (*string*) – if not *None*, weight edges’ bearings by this (non-null) edge attribute. for example, if “length” is provided, this will return 1 bearing observation per meter per street, which could result in a very large *bearings* array.

Returns

entropy – the graph’s orientation entropy

Return type

float

`osmnx.bearing.plot_orientation(Gu, num_bins=36, min_length=0, weight=None, ax=None, figsize=(5, 5), area=True, color='#003366', edgecolor='k', linewidth=0.5, alpha=0.7, title=None, title_y=1.05, title_font=None, xtick_font=None)`

Do not use: deprecated.

The `plot_orientation` function moved to the `plot` module. Calling it via the `bearing` module will raise an error starting in the v2.0.0 release.

Parameters

- **Gu** (*networkx.MultiGraph*) – deprecated, do not use
- **num_bins** (*int*) – deprecated, do not use
- **min_length** (*float*) – deprecated, do not use
- **weight** (*string*) – deprecated, do not use
- **ax** (*matplotlib.axes.PolarAxesSubplot*) – deprecated, do not use
- **figsize** (*tuple*) – deprecated, do not use
- **area** (*bool*) – deprecated, do not use
- **color** (*string*) – deprecated, do not use
- **edgecolor** (*string*) – deprecated, do not use

- **linewidth** (*float*) – deprecated, do not use
- **alpha** (*float*) – deprecated, do not use
- **title** (*string*) – deprecated, do not use
- **title_y** (*float*) – deprecated, do not use
- **title_font** (*dict*) – deprecated, do not use
- **xtick_font** (*dict*) – deprecated, do not use

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

6.3.2 osmnx.convert module

Convert spatial graphs to/from different data types.

`osmnx.convert.graph_from_gdfs(gdf_nodes, gdf_edges, graph_attrs=None)`

Convert node and edge GeoDataFrames to a MultiDiGraph.

This function is the inverse of *graph_to_gdfs* and is designed to work in conjunction with it.

However, you can convert arbitrary node and edge GeoDataFrames as long as 1) *gdf_nodes* is uniquely indexed by *osmid*, 2) *gdf_nodes* contains *x* and *y* coordinate columns representing node geometries, 3) *gdf_edges* is uniquely multi-indexed by *u*, *v*, *key* (following normal MultiDiGraph structure). This allows you to load any node/edge shapefiles or GeoPackage layers as GeoDataFrames then convert them to a MultiDiGraph for graph analysis. Note that any *geometry* attribute on *gdf_nodes* is discarded since *x* and *y* provide the necessary node geometry information instead.

Parameters

- **gdf_nodes** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph nodes uniquely indexed by *osmid*
- **gdf_edges** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph edges uniquely multi-indexed by *u*, *v*, *key*
- **graph_attrs** (*dict*) – the new *G.graph* attribute dict. if *None*, use *crs* from *gdf_edges* as the only graph-level attribute (*gdf_edges* must have *crs* attribute set)

Returns

G

Return type

`networkx.MultiDiGraph`

`osmnx.convert.graph_to_gdfs(G, nodes=True, edges=True, node_geometry=True, fill_edge_geometry=True)`

Convert a MultiDiGraph to node and/or edge GeoDataFrames.

This function is the inverse of *graph_from_gdfs*.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **nodes** (*bool*) – if *True*, convert graph nodes to a GeoDataFrame and return it
- **edges** (*bool*) – if *True*, convert graph edges to a GeoDataFrame and return it

- **node_geometry** (*bool*) – if True, create a geometry column from node x and y attributes
- **fill_edge_geometry** (*bool*) – if True, fill in missing edge geometry fields using nodes u and v

Returns

gdf_nodes or gdf_edges or tuple of (gdf_nodes, gdf_edges). gdf_nodes is indexed by osmid and gdf_edges is multi-indexed by u, v, key following normal MultiDiGraph structure.

Return type

geopandas.GeoDataFrame or tuple

`osmnx.convert.to_digraph(G, weight='length')`

Convert MultiDiGraph to DiGraph.

Chooses between parallel edges by minimizing *weight* attribute value. Note: see also *to_undirected* to convert MultiDiGraph to MultiGraph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **weight** (*string*) – attribute value to minimize when choosing between parallel edges

Return type

networkx.DiGraph

`osmnx.convert.to_undirected(G)`

Convert MultiDiGraph to undirected MultiGraph.

Maintains parallel edges only if their geometries differ. Note: see also *to_digraph* to convert MultiDiGraph to DiGraph.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Return type

networkx.MultiGraph

6.3.3 osmnx.distance module

Calculate distances and find nearest node/edge(s) to point(s).

`osmnx.distance.add_edge_lengths(G, precision=None, edges=None)`

Add *length* attribute (in meters) to each edge.

Vectorized function to calculate great-circle distance between each edge's incident nodes. Ensure graph is in unprojected coordinates, and unsimplified to get accurate distances.

Note: this function is run by all the *graph.graph_from_x* functions automatically to add *length* attributes to all edges. It calculates edge lengths as the great-circle distance from node *u* to node *v*. When OSMnx automatically runs this function upon graph creation, it does it before simplifying the graph: thus it calculates the straight-line lengths of edge segments that are themselves all straight. Only after simplification do edges take on a (potentially) curvilinear geometry. If you wish to calculate edge lengths later, you are calculating straight-line distances which necessarily ignore the curvilinear geometry. You only want to run this function on a graph with all straight edges (such as is the case with an unsimplified graph).

Parameters

- **G** (*networkx.MultiDiGraph*) – unprojected, unsimplified input graph
- **precision** (*int*) – deprecated, do not use

- **edges** (*tuple*) – tuple of (u, v, k) tuples representing subset of edges to add length attributes to. if None, add lengths to all edges.

Returns

G – graph with edge length attributes

Return type

networkx.MultiDiGraph

osmnx.distance.**euclidean**(y1, x1, y2, x2)

Calculate Euclidean distances between pairs of points.

Vectorized function to calculate the Euclidean distance between two points' coordinates or between arrays of points' coordinates. For accurate results, use projected coordinates rather than decimal degrees.

Parameters

- **y1** (*float or numpy.array of float*) – first point's y coordinate
- **x1** (*float or numpy.array of float*) – first point's x coordinate
- **y2** (*float or numpy.array of float*) – second point's y coordinate
- **x2** (*float or numpy.array of float*) – second point's x coordinate

Returns

dist – distance from each (x1, y1) to each (x2, y2) in coordinates' units

Return type

float or numpy.array of float

osmnx.distance.**euclidean_dist_vec**(y1, x1, y2, x2)

Do not use, deprecated.

The *euclidean_dist_vec* function has been renamed *euclidean*. Calling *euclidean_dist_vec* will raise an error in the v2.0.0 release.

Parameters

- **y1** (*float or numpy.array of float*) – first point's y coordinate
- **x1** (*float or numpy.array of float*) – first point's x coordinate
- **y2** (*float or numpy.array of float*) – second point's y coordinate
- **x2** (*float or numpy.array of float*) – second point's x coordinate

Returns

dist – distance from each (x1, y1) to each (x2, y2) in coordinates' units

Return type

float or numpy.array of float

osmnx.distance.**great_circle**(lat1, lon1, lat2, lon2, earth_radius=6371009)

Calculate great-circle distances between pairs of points.

Vectorized function to calculate the great-circle distance between two points' coordinates or between arrays of points' coordinates using the haversine formula. Expects coordinates in decimal degrees.

Parameters

- **lat1** (*float or numpy.array of float*) – first point's latitude coordinate
- **lon1** (*float or numpy.array of float*) – first point's longitude coordinate
- **lat2** (*float or numpy.array of float*) – second point's latitude coordinate

- **lon2** (*float or numpy.array of float*) – second point’s longitude coordinate
- **earth_radius** (*float*) – earth’s radius in units in which distance will be returned (default is meters)

Returns

dist – distance from each (lat1, lon1) to each (lat2, lon2) in units of earth_radius

Return type

float or numpy.array of float

`osmnx.distance.great_circle_vec(lat1, lng1, lat2, lng2, earth_radius=6371009)`

Do not use, deprecated.

The *great_circle_vec* function has been renamed *great_circle*. Calling *great_circle_vec* will raise an error in the v2.0.0 release.

Parameters

- **lat1** (*float or numpy.array of float*) – first point’s latitude coordinate
- **lng1** (*float or numpy.array of float*) – first point’s longitude coordinate
- **lat2** (*float or numpy.array of float*) – second point’s latitude coordinate
- **lng2** (*float or numpy.array of float*) – second point’s longitude coordinate
- **earth_radius** (*float*) – earth’s radius in units in which distance will be returned (default is meters)

Returns

dist – distance from each (lat1, lng1) to each (lat2, lng2) in units of earth_radius

Return type

float or numpy.array of float

`osmnx.distance.k_shortest_paths(G, orig, dest, k, weight='length')`

Do not use, deprecated.

The *k_shortest_paths* function has moved to the *routing* module. Calling it via the *distance* module will raise an error in the v2.0.0 release.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int*) – origin node ID
- **dest** (*int*) – destination node ID
- **k** (*int*) – number of shortest paths to solve
- **weight** (*string*) – edge attribute to minimize when solving shortest paths. default is edge length in meters.

Yields

path (*list*) – a generator of *k* shortest paths ordered by total weight. each path is a list of node IDs.

`osmnx.distance.nearest_edges(G, X, Y, interpolate=None, return_dist=False)`

Find the nearest edge to a point or to each of several points.

If *X* and *Y* are single coordinate values, this will return the nearest edge to that point. If *X* and *Y* are lists of coordinate values, this will return the nearest edge to each point. This function uses an R-tree spatial index and

minimizes the euclidean distance from each point to the possible matches. For accurate results, use a projected graph and points.

Parameters

- **G** (*networkx.MultiDiGraph*) – graph in which to find nearest edges
- **X** (*float or list*) – points' x (longitude) coordinates, in same CRS/units as graph and containing no nulls
- **Y** (*float or list*) – points' y (latitude) coordinates, in same CRS/units as graph and containing no nulls
- **interpolate** (*float*) – deprecated, do not use
- **return_dist** (*bool*) – optionally also return distance between points and nearest edges

Returns

ne or (ne, dist) – nearest edges as (u, v, key) or optionally a tuple where *dist* contains distances between the points and their nearest edges

Return type

tuple or list

`osmnx.distance.nearest_nodes(G, X, Y, return_dist=False)`

Find the nearest node to a point or to each of several points.

If *X* and *Y* are single coordinate values, this will return the nearest node to that point. If *X* and *Y* are lists of coordinate values, this will return the nearest node to each point.

If the graph is projected, this uses a k-d tree for euclidean nearest neighbor search, which requires that *scipy* is installed as an optional dependency. If it is unprojected, this uses a ball tree for haversine nearest neighbor search, which requires that *scikit-learn* is installed as an optional dependency.

Parameters

- **G** (*networkx.MultiDiGraph*) – graph in which to find nearest nodes
- **X** (*float or list*) – points' x (longitude) coordinates, in same CRS/units as graph and containing no nulls
- **Y** (*float or list*) – points' y (latitude) coordinates, in same CRS/units as graph and containing no nulls
- **return_dist** (*bool*) – optionally also return distance between points and nearest nodes

Returns

nn or (nn, dist) – nearest node IDs or optionally a tuple where *dist* contains distances between the points and their nearest nodes

Return type

int/list or tuple

`osmnx.distance.shortest_path(G, orig, dest, weight='length', cpus=1)`

Do not use, deprecated.

The *shortest_path* function has moved to the *routing* module. Calling it via the *distance* module will raise an error in the v2.0.0 release.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int or list*) – origin node ID, or a list of origin node IDs

- **dest** (*int or list*) – destination node ID, or a list of destination node IDs
- **weight** (*string*) – edge attribute to minimize when solving shortest path
- **cpus** (*int*) – how many CPU cores to use; if None, use all available

Returns

path – list of node IDs constituting the shortest path, or, if orig and dest are lists, then a list of path lists

Return type

list

6.3.4 osmnx.elevation module

Add node elevations from raster files or web APIs, and calculate edge grades.

`osmnx.elevation.add_edge_grades(G, add_absolute=True, precision=None)`

Add *grade* attribute to each graph edge.

Vectorized function to calculate the directed grade (ie, rise over run) for each edge in the graph and add it to the edge as an attribute. Nodes must already have *elevation* attributes to use this function.

See also the `add_node_elevations_raster` and `add_node_elevations_google` functions.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph with *elevation* node attribute
- **add_absolute** (*bool*) – if True, also add absolute value of grade as *grade_abs* attribute
- **precision** (*int*) – deprecated, do not use

Returns

G – graph with edge *grade* (and optionally *grade_abs*) attributes

Return type

networkx.MultiDiGraph

`osmnx.elevation.add_node_elevations_google(G, api_key=None, batch_size=350, pause=0, max_locations_per_batch=None, precision=None, url_template=None)`

Add an *elevation* (meters) attribute to each node using a web service.

By default, this uses the Google Maps Elevation API but you can optionally use an equivalent API with the same interface and response format, such as Open Topo Data, via the `settings` module's `elevation_url_template`. The Google Maps Elevation API requires an API key but other providers may not.

For a free local alternative see the `add_node_elevations_raster` function. See also the `add_edge_grades` function.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **api_key** (*string*) – a valid API key, can be None if the API does not require a key
- **batch_size** (*int*) – max number of coordinate pairs to submit in each API call (if this is too high, the server will reject the request because its character limit exceeds the max allowed)
- **pause** (*float*) – time to pause between API calls, which can be increased if you get rate limited
- **max_locations_per_batch** (*int*) – deprecated, do not use

- **precision** (*int*) – deprecated, do not use
- **url_template** (*string*) – deprecated, do not use

Returns

G – graph with node elevation attributes

Return type

networkx.MultiDiGraph

`osmnx.elevation.add_node_elevations_raster(G, filepath, band=1, cpus=None)`

Add *elevation* attribute to each node from local raster file(s).

If *filepath* is a list of paths, this will generate a virtual raster composed of the files at those paths as an intermediate step.

See also the *add_edge_grades* function.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph, in same CRS as raster
- **filepath** (*string or pathlib.Path or list of strings/Paths*) – path (or list of paths) to the raster file(s) to query
- **band** (*int*) – which raster band to query
- **cpus** (*int*) – how many CPU cores to use; if None, use all available

Returns

G – graph with node elevation attributes

Return type

networkx.MultiDiGraph

6.3.5 osmnx.features module

Download OpenStreetMap geospatial features’ geometries and attributes.

Retrieve points of interest, building footprints, transit lines/stops, or any other map features from OSM, including their geometries and attribute data, then construct a GeoDataFrame of them. You can use this module to query for nodes, ways, and relations (the latter of type “multipolygon” or “boundary” only) by passing a dictionary of desired OSM tags.

For more details, see https://wiki.openstreetmap.org/wiki/Map_features and <https://wiki.openstreetmap.org/wiki/Elements>

Refer to the Getting Started guide for usage limitations.

`osmnx.features.features_from_address(address, tags, dist=1000)`

Create GeoDataFrame of OSM features within some distance N, S, E, W of address.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **address** (*string*) – the address to geocode and use as the central point around which to get the features

- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, `tags = {'building': True}` would return all building footprints in the area. `tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}` would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **dist** (*numeric*) – distance in meters

Returns**gdf****Return type**

geopandas.GeoDataFrame

`osmnx.features.features_from_bbox`(*north=None, south=None, east=None, west=None, bbox=None, tags=None*)

Create a GeoDataFrame of OSM features within a N, S, E, W bounding box.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, `tags = {'building': True}` would return all building footprints in the area. `tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}` would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.

Returns**gdf****Return type**

geopandas.GeoDataFrame

`osmnx.features.features_from_place`(*query, tags, which_result=None, buffer_dist=None*)

Create GeoDataFrame of OSM features within boundaries of some place(s).

The query must be geocodable and OSM must have polygon boundaries for the geocode result. If OSM does not have a polygon for this place, you can instead get features within it using the *features_from_address* function, which geocodes the place name to a point and gets the features within some distance of that point.

If OSM does have polygon boundaries for this place but you're not finding it, try to vary the query string, pass in a structured query dict, or vary the *which_result* argument to use a different geocode result. If you know the

OSM ID of the place, you can retrieve its boundary polygon using the `geocode_to_gdf` function, then pass it to the `features_from_polygon` function.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **query** (*string or dict or list*) – the query or queries to geocode to get place boundary polygon(s)
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, `tags = {'building': True}` would return all building footprints in the area. `tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}` would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **which_result** (*int*) – which geocoding result to use. if *None*, auto-select the first (Multi)Polygon or raise an error if OSM doesn't return one.
- **buffer_dist** (*float*) – deprecated, do not use

Returns

gdf

Return type

geopandas.GeoDataFrame

`osmnx.features.features_from_point(center_point, tags, dist=1000)`

Create GeoDataFrame of OSM features within some distance N, S, E, W of a point.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **center_point** (*tuple*) – the (lat, lon) center point around which to get the features
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, `tags = {'building': True}` would return all building footprints in the area. `tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}` would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **dist** (*numeric*) – distance in meters

Returns

gdf

Return type

geopandas.GeoDataFrame

`osmnx.features.features_from_polygon(polygon, tags)`

Create GeoDataFrame of OSM features within boundaries of a (multi)polygon.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **polygon** (*shapely.geometry.Polygon* or *shapely.geometry.MultiPolygon*) – geographic boundaries to fetch features within
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.

Returns

gdf

Return type

`geopandas.GeoDataFrame`

`osmnx.features.features_from_xml(filepath, polygon=None, tags=None, encoding='utf-8')`

Create a GeoDataFrame of OSM features in an OSM-formatted XML file.

Because this function creates a GeoDataFrame of features from an OSM-formatted XML file that has already been downloaded (i.e. no query is made to the Overpass API) the *polygon* and *tags* arguments are not required. If they are not supplied to the function, *features_from_xml()* will return features for all of the tagged elements in the file. If they are supplied they will be used to filter the final GeoDataFrame.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **filepath** (*string* or *pathlib.Path*) – path to file containing OSM XML data
- **polygon** (*shapely.geometry.Polygon*) – optional geographic boundary to filter elements
- **tags** (*dict*) – optional dict of tags for filtering elements from the XML. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **encoding** (*string*) – the XML file's character encoding

Returns

gdf

Return type

`geopandas.GeoDataFrame`

6.3.6 osmnx.geocoder module

Geocode place names or addresses or retrieve OSM elements by place name or ID.

This module uses the Nominatim API's "search" and "lookup" endpoints. For more details see <https://wiki.openstreetmap.org/wiki/Elements> and <https://nominatim.org/>.

`osmnx.geocoder.geocode(query)`

Geocode place names or addresses to (lat, lon) with the Nominatim API.

This geocodes the query via the Nominatim "search" endpoint.

Parameters

query (*string*) – the query string to geocode

Returns

point – the (lat, lon) coordinates returned by the geocoder

Return type

tuple

`osmnx.geocoder.geocode_to_gdf(query, which_result=None, by_osmid=False, buffer_dist=None)`

Retrieve OSM elements by place name or OSM ID with the Nominatim API.

If searching by place name, the *query* argument can be a string or structured dict, or a list of such strings/dicts to send to the geocoder. This uses the Nominatim "search" endpoint to geocode the place name to the best-matching OSM element, then returns that element and its attribute data.

You can instead query by OSM ID by passing *by_osmid=True*. This uses the Nominatim "lookup" endpoint to retrieve the OSM element with that ID. In this case, the function treats the *query* argument as an OSM ID (or list of OSM IDs), which must be prepended with their types: node (N), way (W), or relation (R) in accordance with the Nominatim API format. For example, *query*=["R2192363", "N240109189", "W427818536"].

If *query* is a list, then *which_result* must be either a single value or a list with the same length as *query*. The queries you provide must be resolvable to elements in the Nominatim database. The resulting GeoDataFrame's geometry column contains place boundaries if they exist.

Parameters

- **query** (*string or dict or list of strings/dicts*) – query string(s) or structured dict(s) to geocode
- **which_result** (*int*) – which search result to return. if None, auto-select the first (Multi)Polygon or raise an error if OSM doesn't return one. to get the top match regardless of geometry type, set *which_result=1*. ignored if *by_osmid=True*.
- **by_osmid** (*bool*) – if True, treat query as an OSM ID lookup rather than text search
- **buffer_dist** (*float*) – deprecated, do not use

Returns

gdf – a GeoDataFrame with one row for each query

Return type

geopandas.GeoDataFrame

6.3.7 osmnx.graph module

Download and create graphs from OpenStreetMap data.

This module uses filters to query the Overpass API: you can either specify a built-in network type or provide your own custom filter with Overpass QL.

Refer to the Getting Started guide for usage limitations.

```
osmnx.graph.graph_from_address(address, dist=1000, dist_type='bbox', network_type='all', simplify=True,
                               retain_all=False, truncate_by_edge=False, return_coords=None,
                               clean_periphery=None, custom_filter=None)
```

Download and create a graph within some distance of an address.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **address** (*string*) – the address to geocode and use as the central point around which to construct the graph
- **dist** (*int*) – retain only those nodes within this many meters of the center of the graph
- **dist_type** (*string* {"network", "bbox"}) – if “bbox”, retain only those nodes within a bounding box of the distance parameter. if “network”, retain only those nodes within some network distance from the center-most node.
- **network_type** (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if custom_filter is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node’s neighbors is within the bounding box
- **return_coords** (*bool*) – deprecated, do not use
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the network_type presets e.g., ["power"~"line"] or ["highway"~"motorway|trunk"]. Also pass in a network_type that is in settings.bidirectional_network_types if you want graph to be fully bi-directional.

Return type

networkx.MultiDiGraph or optionally (networkx.MultiDiGraph, (lat, lon))

Notes

Very large query areas use the *utils_geo._consolidate_subdivide_geometry* function to automatically make multiple requests: see that function’s documentation for caveats.

```
osmnx.graph.graph_from_bbox(north=None, south=None, east=None, west=None, bbox=None,
                             network_type='all', simplify=True, retain_all=False, truncate_by_edge=False,
                             clean_periphery=None, custom_filter=None)
```

Download and create a graph within some bounding box.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)
- **network_type** (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if custom_filter is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node’s neighbors is within the bounding box
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the network_type presets e.g., ["power"~"line"] or ["highway"~"motorway|trunk"]. Also pass in a network_type that is in settings.bidirectional_network_types if you want graph to be fully bi-directional.

Returns

G

Return type

networkx.MultiDiGraph

Notes

Very large query areas use the *utils_geo._consolidate_subdivide_geometry* function to automatically make multiple requests: see that function’s documentation for caveats.

```
osmnx.graph.graph_from_place(query, network_type='all', simplify=True, retain_all=False,
                              truncate_by_edge=False, which_result=None, buffer_dist=None,
                              clean_periphery=None, custom_filter=None)
```

Download and create a graph within the boundaries of some place(s).

The query must be geocodable and OSM must have polygon boundaries for the geocode result. If OSM does not have a polygon for this place, you can instead get its street network using the `graph_from_address` function, which geocodes the place name to a point and gets the network within some distance of that point.

If OSM does have polygon boundaries for this place but you're not finding it, try to vary the query string, pass in a structured query dict, or vary the `which_result` argument to use a different geocode result. If you know the OSM ID of the place, you can retrieve its boundary polygon using the `geocode_to_gdf` function, then pass it to the `graph_from_polygon` function.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **query** (*string or dict or list*) – the query or queries to geocode to get place boundary polygon(s)
- **network_type** (*string {"all", "all_public", "bike", "drive", "drive_service", "walk"}*) – what type of street network to get if `custom_filter` is `None`
- **simplify** (*bool*) – if `True`, simplify graph topology with the `simplify_graph` function
- **retain_all** (*bool*) – if `True`, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if `True`, retain nodes outside boundary polygon if at least one of node's neighbors is within the polygon
- **which_result** (*int*) – which geocoding result to use. if `None`, auto-select the first (Multi)Polygon or raise an error if OSM doesn't return one.
- **buffer_dist** (*float*) – deprecated, do not use
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the `network_type` presets e.g., `["power"~"line"]` or `["highway"~"motorway|trunk"]`. Also pass in a `network_type` that is in `settings.bidirectional_network_types` if you want graph to be fully bi-directional.

Returns

G

Return type

`networkx.MultiDiGraph`

Notes

Very large query areas use the `utils_geo._consolidate_subdivide_geometry` function to automatically make multiple requests: see that function's documentation for caveats.

```
osmnx.graph.graph_from_point(center_point, dist=1000, dist_type='bbox', network_type='all', simplify=True,
                             retain_all=False, truncate_by_edge=False, clean_periphery=None,
                             custom_filter=None)
```

Download and create a graph within some distance of a (lat, lon) point.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **center_point** (*tuple*) – the (lat, lon) center point around which to construct the graph
- **dist** (*int*) – retain only those nodes within this many meters of the center of the graph, with distance determined according to *dist_type* argument
- **dist_type** (*string* {"network", "bbox"}) – if "bbox", retain only those nodes within a bounding box of the distance parameter. if "network", retain only those nodes within some network distance from the center-most node.
- **network_type** (*string*, {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if *custom_filter* is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node's neighbors is within the bounding box
- **clean_periphery** (*bool*,) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the *network_type* presets e.g., ["power"~"line"] or ["highway"~"motorway|trunk"]. Also pass in a *network_type* that is in *settings.bidirectional_network_types* if you want graph to be fully bi-directional.

Returns

G

Return type

networkx.MultiDiGraph

Notes

Very large query areas use the *utils_geo._consolidate_subdivide_geometry* function to automatically make multiple requests: see that function's documentation for caveats.

```
osmnx.graph.graph_from_polygon(polygon, network_type='all', simplify=True, retain_all=False,
                               truncate_by_edge=False, clean_periphery=None, custom_filter=None)
```

Download and create a graph within the boundaries of a (multi)polygon.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **polygon** (*shapely.geometry.Polygon* or *shapely.geometry.MultiPolygon*) – the shape to get network data within. coordinates should be in unprojected latitude-longitude degrees (EPSG:4326).
- **network_type** (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if *custom_filter* is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.

- **truncate_by_edge** (*bool*) – if *True*, retain nodes outside boundary polygon if at least one of node’s neighbors is within the polygon
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the *network_type* presets e.g., `[“power”~”line”]` or `[“highway”~”motorway|trunk”]`. Also pass in a *network_type* that is in `settings.bidirectional_network_types` if you want graph to be fully bi-directional.

Returns**G****Return type**`networkx.MultiDiGraph`**Notes**

Very large query areas use the `utils_geo._consolidate_subdivide_geometry` function to automatically make multiple requests: see that function’s documentation for caveats.

`osmnx.graph.graph_from_xml(filepath, bidirectional=False, simplify=True, retain_all=False, encoding='utf-8')`

Create a graph from data in a .osm formatted XML file.

Do not load an XML file generated by OSMnx: this use case is not supported and may not behave as expected. To save/load graphs to/from disk for later use in OSMnx, use the `io.save_graphml` and `io.load_graphml` functions instead.

Parameters

- **filepath** (*string* or *pathlib.Path*) – path to file containing OSM XML data
- **bidirectional** (*bool*) – if *True*, create bi-directional edges for one-way streets
- **simplify** (*bool*) – if *True*, simplify graph topology with the `simplify_graph` function
- **retain_all** (*bool*) – if *True*, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **encoding** (*string*) – the XML file’s character encoding

Returns**G****Return type**`networkx.MultiDiGraph`

6.3.8 osmnx.io module

Serialize graphs to/from files on disk.

`osmnx.io.load_graphml(filepath=None, graphml_str=None, node_dtypes=None, edge_dtypes=None, graph_dtypes=None)`

Load an OSMnx-saved GraphML file from disk or GraphML string.

This function converts node, edge, and graph-level attributes (serialized as strings) to their appropriate data types. These can be customized as needed by passing in *dtypes* arguments providing types or custom converter functions. For example, if you want to convert some attribute’s values to *bool*, consider using the built-in `ox.io._convert_bool_string` function to properly handle “True”/“False” string literals as *True/False* booleans: `ox.load_graphml(fp, node_dtypes={my_attr: ox.io._convert_bool_string})`.

If you manually configured the `all_oneway=True` setting, you may need to manually specify here that edge `oneway` attributes should be type `str`.

Note that you must pass one and only one of `filepath` or `graphml_str`. If passing `graphml_str`, you may need to decode the bytes read from your file before converting to string to pass to this function.

Parameters

- **filepath** (*string or pathlib.Path*) – path to the GraphML file
- **graphml_str** (*string*) – a valid and decoded string representation of a GraphML file's contents
- **node_dtypes** (*dict*) – dict of node attribute names:types to convert values' data types. the type can be a python type or a custom string converter function.
- **edge_dtypes** (*dict*) – dict of edge attribute names:types to convert values' data types. the type can be a python type or a custom string converter function.
- **graph_dtypes** (*dict*) – dict of graph-level attribute names:types to convert values' data types. the type can be a python type or a custom string converter function.

Returns

G

Return type

`networkx.MultiDiGraph`

`osmnx.io.save_graph_geopackage(G, filepath=None, encoding='utf-8', directed=False)`

Save graph nodes and edges to disk as layers in a GeoPackage file.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **filepath** (*string or pathlib.Path*) – path to the GeoPackage file including extension. if None, use default data folder + `graph.gpkg`
- **encoding** (*string*) – the character encoding for the saved file
- **directed** (*bool*) – if False, save one edge for each undirected edge in the graph but retain original oneway and to/from information as edge attributes; if True, save one edge for each directed edge in the graph

Return type

None

`osmnx.io.save_graph_shapefile(G, filepath=None, encoding='utf-8', directed=False)`

Do not use: deprecated. Use the `save_graph_geopackage` function instead.

The Shapefile format is proprietary and outdated. Instead, use the superior GeoPackage file format via the `save_graph_geopackage` function. See <http://switchfromshapefile.org/> for more information.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **filepath** (*string or pathlib.Path*) – path to the shapefiles folder (no file extension). if None, use default data folder + `graph_shapefile`
- **encoding** (*string*) – the character encoding for the saved files
- **directed** (*bool*) – if False, save one edge for each undirected edge in the graph but retain original oneway and to/from information as edge attributes; if True, save one edge for each directed edge in the graph

Return type

None

```
osmnx.io.save_graph_xml(data, filepath=None, node_tags=None, node_attrs=None, edge_tags=None,
                        edge_attrs=None, oneway=None, merge_edges=None, edge_tag_aggs=None,
                        api_version=None, precision=None, way_tag_aggs=None)
```

Save graph to disk as an OSM-formatted XML .osm file.

This function exists only to allow serialization to the .osm file format for applications that require it, and has constraints to conform to that. As such, this function has a limited use case which does not include saving/loading graphs for subsequent OSMnx analysis. To save/load graphs to/from disk for later use in OSMnx, use the `io.save_graphml` and `io.load_graphml` functions instead. To load a graph from a .osm file that you have downloaded or generated elsewhere, use the `graph.graph_from_xml` function.

Parameters

- **data** (*networkx.MultiDiGraph*) – the input graph
- **filepath** (*string or pathlib.Path*) – do not use, deprecated
- **node_tags** (*list*) – do not use, deprecated
- **node_attrs** (*list*) – do not use, deprecated
- **edge_tags** (*list*) – do not use, deprecated
- **edge_attrs** (*list*) – do not use, deprecated
- **oneway** (*bool*) – do not use, deprecated
- **merge_edges** (*bool*) – do not use, deprecated
- **edge_tag_aggs** (*tuple*) – do not use, deprecated
- **api_version** (*float*) – do not use, deprecated
- **precision** (*int*) – do not use, deprecated
- **way_tag_aggs** (*dict*) – Keys are OSM way tag keys and values are aggregation functions (anything accepted as an argument by `pandas.agg`). Allows user to aggregate graph edge attribute values into single OSM way values. If `None`, or if some tag's key does not exist in the dict, the way attribute will be assigned the value of the first edge of the way.

Return type

None

```
osmnx.io.save_graphml(G, filepath=None, gephi=False, encoding='utf-8')
```

Save graph to disk as GraphML file.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **filepath** (*string or pathlib.Path*) – path to the GraphML file including extension. if `None`, use default data folder + `graph.graphml`
- **gephi** (*bool*) – if `True`, give each edge a unique key/id to work around Gephi's interpretation of the GraphML specification
- **encoding** (*string*) – the character encoding for the saved file

Return type

None

6.3.9 osmnx.plot module

Visualize street networks, routes, orientations, and geospatial features.

`osmnx.plot.get_colors(n, cmap='viridis', start=0.0, stop=1.0, alpha=1.0, return_hex=None)`

Get n evenly-spaced colors from a matplotlib colormap.

Parameters

- **n** (*int*) – number of colors
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace
- **stop** (*float*) – where to end in the colorspace
- **alpha** (*float*) – If *None*, return colors as HTML-like hex triplet “#rrggbb” RGB strings. If *float*, return as “#rrggbbaa” RGBA strings.
- **return_hex** (*bool*) – deprecated, do not use

Returns

color_list

Return type

list

`osmnx.plot.get_edge_colors_by_attr(G, attr, num_bins=None, cmap='viridis', start=0, stop=1, na_color='none', equal_size=False)`

Get colors based on edge attribute values.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **attr** (*string*) – name of a numerical edge attribute
- **num_bins** (*int*) – if *None*, linearly map a color to each value. otherwise, assign values to this many bins then assign a color to each bin.
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace
- **stop** (*float*) – where to end in the colorspace
- **na_color** (*string*) – what color to assign edges with missing attr values
- **equal_size** (*bool*) – ignored if num_bins is *None*. if *True*, bin into equal-sized quantiles (requires unique bin edges). if *False*, bin into equal-spaced bins.

Returns

edge_colors – series labels are edge IDs (u, v, key) and values are colors

Return type

pandas.Series

`osmnx.plot.get_node_colors_by_attr(G, attr, num_bins=None, cmap='viridis', start=0, stop=1, na_color='none', equal_size=False)`

Get colors based on node attribute values.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph

- **attr** (*string*) – name of a numerical node attribute
- **num_bins** (*int*) – if *None*, linearly map a color to each value. otherwise, assign values to this many bins then assign a color to each bin.
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace
- **stop** (*float*) – where to end in the colorspace
- **na_color** (*string*) – what color to assign nodes with missing attr values
- **equal_size** (*bool*) – ignored if num_bins is *None*. if *True*, bin into equal-sized quantiles (requires unique bin edges). if *False*, bin into equal-spaced bins.

Returns

node_colors – series labels are node IDs and values are colors

Return type

pandas.Series

```
osmnx.plot.plot_figure_ground(G=None, address=None, point=None, dist=805,  
                             network_type='drive_service', street_widths=None, default_width=4,  
                             color='w', edge_color=None, smooth_joints=None, **pg_kwargs)
```

Plot a figure-ground diagram of a street network.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph, must be unprojected
- **address** (*string*) – deprecated, do not use
- **point** (*tuple*) – deprecated, do not use
- **dist** (*numeric*) – how many meters to extend north, south, east, west from center point
- **network_type** (*string*) – deprecated, do not use
- **street_widths** (*dict*) – dict keys are street types and values are widths to plot in pixels
- **default_width** (*numeric*) – fallback width in pixels for any street type not in street_widths
- **color** (*string*) – color of the streets
- **edge_color** (*string*) – deprecated, do not use
- **smooth_joints** (*bool*) – deprecated, do not use
- **pg_kwargs** – keyword arguments to pass to plot_graph

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_footprints(gdf, ax=None, figsize=(8, 8), color='orange', edge_color='none',  
                           edge_linewidth=0, alpha=None, bgcolor='#111111', bbox=None, save=False,  
                           show=True, close=False, filepath=None, dpi=600)
```

Visualize a GeoDataFrame of geospatial features' footprints.

Parameters

- **gdf** (*geopandas.GeoDataFrame*) – GeoDataFrame of footprints (shapely Polygons and MultiPolygons)

- **ax** (*axis*) – if not None, plot on this preexisting axis
- **figsize** (*tuple*) – if ax is None, create new figure with size (width, height)
- **color** (*string*) – color of the footprints
- **edge_color** (*string*) – color of the edge of the footprints
- **edge_linewidth** (*float*) – width of the edge of the footprints
- **alpha** (*float*) – opacity of the footprints
- **bgcolor** (*string*) – background color of the plot
- **bbox** (*tuple*) – bounding box as (north, south, east, west). if None, will calculate from the spatial extents of the geometries in gdf
- **save** (*bool*) – if True, save the figure to disk at filepath
- **show** (*bool*) – if True, call `pyplot.show()` to show the figure
- **close** (*bool*) – if True, call `pyplot.close()` to close the figure
- **filepath** (*string*) – if save is True, the path to the file. file format determined from extension. if None, use `settings.imgs_folder/image.png`
- **dpi** (*int*) – if save is True, the resolution of saved file

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_graph(G, ax=None, figsize=(8, 8), bgcolor='#111111', node_color='w', node_size=15,
                      node_alpha=None, node_edgecolor='none', node_zorder=1, edge_color='#999999',
                      edge_linewidth=1, edge_alpha=None, show=True, close=False, save=False,
                      filepath=None, dpi=300, bbox=None)
```

Visualize a graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **ax** (*matplotlib axis*) – if not None, plot on this preexisting axis
- **figsize** (*tuple*) – if ax is None, create new figure with size (width, height)
- **bgcolor** (*string*) – background color of plot
- **node_color** (*string or list*) – color(s) of the nodes
- **node_size** (*int*) – size of the nodes: if 0, then skip plotting the nodes
- **node_alpha** (*float*) – opacity of the nodes, note: if you passed RGBA values to `node_color`, set `node_alpha=None` to use the alpha channel in `node_color`
- **node_edgecolor** (*string*) – color of the nodes' markers' borders
- **node_zorder** (*int*) – zorder to plot nodes: edges are always 1, so set `node_zorder=0` to plot nodes below edges
- **edge_color** (*string or list*) – color(s) of the edges' lines
- **edge_linewidth** (*float*) – width of the edges' lines: if 0, then skip plotting the edges
- **edge_alpha** (*float*) – opacity of the edges, note: if you passed RGBA values to `edge_color`, set `edge_alpha=None` to use the alpha channel in `edge_color`

- **show** (*bool*) – if True, call `pyplot.show()` to show the figure
- **close** (*bool*) – if True, call `pyplot.close()` to close the figure
- **save** (*bool*) – if True, save the figure to disk at `filepath`
- **filepath** (*string*) – if save is True, the path to the file. file format determined from extension. if None, use `settings.imgs_folder/image.png`
- **dpi** (*int*) – if save is True, the resolution of saved file
- **bbox** (*tuple*) – bounding box as (north, south, east, west). if None, will calculate from spatial extents of plotted geometries.

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_graph_route(G, route, route_color='r', route_linewidth=4, route_alpha=0.5,  
                             orig_dest_size=100, ax=None, **pg_kwargs)
```

Visualize a route along a graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **route** (*list*) – route as a list of node IDs
- **route_color** (*string*) – color of the route
- **route_linewidth** (*int*) – width of the route line
- **route_alpha** (*float*) – opacity of the route line
- **orig_dest_size** (*int*) – size of the origin and destination nodes
- **ax** (*matplotlib axis*) – if not None, plot route on this preexisting axis instead of creating a new fig, ax and drawing the underlying graph
- **pg_kwargs** – keyword arguments to pass to `plot_graph`

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_graph_routes(G, routes, route_colors='r', route_linewidths=4, **pgr_kwargs)
```

Visualize several routes along a graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **routes** (*list*) – routes as a list of lists of node IDs
- **route_colors** (*string or list*) – if string, 1 color for all routes. if list, the colors for each route.
- **route_linewidths** (*int or list*) – if int, 1 linewidth for all routes. if list, the linewidth for each route.
- **pgr_kwargs** – keyword arguments to pass to `plot_graph_route`

Returns**fig, ax** – matplotlib figure, axis**Return type**

tuple

```
osmnx.plot.plot_orientation(Gu, num_bins=36, min_length=0, weight=None, ax=None, figsize=(5, 5),
                           area=True, color='#003366', edgecolor='k', linewidth=0.5, alpha=0.7,
                           title=None, title_y=1.05, title_font=None, xtick_font=None)
```

Plot a polar histogram of a spatial network's bidirectional edge bearings.

Ignores self-loop edges as their bearings are undefined.

For more info see: Boeing, G. 2019. "Urban Spatial Order: Street Network Orientation, Configuration, and Entropy." *Applied Network Science*, 4 (1), 67. <https://doi.org/10.1007/s41109-019-0189-1>

Parameters

- **Gu** (*networkx.MultiGraph*) – undirected, unprojected graph with *bearing* attributes on each edge
- **num_bins** (*int*) – number of bins; for example, if *num_bins=36* is provided, then each bin will represent 10 degrees around the compass
- **min_length** (*float*) – ignore edges with *length* attributes less than *min_length*
- **weight** (*string*) – if not None, weight edges' bearings by this (non-null) edge attribute
- **ax** (*matplotlib.axes.PolarAxesSubplot*) – if not None, plot on this preexisting axis; must have *projection=polar*
- **figsize** (*tuple*) – if ax is None, create new figure with size (width, height)
- **area** (*bool*) – if True, set bar length so area is proportional to frequency, otherwise set bar length so height is proportional to frequency
- **color** (*string*) – color of histogram bars
- **edgecolor** (*string*) – color of histogram bar edges
- **linewidth** (*float*) – width of histogram bar edges
- **alpha** (*float*) – opacity of histogram bars
- **title** (*string*) – title for plot
- **title_y** (*float*) – y position to place title
- **title_font** (*dict*) – the title's fontdict to pass to matplotlib
- **xtick_font** (*dict*) – the xtick labels' fontdict to pass to matplotlib

Returns**fig, ax** – matplotlib figure, axis**Return type**

tuple

6.3.10 osmnx.projection module

Project a graph, GeoDataFrame, or geometry to a different CRS.

`osmnx.projection.is_projected(crs)`

Determine if a coordinate reference system is projected or not.

Parameters

crs (*string or pyproj.CRS*) – the identifier of the coordinate reference system, which can be anything accepted by *pyproj.CRS.from_user_input()* such as an authority string or a WKT string

Returns

projected – True if crs is projected, otherwise False

Return type

bool

`osmnx.projection.project_gdf(gdf, to_crs=None, to_latlong=False)`

Project a GeoDataFrame from its current CRS to another.

If *to_latlong* is *True*, this projects the GeoDataFrame to the CRS defined by *settings.default_crs*, otherwise it projects it to the CRS defined by *to_crs*. If *to_crs* is *None*, it projects it to the CRS of an appropriate UTM zone given *gdf*'s bounds.

Parameters

- **gdf** (*geopandas.GeoDataFrame*) – the GeoDataFrame to be projected
- **to_crs** (*string or pyproj.CRS*) – if *None*, project to an appropriate UTM zone, otherwise project to this CRS
- **to_latlong** (*bool*) – if *True*, project to *settings.default_crs* and ignore *to_crs*

Returns

gdf_proj – the projected GeoDataFrame

Return type

geopandas.GeoDataFrame

`osmnx.projection.project_geometry(geometry, crs=None, to_crs=None, to_latlong=False)`

Project a Shapely geometry from its current CRS to another.

If *to_latlong* is *True*, this projects the GeoDataFrame to the CRS defined by *settings.default_crs*, otherwise it projects it to the CRS defined by *to_crs*. If *to_crs* is *None*, it projects it to the CRS of an appropriate UTM zone given *geometry*'s bounds.

Parameters

- **geometry** (*shapely geometry*) – the geometry to be projected
- **crs** (*string or pyproj.CRS*) – the initial CRS of *geometry*. if *None*, it will be set to *settings.default_crs*
- **to_crs** (*string or pyproj.CRS*) – if *None*, project to an appropriate UTM zone, otherwise project to this CRS
- **to_latlong** (*bool*) – if *True*, project to *settings.default_crs* and ignore *to_crs*

Returns

geometry_proj, crs – the projected geometry and its new CRS

Return type

tuple

`osmnx.projection.project_graph(G, to_crs=None, to_latlong=False)`

Project a graph from its current CRS to another.

If `to_latlong` is `True`, this projects the GeoDataFrame to the CRS defined by `settings.default_crs`, otherwise it projects it to the CRS defined by `to_crs`. If `to_crs` is `None`, it projects it to the CRS of an appropriate UTM zone given `G`'s bounds.

Parameters

- **G** (`networkx.MultiDiGraph`) – the graph to be projected
- **to_crs** (`string` or `pyproj.CRS`) – if `None`, project to an appropriate UTM zone, otherwise project to this CRS
- **to_latlong** (`bool`) – if `True`, project to `settings.default_crs` and ignore `to_crs`

Returns

G_proj – the projected graph

Return type

`networkx.MultiDiGraph`

6.3.11 osmnx.routing module

Calculate weighted shortest paths between graph nodes.

`osmnx.routing.add_edge_speeds(G, hwy_speeds=None, fallback=None, precision=None, agg=<function mean>)`

Add edge speeds (km per hour) to graph as new `speed_kph` edge attributes.

By default, this imputes free-flow travel speeds for all edges via the mean `maxspeed` value of the edges of each highway type. For highway types in the graph that have no `maxspeed` value on any edge, it assigns the mean of all `maxspeed` values in graph.

This default mean-imputation can obviously be imprecise, and the user can override it by passing in `hwy_speeds` and/or `fallback` arguments that correspond to local speed limit standards. The user can also specify a different aggregation function (such as the median) to impute missing values from the observed values.

If edge `maxspeed` attribute has “mph” in it, value will automatically be converted from miles per hour to km per hour. Any other speed units should be manually converted to km per hour prior to running this function, otherwise there could be unexpected results. If “mph” does not appear in the edge’s `maxspeed` attribute string, then function assumes kph, per OSM guidelines: https://wiki.openstreetmap.org/wiki/Map_Features/Units

Parameters

- **G** (`networkx.MultiDiGraph`) – input graph
- **hwy_speeds** (`dict`) – dict keys = OSM highway types and values = typical speeds (km per hour) to assign to edges of that highway type for any edges missing speed data. Any edges with highway type not in `hwy_speeds` will be assigned the mean preexisting speed value of all edges of that highway type.
- **fallback** (`numeric`) – default speed value (km per hour) to assign to edges whose highway type did not appear in `hwy_speeds` and had no preexisting speed values on any edge
- **precision** (`int`) – deprecated, do not use
- **agg** (`function`) – aggregation function to impute missing values from observed values. the default is `numpy.mean`, but you might also consider for example `numpy.median`, `numpy.nanmedian`, or your own custom function

Returns

G – graph with `speed_kph` attributes on all edges

Return type

`networkx.MultiDiGraph`

`osmnx.routing.add_edge_travel_times(G, precision=None)`

Add edge travel time (seconds) to graph as new `travel_time` edge attributes.

Calculates free-flow travel time along each edge, based on `length` and `speed_kph` attributes. Note: run `add_edge_speeds` first to generate the `speed_kph` attribute. All edges must have `length` and `speed_kph` attributes and all their values must be non-null.

Parameters

- **G** (`networkx.MultiDiGraph`) – input graph
- **precision** (`int`) – deprecated, do not use

Returns

G – graph with `travel_time` attributes on all edges

Return type

`networkx.MultiDiGraph`

`osmnx.routing.k_shortest_paths(G, orig, dest, k, weight='length')`

Solve *k* shortest paths from an origin node to a destination node.

Uses Yen's algorithm. See also `shortest_path` to solve just the one shortest path.

Parameters

- **G** (`networkx.MultiDiGraph`) – input graph
- **orig** (`int`) – origin node ID
- **dest** (`int`) – destination node ID
- **k** (`int`) – number of shortest paths to solve
- **weight** (`string`) – edge attribute to minimize when solving shortest paths. default is edge length in meters.

Yields

path (`list`) – a generator of *k* shortest paths ordered by total weight. each path is a list of node IDs.

`osmnx.routing.route_to_gdf(G, route, weight='length')`

Return a GeoDataFrame of the edges in a path, in order.

Parameters

- **G** (`networkx.MultiDiGraph`) – input graph
- **route** (`list`) – list of node IDs constituting the path
- **weight** (`string`) – if there are parallel edges between two nodes, choose lowest weight

Returns

gdf_edges – GeoDataFrame of the edges

Return type

`geopandas.GeoDataFrame`

`osmnx.routing.shortest_path(G, orig, dest, weight='length', cpus=1)`

Solve shortest path from origin node(s) to destination node(s).

Uses Dijkstra's algorithm. If *orig* and *dest* are single node IDs, this will return a list of the nodes constituting the shortest path between them. If *orig* and *dest* are lists of node IDs, this will return a list of lists of the nodes constituting the shortest path between each origin-destination pair. If a path cannot be solved, this will return *None* for that path. You can parallelize solving multiple paths with the *cpus* parameter, but be careful to not exceed your available RAM.

See also *k_shortest_paths* to solve multiple shortest paths between a single origin and destination. For additional functionality or different solver algorithms, use NetworkX directly.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int or list*) – origin node ID, or a list of origin node IDs
- **dest** (*int or list*) – destination node ID, or a list of destination node IDs
- **weight** (*string*) – edge attribute to minimize when solving shortest path
- **cpus** (*int*) – how many CPU cores to use; if *None*, use all available

Returns

path – list of node IDs constituting the shortest path, or, if *orig* and *dest* are lists, then a list of path lists

Return type

list

6.3.12 osmnx.settings module

Global settings that can be configured by the user.

all_oneway

[bool] Only use if specifically saving to .osm XML file with the *save_graph_xml* function. If *True*, forces all ways to be loaded as oneway ways, preserving the original order of nodes stored in the OSM way XML. This also retains original OSM string values for oneway attribute values, rather than converting them to a *True/False* bool. Default is *False*.

bidirectional_network_types

[list] Network types for which a fully bidirectional graph will be created. Default is [*"walk"*].

cache_folder

[str or *pathlib.Path*] Path to folder in which to save/load HTTP response cache, if the *use_cache* setting equals *True*. Default is *"./cache"*.

cache_only_mode

[bool] If *True*, download network data from Overpass then raise a *CacheOnlyModeInterrupt* error for user to catch. This prevents graph building from taking place and instead just saves OSM response data to cache. Useful for sequentially caching lots of raw data (as you can only query Overpass one request at a time) then using the local cache to quickly build many graphs simultaneously with multiprocessing. Default is *False*.

data_folder

[str or *pathlib.Path*] Path to folder in which to save/load graph files by default. Default is *"./data"*.

default_accept_language

[str] Do not use, deprecated. Use *http_accept_language* instead.

default_access

[str] Default filter for OSM “access” key. Default is `[“access”!~“private”]`. Note that also filtering out “access=no” ways prevents including transit-only bridges (e.g., Tilikum Crossing) from appearing in drivable road network (e.g., `[“access”!~“private|no”]`). However, some drivable tollroads have “access=no” plus a “access:conditional” key to clarify when it is accessible, so we can’t filter out all “access=no” ways by default. Best to be permissive here then remove complicated combinations of tags programatically after the full graph is downloaded and constructed.

default_crs

[str] Default coordinate reference system to set when creating graphs. Default is `“epsg:4326”`.

default_referer

[str] Do not use, deprecated. Use `http_referer` instead.

default_user_agent

[str] Do not use, deprecated. Use `http_user_agent` instead.

doh_url_template

[str] Endpoint to resolve DNS-over-HTTPS if local DNS resolution fails. Set to None to disable DoH, but see `downloader._config_dns` documentation for caveats. Default is: `“https://8.8.8.8/resolve?name={hostname}”`

elevation_url_template

[str] Endpoint of the Google Maps Elevation API (or equivalent), containing exactly two parameters: `locations` and `key`. Default is: `“https://maps.googleapis.com/maps/api/elevation/json?locations={locations}&key={key}”`
One example of an alternative equivalent would be Open Topo Data: `“https://api.opentopodata.org/v1/aster30m?locations={locations}&key={key}”`

http_accept_language

[str] HTTP header accept-language. Default is `“en”`. Note that Nominatim’s default language is “en” and it can sort result importance scores differently if a different language is specified.

http_referer

[str] HTTP header referer. Default is `“OSMnx Python package (https://github.com/gboeing/osmnx)”`.

http_user_agent

[str] HTTP header user-agent. Default is `“OSMnx Python package (https://github.com/gboeing/osmnx)”`.

imgs_folder

[str or pathlib.Path] Path to folder in which to save plotted images by default. Default is `“./images”`.

log_file

[bool] If True, save log output to a file in `logs_folder`. Default is `False`.

log_filename

[str] Name of the log file, without file extension. Default is `“osmnx”`.

log_console

[bool] If True, print log output to the console (terminal window). Default is `False`.

log_level

[int] One of Python’s `logger.level` constants. Default is `logging.INFO`.

log_name

[str] Name of the logger. Default is `“OSMnx”`.

logs_folder

[str or pathlib.Path] Path to folder in which to save log files. Default is `“./logs”`.

max_query_area_size

[int] Maximum area for any part of the geometry in meters: any polygon bigger than this will get divided up for multiple queries to the API. Default is `2500000000`.

memory

[int] Do not use, deprecated. Use *overpass_memory* instead.

nominatim_endpoint

[str] Do not use, deprecated. Use *nominatim_url* instead.

nominatim_key

[str] Your Nominatim API key, if you are using an API instance that requires one. Default is *None*.

nominatim_url

[str] The base API url to use for Nominatim queries. Default is *"https://nominatim.openstreetmap.org/"*.

osm_xml_node_attrs

[list] Do not use, deprecated.

osm_xml_node_tags

[list] Do not use, deprecated.

osm_xml_way_attrs

[list] Do not use, deprecated.

osm_xml_way_tags

[list] Do not use, deprecated.

overpass_endpoint

[str] Do not use, deprecated. Use *overpass_url* instead.

overpass_memory

[int | None] Overpass server memory allocation size for the query, in bytes. If *None*, server will choose its default allocation size. Use with caution. Default is *None*.

overpass_rate_limit

[bool] If *True*, check the Overpass server status endpoint for how long to pause before making request. Necessary if server uses slot management, but can be set to *False* if you are running your own overpass instance without rate limiting. Default is *True*.

overpass_settings

[str] Settings string for Overpass queries. Default is *"[out:json][timeout:{timeout}][maxsize]"*. By default, the {timeout} and {maxsize} values are set dynamically by OSMnx when used. To query, for example, historical OSM data as of a certain date: *'[out:json][timeout:90][date:"2019-10-28T19:20:00Z"]'*. Use with caution.

overpass_url

[str] The base API url to use for Overpass queries. Default is *"https://overpass-api.de/api"*.

requests_kwargs

[dict] Optional keyword args to pass to the requests package when connecting to APIs, for example to configure authentication or provide a path to a local certificate file. More info on options such as auth, cert, verify, and proxies can be found in the requests package advanced docs. Default is *{}*.

requests_timeout

[int] The timeout interval in seconds for HTTP requests, and (when applicable) for Overpass server to use for executing the query. Default is *180*.

timeout

[int] Do not use, deprecated. Use *requests_timeout* instead.

use_cache

[bool] If *True*, cache HTTP responses locally instead of calling API repeatedly for the same request. Default is *True*.

useful_tags_node

[list] OSM “node” tags to add as graph node attributes, when present in the data retrieved from OSM. Default is [“ref”, “highway”].

useful_tags_way

[list] OSM “way” tags to add as graph edge attributes, when present in the data retrieved from OSM. Default is [“bridge”, “tunnel”, “oneway”, “lanes”, “ref”, “name”, “highway”, “maxspeed”, “service”, “access”, “area”, “landuse”, “width”, “est_width”, “junction”].

6.3.13 osmnx.simplification module

Simplify, correct, and consolidate network topology.

`osmnx.simplification.consolidate_intersections(G, tolerance=10, rebuild_graph=True, dead_ends=False, reconnect_edges=True)`

Consolidate intersections comprising clusters of nearby nodes.

Merges nearby nodes and returns either their centroids or a rebuilt graph with consolidated intersections and reconnected edge geometries. The tolerance argument should be adjusted to approximately match street design standards in the specific street network, and you should always use a projected graph to work in meaningful and consistent units like meters. Note the tolerance represents a per-node buffering radius: for example, to consolidate nodes within 10 meters of each other, use `tolerance=5`.

When `rebuild_graph=False`, it uses a purely geometrical (and relatively fast) algorithm to identify “geometrically close” nodes, merge them, and return just the merged intersections’ centroids. When `rebuild_graph=True`, it uses a topological (and slower but more accurate) algorithm to identify “topologically close” nodes, merge them, then rebuild/return the graph. Returned graph’s node IDs represent clusters rather than osmids. Refer to nodes’ `osmid_original` attributes for original osmids. If multiple nodes were merged together, the `osmid_original` attribute is a list of merged nodes’ osmids.

Divided roads are often represented by separate centerline edges. The intersection of two divided roads thus creates 4 nodes, representing where each edge intersects a perpendicular edge. These 4 nodes represent a single intersection in the real world. A similar situation occurs with roundabouts and traffic circles. This function consolidates nearby nodes by buffering them to an arbitrary distance, merging overlapping buffers, and taking their centroid.

Parameters

- **G** (*networkx.MultiDiGraph*) – a projected graph
- **tolerance** (*float*) – nodes are buffered to this distance (in graph’s geometry’s units) and subsequent overlaps are dissolved into a single node
- **rebuild_graph** (*bool*) – if True, consolidate the nodes topologically, rebuild the graph, and return as *networkx.MultiDiGraph*. if False, consolidate the nodes geometrically and return the consolidated node points as *geopandas.GeoSeries*
- **dead_ends** (*bool*) – if False, discard dead-end nodes to return only street-intersection points
- **reconnect_edges** (*bool*) – ignored if `rebuild_graph` is not True. if True, reconnect edges and their geometries in rebuilt graph to the consolidated nodes and update edge length attributes; if False, returned graph has no edges (which is faster if you just need topologically consolidated intersection counts).

Returns

if `rebuild_graph=True`, returns *MultiDiGraph* with consolidated intersections and reconnected edge geometries. if `rebuild_graph=False`, returns *GeoSeries* of shapely Points representing the centroids of street intersections

Return type

networkx.MultiDiGraph or geopandas.GeoSeries

```
osmnx.simplification.simplify_graph(G, strict=None, edge_attrs_differ=None, endpoint_attrs=None,
                                   remove_rings=True, track_merged=False)
```

Simplify a graph's topology by removing interstitial nodes.

This simplifies graph topology by removing all nodes that are not intersections or dead-ends, by creating an edge directly between the end points that encapsulate them while retaining the full geometry of the original edges, saved as a new *geometry* attribute on the new edge.

Note that only simplified edges receive a *geometry* attribute. Some of the resulting consolidated edges may comprise multiple OSM ways, and if so, their multiple attribute values are stored as a list. Optionally, the simplified edges can receive a *merged_edges* attribute that contains a list of all the (u, v) node pairs that were merged together.

Use the *edge_attrs_differ* parameter to relax simplification strictness. For example, *edge_attrs_differ=['osmid']* will retain every node whose incident edges have different OSM IDs. This lets you keep nodes at elbow two-way intersections (but be aware that sometimes individual blocks have multiple OSM IDs within them too). You could also use this parameter to retain nodes where sidewalks or bike lanes begin/end in the middle of a block.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **strict** (*bool*) – deprecated, do not use
- **edge_attrs_differ** (*iterable*) – An iterable of edge attribute names for relaxing the strictness of endpoint determination. If not None, a node is an endpoint if its incident edges have different values then each other for any of the edge attributes in *edge_attrs_differ*.
- **endpoint_attrs** (*iterable*) – deprecated, do not use
- **remove_rings** (*bool*) – if True, remove isolated self-contained rings that have no endpoints
- **track_merged** (*bool*) – if True, add *merged_edges* attribute on simplified edges, containing a list of all the (u, v) node pairs that were merged together

Returns

G – topologically simplified graph, with a new *geometry* attribute on each simplified edge

Return type

networkx.MultiDiGraph

6.3.14 osmnx.speed module

Calculate graph edge speeds and travel times.

```
osmnx.speed.add_edge_speeds(G, hwy_speeds=None, fallback=None, precision=None, agg=<function
                             mean>)
```

Do not use: deprecated.

Use the *routing.add_edge_speeds* function instead.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **hwy_speeds** (*dict*) – deprecated, do not use
- **fallback** (*numeric*) – deprecated, do not use

- **precision** (*int*) – deprecated, do not use
- **agg** (*function*) – deprecated, do not use

Returns**G****Return type**

networkx.MultiDiGraph

`osmnx.speed.add_edge_travel_times(G, precision=None)`

Do not use: deprecated.

Use the `routing.add_edge_travel_times` function instead.**Parameters**

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **precision** (*int*) – deprecated, do not use

Returns**G****Return type**

networkx.MultiDiGraph

6.3.15 osmnx.stats module

Calculate geometric and topological network measures.

This module defines streets as the edges in an undirected representation of the graph. Using undirected graph edges prevents double-counting bidirectional edges of a two-way street, but may double-count a divided road's separate centerlines with different end point nodes. If `clean_periphery=True` when the graph was created (which is the default parameterization), then you will get accurate node degrees (and in turn streets-per-node counts) even at the periphery of the graph.

You can use NetworkX directly for additional topological network measures.

`osmnx.stats.basic_stats(G, area=None, clean_int_tol=None)`

Calculate basic descriptive geometric and topological measures of a graph.

Density measures are only calculated if `area` is provided and clean intersection measures are only calculated if `clean_int_tol` is provided.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **area** (*float*) – if not None, calculate density measures and use this value (in square meters) as the denominator
- **clean_int_tol** (*float*) – if not None, calculate consolidated intersections count (and density, if `area` is also provided) and use this tolerance value; refer to the *simplification consolidate_intersections* function documentation for details

Returns**stats** –**dictionary containing the following keys**

- `circuitry_avg` - see `circuitry_avg` function documentation

- *clean_intersection_count* - see *clean_intersection_count* function documentation
- *clean_intersection_density_km* - *clean_intersection_count* per sq km
- *edge_density_km* - *edge_length_total* per sq km
- *edge_length_avg* - *edge_length_total* / *m*
- *edge_length_total* - see *edge_length_total* function documentation
- *intersection_count* - see *intersection_count* function documentation
- *intersection_density_km* - *intersection_count* per sq km
- *k_avg* - graph's average node degree (in-degree and out-degree)
- *m* - count of edges in graph
- *n* - count of nodes in graph
- *node_density_km* - *n* per sq km
- *self_loop_proportion* - see *self_loop_proportion* function documentation
- *street_density_km* - *street_length_total* per sq km
- *street_length_avg* - *street_length_total* / *street_segment_count*
- *street_length_total* - see *street_length_total* function documentation
- *street_segment_count* - see *street_segment_count* function documentation
- *streets_per_node_avg* - see *streets_per_node_avg* function documentation
- *streets_per_node_counts* - see *streets_per_node_counts* function documentation
- *streets_per_node_proportions* - see *streets_per_node_proportions* function documentation

Return type

dict

`osmnx.stats.circuitry_avg(Gu)`

Calculate average street circuitry using edges of undirected graph.

Circuitry is the sum of edge lengths divided by the sum of straight-line distances between edge endpoints. Calculates straight-line distance as euclidean distance if projected or great-circle distance if unprojected.

Parameters

Gu (*networkx.MultiGraph*) – undirected input graph

Returns

circuitry_avg – the graph's average undirected edge circuitry

Return type

float

`osmnx.stats.count_streets_per_node(G, nodes=None)`

Count how many physical street segments connect to each node in a graph.

This function uses an undirected representation of the graph and special handling of self-loops to accurately count physical streets rather than directed edges. Note: this function is automatically run by all the *graph.graph_from_x* functions prior to truncating the graph to the requested boundaries, to add accurate *street_count* attributes to each node even if some of its neighbors are outside the requested graph boundaries.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **nodes** (*list*) – which node IDs to get counts for. if None, use all graph nodes, otherwise calculate counts only for these node IDs

Returns

streets_per_node – counts of how many physical streets connect to each node, with keys = node ids and values = counts

Return type

dict

`osmnx.stats.edge_length_total(G)`

Calculate graph's total edge length.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

length – total length (meters) of edges in graph

Return type

float

`osmnx.stats.intersection_count(G=None, min_streets=2)`

Count the intersections in a graph.

Intersections are defined as nodes with at least *min_streets* number of streets incident on them.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **min_streets** (*int*) – a node must have at least *min_streets* incident on them to count as an intersection

Returns

count – count of intersections in graph

Return type

int

`osmnx.stats.self_loop_proportion(Gu)`

Calculate percent of edges that are self-loops in a graph.

A self-loop is defined as an edge from node *u* to node *v* where *u==v*.

Parameters

Gu (*networkx.MultiGraph*) – undirected input graph

Returns

proportion – proportion of graph edges that are self-loops

Return type

float

`osmnx.stats.street_length_total(Gu)`

Calculate graph's total street segment length.

Parameters

Gu (*networkx.MultiGraph*) – undirected input graph

Returns

length – total length (meters) of streets in graph

Return type

float

`osmnx.stats.street_segment_count(Gu)`

Count the street segments in a graph.

Parameters**Gu** (*networkx.MultiGraph*) – undirected input graph**Returns****count** – count of street segments in graph**Return type**

int

`osmnx.stats.streets_per_node(G)`

Count streets (undirected edges) incident on each node.

Parameters**G** (*networkx.MultiDiGraph*) – input graph**Returns****spn** – dictionary with node ID keys and street count values**Return type**

dict

`osmnx.stats.streets_per_node_avg(G)`

Calculate graph's average count of streets per node.

Parameters**G** (*networkx.MultiDiGraph*) – input graph**Returns****spna** – average count of streets per node**Return type**

float

`osmnx.stats.streets_per_node_counts(G)`

Calculate streets-per-node counts.

Parameters**G** (*networkx.MultiDiGraph*) – input graph**Returns****spnc** – dictionary keyed by count of streets incident on each node, and with values of how many nodes in the graph have this count**Return type**

dict

`osmnx.stats.streets_per_node_proportions(G)`

Calculate streets-per-node proportions.

Parameters**G** (*networkx.MultiDiGraph*) – input graph**Returns****spnp** – dictionary keyed by count of streets incident on each node, and with values of what proportion of nodes in the graph have this count

Return type

dict

6.3.16 osmnx.truncate module

Truncate graph by distance, bounding box, or polygon.

`osmnx.truncate.largest_component(G, strongly=False)`

Get subgraph of G's largest weakly/strongly connected component.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **strongly** (*bool*) – if True, return the largest strongly instead of weakly connected component

Returns

G – the largest connected component subgraph of the original graph

Return type

networkx.MultiDiGraph

`osmnx.truncate.truncate_graph_bbox(G, north=None, south=None, east=None, west=None, bbox=None, truncate_by_edge=False, retain_all=False, quadrat_width=None, min_num=None)`

Remove every node in graph that falls outside a bounding box.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node's neighbors is within the bounding box
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **quadrat_width** (*float*) – deprecated, do not use
- **min_num** (*int*) – deprecated, do not use

Returns

G – the truncated graph

Return type

networkx.MultiDiGraph

`osmnx.truncate.truncate_graph_dist(G, source_node, max_dist=1000, weight='length', retain_all=False)`

Remove every node farther than some network distance from `source_node`.

This function can be slow for large graphs, as it must calculate shortest path distances between `source_node` and every other graph node.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **source_node** (*int*) – node in graph from which to measure network distances to other nodes
- **max_dist** (*float*) – remove every node in the graph that is greater than this distance (in same units as *weight* attribute) along the network from *source_node*
- **weight** (*string*) – graph edge attribute to use to measure distance
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.

Returns

G – the truncated graph

Return type

networkx.MultiDiGraph

```
osmnx.truncate.truncate_graph_polygon(G, polygon, retain_all=False, truncate_by_edge=False,
                                       quadrat_width=None, min_num=None)
```

Remove every node in graph that falls outside a (Multi)Polygon.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **polygon** (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – only retain nodes in graph that lie within this geometry
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside boundary polygon if at least one of node's neighbors is within the polygon
- **quadrat_width** (*float*) – deprecated, do not use
- **min_num** (*int*) – deprecated, do not use

Returns

G – the truncated graph

Return type

networkx.MultiDiGraph

6.3.17 osmnx.utils module

General utility functions.

```
osmnx.utils.citation(style='bibtex')
```

Print the OSMnx package's citation information.

Boeing, G. (2024). Modeling and Analyzing Urban Networks and Amenities with OSMnx. Working paper. <https://geoffboeing.com/publications/osmnx-paper/>

Parameters

style (*string {"apa", "bibtex", "ieee"}*) – citation format, either APA or BibTeX or IEEE

Return type

None

```
osmnx.utils.config(all_oneway=False, bidirectional_network_types=['walk'], cache_folder='./cache',
                   cache_only_mode=False, data_folder='./data', default_accept_language=None,
                   default_access=['"access"!~"private"'], default_crs='epsg:4326', default_referer=None,
                   default_user_agent=None, imgs_folder='./images', log_console=False, log_file=False,
                   log_filename='osmnx', log_level=20, log_name='OSMnx', logs_folder='./logs',
                   max_query_area_size=2500000000, memory=None, nominatim_endpoint=None,
                   nominatim_key=None, osm_xml_node_attrs=None, osm_xml_node_tags=None,
                   osm_xml_way_attrs=None, osm_xml_way_tags=None, overpass_endpoint=None,
                   overpass_rate_limit=True, overpass_settings=['out:json'][timeout:{timeout}][maxsize],
                   requests_kwargs={}, timeout=None, use_cache=True, useful_tags_node=['ref', 'highway'],
                   useful_tags_way=['bridge', 'tunnel', 'oneway', 'lanes', 'ref', 'name', 'highway', 'maxspeed',
                                   'service', 'access', 'area', 'landuse', 'width', 'est_width', 'junction'])
```

Do not use: deprecated. Use the settings module directly.

Parameters

- **all_oneway** (*bool*) – deprecated
- **bidirectional_network_types** (*list*) – deprecated
- **cache_folder** (*string or pathlib.Path*) – deprecated
- **data_folder** (*string or pathlib.Path*) – deprecated
- **cache_only_mode** (*bool*) – deprecated
- **default_accept_language** (*string*) – deprecated
- **default_access** (*string*) – deprecated
- **default_crs** (*string*) – deprecated
- **default_referer** (*string*) – deprecated
- **default_user_agent** (*string*) – deprecated
- **imgs_folder** (*string or pathlib.Path*) – deprecated
- **log_file** (*bool*) – deprecated
- **log_filename** (*string*) – deprecated
- **log_console** (*bool*) – deprecated
- **log_level** (*int*) – deprecated
- **log_name** (*string*) – deprecated
- **logs_folder** (*string or pathlib.Path*) – deprecated
- **max_query_area_size** (*int*) – deprecated
- **memory** (*int*) – deprecated
- **nominatim_endpoint** (*string*) – deprecated
- **nominatim_key** (*string*) – deprecated
- **osm_xml_node_attrs** (*list*) – deprecated
- **osm_xml_node_tags** (*list*) – deprecated
- **osm_xml_way_attrs** (*list*) – deprecated

- **osm_xml_way_tags** (*list*) – deprecated
- **overpass_endpoint** (*string*) – deprecated
- **overpass_rate_limit** (*bool*) – deprecated
- **overpass_settings** (*string*) – deprecated
- **requests_kwargs** (*dict*) – deprecated
- **timeout** (*int*) – deprecated
- **use_cache** (*bool*) – deprecated
- **useful_tags_node** (*list*) – deprecated
- **useful_tags_way** (*list*) – deprecated

Return type

None

`osmnx.utils.log(message, level=None, name=None, filename=None)`

Write a message to the logger.

This logs to file and/or prints to the console (terminal), depending on the current configuration of settings.log_file and settings.log_console.

Parameters

- **message** (*string*) – the message to log
- **level** (*int*) – one of Python's logger.level constants
- **name** (*string*) – name of the logger
- **filename** (*string*) – name of the log file, without file extension

Return type

None

`osmnx.utils.ts(style='datetime', template=None)`

Return current local timestamp as a string.

Parameters

- **style** (*string* {"datetime", "date", "time"}) – format the timestamp with this built-in style
- **template** (*string*) – if not None, format the timestamp with this format string instead of one of the built-in styles

Returns

ts – local timestamp string

Return type

string

6.3.18 osmnx.utils_geo module

Geospatial utility functions.

`osmnx.utils_geo.bbox_from_point(point, dist=1000, project_utm=False, return_crs=False)`

Create a bounding box around a (lat, lon) point.

Create a bounding box some distance (in meters) in each direction (north, south, east, and west) from the center point and optionally project it.

Parameters

- **point** (*tuple*) – the (lat, lon) center point to create the bounding box around
- **dist** (*int*) – bounding box distance in meters from the center point
- **project_utm** (*bool*) – if True, return bounding box as UTM-projected coordinates
- **return_crs** (*bool*) – if True, and project_utm=True, return the projected CRS too

Returns

bbox or **bbox**, **crs** – (north, south, east, west) or ((north, south, east, west), crs)

Return type

tuple or tuple, crs

`osmnx.utils_geo.bbox_to_poly(north=None, south=None, east=None, west=None, bbox=None)`

Convert bounding box coordinates to shapely Polygon.

Parameters

- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)

Return type

shapely.geometry.Polygon

`osmnx.utils_geo.interpolate_points(geom, dist)`

Interpolate evenly spaced points along a LineString.

The spacing is approximate because the LineString's length may not be evenly divisible by it.

Parameters

- **geom** (*shapely.geometry.LineString*) – a LineString geometry
- **dist** (*float*) – spacing distance between interpolated points, in same units as *geom*. smaller values accordingly generate more points.

Yields

points (*generator*) – tuples of (x, y) floats of the interpolated points' coordinates

`osmnx.utils_geo.round_geometry_coords(geom, precision)`

Do not use: deprecated.

Parameters

- **geom** (*shapely.geometry.geometry {Point, MultiPoint, LineString, MultiLineString, Polygon, MultiPolygon}*) – deprecated, do not use

- **precision** (*int*) – deprecated, do not use

Return type

shapely.geometry.geometry

`osmnx.utils_geo.sample_points(G, n)`

Randomly sample points constrained to a spatial graph.

This generates a graph-constrained uniform random sample of points. Unlike typical spatially uniform random sampling, this method accounts for the graph's geometry. And unlike equal-length edge segmenting, this method guarantees uniform randomness.

Parameters

- **G** (*networkx.MultiGraph*) – graph from which to sample points. should be undirected (to avoid oversampling bidirectional edges) and projected (for accurate point interpolation)
- **n** (*int*) – how many points to sample

Returns

points – the sampled points, multi-indexed by (u, v, key) of the edge from which each point was drawn

Return type

geopandas.GeoSeries

6.3.19 osmnx.utils_graph module

Graph utility functions.

`osmnx.utils_graph.get_digraph(G, weight='length')`

Do not use: deprecated.

Use the `convert.to_digraph` function instead.**Parameters**

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **weight** (*string*) – deprecated, do not use

Return type

networkx.DiGraph

`osmnx.utils_graph.get_largest_component(G, strongly=False)`

Do not use: deprecated.

Use the `truncate.largest_component` function instead.**Parameters**

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **strongly** (*bool*) – deprecated, do not use

Returns**G****Return type**

networkx.MultiDiGraph

`osmnx.utils_graph.get_route_edge_attributes(G, route, attribute=None, minimize_key='length', retrieve_default=None)`

Do not use: deprecated.

Use the `routing.route_to_gdf` function instead.

Parameters

- **G** (`networkx.MultiDiGraph`) – deprecated, do not use
- **route** (`list`) – deprecated, do not use
- **attribute** (`string`) – deprecated, do not use
- **minimize_key** (`string`) – deprecated, do not use
- **retrieve_default** (`Callable[Tuple[Any, Any], Any]`) – deprecated, do not use

Returns

`attribute_values`

Return type

`list`

`osmnx.utils_graph.get_undirected(G)`

Do not use: deprecated.

Use the `convert.to_undirected` function instead.

Parameters

G (`networkx.MultiDiGraph`) – deprecated, do not use

Return type

`networkx.MultiGraph`

`osmnx.utils_graph.graph_from_gdfs(gdf_nodes, gdf_edges, graph_attrs=None)`

Do not use: deprecated.

Use the `convert.graph_from_gdfs` function instead.

Parameters

- **gdf_nodes** (`geopandas.GeoDataFrame`) – deprecated, do not use
- **gdf_edges** (`geopandas.GeoDataFrame`) – deprecated, do not use
- **graph_attrs** (`dict`) – deprecated, do not use

Returns

G

Return type

`networkx.MultiDiGraph`

`osmnx.utils_graph.graph_to_gdfs(G, nodes=True, edges=True, node_geometry=True, fill_edge_geometry=True)`

Do not use: deprecated.

Use the `convert.graph_to_gdfs` function instead.

Parameters

- **G** (`networkx.MultiDiGraph`) – deprecated, do not use
- **nodes** (`bool`) – deprecated, do not use

- **edges** (*bool*) – deprecated, do not use
- **node_geometry** (*bool*) – deprecated, do not use
- **fill_edge_geometry** (*bool*) – deprecated, do not use

Return type

geopandas.GeoDataFrame or tuple

`osmnx.utils_graph.remove_isolated_nodes(G, warn=True)`

Do not use: deprecated.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **warn** (*bool*) – deprecated, do not use

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.utils_graph.route_to_gdf(G, route, weight='length')`

Do not use: deprecated.

Use the `routing.route_to_gdf` function instead.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **route** (*list*) – deprecated, do not use
- **weight** (*string*) – deprecated, do not use

Returns

gdf_edges

Return type

geopandas.GeoDataFrame

6.4 Internals Reference

This is the complete OSMnx internals reference for developers, including private internal modules and functions. If you are instead looking for a user guide to OSMnx’s public API, see the [User Reference](#).

6.4.1 osmnx._api module

Expose most common parts of public API directly in package namespace.

6.4.2 osmnx.bearing module

Calculate graph edge bearings.

`osmnx.bearing._bearings_distribution(Gu, num_bins, min_length=0, weight=None)`

Compute distribution of bearings across evenly spaced bins.

Prevents bin-edge effects around common values like 0 degrees and 90 degrees by initially creating twice as many bins as desired, then merging them in pairs. For example, if `num_bins=36` is provided, then each bin will represent 10 degrees around the compass, with the first bin representing 355 degrees to 5 degrees.

Parameters

- **Gu** (*networkx.MultiGraph*) – undirected, unprojected graph with *bearing* attributes on each edge
- **num_bins** (*int*) – number of bins for the bearings histogram
- **min_length** (*float*) – ignore edges with *length* attributes less than *min_length*; useful to ignore the noise of many very short edges
- **weight** (*string*) – if not None, weight edges' bearings by this (non-null) edge attribute. for example, if “length” is provided, this will return 1 bearing observation per meter per street, which could result in a very large *bearings* array.

Returns

bin_counts, bin_edges – counts of bearings per bin and the bins edges

Return type

tuple of numpy.array

`osmnx.bearing._extract_edge_bearings(Gu, min_length=0, weight=None)`

Extract undirected graph's bidirectional edge bearings.

For example, if an edge has a bearing of 90 degrees then we will record bearings of both 90 degrees and 270 degrees for this edge.

Parameters

- **Gu** (*networkx.MultiGraph*) – undirected, unprojected graph with *bearing* attributes on each edge
- **min_length** (*float*) – ignore edges with *length* attributes less than *min_length*; useful to ignore the noise of many very short edges
- **weight** (*string*) – if not None, weight edges' bearings by this (non-null) edge attribute. for example, if “length” is provided, this will return 1 bearing observation per meter per street, which could result in a very large *bearings* array.

Returns

bearings – the graph's bidirectional edge bearings

Return type

numpy.array

`osmnx.bearing.add_edge_bearings(G, precision=None)`

Add compass *bearing* attributes to all graph edges.

Vectorized function to calculate (initial) bearing from origin node to destination node for each edge in a directed, unprojected graph then add these bearings as new edge attributes. Bearing represents angle in degrees (clock-wise) between north and the geodesic line from the origin node to the destination node. Ignores self-loop edges as their bearings are undefined.

Parameters

- **G** (*networkx.MultiDiGraph*) – unprojected graph
- **precision** (*int*) – deprecated, do not use

Returns

G – graph with edge bearing attributes

Return type

networkx.MultiDiGraph

`osmnx.bearing.calculate_bearing(lat1, lon1, lat2, lon2)`

Calculate the compass bearing(s) between pairs of lat-lon points.

Vectorized function to calculate initial bearings between two points' coordinates or between arrays of points' coordinates. Expects coordinates in decimal degrees. Bearing represents the clockwise angle in degrees between north and the geodesic line from (lat1, lon1) to (lat2, lon2).

Parameters

- **lat1** (*float or numpy.array of float*) – first point's latitude coordinate
- **lon1** (*float or numpy.array of float*) – first point's longitude coordinate
- **lat2** (*float or numpy.array of float*) – second point's latitude coordinate
- **lon2** (*float or numpy.array of float*) – second point's longitude coordinate

Returns

bearing – the bearing(s) in decimal degrees

Return type

float or numpy.array of float

`osmnx.bearing.orientation_entropy(Gu, num_bins=36, min_length=0, weight=None)`

Calculate undirected graph's orientation entropy.

Orientation entropy is the entropy of its edges' bidirectional bearings across evenly spaced bins. Ignores self-loop edges as their bearings are undefined.

For more info see: Boeing, G. 2019. "Urban Spatial Order: Street Network Orientation, Configuration, and Entropy." *Applied Network Science*, 4 (1), 67. <https://doi.org/10.1007/s41109-019-0189-1>

Parameters

- **Gu** (*networkx.MultiGraph*) – undirected, unprojected graph with *bearing* attributes on each edge
- **num_bins** (*int*) – number of bins; for example, if *num_bins=36* is provided, then each bin will represent 10 degrees around the compass
- **min_length** (*float*) – ignore edges with *length* attributes less than *min_length*; useful to ignore the noise of many very short edges
- **weight** (*string*) – if not *None*, weight edges' bearings by this (non-null) edge attribute. for example, if "length" is provided, this will return 1 bearing observation per meter per street, which could result in a very large *bearings* array.

Returns

entropy – the graph's orientation entropy

Return type

float

```
osmnx.bearing.plot_orientation(Gu, num_bins=36, min_length=0, weight=None, ax=None, figsize=(5, 5),
                               area=True, color='#003366', edgecolor='k', linewidth=0.5, alpha=0.7,
                               title=None, title_y=1.05, title_font=None, xtick_font=None)
```

Do not use: deprecated.

The `plot_orientation` function moved to the `plot` module. Calling it via the `bearing` module will raise an error starting in the v2.0.0 release.

Parameters

- **Gu** (*networkx.MultiGraph*) – deprecated, do not use
- **num_bins** (*int*) – deprecated, do not use
- **min_length** (*float*) – deprecated, do not use
- **weight** (*string*) – deprecated, do not use
- **ax** (*matplotlib.axes.PolarAxesSubplot*) – deprecated, do not use
- **figsize** (*tuple*) – deprecated, do not use
- **area** (*bool*) – deprecated, do not use
- **color** (*string*) – deprecated, do not use
- **edgecolor** (*string*) – deprecated, do not use
- **linewidth** (*float*) – deprecated, do not use
- **alpha** (*float*) – deprecated, do not use
- **title** (*string*) – deprecated, do not use
- **title_y** (*float*) – deprecated, do not use
- **title_font** (*dict*) – deprecated, do not use
- **xtick_font** (*dict*) – deprecated, do not use

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

6.4.3 osmnx.convert module

Convert spatial graphs to/from different data types.

```
osmnx.convert._is_duplicate_edge(data1, data2)
```

Check if two graph edge data dicts have the same osmid and geometry.

Parameters

- **data1** (*dict*) – the first edge's data
- **data2** (*dict*) – the second edge's data

Returns

is_dupe

Return type

bool

`osmnx.convert._is_same_geometry(ls1, ls2)`

Determine if two LineString geometries are the same (in either direction).

Check both the normal and reversed orders of their constituent points.

Parameters

- **ls1** (*shapely.geometry.LineString*) – the first LineString geometry
- **ls2** (*shapely.geometry.LineString*) – the second LineString geometry

Return type

bool

`osmnx.convert._update_edge_keys(G)`

Increment key of one edge of parallel edges that differ in geometry.

For example, two streets from u to v that bow away from each other as separate streets, rather than opposite direction edges of a single street. Increment one of these edge's keys so that they do not match across u, v, k or v, u, k so we can add both to an undirected MultiGraph.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.convert.graph_from_gdfs(gdf_nodes, gdf_edges, graph_attrs=None)`

Convert node and edge GeoDataFrames to a MultiDiGraph.

This function is the inverse of *graph_to_gdfs* and is designed to work in conjunction with it.

However, you can convert arbitrary node and edge GeoDataFrames as long as 1) *gdf_nodes* is uniquely indexed by *osmid*, 2) *gdf_nodes* contains *x* and *y* coordinate columns representing node geometries, 3) *gdf_edges* is uniquely multi-indexed by *u*, *v*, *key* (following normal MultiDiGraph structure). This allows you to load any node/edge shapefiles or GeoPackage layers as GeoDataFrames then convert them to a MultiDiGraph for graph analysis. Note that any *geometry* attribute on *gdf_nodes* is discarded since *x* and *y* provide the necessary node geometry information instead.

Parameters

- **gdf_nodes** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph nodes uniquely indexed by *osmid*
- **gdf_edges** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph edges uniquely multi-indexed by *u*, *v*, *key*
- **graph_attrs** (*dict*) – the new G.graph attribute dict. if None, use crs from *gdf_edges* as the only graph-level attribute (*gdf_edges* must have crs attribute set)

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.convert.graph_to_gdfs(G, nodes=True, edges=True, node_geometry=True, fill_edge_geometry=True)`

Convert a MultiDiGraph to node and/or edge GeoDataFrames.

This function is the inverse of *graph_from_gdfs*.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **nodes** (*bool*) – if True, convert graph nodes to a GeoDataFrame and return it
- **edges** (*bool*) – if True, convert graph edges to a GeoDataFrame and return it
- **node_geometry** (*bool*) – if True, create a geometry column from node x and y attributes
- **fill_edge_geometry** (*bool*) – if True, fill in missing edge geometry fields using nodes u and v

Returns

gdf_nodes or gdf_edges or tuple of (gdf_nodes, gdf_edges). gdf_nodes is indexed by osmid and gdf_edges is multi-indexed by u, v, key following normal MultiDiGraph structure.

Return type

geopandas.GeoDataFrame or tuple

`osmnx.convert.to_digraph(G, weight='length')`

Convert MultiDiGraph to DiGraph.

Chooses between parallel edges by minimizing *weight* attribute value. Note: see also *to_undirected* to convert MultiDiGraph to MultiGraph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **weight** (*string*) – attribute value to minimize when choosing between parallel edges

Return type

networkx.DiGraph

`osmnx.convert.to_undirected(G)`

Convert MultiDiGraph to undirected MultiGraph.

Maintains parallel edges only if their geometries differ. Note: see also *to_digraph* to convert MultiDiGraph to DiGraph.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Return type

networkx.MultiGraph

6.4.4 osmnx.distance module

Calculate distances and find nearest node/edge(s) to point(s).

`osmnx.distance.add_edge_lengths(G, precision=None, edges=None)`

Add *length* attribute (in meters) to each edge.

Vectorized function to calculate great-circle distance between each edge's incident nodes. Ensure graph is in unprojected coordinates, and unsimplified to get accurate distances.

Note: this function is run by all the *graph.graph_from_x* functions automatically to add *length* attributes to all edges. It calculates edge lengths as the great-circle distance from node *u* to node *v*. When OSMnx automatically runs this function upon graph creation, it does it before simplifying the graph: thus it calculates the straight-line lengths of edge segments that are themselves all straight. Only after simplification do edges take on a (potentially) curvilinear geometry. If you wish to calculate edge lengths later, you are calculating straight-line distances which

necessarily ignore the curvilinear geometry. You only want to run this function on a graph with all straight edges (such as is the case with an unsimplified graph).

Parameters

- **G** (*networkx.MultiDiGraph*) – unprojected, unsimplified input graph
- **precision** (*int*) – deprecated, do not use
- **edges** (*tuple*) – tuple of (u, v, k) tuples representing subset of edges to add length attributes to. if None, add lengths to all edges.

Returns

G – graph with edge length attributes

Return type

networkx.MultiDiGraph

osmnx.distance.**euclidean**(y1, x1, y2, x2)

Calculate Euclidean distances between pairs of points.

Vectorized function to calculate the Euclidean distance between two points' coordinates or between arrays of points' coordinates. For accurate results, use projected coordinates rather than decimal degrees.

Parameters

- **y1** (*float or numpy.array of float*) – first point's y coordinate
- **x1** (*float or numpy.array of float*) – first point's x coordinate
- **y2** (*float or numpy.array of float*) – second point's y coordinate
- **x2** (*float or numpy.array of float*) – second point's x coordinate

Returns

dist – distance from each (x1, y1) to each (x2, y2) in coordinates' units

Return type

float or numpy.array of float

osmnx.distance.**euclidean_dist_vec**(y1, x1, y2, x2)

Do not use, deprecated.

The *euclidean_dist_vec* function has been renamed *euclidean*. Calling *euclidean_dist_vec* will raise an error in the v2.0.0 release.

Parameters

- **y1** (*float or numpy.array of float*) – first point's y coordinate
- **x1** (*float or numpy.array of float*) – first point's x coordinate
- **y2** (*float or numpy.array of float*) – second point's y coordinate
- **x2** (*float or numpy.array of float*) – second point's x coordinate

Returns

dist – distance from each (x1, y1) to each (x2, y2) in coordinates' units

Return type

float or numpy.array of float

`osmnx.distance.great_circle(lat1, lon1, lat2, lon2, earth_radius=6371009)`

Calculate great-circle distances between pairs of points.

Vectorized function to calculate the great-circle distance between two points' coordinates or between arrays of points' coordinates using the haversine formula. Expects coordinates in decimal degrees.

Parameters

- **lat1** (*float or numpy.array of float*) – first point's latitude coordinate
- **lon1** (*float or numpy.array of float*) – first point's longitude coordinate
- **lat2** (*float or numpy.array of float*) – second point's latitude coordinate
- **lon2** (*float or numpy.array of float*) – second point's longitude coordinate
- **earth_radius** (*float*) – earth's radius in units in which distance will be returned (default is meters)

Returns

dist – distance from each (lat1, lon1) to each (lat2, lon2) in units of earth_radius

Return type

float or numpy.array of float

`osmnx.distance.great_circle_vec(lat1, lng1, lat2, lng2, earth_radius=6371009)`

Do not use, deprecated.

The *great_circle_vec* function has been renamed *great_circle*. Calling *great_circle_vec* will raise an error in the v2.0.0 release.

Parameters

- **lat1** (*float or numpy.array of float*) – first point's latitude coordinate
- **lng1** (*float or numpy.array of float*) – first point's longitude coordinate
- **lat2** (*float or numpy.array of float*) – second point's latitude coordinate
- **lng2** (*float or numpy.array of float*) – second point's longitude coordinate
- **earth_radius** (*float*) – earth's radius in units in which distance will be returned (default is meters)

Returns

dist – distance from each (lat1, lng1) to each (lat2, lng2) in units of earth_radius

Return type

float or numpy.array of float

`osmnx.distance.k_shortest_paths(G, orig, dest, k, weight='length')`

Do not use, deprecated.

The *k_shortest_paths* function has moved to the *routing* module. Calling it via the *distance* module will raise an error in the v2.0.0 release.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int*) – origin node ID
- **dest** (*int*) – destination node ID
- **k** (*int*) – number of shortest paths to solve

- **weight** (*string*) – edge attribute to minimize when solving shortest paths. default is edge length in meters.

Yields

path (*list*) – a generator of k shortest paths ordered by total weight. each path is a list of node IDs.

`osmnx.distance.nearest_edges(G, X, Y, interpolate=None, return_dist=False)`

Find the nearest edge to a point or to each of several points.

If X and Y are single coordinate values, this will return the nearest edge to that point. If X and Y are lists of coordinate values, this will return the nearest edge to each point. This function uses an R-tree spatial index and minimizes the euclidean distance from each point to the possible matches. For accurate results, use a projected graph and points.

Parameters

- **G** (*networkx.MultiDiGraph*) – graph in which to find nearest edges
- **X** (*float or list*) – points' x (longitude) coordinates, in same CRS/units as graph and containing no nulls
- **Y** (*float or list*) – points' y (latitude) coordinates, in same CRS/units as graph and containing no nulls
- **interpolate** (*float*) – deprecated, do not use
- **return_dist** (*bool*) – optionally also return distance between points and nearest edges

Returns

ne or (**ne, dist**) – nearest edges as (u, v, key) or optionally a tuple where *dist* contains distances between the points and their nearest edges

Return type

tuple or list

`osmnx.distance.nearest_nodes(G, X, Y, return_dist=False)`

Find the nearest node to a point or to each of several points.

If X and Y are single coordinate values, this will return the nearest node to that point. If X and Y are lists of coordinate values, this will return the nearest node to each point.

If the graph is projected, this uses a k-d tree for euclidean nearest neighbor search, which requires that *scipy* is installed as an optional dependency. If it is unprojected, this uses a ball tree for haversine nearest neighbor search, which requires that *scikit-learn* is installed as an optional dependency.

Parameters

- **G** (*networkx.MultiDiGraph*) – graph in which to find nearest nodes
- **X** (*float or list*) – points' x (longitude) coordinates, in same CRS/units as graph and containing no nulls
- **Y** (*float or list*) – points' y (latitude) coordinates, in same CRS/units as graph and containing no nulls
- **return_dist** (*bool*) – optionally also return distance between points and nearest nodes

Returns

nn or (**nn, dist**) – nearest node IDs or optionally a tuple where *dist* contains distances between the points and their nearest nodes

Return type

int/list or tuple

`osmnx.distance.shortest_path(G, orig, dest, weight='length', cpus=1)`

Do not use, deprecated.

The *shortest_path* function has moved to the *routing* module. Calling it via the *distance* module will raise an error in the v2.0.0 release.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int or list*) – origin node ID, or a list of origin node IDs
- **dest** (*int or list*) – destination node ID, or a list of destination node IDs
- **weight** (*string*) – edge attribute to minimize when solving shortest path
- **cpus** (*int*) – how many CPU cores to use; if None, use all available

Returns

path – list of node IDs constituting the shortest path, or, if orig and dest are lists, then a list of path lists

Return type

list

6.4.5 osmnx._downloader module

Handle HTTP requests to web APIs.

`osmnx._downloader._config_dns(url)`

Force socket.getaddrinfo to use IP address instead of hostname.

Resolves the URL's domain to an IP address so that we use the same server for both 1) checking the necessary pause duration and 2) sending the query itself even if there is round-robin redirecting among multiple server machines on the server-side. Mutates the getaddrinfo function so it uses the same IP address everytime it finds the hostname in the URL.

For example, the server `overpass-api.de` just redirects to one of the other servers (currently `gall.openstreetmap.de` and `lambert.openstreetmap.de`). So if we check the status endpoint of `overpass-api.de`, we may see results for server `gall`, but when we submit the query itself it gets redirected to server `lambert`. This could result in violating server `lambert`'s slot management timing.

Parameters

url (*string*) – the URL to consistently resolve the IP address of

Return type

None

`osmnx._downloader._get_http_headers(user_agent=None, referer=None, accept_language=None)`

Update the default requests HTTP headers with OSMnx info.

Parameters

- **user_agent** (*string*) – the user agent string, if None will set with OSMnx default
- **referer** (*string*) – the referer string, if None will set with OSMnx default
- **accept_language** (*string*) – make accept-language explicit e.g. for consistent nominatim result sorting

Returns

headers

Return type

dict

`osmnx._downloader._hostname_from_url(url)`

Extract the hostname (domain) from a URL.

Parameters**url** (*string*) – the url from which to extract the hostname**Returns****hostname** – the extracted hostname (domain)**Return type**

string

`osmnx._downloader._parse_response(response)`

Parse JSON from a requests response and log the details.

Parameters**response** (*requests.response*) – the response object**Returns****response_json****Return type**

dict

`osmnx._downloader._resolve_host_via_doh(hostname)`

Resolve hostname to IP address via Google's public DNS-over-HTTPS API.

Necessary fallback as `socket.gethostbyname` will not always work when using a proxy. See <https://developers.google.com/speed/public-dns/docs/doh/json> If the user has set `settings.doh_url_template=None` or if resolution fails (e.g., due to local network blocking DNS-over-HTTPS) the hostname itself will be returned instead. Note that this means that server slot management may be violated: see `_config_dns` documentation for details.

Parameters**hostname** (*string*) – the hostname to consistently resolve the IP address of**Returns****ip_address** – resolved IP address of host, or hostname itself if resolution failed**Return type**

string

`osmnx._downloader._retrieve_from_cache(url, check_remark=True)`

Retrieve a HTTP response JSON object from the cache, if it exists.

Parameters

- **url** (*string*) – the URL of the request
- **check_remark** (*string*) – if True, only return filepath if cached response does not have a remark key indicating a server warning

Returns**response_json** – cached response for url if it exists in the cache, otherwise None**Return type**

dict

`osmnx._downloader._save_to_cache(url, response_json, ok)`

Save a HTTP response JSON object to a file in the cache folder.

Function calculates the checksum of url to generate the cache file's name. If the request was sent to server via POST instead of GET, then URL should be a GET-style representation of request. Response is only saved to a cache file if `settings.use_cache` is True, `response_json` is not None, and `ok` is True.

Users should always pass OrderedDicts instead of dicts of parameters into request functions, so the parameters remain in the same order each time, producing the same URL string, and thus the same hash. Otherwise the cache will eventually contain multiple saved responses for the same request because the URL's parameters appeared in a different order each time.

Parameters

- **url** (*string*) – the URL of the request
- **response_json** (*dict*) – the JSON response
- **ok** (*bool*) – requests response.ok value

Return type

None

`osmnx._downloader._url_in_cache(url)`

Determine if a URL's response exists in the cache.

Calculates the checksum of url to determine the cache file's name.

Parameters

url (*string*) – the URL to look for in the cache

Returns

filepath – path to cached response for url if it exists, otherwise None

Return type

pathlib.Path

6.4.6 osmnx.elevation module

Add node elevations from raster files or web APIs, and calculate edge grades.

`osmnx.elevation._elevation_request(url, pause)`

Send a HTTP GET request to Google Maps-style Elevation API.

Parameters

- **url** (*string*) – URL for API endpoint populated with request data
- **pause** (*float*) – how long to pause in seconds before request

Returns

response_json

Return type

dict

`osmnx.elevation._query_raster(nodes, filepath, band)`

Query a raster for values at coordinates in a DataFrame's x/y columns.

Parameters

- **nodes** (*pandas.DataFrame*) – DataFrame indexed by node ID and with two columns: x and y

- **filepath** (*string* or *pathlib.Path*) – path to the raster file or VRT to query
- **band** (*int*) – which raster band to query

Returns

nodes_values – zipped node IDs and corresponding raster values

Return type

zip

`osmnx.elevation.add_edge_grades(G, add_absolute=True, precision=None)`

Add *grade* attribute to each graph edge.

Vectorized function to calculate the directed grade (ie, rise over run) for each edge in the graph and add it to the edge as an attribute. Nodes must already have *elevation* attributes to use this function.

See also the *add_node_elevations_raster* and *add_node_elevations_google* functions.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph with *elevation* node attribute
- **add_absolute** (*bool*) – if True, also add absolute value of grade as *grade_abs* attribute
- **precision** (*int*) – deprecated, do not use

Returns

G – graph with edge *grade* (and optionally *grade_abs*) attributes

Return type

networkx.MultiDiGraph

`osmnx.elevation.add_node_elevations_google(G, api_key=None, batch_size=350, pause=0, max_locations_per_batch=None, precision=None, url_template=None)`

Add an *elevation* (meters) attribute to each node using a web service.

By default, this uses the Google Maps Elevation API but you can optionally use an equivalent API with the same interface and response format, such as Open Topo Data, via the *settings* module's *elevation_url_template*. The Google Maps Elevation API requires an API key but other providers may not.

For a free local alternative see the *add_node_elevations_raster* function. See also the *add_edge_grades* function.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **api_key** (*string*) – a valid API key, can be None if the API does not require a key
- **batch_size** (*int*) – max number of coordinate pairs to submit in each API call (if this is too high, the server will reject the request because its character limit exceeds the max allowed)
- **pause** (*float*) – time to pause between API calls, which can be increased if you get rate limited
- **max_locations_per_batch** (*int*) – deprecated, do not use
- **precision** (*int*) – deprecated, do not use
- **url_template** (*string*) – deprecated, do not use

Returns

G – graph with node elevation attributes

Return type

networkx.MultiDiGraph

`osmnx.elevation.add_node_elevations_raster(G, filepath, band=1, cpus=None)`

Add *elevation* attribute to each node from local raster file(s).

If *filepath* is a list of paths, this will generate a virtual raster composed of the files at those paths as an intermediate step.

See also the *add_edge_grades* function.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph, in same CRS as raster
- **filepath** (*string or pathlib.Path or list of strings/Paths*) – path (or list of paths) to the raster file(s) to query
- **band** (*int*) – which raster band to query
- **cpus** (*int*) – how many CPU cores to use; if *None*, use all available

Returns

G – graph with node elevation attributes

Return type

`networkx.MultiDiGraph`

6.4.7 osmnx._errors module

Define custom errors and exceptions.

exception `osmnx._errors.CacheOnlyInterruptError`

Exception for `settings.cache_only_mode=True` interruption.

exception `osmnx._errors.GraphSimplificationError`

Exception for a problem with graph simplification.

exception `osmnx._errors.InsufficientResponseError`

Exception for empty or too few results in server response.

exception `osmnx._errors.ResponseStatusCodeError`

Exception for an unhandled server response status code.

6.4.8 osmnx.features module

Download OpenStreetMap geospatial features' geometries and attributes.

Retrieve points of interest, building footprints, transit lines/stops, or any other map features from OSM, including their geometries and attribute data, then construct a `GeoDataFrame` of them. You can use this module to query for nodes, ways, and relations (the latter of type “multipolygon” or “boundary” only) by passing a dictionary of desired OSM tags.

For more details, see https://wiki.openstreetmap.org/wiki/Map_features and <https://wiki.openstreetmap.org/wiki/Elements>

Refer to the Getting Started guide for usage limitations.

`osmnx.features._assemble_multipolygon_component_polygons(element, geometries)`

Assemble a `MultiPolygon` from its component `LineStrings` and `Polygons`.

The OSM wiki suggests an algorithm for assembling multipolygon geometries <https://wiki.openstreetmap.org/wiki/Relation:multipolygon/Algorithm>. This method takes a simpler approach relying on the accurate tagging

of component ways with ‘inner’ and ‘outer’ roles as required on this page <https://wiki.openstreetmap.org/wiki/Relation:multipolygon>.

Parameters

- **element** (*dict*) – element type “relation” from overpass response JSON
- **geometries** (*dict*) – dict containing all linestrings and polygons generated from OSM ways

Returns

geometry – a single MultiPolygon object

Return type

shapely.geometry.MultiPolygon

`osmnx.features._buffer_invalid_geometries(gdf)`

Buffer any invalid geometries remaining in the GeoDataFrame.

Invalid geometries in the GeoDataFrame (which may accurately reproduce invalid geometries in OpenStreetMap) can cause the filtering to the query polygon and other subsequent geometric operations to fail. This function logs the ids of the invalid geometries and applies a buffer of zero to try to make them valid.

Note: the resulting geometries may differ from the originals - please check them against OpenStreetMap

Parameters

gdf (*geopandas.GeoDataFrame*) – a GeoDataFrame with possibly invalid geometries

Returns

gdf – the GeoDataFrame with `.buffer(0)` applied to invalid geometries

Return type

geopandas.GeoDataFrame

`osmnx.features._create_gdf(response_jsons, polygon, tags)`

Parse JSON responses from the Overpass API to a GeoDataFrame.

Note: the *polygon* and *tags* arguments can both be *None* and the GeoDataFrame will still be created but it won’t be filtered at the end i.e. the final GeoDataFrame will contain all tagged features in the *response_jsons*.

Parameters

- **response_jsons** (*list*) – list of JSON responses from from the Overpass API
- **polygon** (*shapely.geometry.Polygon*) – geographic boundary used for filtering the final GeoDataFrame
- **tags** (*dict*) – dict of tags used for filtering the final GeoDataFrame

Returns

gdf – GeoDataFrame of features and their associated tags

Return type

geopandas.GeoDataFrame

`osmnx.features._filter_gdf_by_polygon_and_tags(gdf, polygon, tags)`

Filter the GeoDataFrame to the requested bounding polygon and tags.

Filters GeoDataFrame to query polygon and tags. Removes columns of all NaNs (that held values only in rows removed by the filters). Resets the index of GeoDataFrame, writing it into a new column called ‘unique_id’.

Parameters

- **gdf** (*geopandas.GeoDataFrame*) – the GeoDataFrame to filter

- **polygon** (*shapely.geometry.Polygon*) – polygon defining the boundary of the requested area
- **tags** (*dict*) – the tags requested

Returns

gdf – final filtered GeoDataFrame

Return type

geopandas.GeoDataFrame

```
osmnx.features._is_closed_way_a_polygon(element, polygon_features={'aeroway': {'polygon': 'blocklist',  
                                     'values': ['taxiway']}, 'amenity': {'polygon': 'all', 'area':  
                                     {'polygon': 'all', 'area': highway: {'polygon': 'all', 'barrier':  
                                     {'polygon': 'passlist', 'values': ['city_wall', 'ditch', 'hedge',  
                                     'retaining_wall', 'spikes']}, 'boundary': {'polygon': 'all',  
                                     'building': {'polygon': 'all', 'building:part': {'polygon': 'all',  
                                     'craft': {'polygon': 'all', 'golf': {'polygon': 'all', 'highway':  
                                     {'polygon': 'passlist', 'values': ['services', 'rest_area', 'escape',  
                                     'elevator']}, 'historic': {'polygon': 'all', 'indoor': {'polygon':  
                                     'all', 'landuse': {'polygon': 'all', 'leisure': {'polygon': 'all',  
                                     'man_made': {'polygon': 'blocklist', 'values': ['cutline',  
                                     'embankment', 'pipeline']}, 'military': {'polygon': 'all', 'natural':  
                                     {'polygon': 'blocklist', 'values': ['coastline', 'cliff', 'ridge', 'arete',  
                                     'tree_row']}, 'office': {'polygon': 'all', 'place': {'polygon': 'all',  
                                     'power': {'polygon': 'passlist', 'values': ['plant', 'substation',  
                                     'generator', 'transformer']}, 'public_transport': {'polygon': 'all',  
                                     'railway': {'polygon': 'passlist', 'values': ['station', 'turntable',  
                                     'roundhouse', 'platform']}, 'ruins': {'polygon': 'all', 'shop':  
                                     {'polygon': 'all', 'tourism': {'polygon': 'all', 'waterway':  
                                     {'polygon': 'passlist', 'values': ['riverbank', 'dock', 'boatyard',  
                                     'dam']}}})
```

Determine whether a closed OSM way represents a Polygon, not a LineString.

Closed OSM ways may represent LineStrings (e.g. a roundabout or hedge round a field) or Polygons (e.g. a building footprint or land use area) depending on the tags applied to them.

The starting assumption is that it is not a polygon, however any polygon type tagging will return a polygon unless explicitly tagged with area:no.

It is possible for a single closed OSM way to have both LineString and Polygon type tags (e.g. both barrier=fence and landuse=agricultural). OSMnx will return a single Polygon for elements tagged in this way. For more information see: https://wiki.openstreetmap.org/wiki/One_feature,_one_OSM_element)

Parameters

- **element** (*dict*) – closed element type “way” from overpass response JSON
- **polygon_features** (*dict*) – dict of tag keys with associated values and blocklist/passlist

Returns

is_polygon – True if the tags are for a polygon type geometry

Return type

bool

```
osmnx.features._parse_node_to_coords(element)
```

Parse coordinates from a node in the overpass response.

The coords are only used to create LineStrings and Polygons.

Parameters

element (*dict*) – element type “node” from overpass response JSON

Returns

coords – dict of latitude/longitude coordinates

Return type

dict

`osmnx.features._parse_node_to_point(element)`

Parse point from a tagged node in the overpass response.

The points are geometries in their own right.

Parameters

element (*dict*) – element type “node” from overpass response JSON

Returns

point – dict of OSM ID, OSM element type, tags and geometry

Return type

dict

`osmnx.features._parse_relation_to_multipolygon(element, geometries)`

Parse multipolygon from OSM relation (type:MultiPolygon).

See more information about relations from OSM documentation: <https://wiki.openstreetmap.org/wiki/Relation>

Parameters

- **element** (*dict*) – element type “relation” from overpass response JSON
- **geometries** (*dict*) – dict containing all linestrings and polygons generated from OSM ways

Returns

multipolygon – dict of tags and geometry for a single multipolygon

Return type

dict

`osmnx.features._parse_way_to_linestring_or_polygon(element, coords)`

Parse open LineString, closed LineString or Polygon from OSM ‘way’.

Please see https://wiki.openstreetmap.org/wiki/Overpass_turbo/Polygon_Features for more information on which tags should be parsed to polygons

Parameters

- **element** (*dict*) – element type “way” from overpass response JSON
- **coords** (*dict*) – dict of node IDs and their latitude/longitude coordinates

Returns

linestring_or_polygon – dict of OSM ID, OSM element type, nodes, tags and geometry

Return type

dict

`osmnx.features._subtract_inner_polygons_from_outer_polygons(element, outer_polygons, inner_polygons)`

Subtract inner polygons from outer polygons.

Creates a Polygon or MultiPolygon with holes.

Parameters

- **element** (*dict*) – element type “relation” from overpass response JSON
- **outer_polygons** (*list*) – list of outer polygons that are part of a multipolygon
- **inner_polygons** (*list*) – list of inner polygons that are part of a multipolygon

Returns

geometry – a single Polygon or MultiPolygon

Return type

shapely.geometry.Polygon or shapely.geometry.MultiPolygon

`osmnx.features.features_from_address(address, tags, dist=1000)`

Create GeoDataFrame of OSM features within some distance N, S, E, W of address.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **address** (*string*) – the address to geocode and use as the central point around which to get the features
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, `tags = {'building': True}` would return all building footprints in the area. `tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}` would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **dist** (*numeric*) – distance in meters

Returns

gdf

Return type

geopandas.GeoDataFrame

`osmnx.features.features_from_bbox(north=None, south=None, east=None, west=None, bbox=None, tags=None)`

Create a GeoDataFrame of OSM features within a N, S, E, W bounding box.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)

- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.

Returns**gdf****Return type**

geopandas.GeoDataFrame

`osmnx.features.features_from_place(query, tags, which_result=None, buffer_dist=None)`

Create GeoDataFrame of OSM features within boundaries of some place(s).

The query must be geocodable and OSM must have polygon boundaries for the geocode result. If OSM does not have a polygon for this place, you can instead get features within it using the *features_from_address* function, which geocodes the place name to a point and gets the features within some distance of that point.

If OSM does have polygon boundaries for this place but you're not finding it, try to vary the query string, pass in a structured query dict, or vary the *which_result* argument to use a different geocode result. If you know the OSM ID of the place, you can retrieve its boundary polygon using the *geocode_to_gdf* function, then pass it to the *features_from_polygon* function.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **query** (*string or dict or list*) – the query or queries to geocode to get place boundary polygon(s)
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **which_result** (*int*) – which geocoding result to use. if None, auto-select the first (Multi)Polygon or raise an error if OSM doesn't return one.
- **buffer_dist** (*float*) – deprecated, do not use

Returns**gdf****Return type**

geopandas.GeoDataFrame

`osmnx.features.features_from_point(center_point, tags, dist=1000)`

Create GeoDataFrame of OSM features within some distance N, S, E, W of a point.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **center_point** (*tuple*) – the (lat, lon) center point around which to get the features
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **dist** (*numeric*) – distance in meters

Returns

gdf

Return type

geopandas.GeoDataFrame

`osmnx.features.features_from_polygon(polygon, tags)`

Create GeoDataFrame of OSM features within boundaries of a (multi)polygon.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **polygon** (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – geographic boundaries to fetch features within
- **tags** (*dict*) – Dict of tags used for finding elements in the selected area. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.

Returns

gdf

Return type

geopandas.GeoDataFrame

`osmnx.features.features_from_xml(filepath, polygon=None, tags=None, encoding='utf-8')`

Create a GeoDataFrame of OSM features in an OSM-formatted XML file.

Because this function creates a GeoDataFrame of features from an OSM-formatted XML file that has already been downloaded (i.e. no query is made to the Overpass API) the polygon and tags arguments are not required. If they are not supplied to the function, `features_from_xml()` will return features for all of the tagged elements in the file. If they are supplied they will be used to filter the final GeoDataFrame.

For more details, see: https://wiki.openstreetmap.org/wiki/Map_features

Parameters

- **filepath** (*string* or *pathlib.Path*) – path to file containing OSM XML data
- **polygon** (*shapely.geometry.Polygon*) – optional geographic boundary to filter elements
- **tags** (*dict*) – optional dict of tags for filtering elements from the XML. Results returned are the union, not intersection of each individual tag. Each result matches at least one given tag. The dict keys should be OSM tags, (e.g., *building*, *landuse*, *highway*, etc) and the dict values should be either *True* to retrieve all items with the given tag, or a string to get a single tag-value combination, or a list of strings to get multiple values for the given tag. For example, *tags = {'building': True}* would return all building footprints in the area. *tags = {'amenity': True, 'landuse': ['retail', 'commercial'], 'highway': 'bus_stop'}* would return all amenities, landuse=retail, landuse=commercial, and highway=bus_stop.
- **encoding** (*string*) – the XML file's character encoding

Returns**gdf****Return type**

geopandas.GeoDataFrame

6.4.9 osmnx.folium module

Create interactive Leaflet web maps of graphs and routes via folium.

This module is deprecated. Do not use. It will be removed in the v2.0.0 release. You can generate and explore interactive web maps of graph nodes, edges, and/or routes automatically using `GeoPandas.GeoDataFrame.explore` instead, for example like: `ox.graph_to_gdfs(G, nodes=False).explore()`. See the OSMnx examples gallery for complete details and demonstrations.

`osmnx.folium._make_folium_polyline(geom, popup_val=None, **kwargs)`

Turn LineString geometry into a folium PolyLine with attributes.

Parameters

- **geom** (*shapely LineString*) – geometry of the line
- **popup_val** (*string*) – text to display in pop-up when a line is clicked, if None, no popup
- **kwargs** – keyword arguments to pass to `folium.PolyLine()`

Returns**pl****Return type**

folium.PolyLine

`osmnx.folium._plot_folium(gdf, m, popup_attribute, tiles, zoom, fit_bounds, **kwargs)`

Plot a GeoDataFrame of LineStrings on a folium map object.

Parameters

- **gdf** (*geopandas.GeoDataFrame*) – a GeoDataFrame of LineString geometries and attributes
- **m** (*folium.folium.Map* or *folium.FeatureGroup*) – if not None, plot on this preexisting folium map object
- **popup_attribute** (*string*) – attribute to display in pop-up on-click, if None, no popup
- **tiles** (*string*) – name of a folium tileset

- **zoom** (*int*) – initial zoom level for the map
- **fit_bounds** (*bool*) – if True, fit the map to gdf’s boundaries
- **kwargs** – keyword arguments to pass to folium.PolyLine()

Returns

m

Return type

folium.folium.Map

```
osmnx.folium.plot_graph_folium(G, graph_map=None, popup_attribute=None, tiles='cartodbpositron',
                               zoom=1, fit_bounds=True, **kwargs)
```

Do not use: deprecated.

You can generate and explore interactive web maps of graph nodes, edges, and/or routes automatically using GeoPandas.GeoDataFrame.explore instead, for example like: *ox.graph_to_gdfs(G, nodes=False).explore()*. See the OSMnx examples gallery for complete details and demonstrations.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated
- **graph_map** (*folium.folium.Map*) – deprecated
- **popup_attribute** (*string*) – deprecated
- **tiles** (*string*) – deprecated
- **zoom** (*int*) – deprecated
- **fit_bounds** (*bool*) – deprecated
- **kwargs** – deprecated

Return type

folium.folium.Map

```
osmnx.folium.plot_route_folium(G, route, route_map=None, popup_attribute=None, tiles='cartodbpositron',
                               zoom=1, fit_bounds=True, **kwargs)
```

Do not use: deprecated.

You can generate and explore interactive web maps of graph nodes, edges, and/or routes automatically using GeoPandas.GeoDataFrame.explore instead, for example like: *ox.graph_to_gdfs(G, nodes=False).explore()*. See the OSMnx examples gallery for complete details and demonstrations.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated
- **route** (*list*) – deprecated
- **route_map** (*folium.folium.Map*) – deprecated
- **popup_attribute** (*string*) – deprecated
- **tiles** (*string*) – deprecated
- **zoom** (*int*) – deprecated
- **fit_bounds** (*bool*) – deprecated
- **kwargs** – deprecated

Return type

folium.folium.Map

6.4.10 osmnx.geocoder module

Geocode place names or addresses or retrieve OSM elements by place name or ID.

This module uses the Nominatim API’s “search” and “lookup” endpoints. For more details see <https://wiki.openstreetmap.org/wiki/Elements> and <https://nominatim.org/>.

`osmnx.geocoder._geocode_query_to_gdf(query, which_result, by_osmid)`

Geocode a single place query to a GeoDataFrame.

Parameters

- **query** (*string or dict*) – query string or structured dict to geocode
- **which_result** (*int*) – which geocoding result to use. if None, auto-select the first (Multi)Polygon or raise an error if OSM doesn’t return one. to get the top match regardless of geometry type, set `which_result=1`. ignored if `by_osmid=True`.
- **by_osmid** (*bool*) – if True, handle query as an OSM ID for lookup rather than text search

Returns

gdf – a GeoDataFrame with one row containing the result of geocoding

Return type

geopandas.GeoDataFrame

`osmnx.geocoder._get_first_polygon(results, query)`

Choose first result of geometry type (Multi)Polygon from list of results.

Parameters

- **results** (*list*) – list of results from `_downloader._osm_place_download`
- **query** (*str*) – the query string or structured dict that was geocoded

Returns

result – the chosen result

Return type

dict

`osmnx.geocoder.geocode(query)`

Geocode place names or addresses to (lat, lon) with the Nominatim API.

This geocodes the query via the Nominatim “search” endpoint.

Parameters

query (*string*) – the query string to geocode

Returns

point – the (lat, lon) coordinates returned by the geocoder

Return type

tuple

`osmnx.geocoder.geocode_to_gdf(query, which_result=None, by_osmid=False, buffer_dist=None)`

Retrieve OSM elements by place name or OSM ID with the Nominatim API.

If searching by place name, the *query* argument can be a string or structured dict, or a list of such strings/dicts to send to the geocoder. This uses the Nominatim “search” endpoint to geocode the place name to the best-matching OSM element, then returns that element and its attribute data.

You can instead query by OSM ID by passing *by_osmid=True*. This uses the Nominatim “lookup” endpoint to retrieve the OSM element with that ID. In this case, the function treats the *query* argument as an OSM ID (or list

of OSM IDs), which must be prepended with their types: node (N), way (W), or relation (R) in accordance with the Nominatim API format. For example, `query=["R2192363", "N240109189", "W427818536"]`.

If `query` is a list, then `which_result` must be either a single value or a list with the same length as `query`. The queries you provide must be resolvable to elements in the Nominatim database. The resulting `GeoDataFrame`'s geometry column contains place boundaries if they exist.

Parameters

- **query** (*string or dict or list of strings/dicts*) – query string(s) or structured dict(s) to geocode
- **which_result** (*int*) – which search result to return. if None, auto-select the first (Multi)Polygon or raise an error if OSM doesn't return one. to get the top match regardless of geometry type, set `which_result=1`. ignored if `by_osmid=True`.
- **by_osmid** (*bool*) – if True, treat query as an OSM ID lookup rather than text search
- **buffer_dist** (*float*) – deprecated, do not use

Returns

gdf – a `GeoDataFrame` with one row for each query

Return type

`geopandas.GeoDataFrame`

6.4.11 osmnx.geometries module

Do not use: deprecated.

The *geometries* module has been renamed the *features* module. The *geometries* module is deprecated and will be removed in the v2.0.0 release.

`osmnx.geometries.geometries_from_address(address, tags, dist=1000)`

Do not use: deprecated.

The *geometries* module and *geometries_from_X* functions have been renamed the *features* module and *features_from_X* functions. Use these instead. The *geometries* module and functions are deprecated and will be removed in the v2.0.0 release.

Parameters

- **address** (*string*) – Do not use: deprecated.
- **tags** (*dict*) – Do not use: deprecated.
- **dist** (*numeric*) – Do not use: deprecated.

Returns

gdf

Return type

`geopandas.GeoDataFrame`

`osmnx.geometries.geometries_from_bbox(north, south, east, west, tags)`

Do not use: deprecated.

The *geometries* module and *geometries_from_X* functions have been renamed the *features* module and *features_from_X* functions. Use these instead. The *geometries* module and functions are deprecated and will be removed in the v2.0.0 release.

Parameters

- **north** (*float*) – Do not use: deprecated.
- **south** (*float*) – Do not use: deprecated.
- **east** (*float*) – Do not use: deprecated.
- **west** (*float*) – Do not use: deprecated.
- **tags** (*dict*) – Do not use: deprecated.

Returns
gdf

Return type
geopandas.GeoDataFrame

`osmnx.geometries.geometries_from_place(query, tags, which_result=None, buffer_dist=None)`

Do not use: deprecated.

The *geometries* module and *geometries_from_X* functions have been renamed the *features* module and *features_from_X* functions. Use these instead. The *geometries* module and functions are deprecated and will be removed in the v2.0.0 release.

Parameters

- **query** (*string or dict or list*) – Do not use: deprecated.
- **tags** (*dict*) – Do not use: deprecated.
- **which_result** (*int*) – Do not use: deprecated.
- **buffer_dist** (*float*) – Do not use: deprecated.

Returns
gdf

Return type
geopandas.GeoDataFrame

`osmnx.geometries.geometries_from_point(center_point, tags, dist=1000)`

Do not use: deprecated.

The *geometries* module and *geometries_from_X* functions have been renamed the *features* module and *features_from_X* functions. Use these instead. The *geometries* module and functions are deprecated and will be removed in the v2.0.0 release.

Parameters

- **center_point** (*tuple*) – Do not use: deprecated.
- **tags** (*dict*) – Do not use: deprecated.
- **dist** (*numeric*) – Do not use: deprecated.

Returns
gdf

Return type
geopandas.GeoDataFrame

`osmnx.geometries.geometries_from_polygon(polygon, tags)`

Do not use: deprecated.

The *geometries* module and *geometries_from_X* functions have been renamed the *features* module and *features_from_X* functions. Use these instead. The *geometries* module and functions are deprecated and will be removed in the v2.0.0 release.

Parameters

- **polygon** (*shapely.geometry.Polygon* or *shapely.geometry.MultiPolygon*) – Do not use: deprecated.
- **tags** (*dict*) – Do not use: deprecated.

Returns**gdf****Return type**

geopandas.GeoDataFrame

`osmnx.geometries.geometries_from_xml(filepath, polygon=None, tags=None)`

Do not use: deprecated.

The *geometries* module and *geometries_from_X* functions have been renamed the *features* module and *features_from_X* functions. Use these instead. The *geometries* module and functions are deprecated and will be removed in the v2.0.0 release.

Parameters

- **filepath** (*string* or *pathlib.Path*) – Do not use: deprecated.
- **polygon** (*shapely.geometry.Polygon*) – Do not use: deprecated.
- **tags** (*dict*) – Do not use: deprecated.

Returns**gdf****Return type**

geopandas.GeoDataFrame

6.4.12 osmnx.graph module

Download and create graphs from OpenStreetMap data.

This module uses filters to query the Overpass API: you can either specify a built-in network type or provide your own custom filter with Overpass QL.

Refer to the Getting Started guide for usage limitations.

`osmnx.graph._add_paths(G, paths, bidirectional=False)`

Add a list of paths to the graph as edges.

Parameters

- **G** (*networkx.MultiDiGraph*) – graph to add paths to
- **paths** (*list*) – list of paths' *tag:value* attribute data dicts
- **bidirectional** (*bool*) – if True, create bi-directional edges for one-way streets

Return type

None

`osmnx.graph._convert_node(element)`

Convert an OSM node element into the format for a networkx node.

Parameters**element** (*dict*) – an OSM node element

Returns
node

Return type
dict

`osmnx.graph._convert_path(element)`

Convert an OSM way element into the format for a networkx path.

Parameters
element (*dict*) – an OSM way element

Returns
path

Return type
dict

`osmnx.graph._create_graph(response_jsons, retain_all=False, bidirectional=False)`

Create a networkx MultiDiGraph from Overpass API responses.

Adds length attributes in meters (great-circle distance between endpoints) to all of the graph's (pre-simplified, straight-line) edges via the *distance.add_edge_lengths* function.

Parameters

- **response_jsons** (*iterable*) – iterable of dicts of JSON responses from from the Overpass API
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **bidirectional** (*bool*) – if True, create bi-directional edges for one-way streets

Returns
G

Return type
networkx.MultiDiGraph

`osmnx.graph._is_path_one_way(path, bidirectional, oneway_values)`

Determine if a path of nodes allows travel in only one direction.

Parameters

- **path** (*dict*) – a path's *tag:value* attribute data
- **bidirectional** (*bool*) – whether this is a bi-directional network type
- **oneway_values** (*set*) – the values OSM uses in its 'oneway' tag to denote True

Return type
bool

`osmnx.graph._is_path_reversed(path, reversed_values)`

Determine if the order of nodes in a path should be reversed.

Parameters

- **path** (*dict*) – a path's *tag:value* attribute data
- **reversed_values** (*set*) – the values OSM uses in its 'oneway' tag to denote travel can only occur in the opposite direction of the node order

Return type

bool

`osmnx.graph._parse_nodes_paths(response_json)`

Construct dicts of nodes and paths from an Overpass response.

Parameters**response_json** (*dict*) – JSON response from the Overpass API**Returns****nodes, paths** – dicts' keys = osmid and values = dict of attributes**Return type**

tuple of dicts

`osmnx.graph.graph_from_address(address, dist=1000, dist_type='bbox', network_type='all', simplify=True, retain_all=False, truncate_by_edge=False, return_coords=None, clean_periphery=None, custom_filter=None)`

Download and create a graph within some distance of an address.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.**Parameters**

- **address** (*string*) – the address to geocode and use as the central point around which to construct the graph
- **dist** (*int*) – retain only those nodes within this many meters of the center of the graph
- **dist_type** (*string* {"network", "bbox"}) – if "bbox", retain only those nodes within a bounding box of the distance parameter. if "network", retain only those nodes within some network distance from the center-most node.
- **network_type** (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if custom_filter is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node's neighbors is within the bounding box
- **return_coords** (*bool*) – deprecated, do not use
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the network_type presets e.g., ["power"~"line"] or ["highway"~"motorway|trunk"]. Also pass in a network_type that is in settings.bidirectional_network_types if you want graph to be fully bi-directional.

Return type

networkx.MultiDiGraph or optionally (networkx.MultiDiGraph, (lat, lon))

Notes

Very large query areas use the `utils_geo._consolidate_subdivide_geometry` function to automatically make multiple requests: see that function's documentation for caveats.

```
osmnx.graph.graph_from_bbox(north=None, south=None, east=None, west=None, bbox=None,
                             network_type='all', simplify=True, retain_all=False, truncate_by_edge=False,
                             clean_periphery=None, custom_filter=None)
```

Download and create a graph within some bounding box.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)
- **network_type** (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if custom_filter is None
- **simplify** (*bool*) – if True, simplify graph topology with the `simplify_graph` function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node's neighbors is within the bounding box
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the network_type presets e.g., ["power"~"line"] or ["highway"~"motorway|trunk"]. Also pass in a network_type that is in settings.bidirectional_network_types if you want graph to be fully bi-directional.

Returns

G

Return type

networkx.MultiDiGraph

Notes

Very large query areas use the `utils_geo._consolidate_subdivide_geometry` function to automatically make multiple requests: see that function's documentation for caveats.

```
osmnx.graph.graph_from_place(query, network_type='all', simplify=True, retain_all=False,
                              truncate_by_edge=False, which_result=None, buffer_dist=None,
                              clean_periphery=None, custom_filter=None)
```

Download and create a graph within the boundaries of some place(s).

The query must be geocodable and OSM must have polygon boundaries for the geocode result. If OSM does not have a polygon for this place, you can instead get its street network using the `graph_from_address` function, which geocodes the place name to a point and gets the network within some distance of that point.

If OSM does have polygon boundaries for this place but you're not finding it, try to vary the query string, pass in a structured query dict, or vary the `which_result` argument to use a different geocode result. If you know the OSM ID of the place, you can retrieve its boundary polygon using the `geocode_to_gdf` function, then pass it to the `graph_from_polygon` function.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **query** (*string or dict or list*) – the query or queries to geocode to get place boundary polygon(s)
- **network_type** (*string {"all", "all_public", "bike", "drive", "drive_service", "walk"}*) – what type of street network to get if `custom_filter` is `None`
- **simplify** (*bool*) – if `True`, simplify graph topology with the `simplify_graph` function
- **retain_all** (*bool*) – if `True`, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if `True`, retain nodes outside boundary polygon if at least one of node's neighbors is within the polygon
- **which_result** (*int*) – which geocoding result to use. if `None`, auto-select the first (Multi)Polygon or raise an error if OSM doesn't return one.
- **buffer_dist** (*float*) – deprecated, do not use
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the `network_type` presets e.g., `["power"~"line"]` or `["highway"~"motorway|trunk"]`. Also pass in a `network_type` that is in `settings.bidirectional_network_types` if you want graph to be fully bi-directional.

Returns

G

Return type

`networkx.MultiDiGraph`

Notes

Very large query areas use the `utils_geo._consolidate_subdivide_geometry` function to automatically make multiple requests: see that function's documentation for caveats.

```
osmnx.graph.graph_from_point(center_point, dist=1000, dist_type='bbox', network_type='all', simplify=True,
                             retain_all=False, truncate_by_edge=False, clean_periphery=None,
                             custom_filter=None)
```

Download and create a graph within some distance of a (lat, lon) point.

You can use the `settings` module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **center_point** (*tuple*) – the (lat, lon) center point around which to construct the graph
- **dist** (*int*) – retain only those nodes within this many meters of the center of the graph, with distance determined according to *dist_type* argument
- **dist_type** (*string* {"network", "bbox"}) – if "bbox", retain only those nodes within a bounding box of the distance parameter. if "network", retain only those nodes within some network distance from the center-most node.
- **network_type** (*string*, {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if *custom_filter* is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node's neighbors is within the bounding box
- **clean_periphery** (*bool*,) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the *network_type* presets e.g., ["power"~"line"] or ["highway"~"motorway|trunk"]. Also pass in a *network_type* that is in *settings.bidirectional_network_types* if you want graph to be fully bi-directional.

Returns

G

Return type

networkx.MultiDiGraph

Notes

Very large query areas use the *utils_geo._consolidate_subdivide_geometry* function to automatically make multiple requests: see that function's documentation for caveats.

```
osmnx.graph.graph_from_polygon(polygon, network_type='all', simplify=True, retain_all=False,
                               truncate_by_edge=False, clean_periphery=None, custom_filter=None)
```

Download and create a graph within the boundaries of a (multi)polygon.

You can use the *settings* module to retrieve a snapshot of historical OSM data as of a certain date, or to configure the Overpass server timeout, memory allocation, and other custom settings.

Parameters

- **polygon** (*shapely.geometry.Polygon* or *shapely.geometry.MultiPolygon*) – the shape to get network data within. coordinates should be in unprojected latitude-longitude degrees (EPSG:4326).
- **network_type** (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get if *custom_filter* is None
- **simplify** (*bool*) – if True, simplify graph topology with the *simplify_graph* function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.

- **truncate_by_edge** (*bool*) – if True, retain nodes outside boundary polygon if at least one of node’s neighbors is within the polygon
- **clean_periphery** (*bool*) – deprecated, do not use
- **custom_filter** (*string*) – a custom ways filter to be used instead of the `network_type` presets e.g., `[“power”~”line”]` or `[“highway”~”motorway|trunk”]`. Also pass in a `network_type` that is in `settings.bidirectional_network_types` if you want graph to be fully bi-directional.

Returns**G****Return type**`networkx.MultiDiGraph`**Notes**

Very large query areas use the `utils_geo._consolidate_subdivide_geometry` function to automatically make multiple requests: see that function’s documentation for caveats.

`osmnx.graph.graph_from_xml(filepath, bidirectional=False, simplify=True, retain_all=False, encoding='utf-8')`

Create a graph from data in a .osm formatted XML file.

Do not load an XML file generated by OSMnx: this use case is not supported and may not behave as expected. To save/load graphs to/from disk for later use in OSMnx, use the `io.save_graphml` and `io.load_graphml` functions instead.

Parameters

- **filepath** (*string or pathlib.Path*) – path to file containing OSM XML data
- **bidirectional** (*bool*) – if True, create bi-directional edges for one-way streets
- **simplify** (*bool*) – if True, simplify graph topology with the `simplify_graph` function
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **encoding** (*string*) – the XML file’s character encoding

Returns**G****Return type**`networkx.MultiDiGraph`

6.4.13 osmnx.io module

Serialize graphs to/from files on disk.

`osmnx.io._convert_bool_string(value)`

Convert a “True” or “False” string literal to corresponding boolean type.

This is necessary because Python will otherwise parse the string “False” to the boolean value True, that is, `bool(“False”) == True`. This function raises a `ValueError` if a value other than “True” or “False” is passed.

If the value is already a boolean, this function just returns it, to accommodate usage when the value was originally inside a stringified list.

Parameters

value (*string* {"True", "False"}) – the value to convert

Return type

bool

`osmnx.io._convert_edge_attr_types(G, dtypes=None)`

Convert graph edges' attributes using a dict of data types.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **dtypes** (*dict*) – dict of edge attribute names:types

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.io._convert_graph_attr_types(G, dtypes=None)`

Convert graph-level attributes using a dict of data types.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **dtypes** (*dict*) – dict of graph-level attribute names:types

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.io._convert_node_attr_types(G, dtypes=None)`

Convert graph nodes' attributes using a dict of data types.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **dtypes** (*dict*) – dict of node attribute names:types

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.io._stringify_nonnumeric_cols(gdf)`

Make every non-numeric GeoDataFrame column (besides geometry) a string.

This allows proper serializing via Fiona of GeoDataFrames with mixed types such as strings and ints in the same column.

Parameters

gdf (*geopandas.GeoDataFrame*) – gdf to stringify non-numeric columns of

Returns

gdf – gdf with non-numeric columns stringified

Return type

geopandas.GeoDataFrame

```
osmnx.io.load_graphml(filepath=None, graphml_str=None, node_dtypes=None, edge_dtypes=None,
                      graph_dtypes=None)
```

Load an OSMnx-saved GraphML file from disk or GraphML string.

This function converts node, edge, and graph-level attributes (serialized as strings) to their appropriate data types. These can be customized as needed by passing in `dtypes` arguments providing types or custom converter functions. For example, if you want to convert some attribute's values to *bool*, consider using the built-in `ox.io._convert_bool_string` function to properly handle "True"/"False" string literals as True/False booleans: `ox.load_graphml(fp, node_dtypes={my_attr: ox.io._convert_bool_string})`.

If you manually configured the `all_oneway=True` setting, you may need to manually specify here that edge *oneway* attributes should be type *str*.

Note that you must pass one and only one of *filepath* or *graphml_str*. If passing *graphml_str*, you may need to decode the bytes read from your file before converting to string to pass to this function.

Parameters

- **filepath** (*string* or *pathlib.Path*) – path to the GraphML file
- **graphml_str** (*string*) – a valid and decoded string representation of a GraphML file's contents
- **node_dtypes** (*dict*) – dict of node attribute names:types to convert values' data types. the type can be a python type or a custom string converter function.
- **edge_dtypes** (*dict*) – dict of edge attribute names:types to convert values' data types. the type can be a python type or a custom string converter function.
- **graph_dtypes** (*dict*) – dict of graph-level attribute names:types to convert values' data types. the type can be a python type or a custom string converter function.

Returns

G

Return type

`networkx.MultiDiGraph`

```
osmnx.io.save_graph_geopackage(G, filepath=None, encoding='utf-8', directed=False)
```

Save graph nodes and edges to disk as layers in a GeoPackage file.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **filepath** (*string* or *pathlib.Path*) – path to the GeoPackage file including extension. if None, use default data folder + `graph.gpkg`
- **encoding** (*string*) – the character encoding for the saved file
- **directed** (*bool*) – if False, save one edge for each undirected edge in the graph but retain original oneway and to/from information as edge attributes; if True, save one edge for each directed edge in the graph

Return type

None

```
osmnx.io.save_graph_shapefile(G, filepath=None, encoding='utf-8', directed=False)
```

Do not use: deprecated. Use the `save_graph_geopackage` function instead.

The Shapefile format is proprietary and outdated. Instead, use the superior GeoPackage file format via the `save_graph_geopackage` function. See <http://switchfromshapefile.org/> for more information.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **filepath** (*string or pathlib.Path*) – path to the shapefiles folder (no file extension). if None, use default data folder + graph_shapefile
- **encoding** (*string*) – the character encoding for the saved files
- **directed** (*bool*) – if False, save one edge for each undirected edge in the graph but retain original oneway and to/from information as edge attributes; if True, save one edge for each directed edge in the graph

Return type

None

`osmnx.io.save_graph_xml(data, filepath=None, node_tags=None, node_attrs=None, edge_tags=None, edge_attrs=None, oneway=None, merge_edges=None, edge_tag_aggs=None, api_version=None, precision=None, way_tag_aggs=None)`

Save graph to disk as an OSM-formatted XML .osm file.

This function exists only to allow serialization to the .osm file format for applications that require it, and has constraints to conform to that. As such, this function has a limited use case which does not include saving/loading graphs for subsequent OSMnx analysis. To save/load graphs to/from disk for later use in OSMnx, use the `io.save_graphml` and `io.load_graphml` functions instead. To load a graph from a .osm file that you have downloaded or generated elsewhere, use the `graph.graph_from_xml` function.

Parameters

- **data** (*networkx.MultiDiGraph*) – the input graph
- **filepath** (*string or pathlib.Path*) – do not use, deprecated
- **node_tags** (*list*) – do not use, deprecated
- **node_attrs** (*list*) – do not use, deprecated
- **edge_tags** (*list*) – do not use, deprecated
- **edge_attrs** (*list*) – do not use, deprecated
- **oneway** (*bool*) – do not use, deprecated
- **merge_edges** (*bool*) – do not use, deprecated
- **edge_tag_aggs** (*tuple*) – do not use, deprecated
- **api_version** (*float*) – do not use, deprecated
- **precision** (*int*) – do not use, deprecated
- **way_tag_aggs** (*dict*) – Keys are OSM way tag keys and values are aggregation functions (anything accepted as an argument by `pandas.agg`). Allows user to aggregate graph edge attribute values into single OSM way values. If None, or if some tag's key does not exist in the dict, the way attribute will be assigned the value of the first edge of the way.

Return type

None

`osmnx.io.save_graphml(G, filepath=None, gephi=False, encoding='utf-8')`

Save graph to disk as GraphML file.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph

- **filepath** (*string or pathlib.Path*) – path to the GraphML file including extension. if None, use default data folder + graph.graphml
- **gephi** (*bool*) – if True, give each edge a unique key/id to work around Gephi’s interpretation of the GraphML specification
- **encoding** (*string*) – the character encoding for the saved file

Return type

None

6.4.14 osmnx._nominatim module

Tools to work with the Nominatim API.

`osmnx._nominatim._download_nominatim_element(query, by_osmid=False, limit=1, polygon_geojson=1)`

Retrieve an OSM element from the Nominatim API.

Parameters

- **query** (*string or dict*) – query string or structured query dict
- **by_osmid** (*bool*) – if True, treat query as an OSM ID lookup rather than text search
- **limit** (*int*) – max number of results to return
- **polygon_geojson** (*int*) – retrieve the place’s geometry from the API, 0=no, 1=yes

Returns

response_json – JSON response from the Nominatim server

Return type

dict

`osmnx._nominatim._nominatim_request(params, request_type='search', pause=1, error_pause=60)`

Send a HTTP GET request to the Nominatim API and return response.

Parameters

- **params** (*OrderedDict*) – key-value pairs of parameters
- **request_type** (*string {"search", "reverse", "lookup"}*) – which Nominatim API endpoint to query
- **pause** (*float*) – how long to pause before request, in seconds. per the nominatim usage policy: “an absolute maximum of 1 request per second” is allowed
- **error_pause** (*float*) – how long to pause in seconds before re-trying request if error

Returns

response_json

Return type

dict

6.4.15 osmnx.osm_xml module

Read/write .osm formatted XML files.

class `osmnx.osm_xml._OSMContentHandler`

SAX content handler for OSM XML.

Used to build an Overpass-like response JSON object in `self.object`. For format notes, see https://wiki.openstreetmap.org/wiki/OSM_XML and <https://overpass-api.de>

endElement(*name*)

Signals the end of an element in non-namespace mode.

The name parameter contains the name of the element type, just as with the `startElement` event.

startElement(*name, attrs*)

Signals the start of an element in non-namespace mode.

The name parameter contains the raw XML 1.0 name of the element type as a string and the `attrs` parameter holds an instance of the `Attributes` class containing the attributes of the element.

`osmnx.osm_xml._append_edges_xml_tree(root, gdf_edges, edge_attrs, edge_tags, edge_tag_aggs, merge_edges)`

Append edges to an XML tree.

Parameters

- **root** (*ElementTree.Element*) – xml tree
- **gdf_edges** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph edges
- **edge_attrs** (*list*) – osm way attributes to include in output OSM XML
- **edge_tags** (*list*) – osm way tags to include in output OSM XML
- **edge_tag_aggs** (*list of length-2 string tuples*) – useful only if `merge_edges` is True, this argument allows the user to specify edge attributes to aggregate such that the merged OSM way entry tags accurately represent the sum total of their component edge attributes. For example, if the user wants the OSM way to have a “length” attribute, the user must specify `edge_tag_aggs=[('length', 'sum')]` in order to tell this method to aggregate the lengths of the individual component edges. Otherwise, the length attribute will simply reflect the length of the first edge associated with the way.
- **merge_edges** (*bool*) – if True merges graph edges such that each OSM way has one entry and one entry only in the OSM XML. Otherwise, every OSM way will have a separate entry for each node pair it contains.

Returns

root – XML tree with edges appended

Return type

`ElementTree.Element`

`osmnx.osm_xml._append_merged_edge_attrs(xml_edge, sample_edge, all_edges_df, edge_tags, edge_tag_aggs)`

Extract edge attributes and append to XML edge.

Parameters

- **xml_edge** (*ElementTree.SubElement*) – XML representation of an output graph edge
- **sample_edge** (*pandas.Series*) – sample row from the the dataframe of way edges

- **all_edges_df** (*pandas.DataFrame*) – a dataframe with one row for each edge in an OSM way
- **edge_tags** (*list*) – osm way tags to include in output OSM XML
- **edge_tag_aggs** (*list of length-2 string tuples*) – useful only if `merge_edges` is `True`, this argument allows the user to specify edge attributes to aggregate such that the merged OSM way entry tags accurately represent the sum total of their component edge attributes. For example if the user wants the OSM way to have a length attribute, the user must specify `edge_tag_aggs=[('length', 'sum')]` to tell this method to aggregate the lengths of the individual component edges. Otherwise, the length attribute will simply reflect the length of the first edge associated with the way.

`osmnx.osm_xml._append_nodes_as_edge_attrs(xml_edge, sample_edge, all_edges_df)`

Extract list of ordered nodes and append as attributes of XML edge.

Parameters

- **xml_edge** (*ElementTree.SubElement*) – XML representation of an output graph edge
- **sample_edge** (*pandas.Series*) – sample row from the the dataframe of way edges
- **all_edges_df** (*pandas.DataFrame*) – a dataframe with one row for each edge in an OSM way

`osmnx.osm_xml._append_nodes_xml_tree(root, gdf_nodes, node_attrs, node_tags)`

Append nodes to an XML tree.

Parameters

- **root** (*ElementTree.Element*) – xml tree
- **gdf_nodes** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph nodes
- **node_attrs** (*list*) – osm way attributes to include in output OSM XML
- **node_tags** (*list*) – osm way tags to include in output OSM XML

Returns

root – xml tree with nodes appended

Return type

`ElementTree.Element`

`osmnx.osm_xml._create_way_for_each_edge(root, gdf_edges, edge_attrs, edge_tags)`

Append a new way to an empty XML tree graph for each edge in way.

This will generate separate OSM ways for each network edge, even if the edges are all part of the same original OSM way. As such, each way will be composed of two nodes, and there will be many ways with the same OSM ID. This does not conform to the OSM XML schema standard, but the data will still comprise a valid network and will be readable by most OSM tools.

Parameters

- **root** (*ElementTree.Element*) – an empty XML tree
- **gdf_edges** (*geopandas.GeoDataFrame*) – GeoDataFrame of graph edges
- **edge_attrs** (*list*) – osm way attributes to include in output OSM XML
- **edge_tags** (*list*) – osm way tags to include in output OSM XML

`osmnx.osm_xml._get_unique_nodes_ordered_from_way(df_way_edges)`

Recover original node order from edges associated with a single OSM way.

Parameters

df_way_edges (*pandas.DataFrame*) – Dataframe containing columns ‘u’ and ‘v’ corresponding to origin/destination nodes.

Returns

unique_ordered_nodes – An ordered list of unique node IDs. If the edges do not all connect (e.g. [(1, 2), (2,3), (10, 11), (11, 12), (12, 13)]), then this method will return only those nodes associated with the largest component of connected edges, even if subsequent connected chunks are contain more total nodes. This ensures a proper topological representation of nodes in the XML way records because if there are unconnected components, the sorting algorithm cannot recover their original order. We would not likely ever encounter this kind of disconnected structure of nodes within a given way, but it is not explicitly forbidden in the OSM XML design schema.

Return type

list

`osmnx.osm_xml._overpass_json_from_file(filepath, encoding)`

Read OSM XML from file and return Overpass-like JSON.

Parameters

- **filepath** (*string or pathlib.Path*) – path to file containing OSM XML data
- **encoding** (*string*) – the XML file’s character encoding

Return type

OSMContentHandler object

`osmnx.osm_xml._save_graph_xml(data, filepath, node_tags, node_attrs, edge_tags, edge_attrs, oneway, merge_edges, edge_tag_aggs, api_version, precision, way_tag_aggs)`

Save graph to disk as an OSM-formatted UTF-8 encoded XML .osm file.

Parameters

- **data** (*networkx.MultiDiGraph*) – the input graph
- **filepath** (*string or pathlib.Path*) – do not use, deprecated
- **node_tags** (*list*) – do not use, deprecated
- **node_attrs** (*list*) – do not use, deprecated
- **edge_tags** (*list*) – do not use, deprecated
- **edge_attrs** (*list*) – do not use, deprecated
- **oneway** (*bool*) – do not use, deprecated
- **merge_edges** (*bool*) – do not use, deprecated
- **edge_tag_aggs** (*tuple*) – do not use, deprecated
- **api_version** (*float*) – do not use, deprecated
- **precision** (*int*) – do not use, deprecated
- **way_tag_aggs** (*dict*) – Keys are OSM way tag keys and values are aggregation functions (anything accepted as an argument by `pandas.agg`). Allows user to aggregate graph edge attribute values into single OSM way values. If None, or if some tag’s key does not exist in the dict, the way attribute will be assigned the value of the first edge of the way.

Return type

None

`osmnx.osm_xml.save_graph_xml(data, filepath=None, node_tags=None, node_attrs=None, edge_tags=None, edge_attrs=None, oneway=None, merge_edges=None, edge_tag_aggs=None, api_version=None, precision=None, way_tag_aggs=None)`

Do not use: deprecated.

The `save_graph_xml` has moved from the `osm_xml` module to the `io` module. `osm_xml.save_graph_xml` has been deprecated and will be removed in the v2.0.0 release. Access the function via the `io` module instead.

Parameters

- **data** (*networkx.MultiDiGraph*) – do not use, deprecated
- **filepath** (*string or pathlib.Path*) – do not use, deprecated
- **node_tags** (*list*) – do not use, deprecated
- **node_attrs** (*list*) – do not use, deprecated
- **edge_tags** (*list*) – do not use, deprecated
- **edge_attrs** (*list*) – do not use, deprecated
- **oneway** (*bool*) – do not use, deprecated
- **merge_edges** (*bool*) – do not use, deprecated
- **edge_tag_aggs** (*tuple*) – do not use, deprecated
- **api_version** (*float*) – do not use, deprecated
- **precision** (*int*) – do not use, deprecated
- **way_tag_aggs** (*dict*) – do not use, deprecated

Return type

None

6.4.16 osmnx._overpass module

Tools to work with the Overpass API.

`osmnx._overpass._create_overpass_query(polygon_coord_str, tags)`

Create an Overpass features query string based on passed tags.

Parameters

- **polygon_coord_str** (*list*) – list of lat lon coordinates
- **tags** (*dict*) – dict of tags used for finding elements in the search area

Returns

query

Return type

string

`osmnx._overpass._download_overpass_features(polygon, tags)`

Retrieve OSM features within boundary from the Overpass API.

Parameters

- **polygon** (*shapely.geometry.Polygon*) – boundaries to fetch elements within

- **tags** (*dict*) – dict of tags used for finding elements in the selected area

Yields

response_json (*dict*) – a generator of JSON responses from the Overpass server

`osmnx._overpass._download_overpass_network`(*polygon, network_type, custom_filter*)

Retrieve networked ways and nodes within boundary from the Overpass API.

Parameters

- **polygon** (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – boundary to fetch the network ways/nodes within
- **network_type** (*string*) – what type of street network to get if *custom_filter* is *None*
- **custom_filter** (*string*) – a custom “ways” filter to be used instead of the *network_type* presets

Yields

response_json (*dict*) – a generator of JSON responses from the Overpass server

`osmnx._overpass._get_osm_filter`(*network_type*)

Create a filter to query OSM for the specified network type.

Parameters

network_type (*string* {"all", "all_public", "bike", "drive", "drive_service", "walk"}) – what type of street network to get

Return type

string

`osmnx._overpass._get_overpass_pause`(*base_endpoint, recursive_delay=5, default_duration=60*)

Retrieve a pause duration from the Overpass API status endpoint.

Check the Overpass API status endpoint to determine how long to wait until the next slot is available. You can disable this via the *settings* module’s *overpass_rate_limit* setting.

Parameters

- **base_endpoint** (*string*) – base Overpass API url (without “/status” at the end)
- **recursive_delay** (*int*) – how long to wait between recursive calls if the server is currently running a query
- **default_duration** (*int*) – if fatal error, fall back on returning this value

Returns

pause

Return type

int

`osmnx._overpass._make_overpass_polygon_coord_strs`(*polygon*)

Subdivide query polygon and return list of coordinate strings.

Project to utm, divide polygon up into sub-polygons if area exceeds a max size (in meters), project back to lat-lon, then get a list of polygon(s) exterior coordinates. Ignore interior (“holes”) coordinates.

Parameters

polygon (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – polygon to convert to exterior coordinate strings

Returns

coord_strs – list of strings of exterior coordinates of polygon(s)

Return type

list

`osmnx._overpass._make_overpass_settings()`

Make settings string to send in Overpass query.

Return type

string

`osmnx._overpass._overpass_request(data, pause=None, error_pause=60)`

Send a HTTP POST request to the Overpass API and return response.

Parameters

- **data** (*OrderedDict*) – key-value pairs of parameters
- **pause** (*float*) – how long to pause in seconds before request, if None, will query API status endpoint to find when next slot is available
- **error_pause** (*float*) – how long to pause in seconds (in addition to *pause*) before re-trying request if error

Returns

response_json

Return type

dict

6.4.17 osmnx.plot module

Visualize street networks, routes, orientations, and geospatial features.

`osmnx.plot._config_ax(ax, crs, bbox, padding)`

Configure axis for display.

Parameters

- **ax** (*matplotlib axis*) – the axis containing the plot
- **crs** (*dict or string or pyproj.CRS*) – the CRS of the plotted geometries
- **bbox** (*tuple*) – bounding box as (north, south, east, west)
- **padding** (*float*) – relative padding to add around the plot's bbox

Returns

ax – the configured/styled axis

Return type

matplotlib axis

`osmnx.plot._get_colors_by_value(vals, num_bins, cmap, start, stop, na_color, equal_size)`

Map colors to the values in a series.

Parameters

- **vals** (*pandas.Series*) – series labels are node/edge IDs and values are attribute values
- **num_bins** (*int*) – if None, linearly map a color to each value. otherwise, assign values to this many bins then assign a color to each bin.
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace

- **stop** (*float*) – where to end in the colorspace
- **na_color** (*string*) – what color to assign to missing values
- **equal_size** (*bool*) – ignored if num_bins is None. if True, bin into equal-sized quantiles (requires unique bin edges). if False, bin into equal-spaced bins.

Returns

color_series – series labels are node/edge IDs and values are colors

Return type

pandas.Series

`osmnx.plot._save_and_show(fig, ax, save=False, show=True, close=True, filepath=None, dpi=300)`

Save a figure to disk and/or show it, as specified by args.

Parameters

- **fig** (*figure*) – matplotlib figure
- **ax** (*axis*) – matplotlib axis
- **save** (*bool*) – if True, save the figure to disk at filepath
- **show** (*bool*) – if True, call `pyplot.show()` to show the figure
- **close** (*bool*) – if True, call `pyplot.close()` to close the figure
- **filepath** (*string*) – if save is True, the path to the file. file format determined from extension. if None, use `settings.imgs_folder/image.png`
- **dpi** (*int*) – if save is True, the resolution of saved file

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

`osmnx.plot._verify_mpl()`

Verify that matplotlib is installed and successfully imported.

Return type

None

`osmnx.plot.get_colors(n, cmap='viridis', start=0.0, stop=1.0, alpha=1.0, return_hex=None)`

Get *n* evenly-spaced colors from a matplotlib colormap.

Parameters

- **n** (*int*) – number of colors
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace
- **stop** (*float*) – where to end in the colorspace
- **alpha** (*float*) – If *None*, return colors as HTML-like hex triplet “#rrggbb” RGB strings. If *float*, return as “#rrggbbaa” RGBA strings.
- **return_hex** (*bool*) – deprecated, do not use

Returns

color_list

Return type

list

```
osmnx.plot.get_edge_colors_by_attr(G, attr, num_bins=None, cmap='viridis', start=0, stop=1,  
                                   na_color='none', equal_size=False)
```

Get colors based on edge attribute values.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **attr** (*string*) – name of a numerical edge attribute
- **num_bins** (*int*) – if None, linearly map a color to each value. otherwise, assign values to this many bins then assign a color to each bin.
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace
- **stop** (*float*) – where to end in the colorspace
- **na_color** (*string*) – what color to assign edges with missing attr values
- **equal_size** (*bool*) – ignored if num_bins is None. if True, bin into equal-sized quantiles (requires unique bin edges). if False, bin into equal-spaced bins.

Returns

edge_colors – series labels are edge IDs (u, v, key) and values are colors

Return type

pandas.Series

```
osmnx.plot.get_node_colors_by_attr(G, attr, num_bins=None, cmap='viridis', start=0, stop=1,  
                                   na_color='none', equal_size=False)
```

Get colors based on node attribute values.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **attr** (*string*) – name of a numerical node attribute
- **num_bins** (*int*) – if None, linearly map a color to each value. otherwise, assign values to this many bins then assign a color to each bin.
- **cmap** (*string*) – name of a matplotlib colormap
- **start** (*float*) – where to start in the colorspace
- **stop** (*float*) – where to end in the colorspace
- **na_color** (*string*) – what color to assign nodes with missing attr values
- **equal_size** (*bool*) – ignored if num_bins is None. if True, bin into equal-sized quantiles (requires unique bin edges). if False, bin into equal-spaced bins.

Returns

node_colors – series labels are node IDs and values are colors

Return type

pandas.Series

```
osmnx.plot.plot_figure_ground(G=None, address=None, point=None, dist=805,
                              network_type='drive_service', street_widths=None, default_width=4,
                              color='w', edge_color=None, smooth_joints=None, **pg_kwargs)
```

Plot a figure-ground diagram of a street network.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph, must be unprojected
- **address** (*string*) – deprecated, do not use
- **point** (*tuple*) – deprecated, do not use
- **dist** (*numeric*) – how many meters to extend north, south, east, west from center point
- **network_type** (*string*) – deprecated, do not use
- **street_widths** (*dict*) – dict keys are street types and values are widths to plot in pixels
- **default_width** (*numeric*) – fallback width in pixels for any street type not in *street_widths*
- **color** (*string*) – color of the streets
- **edge_color** (*string*) – deprecated, do not use
- **smooth_joints** (*bool*) – deprecated, do not use
- **pg_kwargs** – keyword arguments to pass to *plot_graph*

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_footprints(gdf, ax=None, figsize=(8, 8), color='orange', edge_color='none',
                           edge_linewidth=0, alpha=None, bgcolor='#111111', bbox=None, save=False,
                           show=True, close=False, filepath=None, dpi=600)
```

Visualize a GeoDataFrame of geospatial features' footprints.

Parameters

- **gdf** (*geopandas.GeoDataFrame*) – GeoDataFrame of footprints (shapely Polygons and MultiPolygons)
- **ax** (*axis*) – if not None, plot on this preexisting axis
- **figsize** (*tuple*) – if ax is None, create new figure with size (width, height)
- **color** (*string*) – color of the footprints
- **edge_color** (*string*) – color of the edge of the footprints
- **edge_linewidth** (*float*) – width of the edge of the footprints
- **alpha** (*float*) – opacity of the footprints
- **bgcolor** (*string*) – background color of the plot
- **bbox** (*tuple*) – bounding box as (north, south, east, west). if None, will calculate from the spatial extents of the geometries in *gdf*
- **save** (*bool*) – if True, save the figure to disk at *filepath*
- **show** (*bool*) – if True, call *pyplot.show()* to show the figure
- **close** (*bool*) – if True, call *pyplot.close()* to close the figure

- **filepath** (*string*) – if save is True, the path to the file. file format determined from extension. if None, use settings.imgs_folder/image.png
- **dpi** (*int*) – if save is True, the resolution of saved file

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_graph(G, ax=None, figsize=(8, 8), bgcolor='#111111', node_color='w', node_size=15,
                      node_alpha=None, node_edgecolor='none', node_zorder=1, edge_color='#999999',
                      edge_linewidth=1, edge_alpha=None, show=True, close=False, save=False,
                      filepath=None, dpi=300, bbox=None)
```

Visualize a graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **ax** (*matplotlib axis*) – if not None, plot on this preexisting axis
- **figsize** (*tuple*) – if ax is None, create new figure with size (width, height)
- **bgcolor** (*string*) – background color of plot
- **node_color** (*string or list*) – color(s) of the nodes
- **node_size** (*int*) – size of the nodes: if 0, then skip plotting the nodes
- **node_alpha** (*float*) – opacity of the nodes, note: if you passed RGBA values to node_color, set node_alpha=None to use the alpha channel in node_color
- **node_edgecolor** (*string*) – color of the nodes' markers' borders
- **node_zorder** (*int*) – zorder to plot nodes: edges are always 1, so set node_zorder=0 to plot nodes below edges
- **edge_color** (*string or list*) – color(s) of the edges' lines
- **edge_linewidth** (*float*) – width of the edges' lines: if 0, then skip plotting the edges
- **edge_alpha** (*float*) – opacity of the edges, note: if you passed RGBA values to edge_color, set edge_alpha=None to use the alpha channel in edge_color
- **show** (*bool*) – if True, call pyplot.show() to show the figure
- **close** (*bool*) – if True, call pyplot.close() to close the figure
- **save** (*bool*) – if True, save the figure to disk at filepath
- **filepath** (*string*) – if save is True, the path to the file. file format determined from extension. if None, use settings.imgs_folder/image.png
- **dpi** (*int*) – if save is True, the resolution of saved file
- **bbox** (*tuple*) – bounding box as (north, south, east, west). if None, will calculate from spatial extents of plotted geometries.

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_graph_route(G, route, route_color='r', route_linewidth=4, route_alpha=0.5,
                             orig_dest_size=100, ax=None, **pg_kwargs)
```

Visualize a route along a graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **route** (*list*) – route as a list of node IDs
- **route_color** (*string*) – color of the route
- **route_linewidth** (*int*) – width of the route line
- **route_alpha** (*float*) – opacity of the route line
- **orig_dest_size** (*int*) – size of the origin and destination nodes
- **ax** (*matplotlib axis*) – if not None, plot route on this preexisting axis instead of creating a new fig, ax and drawing the underlying graph
- **pg_kwargs** – keyword arguments to pass to plot_graph

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_graph_routes(G, routes, route_colors='r', route_linewidths=4, **pgr_kwargs)
```

Visualize several routes along a graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **routes** (*list*) – routes as a list of lists of node IDs
- **route_colors** (*string or list*) – if string, 1 color for all routes. if list, the colors for each route.
- **route_linewidths** (*int or list*) – if int, 1 linewidth for all routes. if list, the linewidth for each route.
- **pgr_kwargs** – keyword arguments to pass to plot_graph_route

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

```
osmnx.plot.plot_orientation(Gu, num_bins=36, min_length=0, weight=None, ax=None, figsize=(5, 5),
                             area=True, color='#003366', edgecolor='k', linewidth=0.5, alpha=0.7,
                             title=None, title_y=1.05, title_font=None, xtick_font=None)
```

Plot a polar histogram of a spatial network's bidirectional edge bearings.

Ignores self-loop edges as their bearings are undefined.

For more info see: Boeing, G. 2019. "Urban Spatial Order: Street Network Orientation, Configuration, and Entropy." *Applied Network Science*, 4 (1), 67. <https://doi.org/10.1007/s41109-019-0189-1>

Parameters

- **Gu** (*networkx.MultiGraph*) – undirected, unprojected graph with *bearing* attributes on each edge

- **num_bins** (*int*) – number of bins; for example, if *num_bins*=36 is provided, then each bin will represent 10 degrees around the compass
- **min_length** (*float*) – ignore edges with *length* attributes less than *min_length*
- **weight** (*string*) – if not None, weight edges' bearings by this (non-null) edge attribute
- **ax** (*matplotlib.axes.PolarAxesSubplot*) – if not None, plot on this preexisting axis; must have *projection=polar*
- **figsize** (*tuple*) – if ax is None, create new figure with size (width, height)
- **area** (*bool*) – if True, set bar length so area is proportional to frequency, otherwise set bar length so height is proportional to frequency
- **color** (*string*) – color of histogram bars
- **edgecolor** (*string*) – color of histogram bar edges
- **linewidth** (*float*) – width of histogram bar edges
- **alpha** (*float*) – opacity of histogram bars
- **title** (*string*) – title for plot
- **title_y** (*float*) – y position to place title
- **title_font** (*dict*) – the title's fontdict to pass to matplotlib
- **xtick_font** (*dict*) – the xtick labels' fontdict to pass to matplotlib

Returns

fig, ax – matplotlib figure, axis

Return type

tuple

6.4.18 osmnx.projection module

Project a graph, GeoDataFrame, or geometry to a different CRS.

`osmnx.projection.is_projected(crs)`

Determine if a coordinate reference system is projected or not.

Parameters

crs (*string or pyproj.CRS*) – the identifier of the coordinate reference system, which can be anything accepted by *pyproj.CRS.from_user_input()* such as an authority string or a WKT string

Returns

projected – True if crs is projected, otherwise False

Return type

bool

`osmnx.projection.project_gdf(gdf, to_crs=None, to_latlong=False)`

Project a GeoDataFrame from its current CRS to another.

If *to_latlong* is *True*, this projects the GeoDataFrame to the CRS defined by *settings.default_crs*, otherwise it projects it to the CRS defined by *to_crs*. If *to_crs* is *None*, it projects it to the CRS of an appropriate UTM zone given *gdf*'s bounds.

Parameters

- **gdf** (*geopandas.GeoDataFrame*) – the GeoDataFrame to be projected

- **to_crs** (*string or pyproj.CRS*) – if *None*, project to an appropriate UTM zone, otherwise project to this CRS
- **to_latlong** (*bool*) – if *True*, project to *settings.default_crs* and ignore *to_crs*

Returns

gdf_proj – the projected GeoDataFrame

Return type

geopandas.GeoDataFrame

`osmnx.projection.project_geometry(geometry, crs=None, to_crs=None, to_latlong=False)`

Project a Shapely geometry from its current CRS to another.

If *to_latlong* is *True*, this projects the GeoDataFrame to the CRS defined by *settings.default_crs*, otherwise it projects it to the CRS defined by *to_crs*. If *to_crs* is *None*, it projects it to the CRS of an appropriate UTM zone given *geometry*'s bounds.

Parameters

- **geometry** (*shapely geometry*) – the geometry to be projected
- **crs** (*string or pyproj.CRS*) – the initial CRS of *geometry*. if *None*, it will be set to *settings.default_crs*
- **to_crs** (*string or pyproj.CRS*) – if *None*, project to an appropriate UTM zone, otherwise project to this CRS
- **to_latlong** (*bool*) – if *True*, project to *settings.default_crs* and ignore *to_crs*

Returns

geometry_proj, crs – the projected geometry and its new CRS

Return type

tuple

`osmnx.projection.project_graph(G, to_crs=None, to_latlong=False)`

Project a graph from its current CRS to another.

If *to_latlong* is *True*, this projects the GeoDataFrame to the CRS defined by *settings.default_crs*, otherwise it projects it to the CRS defined by *to_crs*. If *to_crs* is *None*, it projects it to the CRS of an appropriate UTM zone given *G*'s bounds.

Parameters

- **G** (*networkx.MultiDiGraph*) – the graph to be projected
- **to_crs** (*string or pyproj.CRS*) – if *None*, project to an appropriate UTM zone, otherwise project to this CRS
- **to_latlong** (*bool*) – if *True*, project to *settings.default_crs* and ignore *to_crs*

Returns

G_proj – the projected graph

Return type

networkx.MultiDiGraph

6.4.19 osmnx.routing module

Calculate weighted shortest paths between graph nodes.

`osmnx.routing._clean_maxspeed(maxspeed, agg=<function mean>, convert_mph=True)`

Clean a maxspeed string and convert mph to kph if necessary.

If present, splits maxspeed on “|” (which denotes that the value contains different speeds per lane) then aggregates the resulting values. Invalid inputs return None. See <https://wiki.openstreetmap.org/wiki/Key:maxspeed> for details on values and formats.

Parameters

- **maxspeed** (*string*) – a valid OpenStreetMap way maxspeed value
- **agg** (*function*) – aggregation function if maxspeed contains multiple values (default is `numpy.mean`)
- **convert_mph** (*bool*) – if True, convert miles per hour to km per hour

Returns

clean_value

Return type

string

`osmnx.routing._collapse_multiple_maxspeed_values(value, agg)`

Collapse a list of maxspeed values to a single value.

Parameters

- **value** (*list or string*) – an OSM way maxspeed value, or a list of them
- **agg** (*function*) – the aggregation function to reduce the list to a single value

Returns

agg_value – an integer representation of the aggregated value in the list, converted to kph if original value was in mph.

Return type

int

`osmnx.routing._single_shortest_path(G, orig, dest, weight)`

Solve the shortest path from an origin node to a destination node.

This function is a convenience wrapper around `networkx.shortest_path`, with exception handling for unsolvable paths. It uses Dijkstra’s algorithm.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int*) – origin node ID
- **dest** (*int*) – destination node ID
- **weight** (*string*) – edge attribute to minimize when solving shortest path

Returns

path – list of node IDs constituting the shortest path

Return type

list

`osmnx.routing._verify_edge_attribute(G, attr)`

Verify attribute values are numeric and non-null across graph edges.

Raises a *ValueError* if attribute contains non-numeric values and raises a warning if attribute is missing or null on any edges.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **attr** (*string*) – edge attribute to verify

Return type

None

`osmnx.routing.add_edge_speeds(G, hwy_speeds=None, fallback=None, precision=None, agg=<function mean>)`

Add edge speeds (km per hour) to graph as new *speed_kph* edge attributes.

By default, this imputes free-flow travel speeds for all edges via the mean *maxspeed* value of the edges of each highway type. For highway types in the graph that have no *maxspeed* value on any edge, it assigns the mean of all *maxspeed* values in graph.

This default mean-imputation can obviously be imprecise, and the user can override it by passing in *hwy_speeds* and/or *fallback* arguments that correspond to local speed limit standards. The user can also specify a different aggregation function (such as the median) to impute missing values from the observed values.

If edge *maxspeed* attribute has “mph” in it, value will automatically be converted from miles per hour to km per hour. Any other speed units should be manually converted to km per hour prior to running this function, otherwise there could be unexpected results. If “mph” does not appear in the edge’s *maxspeed* attribute string, then function assumes kph, per OSM guidelines: https://wiki.openstreetmap.org/wiki/Map_Features/Units

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **hwy_speeds** (*dict*) – dict keys = OSM highway types and values = typical speeds (km per hour) to assign to edges of that highway type for any edges missing speed data. Any edges with highway type not in *hwy_speeds* will be assigned the mean preexisting speed value of all edges of that highway type.
- **fallback** (*numeric*) – default speed value (km per hour) to assign to edges whose highway type did not appear in *hwy_speeds* and had no preexisting speed values on any edge
- **precision** (*int*) – deprecated, do not use
- **agg** (*function*) – aggregation function to impute missing values from observed values. the default is `numpy.mean`, but you might also consider for example `numpy.median`, `numpy.nanmedian`, or your own custom function

Returns

G – graph with *speed_kph* attributes on all edges

Return type

`networkx.MultiDiGraph`

`osmnx.routing.add_edge_travel_times(G, precision=None)`

Add edge travel time (seconds) to graph as new *travel_time* edge attributes.

Calculates free-flow travel time along each edge, based on *length* and *speed_kph* attributes. Note: run *add_edge_speeds* first to generate the *speed_kph* attribute. All edges must have *length* and *speed_kph* attributes and all their values must be non-null.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **precision** (*int*) – deprecated, do not use

Returns

G – graph with `travel_time` attributes on all edges

Return type

`networkx.MultiDiGraph`

`osmnx.routing.k_shortest_paths(G, orig, dest, k, weight='length')`

Solve *k* shortest paths from an origin node to a destination node.

Uses Yen's algorithm. See also *shortest_path* to solve just the one shortest path.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **orig** (*int*) – origin node ID
- **dest** (*int*) – destination node ID
- **k** (*int*) – number of shortest paths to solve
- **weight** (*string*) – edge attribute to minimize when solving shortest paths. default is edge length in meters.

Yields

path (*list*) – a generator of *k* shortest paths ordered by total weight. each path is a list of node IDs.

`osmnx.routing.route_to_gdf(G, route, weight='length')`

Return a GeoDataFrame of the edges in a path, in order.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **route** (*list*) – list of node IDs constituting the path
- **weight** (*string*) – if there are parallel edges between two nodes, choose lowest weight

Returns

gdf_edges – GeoDataFrame of the edges

Return type

`geopandas.GeoDataFrame`

`osmnx.routing.shortest_path(G, orig, dest, weight='length', cpus=1)`

Solve shortest path from origin node(s) to destination node(s).

Uses Dijkstra's algorithm. If *orig* and *dest* are single node IDs, this will return a list of the nodes constituting the shortest path between them. If *orig* and *dest* are lists of node IDs, this will return a list of lists of the nodes constituting the shortest path between each origin-destination pair. If a path cannot be solved, this will return `None` for that path. You can parallelize solving multiple paths with the *cpus* parameter, but be careful to not exceed your available RAM.

See also *k_shortest_paths* to solve multiple shortest paths between a single origin and destination. For additional functionality or different solver algorithms, use NetworkX directly.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph

- **orig** (*int or list*) – origin node ID, or a list of origin node IDs
- **dest** (*int or list*) – destination node ID, or a list of destination node IDs
- **weight** (*string*) – edge attribute to minimize when solving shortest path
- **cpus** (*int*) – how many CPU cores to use; if None, use all available

Returns

path – list of node IDs constituting the shortest path, or, if orig and dest are lists, then a list of path lists

Return type

list

6.4.20 osmnx.settings module

Global settings that can be configured by the user.

all_oneway

[bool] Only use if specifically saving to .osm XML file with the *save_graph_xml* function. If True, forces all ways to be loaded as oneway ways, preserving the original order of nodes stored in the OSM way XML. This also retains original OSM string values for oneway attribute values, rather than converting them to a True/False bool. Default is *False*.

bidirectional_network_types

[list] Network types for which a fully bidirectional graph will be created. Default is [*“walk”*].

cache_folder

[str or pathlib.Path] Path to folder in which to save/load HTTP response cache, if the *use_cache* setting equals *True*. Default is *“./cache”*.

cache_only_mode

[bool] If True, download network data from Overpass then raise a *CacheOnlyModeInterrupt* error for user to catch. This prevents graph building from taking place and instead just saves OSM response data to cache. Useful for sequentially caching lots of raw data (as you can only query Overpass one request at a time) then using the local cache to quickly build many graphs simultaneously with multiprocessing. Default is *False*.

data_folder

[str or pathlib.Path] Path to folder in which to save/load graph files by default. Default is *“./data”*.

default_accept_language

[str] Do not use, deprecated. Use *http_accept_language* instead.

default_access

[str] Default filter for OSM “access” key. Default is [*“access”!~“private”*]. Note that also filtering out “access=no” ways prevents including transit-only bridges (e.g., Tilikum Crossing) from appearing in drivable road network (e.g., [*“access”!~“private|no”*]). However, some drivable tollroads have “access=no” plus a “access:conditional” key to clarify when it is accessible, so we can’t filter out all “access=no” ways by default. Best to be permissive here then remove complicated combinations of tags programatically after the full graph is downloaded and constructed.

default_crs

[str] Default coordinate reference system to set when creating graphs. Default is *“epsg:4326”*.

default_referer

[str] Do not use, deprecated. Use *http_referer* instead.

default_user_agent

[str] Do not use, deprecated. Use *http_user_agent* instead.

doh_url_template

[str] Endpoint to resolve DNS-over-HTTPS if local DNS resolution fails. Set to `None` to disable DoH, but see *downloader._config_dns* documentation for caveats. Default is: `"https://8.8.8.8/resolve?name={hostname}"`

elevation_url_template

[str] Endpoint of the Google Maps Elevation API (or equivalent), containing exactly two parameters: *locations* and *key*. Default is: `"https://maps.googleapis.com/maps/api/elevation/json?locations={locations}&key={key}"`
One example of an alternative equivalent would be Open Topo Data: `"https://api.opentopodata.org/v1/aster30m?locations={locations}&key={key}"`

http_accept_language

[str] HTTP header accept-language. Default is `"en"`. Note that Nominatim's default language is `"en"` and it can sort result importance scores differently if a different language is specified.

http_referer

[str] HTTP header referer. Default is `"OSMnx Python package (https://github.com/gboeing/osmnx)"`.

http_user_agent

[str] HTTP header user-agent. Default is `"OSMnx Python package (https://github.com/gboeing/osmnx)"`.

imgs_folder

[str or pathlib.Path] Path to folder in which to save plotted images by default. Default is `"/images"`.

log_file

[bool] If True, save log output to a file in *logs_folder*. Default is `False`.

log_filename

[str] Name of the log file, without file extension. Default is `"osmnx"`.

log_console

[bool] If True, print log output to the console (terminal window). Default is `False`.

log_level

[int] One of Python's `logging.level` constants. Default is `logging.INFO`.

log_name

[str] Name of the logger. Default is `"OSMnx"`.

logs_folder

[str or pathlib.Path] Path to folder in which to save log files. Default is `"/logs"`.

max_query_area_size

[int] Maximum area for any part of the geometry in meters: any polygon bigger than this will get divided up for multiple queries to the API. Default is `2500000000`.

memory

[int] Do not use, deprecated. Use *overpass_memory* instead.

nominatim_endpoint

[str] Do not use, deprecated. Use *nominatim_url* instead.

nominatim_key

[str] Your Nominatim API key, if you are using an API instance that requires one. Default is `None`.

nominatim_url

[str] The base API url to use for Nominatim queries. Default is `"https://nominatim.openstreetmap.org/"`.

osm_xml_node_attrs

[list] Do not use, deprecated.

osm_xml_node_tags

[list] Do not use, deprecated.

osm_xml_way_attrs

[list] Do not use, deprecated.

osm_xml_way_tags

[list] Do not use, deprecated.

overpass_endpoint

[str] Do not use, deprecated. Use *overpass_url* instead.

overpass_memory

[int | None] Overpass server memory allocation size for the query, in bytes. If None, server will choose its default allocation size. Use with caution. Default is *None*.

overpass_rate_limit

[bool] If True, check the Overpass server status endpoint for how long to pause before making request. Necessary if server uses slot management, but can be set to False if you are running your own overpass instance without rate limiting. Default is *True*.

overpass_settings

[str] Settings string for Overpass queries. Default is “[out:json][timeout:{timeout}][maxsize]”. By default, the {timeout} and {maxsize} values are set dynamically by OSMnx when used. To query, for example, historical OSM data as of a certain date: “[out:json][timeout:90][date:”2019-10-28T19:20:00Z”]”. Use with caution.

overpass_url

[str] The base API url to use for Overpass queries. Default is “https://overpass-api.de/api”.

requests_kwargs

[dict] Optional keyword args to pass to the requests package when connecting to APIs, for example to configure authentication or provide a path to a local certificate file. More info on options such as auth, cert, verify, and proxies can be found in the requests package advanced docs. Default is {}.

requests_timeout

[int] The timeout interval in seconds for HTTP requests, and (when applicable) for Overpass server to use for executing the query. Default is *180*.

timeout

[int] Do not use, deprecated. Use *requests_timeout* instead.

use_cache

[bool] If True, cache HTTP responses locally instead of calling API repeatedly for the same request. Default is *True*.

useful_tags_node

[list] OSM “node” tags to add as graph node attributes, when present in the data retrieved from OSM. Default is [“ref”, “highway”].

useful_tags_way

[list] OSM “way” tags to add as graph edge attributes, when present in the data retrieved from OSM. Default is [“bridge”, “tunnel”, “oneway”, “lanes”, “ref”, “name”, “highway”, “maxspeed”, “service”, “access”, “area”, “landuse”, “width”, “est_width”, “junction”].

6.4.21 osmnx.simplification module

Simplify, correct, and consolidate network topology.

`osmnx.simplification._build_path(G, endpoint, endpoint_successor, endpoints)`

Build a path of nodes from one endpoint node to next endpoint node.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **endpoint** (*int*) – the endpoint node from which to start the path
- **endpoint_successor** (*int*) – the successor of endpoint through which the path to the next endpoint will be built
- **endpoints** (*set*) – the set of all nodes in the graph that are endpoints

Returns

path – the first and last items in the resulting path list are endpoint nodes, and all other items are interstitial nodes that can be removed subsequently

Return type

list

`osmnx.simplification._consolidate_intersections_rebuild_graph(G, tolerance=10, reconnect_edges=True)`

Consolidate intersections comprising clusters of nearby nodes.

Merge nodes and return a rebuilt graph with consolidated intersections and reconnected edge geometries.

The tolerance argument should be adjusted to approximately match street design standards in the specific street network, and you should always use a projected graph to work in meaningful and consistent units like meters.

Returned graph's node IDs represent clusters rather than osmids. Refer to nodes' `osmid_original` attributes for original osmids. If multiple nodes were merged together, the `osmid_original` attribute is a list of merged nodes' osmids.

Parameters

- **G** (*networkx.MultiDiGraph*) – a projected graph
- **tolerance** (*float*) – nodes are buffered to this distance (in graph's geometry's units) and subsequent overlaps are dissolved into a single node
- **reconnect_edges** (*bool*) – ignored if `rebuild_graph` is not `True`. if `True`, reconnect edges and their geometries in rebuilt graph to the consolidated nodes and update edge length attributes; if `False`, returned graph has no edges (which is faster if you just need topologically consolidated intersection counts).

Returns

H – a rebuilt graph with consolidated intersections and reconnected edge geometries

Return type

networkx.MultiDiGraph

`osmnx.simplification._get_paths_to_simplify(G, endpoint_attrs)`

Generate all the paths to be simplified between endpoint nodes.

The path is ordered from the first endpoint, through the interstitial nodes, to the second endpoint.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph

- **endpoint_attrs** (*iterable*) – An iterable of edge attribute names for relaxing the strictness of endpoint determination. If not None, a node is an endpoint if its incident edges have different values then each other for any of the edge attributes in *endpoint_attrs*.

Yields

path_to_simplify (*list*) – a generator of paths to simplify

`osmnx.simplification._is_endpoint(G, node, endpoint_attrs)`

Determine if a node is a true endpoint of an edge.

Return True if the node is a “true” endpoint of an edge in the network, otherwise False. OpenStreetMap data includes many nodes that exist only as geometric vertices to allow ways to curve. A true edge endpoint is a node that satisfies at least 1 of the following 4 rules:

- 1) It is its own neighbor (ie, it self-loops).
- 2) Or, it has no incoming edges or no outgoing edges (ie, all its incident edges are inbound or all its incident edges are outbound).
- 3) Or, it does not have exactly two neighbors and degree of 2 or 4.
- 4) Or, if *endpoint_attrs* is not None, and its incident edges have different values than each other for any of the edge attributes in *endpoint_attrs*.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **node** (*int*) – the node to examine
- **endpoint_attrs** (*iterable*) – An iterable of edge attribute names for relaxing the strictness of endpoint determination. If not None, a node is an endpoint if its incident edges have different values then each other for any of the edge attributes in *endpoint_attrs*.

Return type

bool

`osmnx.simplification._merge_nodes_geometric(G, tolerance)`

Geometrically merge nodes within some distance of each other.

Parameters

- **G** (*networkx.MultiDiGraph*) – a projected graph
- **tolerance** (*float*) – buffer nodes to this distance (in graph’s geometry’s units) then merge overlapping polygons into a single polygon via a unary union operation

Returns

merged – the merged overlapping polygons of the buffered nodes

Return type

GeoSeries

`osmnx.simplification._remove_rings(G, endpoint_attrs)`

Remove all self-contained rings from a graph.

This identifies any connected components that form a self-contained ring without any endpoints, and removes them from the graph.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph

- **endpoint_attrs** (*iterable*) – An iterable of edge attribute names for relaxing the strictness of endpoint determination. If not None, a node is an endpoint if its incident edges have different values than each other for any of the edge attributes in *endpoint_attrs*.

Returns

G – graph with self-contained rings removed

Return type

networkx.MultiDiGraph

`osmnx.simplification.consolidate_intersections(G, tolerance=10, rebuild_graph=True, dead_ends=False, reconnect_edges=True)`

Consolidate intersections comprising clusters of nearby nodes.

Merges nearby nodes and returns either their centroids or a rebuilt graph with consolidated intersections and reconnected edge geometries. The tolerance argument should be adjusted to approximately match street design standards in the specific street network, and you should always use a projected graph to work in meaningful and consistent units like meters. Note the tolerance represents a per-node buffering radius: for example, to consolidate nodes within 10 meters of each other, use `tolerance=5`.

When `rebuild_graph=False`, it uses a purely geometrical (and relatively fast) algorithm to identify “geometrically close” nodes, merge them, and return just the merged intersections’ centroids. When `rebuild_graph=True`, it uses a topological (and slower but more accurate) algorithm to identify “topologically close” nodes, merge them, then rebuild/return the graph. Returned graph’s node IDs represent clusters rather than osmids. Refer to nodes’ `osmid_original` attributes for original osmids. If multiple nodes were merged together, the `osmid_original` attribute is a list of merged nodes’ osmids.

Divided roads are often represented by separate centerline edges. The intersection of two divided roads thus creates 4 nodes, representing where each edge intersects a perpendicular edge. These 4 nodes represent a single intersection in the real world. A similar situation occurs with roundabouts and traffic circles. This function consolidates nearby nodes by buffering them to an arbitrary distance, merging overlapping buffers, and taking their centroid.

Parameters

- **G** (*networkx.MultiDiGraph*) – a projected graph
- **tolerance** (*float*) – nodes are buffered to this distance (in graph’s geometry’s units) and subsequent overlaps are dissolved into a single node
- **rebuild_graph** (*bool*) – if True, consolidate the nodes topologically, rebuild the graph, and return as `networkx.MultiDiGraph`. if False, consolidate the nodes geometrically and return the consolidated node points as `geopandas.GeoSeries`
- **dead_ends** (*bool*) – if False, discard dead-end nodes to return only street-intersection points
- **reconnect_edges** (*bool*) – ignored if `rebuild_graph` is not True. if True, reconnect edges and their geometries in rebuilt graph to the consolidated nodes and update edge length attributes; if False, returned graph has no edges (which is faster if you just need topologically consolidated intersection counts).

Returns

if `rebuild_graph=True`, returns `MultiDiGraph` with consolidated intersections and reconnected edge geometries. if `rebuild_graph=False`, returns `GeoSeries` of shapely Points representing the centroids of street intersections

Return type

`networkx.MultiDiGraph` or `geopandas.GeoSeries`

`osmnx.simplification.simplify_graph(G, strict=None, edge_attrs_differ=None, endpoint_attrs=None, remove_rings=True, track_merged=False)`

Simplify a graph's topology by removing interstitial nodes.

This simplifies graph topology by removing all nodes that are not intersections or dead-ends, by creating an edge directly between the end points that encapsulate them while retaining the full geometry of the original edges, saved as a new *geometry* attribute on the new edge.

Note that only simplified edges receive a *geometry* attribute. Some of the resulting consolidated edges may comprise multiple OSM ways, and if so, their multiple attribute values are stored as a list. Optionally, the simplified edges can receive a *merged_edges* attribute that contains a list of all the (u, v) node pairs that were merged together.

Use the *edge_attrs_differ* parameter to relax simplification strictness. For example, *edge_attrs_differ=['osmid']* will retain every node whose incident edges have different OSM IDs. This lets you keep nodes at elbow two-way intersections (but be aware that sometimes individual blocks have multiple OSM IDs within them too). You could also use this parameter to retain nodes where sidewalks or bike lanes begin/end in the middle of a block.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **strict** (*bool*) – deprecated, do not use
- **edge_attrs_differ** (*iterable*) – An iterable of edge attribute names for relaxing the strictness of endpoint determination. If not None, a node is an endpoint if its incident edges have different values then each other for any of the edge attributes in *edge_attrs_differ*.
- **endpoint_attrs** (*iterable*) – deprecated, do not use
- **remove_rings** (*bool*) – if True, remove isolated self-contained rings that have no endpoints
- **track_merged** (*bool*) – if True, add *merged_edges* attribute on simplified edges, containing a list of all the (u, v) node pairs that were merged together

Returns

G – topologically simplified graph, with a new *geometry* attribute on each simplified edge

Return type

networkx.MultiDiGraph

6.4.22 osmnx.speed module

Calculate graph edge speeds and travel times.

`osmnx.speed.add_edge_speeds(G, hwy_speeds=None, fallback=None, precision=None, agg=<function mean>)`

Do not use: deprecated.

Use the *routing.add_edge_speeds* function instead.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **hwy_speeds** (*dict*) – deprecated, do not use
- **fallback** (*numeric*) – deprecated, do not use
- **precision** (*int*) – deprecated, do not use
- **agg** (*function*) – deprecated, do not use

Returns**G****Return type**

networkx.MultiDiGraph

`osmnx.speed.add_edge_travel_times(G, precision=None)`

Do not use: deprecated.

Use the `routing.add_edge_travel_times` function instead.**Parameters**

- **G** (`networkx.MultiDiGraph`) – deprecated, do not use
- **precision** (`int`) – deprecated, do not use

Returns**G****Return type**

networkx.MultiDiGraph

6.4.23 osmnx.stats module

Calculate geometric and topological network measures.

This module defines streets as the edges in an undirected representation of the graph. Using undirected graph edges prevents double-counting bidirectional edges of a two-way street, but may double-count a divided road's separate centerlines with different end point nodes. If `clean_periphery=True` when the graph was created (which is the default parameterization), then you will get accurate node degrees (and in turn streets-per-node counts) even at the periphery of the graph.

You can use NetworkX directly for additional topological network measures.

`osmnx.stats.basic_stats(G, area=None, clean_int_tol=None)`

Calculate basic descriptive geometric and topological measures of a graph.

Density measures are only calculated if `area` is provided and clean intersection measures are only calculated if `clean_int_tol` is provided.**Parameters**

- **G** (`networkx.MultiDiGraph`) – input graph
- **area** (`float`) – if not None, calculate density measures and use this value (in square meters) as the denominator
- **clean_int_tol** (`float`) – if not None, calculate consolidated intersections count (and density, if `area` is also provided) and use this tolerance value; refer to the *simplification consolidate_intersections* function documentation for details

Returns**stats** –

dictionary containing the following keys

- `circuitry_avg` - see `circuitry_avg` function documentation
- `clean_intersection_count` - see `clean_intersection_count` function documentation
- `clean_intersection_density_km` - `clean_intersection_count` per sq km

- *edge_density_km* - *edge_length_total* per sq km
- *edge_length_avg* - *edge_length_total* / *m*
- *edge_length_total* - see *edge_length_total* function documentation
- *intersection_count* - see *intersection_count* function documentation
- *intersection_density_km* - *intersection_count* per sq km
- *k_avg* - graph's average node degree (in-degree and out-degree)
- *m* - count of edges in graph
- *n* - count of nodes in graph
- *node_density_km* - *n* per sq km
- *self_loop_proportion* - see *self_loop_proportion* function documentation
- *street_density_km* - *street_length_total* per sq km
- *street_length_avg* - *street_length_total* / *street_segment_count*
- *street_length_total* - see *street_length_total* function documentation
- *street_segment_count* - see *street_segment_count* function documentation
- *streets_per_node_avg* - see *streets_per_node_avg* function documentation
- *streets_per_node_counts* - see *streets_per_node_counts* function documentation
- *streets_per_node_proportions* - see *streets_per_node_proportions* function documentation

Return type

dict

`osmnx.stats.circuitry_avg(Gu)`

Calculate average street circuitry using edges of undirected graph.

Circuitry is the sum of edge lengths divided by the sum of straight-line distances between edge endpoints. Calculates straight-line distance as euclidean distance if projected or great-circle distance if unprojected.

Parameters**Gu** (*networkx.MultiGraph*) – undirected input graph**Returns****circuitry_avg** – the graph's average undirected edge circuitry**Return type**

float

`osmnx.stats.count_streets_per_node(G, nodes=None)`

Count how many physical street segments connect to each node in a graph.

This function uses an undirected representation of the graph and special handling of self-loops to accurately count physical streets rather than directed edges. Note: this function is automatically run by all the *graph.graph_from_x* functions prior to truncating the graph to the requested boundaries, to add accurate *street_count* attributes to each node even if some of its neighbors are outside the requested graph boundaries.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **nodes** (*list*) – which node IDs to get counts for. if *None*, use all graph nodes, otherwise calculate counts only for these node IDs

Returns

streets_per_node – counts of how many physical streets connect to each node, with keys = node ids and values = counts

Return type

dict

`osmnx.stats.edge_length_total(G)`

Calculate graph's total edge length.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

length – total length (meters) of edges in graph

Return type

float

`osmnx.stats.intersection_count(G=None, min_streets=2)`

Count the intersections in a graph.

Intersections are defined as nodes with at least *min_streets* number of streets incident on them.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **min_streets** (*int*) – a node must have at least *min_streets* incident on them to count as an intersection

Returns

count – count of intersections in graph

Return type

int

`osmnx.stats.self_loop_proportion(Gu)`

Calculate percent of edges that are self-loops in a graph.

A self-loop is defined as an edge from node *u* to node *v* where *u==v*.

Parameters

Gu (*networkx.MultiGraph*) – undirected input graph

Returns

proportion – proportion of graph edges that are self-loops

Return type

float

`osmnx.stats.street_length_total(Gu)`

Calculate graph's total street segment length.

Parameters

Gu (*networkx.MultiGraph*) – undirected input graph

Returns

length – total length (meters) of streets in graph

Return type

float

`osmnx.stats.street_segment_count(Gu)`

Count the street segments in a graph.

Parameters

Gu (*networkx.MultiGraph*) – undirected input graph

Returns

count – count of street segments in graph

Return type

int

`osmnx.stats.streets_per_node(G)`

Count streets (undirected edges) incident on each node.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

spn – dictionary with node ID keys and street count values

Return type

dict

`osmnx.stats.streets_per_node_avg(G)`

Calculate graph's average count of streets per node.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

spna – average count of streets per node

Return type

float

`osmnx.stats.streets_per_node_counts(G)`

Calculate streets-per-node counts.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

spnc – dictionary keyed by count of streets incident on each node, and with values of how many nodes in the graph have this count

Return type

dict

`osmnx.stats.streets_per_node_proportions(G)`

Calculate streets-per-node proportions.

Parameters

G (*networkx.MultiDiGraph*) – input graph

Returns

spnp – dictionary keyed by count of streets incident on each node, and with values of what proportion of nodes in the graph have this count

Return type

dict

6.4.24 osmnx.truncate module

Truncate graph by distance, bounding box, or polygon.

`osmnx.truncate.largest_component(G, strongly=False)`

Get subgraph of G's largest weakly/strongly connected component.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **strongly** (*bool*) – if True, return the largest strongly instead of weakly connected component

Returns

G – the largest connected component subgraph of the original graph

Return type

networkx.MultiDiGraph

`osmnx.truncate.truncate_graph_bbox(G, north=None, south=None, east=None, west=None, bbox=None, truncate_by_edge=False, retain_all=False, quadrat_width=None, min_num=None)`

Remove every node in graph that falls outside a bounding box.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)
- **truncate_by_edge** (*bool*) – if True, retain nodes outside bounding box if at least one of node's neighbors is within the bounding box
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **quadrat_width** (*float*) – deprecated, do not use
- **min_num** (*int*) – deprecated, do not use

Returns

G – the truncated graph

Return type

networkx.MultiDiGraph

`osmnx.truncate.truncate_graph_dist(G, source_node, max_dist=1000, weight='length', retain_all=False)`

Remove every node farther than some network distance from `source_node`.

This function can be slow for large graphs, as it must calculate shortest path distances between `source_node` and every other graph node.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph

- **source_node** (*int*) – node in graph from which to measure network distances to other nodes
- **max_dist** (*float*) – remove every node in the graph that is greater than this distance (in same units as *weight* attribute) along the network from *source_node*
- **weight** (*string*) – graph edge attribute to use to measure distance
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.

Returns

G – the truncated graph

Return type

networkx.MultiDiGraph

```
osmnx.truncate.truncate_graph_polygon(G, polygon, retain_all=False, truncate_by_edge=False,
                                       quadrat_width=None, min_num=None)
```

Remove every node in graph that falls outside a (Multi)Polygon.

Parameters

- **G** (*networkx.MultiDiGraph*) – input graph
- **polygon** (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – only retain nodes in graph that lie within this geometry
- **retain_all** (*bool*) – if True, return the entire graph even if it is not connected. otherwise, retain only the largest weakly connected component.
- **truncate_by_edge** (*bool*) – if True, retain nodes outside boundary polygon if at least one of node's neighbors is within the polygon
- **quadrat_width** (*float*) – deprecated, do not use
- **min_num** (*int*) – deprecated, do not use

Returns

G – the truncated graph

Return type

networkx.MultiDiGraph

6.4.25 osmnx.utils module

General utility functions.

```
osmnx.utils._get_logger(level, name, filename)
```

Create a logger or return the current one if already instantiated.

Parameters

- **level** (*int*) – one of Python's logger.level constants
- **name** (*string*) – name of the logger
- **filename** (*string*) – name of the log file, without file extension

Returns

logger

Return type

logging.logger

`osmnx.utils.citation(style='bibtex')`

Print the OSMnx package's citation information.

Boeing, G. (2024). Modeling and Analyzing Urban Networks and Amenities with OSMnx. Working paper.
<https://geoffboeing.com/publications/osmnx-paper/>

Parameters

style (*string* {"*apa*", "*bibtex*", "*ieee*"}) – citation format, either APA or BibTeX or IEEE

Return type

None

`osmnx.utils.config(all_oneway=False, bidirectional_network_types=['walk'], cache_folder='./cache',
cache_only_mode=False, data_folder='./data', default_accept_language=None,
default_access='["access"!~"private"]', default_crs='epsg:4326', default_referer=None,
default_user_agent=None, imgs_folder='./images', log_console=False, log_file=False,
log_filename='osmnx', log_level=20, log_name='OSMnx', logs_folder='./logs',
max_query_area_size=2500000000, memory=None, nominatim_endpoint=None,
nominatim_key=None, osm_xml_node_attrs=None, osm_xml_node_tags=None,
osm_xml_way_attrs=None, osm_xml_way_tags=None, overpass_endpoint=None,
overpass_rate_limit=True, overpass_settings='[out:json][timeout:{timeout}][maxsize]',
requests_kwargs={}, timeout=None, use_cache=True, useful_tags_node=['ref', 'highway'],
useful_tags_way=['bridge', 'tunnel', 'oneway', 'lanes', 'ref', 'name', 'highway', 'maxspeed',
'service', 'access', 'area', 'landuse', 'width', 'est_width', 'junction'])`

Do not use: deprecated. Use the settings module directly.

Parameters

- **all_oneway** (*bool*) – deprecated
- **bidirectional_network_types** (*list*) – deprecated
- **cache_folder** (*string* or *pathlib.Path*) – deprecated
- **data_folder** (*string* or *pathlib.Path*) – deprecated
- **cache_only_mode** (*bool*) – deprecated
- **default_accept_language** (*string*) – deprecated
- **default_access** (*string*) – deprecated
- **default_crs** (*string*) – deprecated
- **default_referer** (*string*) – deprecated
- **default_user_agent** (*string*) – deprecated
- **imgs_folder** (*string* or *pathlib.Path*) – deprecated
- **log_file** (*bool*) – deprecated
- **log_filename** (*string*) – deprecated
- **log_console** (*bool*) – deprecated
- **log_level** (*int*) – deprecated
- **log_name** (*string*) – deprecated
- **logs_folder** (*string* or *pathlib.Path*) – deprecated
- **max_query_area_size** (*int*) – deprecated

- **memory** (*int*) – deprecated
- **nominatim_endpoint** (*string*) – deprecated
- **nominatim_key** (*string*) – deprecated
- **osm_xml_node_attrs** (*list*) – deprecated
- **osm_xml_node_tags** (*list*) – deprecated
- **osm_xml_way_attrs** (*list*) – deprecated
- **osm_xml_way_tags** (*list*) – deprecated
- **overpass_endpoint** (*string*) – deprecated
- **overpass_rate_limit** (*bool*) – deprecated
- **overpass_settings** (*string*) – deprecated
- **requests_kwargs** (*dict*) – deprecated
- **timeout** (*int*) – deprecated
- **use_cache** (*bool*) – deprecated
- **useful_tags_node** (*list*) – deprecated
- **useful_tags_way** (*list*) – deprecated

Return type

None

`osmnx.utils.log(message, level=None, name=None, filename=None)`

Write a message to the logger.

This logs to file and/or prints to the console (terminal), depending on the current configuration of settings.log_file and settings.log_console.

Parameters

- **message** (*string*) – the message to log
- **level** (*int*) – one of Python’s logger.level constants
- **name** (*string*) – name of the logger
- **filename** (*string*) – name of the log file, without file extension

Return type

None

`osmnx.utils.ts(style='datetime', template=None)`

Return current local timestamp as a string.

Parameters

- **style** (*string* {"datetime", "date", "time"}) – format the timestamp with this built-in style
- **template** (*string*) – if not None, format the timestamp with this format string instead of one of the built-in styles

Returns

ts – local timestamp string

Return type

string

6.4.26 osmnx.utils_geo module

Geospatial utility functions.

`osmnx.utils_geo._consolidate_subdivide_geometry(geometry)`

Consolidate and subdivide some geometry.

Consolidate a geometry into a convex hull, then subdivide it into smaller sub-polygons if its area exceeds max size (in geometry's units). Configure the max size via `max_query_area_size` in the settings module.

When the geometry has a very large area relative to its vertex count, the resulting MultiPolygon's boundary may differ somewhat from the input, due to the way long straight lines are projected. You can interpolate additional vertices along your input geometry's exterior to mitigate this.

Parameters

geometry (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – the projected (in meter units) geometry to consolidate and subdivide

Returns

geometry

Return type

shapely.geometry.MultiPolygon

`osmnx.utils_geo._intersect_index_quadrats(geometries, polygon)`

Identify geometries that intersect a (Multi)Polygon.

Uses an r-tree spatial index and cuts polygon up into smaller sub-polygons for r-tree acceleration. Ensure that geometries and polygon are in the same coordinate reference system.

Parameters

- **geometries** (*geopandas.GeoSeries*) – the geometries to intersect with the polygon
- **polygon** (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – the polygon to intersect with the geometries

Returns

geoms_in_poly – set of the index labels of the geometries that intersected the polygon

Return type

set

`osmnx.utils_geo._quadrat_cut_geometry(geometry, quadrat_width)`

Split a Polygon or MultiPolygon up into sub-polygons of a specified size.

Parameters

- **geometry** (*shapely.geometry.Polygon or shapely.geometry.MultiPolygon*) – the geometry to split up into smaller sub-polygons
- **quadrat_width** (*float*) – width (in geometry's units) of quadrat squares with which to split up the geometry

Returns

geometry

Return type

shapely.geometry.MultiPolygon

`osmnx.utils_geo._round_linestring_coords(ls, precision)`

Round the coordinates of a shapely LineString to some decimal precision.

Parameters

- **ls** (*shapely.geometry.LineString*) – the LineString to round the coordinates of
- **precision** (*int*) – decimal precision to round coordinates to

Return type

shapely.geometry.LineString

`osmnx.utils_geo._round_multilinestring_coords(mls, precision)`

Round the coordinates of a shapely MultiLineString to some decimal precision.

Parameters

- **mls** (*shapely.geometry.MultiLineString*) – the MultiLineString to round the coordinates of
- **precision** (*int*) – decimal precision to round coordinates to

Return type

shapely.geometry.MultiLineString

`osmnx.utils_geo._round_multipoint_coords(mpt, precision)`

Round the coordinates of a shapely MultiPoint to some decimal precision.

Parameters

- **mpt** (*shapely.geometry.MultiPoint*) – the MultiPoint to round the coordinates of
- **precision** (*int*) – decimal precision to round coordinates to

Return type

shapely.geometry.MultiPoint

`osmnx.utils_geo._round_multipolygon_coords(mp, precision)`

Round the coordinates of a shapely MultiPolygon to some decimal precision.

Parameters

- **mp** (*shapely.geometry.MultiPolygon*) – the MultiPolygon to round the coordinates of
- **precision** (*int*) – decimal precision to round coordinates to

Return type

shapely.geometry.MultiPolygon

`osmnx.utils_geo._round_point_coords(pt, precision)`

Round the coordinates of a shapely Point to some decimal precision.

Parameters

- **pt** (*shapely.geometry.Point*) – the Point to round the coordinates of
- **precision** (*int*) – decimal precision to round coordinates to

Return type

shapely.geometry.Point

`osmnx.utils_geo._round_polygon_coords(p, precision)`

Round the coordinates of a shapely Polygon to some decimal precision.

Parameters

- **p** (*shapely.geometry.Polygon*) – the polygon to round the coordinates of
- **precision** (*int*) – decimal precision to round coordinates to

Return type

shapely.geometry.Polygon

`osmnx.utils_geo.bbox_from_point(point, dist=1000, project_utm=False, return_crs=False)`

Create a bounding box around a (lat, lon) point.

Create a bounding box some distance (in meters) in each direction (north, south, east, and west) from the center point and optionally project it.

Parameters

- **point** (*tuple*) – the (lat, lon) center point to create the bounding box around
- **dist** (*int*) – bounding box distance in meters from the center point
- **project_utm** (*bool*) – if True, return bounding box as UTM-projected coordinates
- **return_crs** (*bool*) – if True, and project_utm=True, return the projected CRS too

Returns

bbox or **bbox, crs** – (north, south, east, west) or ((north, south, east, west), crs)

Return type

tuple or tuple, crs

`osmnx.utils_geo.bbox_to_poly(north=None, south=None, east=None, west=None, bbox=None)`

Convert bounding box coordinates to shapely Polygon.

Parameters

- **north** (*float*) – deprecated, do not use
- **south** (*float*) – deprecated, do not use
- **east** (*float*) – deprecated, do not use
- **west** (*float*) – deprecated, do not use
- **bbox** (*tuple of floats*) – bounding box as (north, south, east, west)

Return type

shapely.geometry.Polygon

`osmnx.utils_geo.interpolate_points(geom, dist)`

Interpolate evenly spaced points along a LineString.

The spacing is approximate because the LineString's length may not be evenly divisible by it.

Parameters

- **geom** (*shapely.geometry.LineString*) – a LineString geometry
- **dist** (*float*) – spacing distance between interpolated points, in same units as *geom*. smaller values accordingly generate more points.

Yields

points (*generator*) – tuples of (x, y) floats of the interpolated points' coordinates

`osmnx.utils_geo.round_geometry_coords(geom, precision)`

Do not use: deprecated.

Parameters

- **geom** (*shapely.geometry.geometry {Point, MultiPoint, LineString, MultiLineString, Polygon, MultiPolygon}*) – deprecated, do not use

- **precision** (*int*) – deprecated, do not use

Return type

shapely.geometry.geometry

`osmnx.utils_geo.sample_points(G, n)`

Randomly sample points constrained to a spatial graph.

This generates a graph-constrained uniform random sample of points. Unlike typical spatially uniform random sampling, this method accounts for the graph's geometry. And unlike equal-length edge segmenting, this method guarantees uniform randomness.

Parameters

- **G** (*networkx.MultiGraph*) – graph from which to sample points. should be undirected (to avoid oversampling bidirectional edges) and projected (for accurate point interpolation)
- **n** (*int*) – how many points to sample

Returns

points – the sampled points, multi-indexed by (u, v, key) of the edge from which each point was drawn

Return type

geopandas.GeoSeries

6.4.27 osmnx.utils_graph module

Graph utility functions.

`osmnx.utils_graph.get_digraph(G, weight='length')`

Do not use: deprecated.

Use the `convert.to_digraph` function instead.**Parameters**

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **weight** (*string*) – deprecated, do not use

Return type

networkx.DiGraph

`osmnx.utils_graph.get_largest_component(G, strongly=False)`

Do not use: deprecated.

Use the `truncate.largest_component` function instead.**Parameters**

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **strongly** (*bool*) – deprecated, do not use

Returns**G****Return type**

networkx.MultiDiGraph

```
osmnx.utils_graph.get_route_edge_attributes(G, route, attribute=None, minimize_key='length',
                                             retrieve_default=None)
```

Do not use: deprecated.

Use the `routing.route_to_gdf` function instead.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **route** (*list*) – deprecated, do not use
- **attribute** (*string*) – deprecated, do not use
- **minimize_key** (*string*) – deprecated, do not use
- **retrieve_default** (*Callable[Tuple[Any, Any], Any]*) – deprecated, do not use

Returns

attribute_values

Return type

list

```
osmnx.utils_graph.get_undirected(G)
```

Do not use: deprecated.

Use the `convert.to_undirected` function instead.

Parameters

G (*networkx.MultiDiGraph*) – deprecated, do not use

Return type

networkx.MultiGraph

```
osmnx.utils_graph.graph_from_gdfs(gdf_nodes, gdf_edges, graph_attrs=None)
```

Do not use: deprecated.

Use the `convert.graph_from_gdfs` function instead.

Parameters

- **gdf_nodes** (*geopandas.GeoDataFrame*) – deprecated, do not use
- **gdf_edges** (*geopandas.GeoDataFrame*) – deprecated, do not use
- **graph_attrs** (*dict*) – deprecated, do not use

Returns

G

Return type

networkx.MultiDiGraph

```
osmnx.utils_graph.graph_to_gdfs(G, nodes=True, edges=True, node_geometry=True,
                                  fill_edge_geometry=True)
```

Do not use: deprecated.

Use the `convert.graph_to_gdfs` function instead.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **nodes** (*bool*) – deprecated, do not use

- **edges** (*bool*) – deprecated, do not use
- **node_geometry** (*bool*) – deprecated, do not use
- **fill_edge_geometry** (*bool*) – deprecated, do not use

Return type

geopandas.GeoDataFrame or tuple

`osmnx.utils_graph.remove_isolated_nodes(G, warn=True)`

Do not use: deprecated.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **warn** (*bool*) – deprecated, do not use

Returns

G

Return type

networkx.MultiDiGraph

`osmnx.utils_graph.route_to_gdf(G, route, weight='length')`

Do not use: deprecated.

Use the `routing.route_to_gdf` function instead.

Parameters

- **G** (*networkx.MultiDiGraph*) – deprecated, do not use
- **route** (*list*) – deprecated, do not use
- **weight** (*string*) – deprecated, do not use

Returns

gdf_edges

Return type

geopandas.GeoDataFrame

6.4.28 osmnx._version module

OSMnx package version information.

6.5 Further Reading

Boeing, G. (2024). *Modeling and Analyzing Urban Networks and Amenities with OSMnx*. Working paper. <https://geoffboeing.com/publications/osmnx-paper/>

This is the official citation for the project.

Boeing, G. (2021). *Street Network Models and Indicators for Every Urban Area in the World*. *Geographical Analysis* 54 (3), 519-535.

This study uses OSMnx to model and analyze the street networks of every urban area in the world: over 160 million OpenStreetMap street network nodes and over 320 million edges across 8,914 urban areas in 178 countries.

Boeing, G. (2020). [The Right Tools for the Job: The Case for Spatial Science Tool-Building](#). *Transactions in GIS* 24 (5), 1299-1314.

This paper was presented as the 8th annual Transactions in GIS plenary address at the American Association of Geographers annual meeting in Washington, DC. It describes the development of OSMnx and reviews its use in scientific research over the previous few years.

Boeing, G. (2020). [Planarity and Street Network Representation in Urban Form Analysis](#). *Environment and Planning B: Urban Analytics and City Science* 47 (5), 855-869.

This paper discusses the importance of using nonplanar graphs when modeling urban street networks, which was one of the original motivations for developing OSMnx.

INDICES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

O

- `osmnx.bearing`, 17
- `osmnx.convert`, 19
- `osmnx.distance`, 20
- `osmnx.elevation`, 24
- `osmnx.features`, 25
- `osmnx.geocoder`, 29
- `osmnx.graph`, 30
- `osmnx.io`, 34
- `osmnx.plot`, 37
- `osmnx.projection`, 42
- `osmnx.routing`, 43
- `osmnx.settings`, 45
- `osmnx.simplification`, 48
- `osmnx.speed`, 49
- `osmnx.stats`, 50
- `osmnx.truncate`, 54
- `osmnx.utils`, 55
- `osmnx.utils_geo`, 58
- `osmnx.utils_graph`, 59

A

add_edge_bearings() (in module *osmnx.bearing*), 17
 add_edge_grades() (in module *osmnx.elevation*), 24
 add_edge_lengths() (in module *osmnx.distance*), 20
 add_edge_speeds() (in module *osmnx.routing*), 43
 add_edge_speeds() (in module *osmnx.speed*), 49
 add_edge_travel_times() (in module *osmnx.routing*), 44
 add_edge_travel_times() (in module *osmnx.speed*), 50
 add_node_elevations_google() (in module *osmnx.elevation*), 24
 add_node_elevations_raster() (in module *osmnx.elevation*), 25

B

basic_stats() (in module *osmnx.stats*), 50
 bbox_from_point() (in module *osmnx.utils_geo*), 58
 bbox_to_poly() (in module *osmnx.utils_geo*), 58

C

calculate_bearing() (in module *osmnx.bearing*), 17
 circuitry_avg() (in module *osmnx.stats*), 51
 citation() (in module *osmnx.utils*), 55
 config() (in module *osmnx.utils*), 56
 consolidate_intersections() (in module *osmnx.simplification*), 48
 count_streets_per_node() (in module *osmnx.stats*), 51

E

edge_length_total() (in module *osmnx.stats*), 52
 euclidean() (in module *osmnx.distance*), 21
 euclidean_dist_vec() (in module *osmnx.distance*), 21

F

features_from_address() (in module *osmnx.features*), 25
 features_from_bbox() (in module *osmnx.features*), 26
 features_from_place() (in module *osmnx.features*), 26

features_from_point() (in module *osmnx.features*), 27
 features_from_polygon() (in module *osmnx.features*), 27
 features_from_xml() (in module *osmnx.features*), 28

G

geocode() (in module *osmnx.geocoder*), 29
 geocode_to_gdf() (in module *osmnx.geocoder*), 29
 get_colors() (in module *osmnx.plot*), 37
 get_digraph() (in module *osmnx.utils_graph*), 59
 get_edge_colors_by_attr() (in module *osmnx.plot*), 37
 get_largest_component() (in module *osmnx.utils_graph*), 59
 get_node_colors_by_attr() (in module *osmnx.plot*), 37
 get_route_edge_attributes() (in module *osmnx.utils_graph*), 59
 get_undirected() (in module *osmnx.utils_graph*), 60
 graph_from_address() (in module *osmnx.graph*), 30
 graph_from_bbox() (in module *osmnx.graph*), 31
 graph_from_gdfs() (in module *osmnx.convert*), 19
 graph_from_gdfs() (in module *osmnx.utils_graph*), 60
 graph_from_place() (in module *osmnx.graph*), 31
 graph_from_point() (in module *osmnx.graph*), 32
 graph_from_polygon() (in module *osmnx.graph*), 33
 graph_from_xml() (in module *osmnx.graph*), 34
 graph_to_gdfs() (in module *osmnx.convert*), 19
 graph_to_gdfs() (in module *osmnx.utils_graph*), 60
 great_circle() (in module *osmnx.distance*), 21
 great_circle_vec() (in module *osmnx.distance*), 22

I

interpolate_points() (in module *osmnx.utils_geo*), 58
 intersection_count() (in module *osmnx.stats*), 52
 is_projected() (in module *osmnx.projection*), 42

K

k_shortest_paths() (in module *osmnx.distance*), 22
 k_shortest_paths() (in module *osmnx.routing*), 44

L

`largest_component()` (in module *osmnx.truncate*), 54
`load_graphml()` (in module *osmnx.io*), 34
`log()` (in module *osmnx.utils*), 57

M

module
 osmnx.bearing, 17
 osmnx.convert, 19
 osmnx.distance, 20
 osmnx.elevation, 24
 osmnx.features, 25
 osmnx.geocoder, 29
 osmnx.graph, 30
 osmnx.io, 34
 osmnx.plot, 37
 osmnx.projection, 42
 osmnx.routing, 43
 osmnx.settings, 45
 osmnx.simplification, 48
 osmnx.speed, 49
 osmnx.stats, 50
 osmnx.truncate, 54
 osmnx.utils, 55
 osmnx.utils_geo, 58
 osmnx.utils_graph, 59

N

`nearest_edges()` (in module *osmnx.distance*), 22
`nearest_nodes()` (in module *osmnx.distance*), 23

O

`orientation_entropy()` (in module *osmnx.bearing*), 18
osmnx.bearing
 module, 17
osmnx.convert
 module, 19
osmnx.distance
 module, 20
osmnx.elevation
 module, 24
osmnx.features
 module, 25
osmnx.geocoder
 module, 29
osmnx.graph
 module, 30
osmnx.io
 module, 34
osmnx.plot
 module, 37
osmnx.projection

 module, 42
osmnx.routing
 module, 43
osmnx.settings
 module, 45
osmnx.simplification
 module, 48
osmnx.speed
 module, 49
osmnx.stats
 module, 50
osmnx.truncate
 module, 54
osmnx.utils
 module, 55
osmnx.utils_geo
 module, 58
osmnx.utils_graph
 module, 59

P

`plot_figure_ground()` (in module *osmnx.plot*), 38
`plot_footprints()` (in module *osmnx.plot*), 38
`plot_graph()` (in module *osmnx.plot*), 39
`plot_graph_route()` (in module *osmnx.plot*), 40
`plot_graph_routes()` (in module *osmnx.plot*), 40
`plot_orientation()` (in module *osmnx.bearing*), 18
`plot_orientation()` (in module *osmnx.plot*), 41
`project_gdf()` (in module *osmnx.projection*), 42
`project_geometry()` (in module *osmnx.projection*), 42
`project_graph()` (in module *osmnx.projection*), 42

R

`remove_isolated_nodes()` (in module *osmnx.utils_graph*), 61
`round_geometry_coords()` (in module *osmnx.utils_geo*), 58
`route_to_gdf()` (in module *osmnx.routing*), 44
`route_to_gdf()` (in module *osmnx.utils_graph*), 61

S

`sample_points()` (in module *osmnx.utils_geo*), 59
`save_graph_geopackage()` (in module *osmnx.io*), 35
`save_graph_shapefile()` (in module *osmnx.io*), 35
`save_graph_xml()` (in module *osmnx.io*), 36
`save_graphml()` (in module *osmnx.io*), 36
`self_loop_proportion()` (in module *osmnx.stats*), 52
`shortest_path()` (in module *osmnx.distance*), 23
`shortest_path()` (in module *osmnx.routing*), 44
`simplify_graph()` (in module *osmnx.simplification*), 49
`street_length_total()` (in module *osmnx.stats*), 52
`street_segment_count()` (in module *osmnx.stats*), 53
`streets_per_node()` (in module *osmnx.stats*), 53
`streets_per_node_avg()` (in module *osmnx.stats*), 53

`streets_per_node_counts()` (*in module osmnx.stats*),
53
`streets_per_node_proportions()` (*in module*
osmnx.stats), 53

T

`to_digraph()` (*in module osmnx.convert*), 20
`to_undirected()` (*in module osmnx.convert*), 20
`truncate_graph_bbox()` (*in module osmnx.truncate*),
54
`truncate_graph_dist()` (*in module osmnx.truncate*),
54
`truncate_graph_polygon()` (*in module*
osmnx.truncate), 55
`ts()` (*in module osmnx.utils*), 57