

Libidn2

Internationalized Domain Names (IDNA2008/TR46)
Version 2.0.2, 24 April 2017

Simon Josefsson

This manual is for Libidn2 (version 2.0.2, 24 April 2017), an implementation of IDNA2008/TR46 internationalized domain names.

Copyright © 2011-2017 Simon Josefsson

Table of Contents

1	Introduction	1
2	Library Functions	2
2.1	Header file <code>idn2.h</code>	2
2.2	Core Functions	2
2.3	Locale Functions	4
2.4	Control Flags	6
2.5	Error Handling	6
2.6	Return Codes	7
2.7	Memory Handling	8
2.8	Version Check	8
3	Converting from <code>libidn</code>	10
4	Examples	11
4.1	ToASCII example	11
4.2	ToUnicode example	12
4.3	Lookup	13
4.4	Register	14
5	Invoking <code>idn2</code>	16
5.1	Options	16
5.2	Environment Variables	16
5.3	Examples	17
5.4	Troubleshooting	17
	Interface Index	20
	Concept Index	21

1 Introduction

Libidn2 is a free software implementation of IDNA2008, Punycode and TR46. It contains functionality to convert internationalized domain names to and from ASCII Compatible Encoding (ACE), following the IDNA2008 and TR46 standards.

For technical reference, see RFC 5890 (<https://tools.ietf.org/html/rfc5890>), RFC 5891 (<https://tools.ietf.org/html/rfc5891>), RFC 5892 (<https://tools.ietf.org/html/rfc5892>), RFC 5893 (<https://tools.ietf.org/html/rfc5893>), and TR46 (<http://www.unicode.org/reports/tr46/>).

Libidn2 uses GNU libunistring (<https://www.gnu.org/software/libunistring/>) for Unicode processing and GNU libiconv (<https://www.gnu.org/software/libiconv/>) for character set conversion.

This library is backwards (API) compatible with the legacy libidn library (<https://www.gnu.org/software/libidn/>). See Chapter 3 [Converting from libidn], page 10 for more information.

Libidn2 is believed to be a complete IDNA2008 and TR46 implementation, but has yet to be as extensively used as the IDNA2003 Libidn library.

The library is dual-licensed under LGPLv3 or GPLv2, see the file COPYING for detailed information.

2 Library Functions

Below are the interfaces of the Libidn2 library documented.

2.1 Header file `idn2.h`

To use the functions documented in this chapter, you need to include the file `idn2.h` like this:

```
#include <idn2.h>
```

2.2 Core Functions

When you have the data encoded in UTF-8 form the direct interfaces to the library are as follows.

`idn2_to_ascii_8z`

```
int idn2_to_ascii_8z (const char * input, char ** output, int flags) [Function]
```

input: zero terminated input UTF-8 string.

output: pointer to newly allocated output string.

flags: are ignored

Convert UTF-8 domain name to ASCII string using the IDNA2008 rules. The domain name may contain several labels, separated by dots. The output buffer must be deallocated by the caller.

When unsure, it is recommended to call this function with the `IDN2_NONTRANSITIONAL` and `IDN2_NFC_INPUT` flags.

Return value: Returns `IDN2_OK` on success, or error code.

Since: 2.0.0

`idn2_to_unicode_8z8z`

```
int idn2_to_unicode_8z8z (const char * input, char ** output, int flags) [Function]
```

input: Input zero-terminated UTF-8 string.

output: Newly allocated UTF-8 output string.

flags: Currently unused.

Converts a possibly ACE encoded domain name in UTF-8 format into a UTF-8 string (punycode decoding). The output buffer will be zero-terminated and must be deallocated by the caller.

output may be NULL to test lookup of *input* without allocating memory.

Since: 2.0.0

idn2_lookup_u8

```
int idn2_lookup_u8 (const uint8_t * src, uint8_t ** lookupname, int flags) [Function]
```

src: input zero-terminated UTF-8 string in Unicode NFC normalized form.

lookupname: newly allocated output variable with name to lookup in DNS.

flags: optional `idn2_flags` to modify behaviour.

Perform IDNA2008 lookup string conversion on domain name *src* , as described in section 5 of RFC 5891. Note that the input string must be encoded in UTF-8 and be in Unicode NFC form.

Pass `IDN2_NFC_INPUT` in *flags* to convert input to NFC form before further processing. Pass `IDN2_ALABEL_ROUNDTRIP` in *flags* to convert any input A-labels to U-labels and perform additional testing. Pass `IDN2_TRANSITIONAL` to enable Unicode TR46 transitional processing, and `IDN2_NONTRANSITIONAL` to enable Unicode TR46 non-transitional processing. Multiple flags may be specified by binary or'ing them together, for example `IDN2_NFC_INPUT | IDN2_NONTRANSITIONAL` .

After version 0.11: *lookupname* may be NULL to test lookup of *src* without allocating memory.

Returns: On successful conversion `IDN2_OK` is returned, if the output domain or any label would have been too long `IDN2_TOO_BIG_DOMAIN` or `IDN2_TOO_BIG_LABEL` is returned, or another error code is returned.

Since: 0.1

idn2_register_u8

```
int idn2_register_u8 (const uint8_t * ulabel, const uint8_t * alabel, uint8_t ** insertname, int flags) [Function]
```

ulabel: input zero-terminated UTF-8 and Unicode NFC string, or NULL.

alabel: input zero-terminated ACE encoded string (xn-), or NULL.

insertname: newly allocated output variable with name to register in DNS.

flags: optional `idn2_flags` to modify behaviour.

Perform IDNA2008 register string conversion on domain label *ulabel* and *alabel* , as described in section 4 of RFC 5891. Note that the input *ulabel* must be encoded in UTF-8 and be in Unicode NFC form.

Pass `IDN2_NFC_INPUT` in *flags* to convert input *ulabel* to NFC form before further processing.

It is recommended to supply both *ulabel* and *alabel* for better error checking, but supplying just one of them will work. Passing in only *alabel* is better than only *ulabel* . See RFC 5891 section 4 for more information.

After version 0.11: *insertname* may be NULL to test conversion of *src* without allocating memory.

Returns: On successful conversion `IDN2_OK` is returned, when the given *ulabel* and *alabel* does not match each other `IDN2_UALABEL_MISMATCH` is returned, when either of the input labels are too long `IDN2_TOO_BIG_LABEL` is returned, when *alabel* does

does not appear to be a proper A-label `IDN2_INVALID_ALABEL` is returned, or another error code is returned.

2.3 Locale Functions

As a convenience, the following functions are provided that will convert the input from the locale encoding format to UTF-8 and normalize the string using NFC, and then apply the core functions described earlier.

`idn2_to_ascii_lz`

`int idn2_to_ascii_lz (const char * input, char ** output, int flags)` [Function]

input: zero terminated input UTF-8 string.

output: pointer to newly allocated output string.

flags: are ignored

Convert a domain name in locale's encoding to ASCII string using the IDNA2008 rules. The domain name may contain several labels, separated by dots. The output buffer must be deallocated by the caller.

When unsure, it is recommended to call this function with the `IDN2_NONTRANSITIONAL` and `IDN2_NFC_INPUT` flags.

Returns: `IDN2_OK` on success, or error code. Same as described in `idn2_lookup_ul()` documentation.

Since: 2.0.0

`idn2_to_unicode_8z1z`

`int idn2_to_unicode_8z1z (const char * input, char ** output, int flags)` [Function]

input: Input zero-terminated UTF-8 string.

output: Newly allocated output string in current locale's character set.

flags: Currently unused.

Converts a possibly ACE encoded domain name in UTF-8 format into a string encoded in the current locale's character set (punycode decoding). The output buffer will be zero-terminated and must be deallocated by the caller.

output may be `NULL` to test lookup of *input* without allocating memory.

Since: 2.0.0

`idn2_to_unicode_lz1z`

`int idn2_to_unicode_lz1z (const char * input, char ** output, int flags)` [Function]

input: Input zero-terminated string encoded in the current locale's character set.

output: Newly allocated output string in current locale's character set.

flags: Currently unused.

Converts a possibly ACE encoded domain name in the locale's character set into a string encoded in the current locale's character set (punycode decoding). The output buffer will be zero-terminated and must be deallocated by the caller.

output may be NULL to test lookup of `input` without allocating memory.

Since: 2.0.0

idn2_lookup_ul

`int idn2_lookup_ul (const char * src, char ** lookupname, int flags)` [Function]

src: input zero-terminated locale encoded string.

lookupname: newly allocated output variable with name to lookup in DNS.

flags: optional `idn2_flags` to modify behaviour.

Perform IDNA2008 lookup string conversion on domain name `src`, as described in section 5 of RFC 5891. Note that the input is assumed to be encoded in the locale's default coding system, and will be transcoded to UTF-8 and NFC normalized by this function.

Pass `IDN2_ALABEL_ROUNDTRIP` in `flags` to convert any input A-labels to U-labels and perform additional testing. Pass `IDN2_TRANSITIONAL` to enable Unicode TR46 transitional processing, and `IDN2_NONTRANSITIONAL` to enable Unicode TR46 non-transitional processing. Multiple flags may be specified by binary or'ing them together, for example `IDN2_ALABEL_ROUNDTRIP | IDN2_NONTRANSITIONAL`. The `IDN2_NFC_INPUT` in `flags` is always enabled in this function.

After version 0.11: `lookupname` may be NULL to test lookup of `src` without allocating memory.

Returns: On successful conversion `IDN2_OK` is returned, if conversion from locale to UTF-8 fails then `IDN2_ICONV_FAIL` is returned, if the output domain or any label would have been too long `IDN2_TOO_BIG_DOMAIN` or `IDN2_TOO_BIG_LABEL` is returned, or another error code is returned.

Since: 0.1

idn2_register_ul

`int idn2_register_ul (const char * ulabel, const char * alabel, char ** insertname, int flags)` [Function]

ulabel: input zero-terminated locale encoded string, or NULL.

alabel: input zero-terminated ACE encoded string (xn-), or NULL.

insertname: newly allocated output variable with name to register in DNS.

flags: optional `idn2_flags` to modify behaviour.

Perform IDNA2008 register string conversion on domain label `ulabel` and `alabel`, as described in section 4 of RFC 5891. Note that the input `ulabel` is assumed to be encoded in the locale's default coding system, and will be transcoded to UTF-8 and NFC normalized by this function.

It is recommended to supply both `ulabel` and `alabel` for better error checking, but supplying just one of them will work. Passing in only `alabel` is better than only `ulabel`. See RFC 5891 section 4 for more information.

After version 0.11: `insertname` may be `NULL` to test conversion of `src` without allocating memory.

Returns: On successful conversion `IDN2_OK` is returned, when the given `ulabel` and `alabel` does not match each other `IDN2_UALABEL_MISMATCH` is returned, when either of the input labels are too long `IDN2_TOO_BIG_LABEL` is returned, when `alabel` does not appear to be a proper A-label `IDN2_INVALID_ALABEL` is returned, or another error code is returned.

2.4 Control Flags

The `flags` parameter can take on the following values, or a bit-wise inclusive or of any subset of the parameters:

`idn2_flags IDN2_NFC_INPUT` [Global flag]
Apply NFC normalization on input.

`idn2_flags IDN2_ALABEL_ROUNDTRIP` [Global flag]
Apply additional round-trip conversion of A-label inputs.

`idn2_flags IDN2_TRANSITIONAL` [Global flag]
Perform Unicode TR46 transitional processing.

`idn2_flags IDN2_NONTRANSITIONAL` [Global flag]
Perform Unicode TR46 non-transitional processing.

2.5 Error Handling

`idn2_strerror`

`const char * idn2_strerror (int rc)` [Function]

`rc`: return code from another libidn2 function.

Convert internal libidn2 error code to a humanly readable string. The returned pointer must not be de-allocated by the caller.

Return value: A humanly readable string describing error.

`idn2_strerror_name`

`const char * idn2_strerror_name (int rc)` [Function]

`rc`: return code from another libidn2 function.

Convert internal libidn2 error code to a string corresponding to internal header file symbols. For example, `idn2_strerror_name(IDN2_MALLOC)` will return the string `"IDN2_MALLOC"`.

The caller must not attempt to de-allocate the returned string.

Return value: A string corresponding to error code symbol.

2.6 Return Codes

The functions normally return 0 on success or a negative error code.

<code>idn2_rc IDN2_OK</code>	[Return code]
Successful return.	
<code>idn2_rc IDN2_MALLOC</code>	[Return code]
Memory allocation error.	
<code>idn2_rc IDN2_NO_CODESET</code>	[Return code]
Could not determine locale string encoding format.	
<code>idn2_rc IDN2_ICONV_FAIL</code>	[Return code]
Could not transcode locale string to UTF-8.	
<code>idn2_rc IDN2_ENCODING_ERROR</code>	[Return code]
Unicode data encoding error.	
<code>idn2_rc IDN2_NFC</code>	[Return code]
Error normalizing string.	
<code>idn2_rc IDN2_PUNYCODE_BAD_INPUT</code>	[Return code]
Punycode invalid input.	
<code>idn2_rc IDN2_PUNYCODE_BIG_OUTPUT</code>	[Return code]
Punycode output buffer too small.	
<code>idn2_rc IDN2_PUNYCODE_OVERFLOW</code>	[Return code]
Punycode conversion would overflow.	
<code>idn2_rc IDN2_TOO_BIG_DOMAIN</code>	[Return code]
Domain name longer than 255 characters.	
<code>idn2_rc IDN2_TOO_BIG_LABEL</code>	[Return code]
Domain label longer than 63 characters.	
<code>idn2_rc IDN2_INVALID_ALABEL</code>	[Return code]
Input A-label is not valid.	
<code>idn2_rc IDN2_UALABEL_MISMATCH</code>	[Return code]
Input A-label and U-label does not match.	
<code>idn2_rc IDN2_INVALID_FLAGS</code>	[Return code]
Invalid combination of flags.	
<code>idn2_rc IDN2_NOT_NFC</code>	[Return code]
String is not NFC.	
<code>idn2_rc IDN2_2HYPHEN</code>	[Return code]
String has forbidden two hyphens.	
<code>idn2_rc IDN2_HYPHEN_STARTEND</code>	[Return code]
String has forbidden starting/ending hyphen.	

<code>idn2_rc IDN2_LEADING_COMBINING</code>	[Return code]
String has forbidden leading combining character.	
<code>idn2_rc IDN2_DISALLOWED</code>	[Return code]
String has disallowed character.	
<code>idn2_rc IDN2_CONTEXTJ</code>	[Return code]
String has forbidden context-j character.	
<code>idn2_rc IDN2_CONTEXTJ_NO_RULE</code>	[Return code]
String has context-j character with no rule.	
<code>idn2_rc IDN2_CONTEXTO</code>	[Return code]
String has forbidden context-o character.	
<code>idn2_rc IDN2_CONTEXTO_NO_RULE</code>	[Return code]
String has context-o character with no rule.	
<code>idn2_rc IDN2_UNASSIGNED</code>	[Return code]
String has forbidden unassigned character.	
<code>idn2_rc IDN2_BIDI</code>	[Return code]
String has forbidden bi-directional properties.	
<code>idn2_rc IDN2_DOT_IN_LABEL</code>	[Return code]
Label has forbidden dot (TR46).	
<code>idn2_rc IDN2_INVALID_TRANSITIONAL</code>	[Return code]
Label has character forbidden in transitional mode (TR46).	
<code>idn2_rc IDN2_INVALID_NONTRANSITIONAL</code>	[Return code]
Label has character forbidden in non-transitional mode (TR46).	

2.7 Memory Handling

`idn2_free`

<code>void idn2_free (void *ptr)</code>	[Function]
<i>ptr</i> : pointer to deallocate	
Call <code>free(3)</code> on the given pointer.	
This function is typically only useful on systems where the library malloc heap is different from the library caller malloc heap, which happens on Windows when the library is a separate DLL.	

2.8 Version Check

It is often desirable to check that the version of Libidn2 used is indeed one which fits all requirements. Even with binary compatibility new features may have been introduced but due to problem with the dynamic linker an old version is actually used. So you may want to check that the version is okay right after program startup.

idn2_check_version

const char * idn2_check_version (*const char * req_version*) [Function]
req_version: version string to compare with, or NULL.

Check IDN2 library version. This function can also be used to read out the version of the library code used. See `IDN2_VERSION` for a suitable `req_version` string, it corresponds to the `idn2.h` header file version. Normally these two version numbers match, but if you are using an application built against an older `libidn2` with a newer `libidn2` shared library they will be different.

Return value: Check that the version of the library is at minimum the one given as a string in `req_version` and return the actual version string of the library; return NULL if the condition is not met. If NULL is passed to this function no check is done and only the version string is returned.

The normal way to use the function is to put something similar to the following first in your `main`:

```
if (!idn2_check_version (IDN2_VERSION))
{
    printf ("idn2_check_version() failed:\n"
           "Header file incompatible with shared library.\n");
    exit(EXIT_FAILURE);
}
```

3 Converting from libidn

This library is backwards (API) compatible with the libidn library (<https://www.gnu.org/software/libidn/>).

Although it is recommended for new software to use the native libidn2 functions (i.e., the ones prefixed with `idn2`), old software isn't always feasible to modify.

As such, libidn2, provides compatibility macros which switch all libidn functions, to libidn2 functions in a backwards compatible way. To take advantage of these compatibility functions, it is sufficient to replace the `idna.h` header in legacy code, with `idn2.h`. That would transform the software from using libidn, i.e., IDNA2003, to using libidn2 with IDNA2008 non-transitional encoding.

However, it is recommended to switch applications to the IDN2 native APIs. The following table provides a mapping of libidn code snippets to libidn2, for switching to IDNA2008.

libidn	libidn2
<code>rc = idna_to_ascii_8z (buf, &p, 0 /* no flags */);</code> <code>if (rc != IDNA_SUCCESS)</code>	<code>rc = idn2_to_ascii_8z (buf, &p, IDN2_NONTRANSITIONAL);</code> <code>if (rc != IDN2_OK)</code>
<code>rc = idna_to_unicode_8z8z (buf, &p, 0 /* no flags */);</code> <code>if (rc != IDNA_SUCCESS)</code>	<code>rc = idn2_to_unicode_8z8z (buf, &p, 0);</code> <code>if (rc != IDN2_OK)</code>

Note that, although the table only lists the UTF-8 functions, the mapping is identical for every other one on the family of `toUnicode` and `toAscii`. As the IDNA2003 details differ significantly to IDNA2008, no flags used in the libidn functions map to any specific flags; it is safe to use the suggested libidn2 flags.

In the special case of software that needs to support both libraries (e.g., both IDNA2003 and IDNA2008), you must define `IDN2_SKIP_LIBIDN_COMPAT` prior to including `idn2.h` in order to be able to use both libraries' functions.

4 Examples

This chapter contains example code which illustrate how Libidn2 is used when you write your own application.

4.1 ToASCII example

This example demonstrates how the library is used to convert internationalized domain names into ASCII compatible names (ACE). It expects input to be in UTF-8 form.

```
/* example-toascii.c --- Example ToASCII() code showing how to use Libidn2.
 *
 * This code is placed under public domain.
 */

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <idn2.h>                /* idn2_to_ascii_8z() */

/*
 * Compiling using pkg-config is recommended:
 *
 * $ cc -o example-toascii example-toascii.c $(pkg-config --cflags --libs libidn2)
 * $ ./example-toascii
 * Input domain encoded as 'UTF-8':  .com
 * Read string (length 15):  ce b2 cf 8c ce bb ce bf cf 82 2e 63 6f 6d 0a
 * ACE label (length 17):  'xn--nxasmm1c.com'
 *
 */

int
main (void)
{
    char buf[BUFSIZ];
    char *p;
    int rc;
    size_t i;

    if (!fgets (buf, BUFSIZ, stdin))
        perror ("fgets");
    buf[strlen (buf) - 1] = '\0';

    printf ("Read string (length %ld):  ", (long int) strlen (buf));
    for (i = 0; i < strlen (buf); i++)
        printf ("%02x ", (unsigned) buf[i] & 0xFF);
    printf ("\n");
}
```

```

/* Use non-transitional IDNA2008 */
rc = idn2_to_ascii_8z (buf, &p, IDN2_NONTRANSITIONAL);
if (rc != IDNA_SUCCESS)
{
    printf ("ToASCII() failed (%d):  %s\n", rc, idn2_strerror (rc));
    return EXIT_FAILURE;
}

printf ("ACE label (length %ld):  '%s'\n", (long int) strlen (p), p);

free (p); /* or idn2_free() */

return 0;
}

```

4.2 ToUnicode example

This example demonstrates how the library is used to convert ASCII compatible names (ACE) to internationalized domain names. Both input and output are in UTF-8 form.

```

/* example-tounicode.c --- Example ToUnicode() code showing how to use Libidn2.
 *
 * This code is placed under public domain.
 */

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <idn2.h>                                /* idn2_to_unicode_8z8z() */

/*
 * Compiling using pkg-config is recommended:
 *
 * $ cc -o example-to-unicode example-to-unicode.c $(pkg-config --cflags --libs libidn2)
 * $ ./example-tounicode
 * Input domain (ACE) encoded as 'UTF-8':  xn--nxasmm1c.com
 *
 * Read string (length 16):  78 6e 2d 2d 6e 78 61 73 6d 6d 31 63 2e 63 6f 6d
 * ACE label (length 14):  '.com'
 *
 */

int
main (void)
{
    char buf[BUFSIZ];
    char *p;
    int rc;

```

```

size_t i;

if (!fgets (buf, BUFSIZ, stdin))
    perror ("fgets");
buf[strlen (buf) - 1] = '\0';

printf ("Read string (length %ld):  ", (long int) strlen (buf));
for (i = 0; i < strlen (buf); i++)
    printf ("%02x ", (unsigned) buf[i] & 0xFF);
printf ("\n");

rc = idn2_to_unicode_8z8z (buf, &p, 0);
if (rc != IDNA_SUCCESS)
{
    printf ("ToUnicode() failed (%d):  %s\n", rc, idn2_strerror (rc));
    return EXIT_FAILURE;
}

printf ("ACE label (length %ld):  '%s'\n", (long int) strlen (p), p);

free (p); /* or idn2_free() */

return 0;
}

```

4.3 Lookup

This example demonstrates how a domain name is processed before it is lookup in the DNS. The input expected is in the locale encoding.

```

#include <stdio.h> /* printf, fflush, fgets, stdin, perror, fprintf */
#include <string.h> /* strlen */
#include <locale.h> /* setlocale */
#include <stdlib.h> /* free */
#include <idn2.h> /* idn2_lookup_ul, IDN2_OK, idn2_strerror, idn2_strerror_name */

int
main (int argc, char *argv[])
{
    int rc;
    char src[BUFSIZ];
    char *lookupname;

    setlocale (LC_ALL, "");

    printf ("Enter (possibly non-ASCII) domain name to lookup:  ");
    fflush (stdout);
    if (!fgets (src, sizeof (src), stdin))

```



```

    {
        perror ("fgets");
        return 1;
    }
    src[strlen (src) - 1] = '\0';

    rc = idn2_lookup_ul (src, &lookupname, 0);
    if (rc != IDN2_OK)
    {
        fprintf (stderr, "error:  %s (%s, %d)\n",
                 idn2_strerror (rc), idn2_strerror_name (rc), rc);
        return 1;
    }

    printf ("IDNA2008 domain name to lookup in DNS: %s\n", lookupname);

    free (lookupname);

    return 0;
}

```

4.4 Register

This example demonstrates how a domain label is processed before it is registered in the DNS. The input expected is in the locale encoding.

```

#include <stdio.h> /* printf, fflush, fgets, stdin, perror, fprintf */
#include <string.h> /* strlen */
#include <locale.h> /* setlocale */
#include <stdlib.h> /* free */
#include <idn2.h> /* idn2_register_ul, IDN2_OK, idn2_strerror, idn2_strerror_name */

int
main (int argc, char *argv[])
{
    int rc;
    char src[BUFSIZ];
    char *insertname;

    setlocale (LC_ALL, "");

    printf ("Enter (possibly non-ASCII) label to register:  ");
    fflush (stdout);
    if (!fgets (src, sizeof (src), stdin))
    {
        perror ("fgets");
        return 1;
    }
}

```

```
src[strlen (src) - 1] = '\\0';

rc = idn2_register_ul (src, NULL, &insertname, 0);
if (rc != IDN2_OK)
{
    fprintf (stderr, "error:  %s (%s, %d)\\n",
             idn2_strerror (rc), idn2_strerror_name (rc), rc);
    return 1;
}

printf ("IDNA2008 label to register in DNS: %s\\n", insertname);

free (insertname);

return 0;
}
```

5 Invoking idn2

`idn2` translates internationalized domain names to the IDNA2008 encoded format, either for lookup or registration.

If strings are specified on the command line, they are used as input and the computed output is printed to standard output `stdout`. If no strings are specified on the command line, the program read data, line by line, from the standard input `stdin`, and print the computed output to standard output. What processing is performed (e.g., lookup or register) is indicated by options. If any errors are encountered, the execution of the applications is aborted.

All strings are expected to be encoded in the preferred charset used by your locale. Use `--debug` to find out what this charset is. On POSIX systems you may use the `LANG` environment variable to specify a different locale.

To process a string that starts with `-`, for example `-foo`, use `--` to signal the end of parameters, as in `idn2 -r -- -foo`.

5.1 Options

`idn2` recognizes these commands:

<code>-h, --help</code>	Print help and exit
<code>-V, --version</code>	Print version and exit
<code>-d, --decode</code>	Decode (punycode) domain name
<code>-l, --lookup</code>	Lookup domain name (default)
<code>-r, --register</code>	Register label
<code>-T, --tr46t</code>	Enable TR46 transitional processing
<code>-N, --tr46nt</code>	Enable TR46 non-transitional processing
<code>--debug</code>	Print debugging information
<code>--quiet</code>	Silent operation

5.2 Environment Variables

On POSIX systems the `LANG` environment variable can be used to override the system locale for the command being invoked. The system locale may influence what character set is used to decode data (i.e., strings on the command line or data read from the standard input stream), and to encode data to the standard output. If your system is set up correctly, however, the application will use the correct locale and character set automatically. Example usage:

```
$ LANG=en_US.UTF-8 idn2
...
```

5.3 Examples

Standard usage, reading input from standard input and disabling license and usage instructions:

```
jas@latte:~$ idn2 --quiet
räksmörgås.se
xn--rksmrgs-5wao1o.se
...
```

Reading input from the command line:

```
jas@latte:~$ idn2 räksmörgås.se blåbærgrød.no
xn--rksmrgs-5wao1o.se
xn--blbrgrd-fxak7p.no
jas@latte:~$
```

Testing the IDNA2008 Register function:

```
jas@latte:~$ idn2 --register fußball
xn--fuball-cta
jas@latte:~$
```

5.4 Troubleshooting

Getting character data encoded right, and making sure Libidn2 use the same encoding, can be difficult. The reason for this is that most systems may encode character data in more than one character encoding, i.e., using UTF-8 together with ISO-8859-1 or ISO-2022-JP. This problem is likely to continue to exist until only one character encoding come out as the evolutionary winner, or (more likely, at least to some extents) forever.

The first step to troubleshooting character encoding problems with Libidn2 is to use the ‘--debug’ parameter to find out which character set encoding ‘idn2’ believe your locale uses.

```
jas@latte:~$ idn2 --debug --quiet ""
Charset: UTF-8

jas@latte:~$
```

If it prints `ANSI_X3.4-1968` (i.e., US-ASCII), this indicate you have not configured your locale properly. To configure the locale, you can, for example, use ‘`LANG=sv_SE.UTF-8; export LANG`’ at a `/bin/sh` prompt, to set up your locale for a Swedish environment using UTF-8 as the encoding.

Sometimes ‘idn2’ appear to be unable to translate from your system locale into UTF-8 (which is used internally), and you will get an error message like this:

```
idn2: lookup: could not convert string to UTF-8
```

One explanation is that you didn’t install the ‘iconv’ conversion tools. You can find it as a standalone library in GNU Libiconv (<https://www.gnu.org/software/libiconv/>). On many GNU/Linux systems, this library is part of the system, but you may have to install additional packages to be able to use it.

Another explanation is that the error is correct and you are feeding ‘idn2’ invalid data. This can happen inadvertently if you are not careful with the character set encoding you use.

For example, if your shell run in a ISO-8859-1 environment, and you invoke ‘idn2’ with the ‘LANG’ environment variable as follows, you will feed it ISO-8859-1 characters but force it to believe they are UTF-8. Naturally this will lead to an error, unless the byte sequences happen to be valid UTF-8. Note that even if you don’t get an error, the output may be incorrect in this situation, because ISO-8859-1 and UTF-8 does not in general encode the same characters as the same byte sequences.

```

jas@latte:~$ idn2 --quiet --debug ""
Charset: ISO-8859-1

jas@latte:~$ LANG=sv_SE.UTF-8 idn2 --debug räksmörgås
Charset: UTF-8
input[0] = 0x72
input[1] = 0xc3
input[2] = 0xa4
input[3] = 0xc3
input[4] = 0xa4
input[5] = 0x6b
input[6] = 0x73
input[7] = 0x6d
input[8] = 0xc3
input[9] = 0xb6
input[10] = 0x72
input[11] = 0x67
input[12] = 0xc3
input[13] = 0xa5
input[14] = 0x73
UCS-4 input[0] = U+0072
UCS-4 input[1] = U+00e4
UCS-4 input[2] = U+00e4
UCS-4 input[3] = U+006b
UCS-4 input[4] = U+0073
UCS-4 input[5] = U+006d
UCS-4 input[6] = U+00f6
UCS-4 input[7] = U+0072
UCS-4 input[8] = U+0067
UCS-4 input[9] = U+00e5
UCS-4 input[10] = U+0073
output[0] = 0x72
output[1] = 0xc3
output[2] = 0xa4
output[3] = 0xc3
output[4] = 0xa4
output[5] = 0x6b
output[6] = 0x73
output[7] = 0x6d
output[8] = 0xc3

```

```
output[9] = 0xb6
output[10] = 0x72
output[11] = 0x67
output[12] = 0xc3
output[13] = 0xa5
output[14] = 0x73
UCS-4 output[0] = U+0072
UCS-4 output[1] = U+00e4
UCS-4 output[2] = U+00e4
UCS-4 output[3] = U+006b
UCS-4 output[4] = U+0073
UCS-4 output[5] = U+006d
UCS-4 output[6] = U+00f6
UCS-4 output[7] = U+0072
UCS-4 output[8] = U+0067
UCS-4 output[9] = U+00e5
UCS-4 output[10] = U+0073
xn--rksmrgs-5waap8p
jas@latte:~$
```

The sense moral here is to forget about ‘LANG’ (instead, configure your system locale properly) unless you know what you are doing, and if you want to use ‘LANG’, do it carefully and after verifying with ‘--debug’ that you get the desired results.

Interface Index

idn2_check_version	9	idn2_strerror_name	6
idn2_free	8	idn2_to_ascii_8z	2
idn2_lookup_u8	3	idn2_to_ascii_lz	4
idn2_lookup_ul	5	idn2_to_unicode_8z8z	2
idn2_register_u8	3	idn2_to_unicode_8z1z	4
idn2_register_ul	5	idn2_to_unicode_lz1z	4
idn2_strerror	6		

Concept Index

C

command line 16

E

Examples..... 11

I

idn2 16
invoking idn2 16

L

libidn 10
Library Functions..... 2